

COREMEDIA CONTENT CLOUD

Blueprint Developer Manual



Copyright CoreMedia GmbH © 2023

CoreMedia GmbH

Altes Klöpperhaus, 5. OG

Rödingsmarkt 9

20459 Hamburg

International

All rights reserved. No part of this manual or the corresponding program may be reproduced or copied in any form (print, photocopy or other process) without the written permission of CoreMedia GmbH.

Germany

Alle Rechte vorbehalten. CoreMedia und weitere im Text erwähnte CoreMedia Produkte sowie die entsprechenden Logos sind Marken oder eingetragene Marken der CoreMedia GmbH in Deutschland. Alle anderen Namen von Produkten sind Marken der jeweiligen Firmen.

Das Handbuch bzw. Teile hiervon sowie die dazugehörigen Programme dürfen in keiner Weise (Druck, Fotokopie oder sonstige Verfahren) ohne schriftliche Genehmigung der CoreMedia GmbH reproduziert oder vervielfältigt werden. Unberührt hiervon bleiben die gesetzlich erlaubten Nutzungsarten nach dem UrhG.

Licenses and Trademarks

All trademarks acknowledged.

December 08, 2023 [Release 2107]

1. Preface	1
1.1. Audience	2
1.2. Typographic Conventions	3
1.3. CoreMedia Services	5
1.3.1. Registration	5
1.3.2. CoreMedia Releases	6
1.3.3. Documentation	6
1.3.4. CoreMedia Training	10
1.3.5. CoreMedia Support	10
1.4. Working with CoreMedia Content Cloud	12
1.4.1. Getting an Overview	12
1.4.2. Learning about Components	13
1.4.3. Working with the GUI	13
1.4.4. Operating the System	14
1.4.5. Extending the System	14
1.5. Change Chapter	16
2. Overview of CoreMedia Content Cloud	17
2.1. Components and Architecture	19
2.1.1. Content Management Environment	20
2.1.2. Content Delivery Environment	22
2.1.3. Shared Components	22
2.1.4. User Management	25
2.1.5. Communication Between the Components	25
2.2. CoreMedia Blueprint Sites	27
3. Getting Started	29
3.1. Prerequisites	30
3.1.1. Developer Setup	32
3.1.2. Test System Setup	33
3.1.3. Additional Software for eCommerce Blueprint only	33
3.2. Quick Start	35
3.2.1. Building the Workspace	35
3.2.2. Docker Compose Setup	40
4. Blueprint Workspace for Developers	52
4.1. Concepts and Architecture	53
4.1.1. Maven Concepts	53
4.1.2. Blueprint Base Modules	56
4.1.3. Application Architecture	57
4.1.4. Structure of the Workspace	59
4.1.5. Project Extensions	67
4.1.6. Application Plugins	72
4.2. Configuring the Workspace	91
4.2.1. Removing Optional Components	91
4.2.2. Configuring the Workspace	104
4.2.3. Configuring Local Setup	105
4.2.4. In-Memory Replacement for MongoDB-Based Services	106
4.3. Build and Run the Applications	109
4.3.1. Starting Applications using IntelliJ IDEA	111
4.3.2. Starting Applications using Maven	112

4.3.3. Local Docker Test System	116
4.4. Development	117
4.4.1. Using Blueprint Base Modules	117
4.4.2. Extending Content Types	123
4.4.3. Developing with Studio	125
4.4.4. Developing with the CAE	129
4.4.5. Customizing the CAE Feeder	131
4.4.6. Handling Personal Data	132
5. CoreMedia Blueprint - Functionality for Websites	138
5.1. Overview of eCommerce Blueprint	139
5.2. Overview of Brand Blueprint	142
5.3. Basic Content Management	144
5.3.1. Common Content Types	144
5.3.2. Adaptive Personalization Content Types	150
5.3.3. Tagging and Taxonomies	151
5.4. Website Management	161
5.4.1. Folder and User Rights Concept	161
5.4.2. Navigation and Contexts	163
5.4.3. Settings	165
5.4.4. Page Assembly	167
5.4.5. Overwriting Product Teaser Images	179
5.4.6. Content Lists	179
5.4.7. View Types	180
5.4.8. CMS Catalog	183
5.4.9. Teaser Management	186
5.4.10. Dynamic Templating	187
5.4.11. View Repositories	190
5.4.12. Client Code Delivery	191
5.4.13. Managing End User Interactions	195
5.4.14. Images	199
5.4.15. URLs	201
5.4.16. Vanity URLs	201
5.4.17. Content Visibility	203
5.4.18. Content Type Sitemap	204
5.4.19. Robots File	205
5.4.20. Sitemap	209
5.4.21. Website Search	212
5.4.22. Topic Pages	218
5.4.23. Search Landing Pages	224
5.4.24. Theme Importer	225
5.4.25. Tag Management	225
5.5. Localized Content Management	227
5.5.1. Concept	227
5.5.2. Administration	232
5.5.3. Development	237
5.6. Workflow Management	273
5.6.1. Publication	273
5.6.2. Translation Workflow	280
5.6.3. Deriving Sites	293

5.6.4. Synchronization Workflow	294
6. Editorial and Backend Functionality	295
6.1. Studio Enhancements	296
6.1.1. Content Query Form	296
6.1.2. Call-to-Action Button	298
6.1.3. Media Player Configuration	299
6.1.4. Displayed Date	300
6.1.5. Library	301
6.1.6. Bookmarks	303
6.1.7. External Preview	303
6.1.8. Settings for Studio	304
6.1.9. Content Creation	305
6.1.10. Create from Template	311
6.1.11. Site-specific configuration of Document Forms	313
6.1.12. Open Street Map	314
6.1.13. Site Selection	315
6.1.14. Upload Files	316
6.1.15. Studio Preview Slider	320
6.1.16. Uploading Content to Salesforce Marketing Cloud	323
6.2. CAE Enhancements	325
6.2.1. Using Dynamic Fragments in HTML Responses	325
6.2.2. Image Cropping in CAE	328
6.2.3. RSS Feeds	329
6.3. Elastic Social	331
6.3.1. Configuring Elastic Social	332
6.3.2. Displaying Custom Information in Studio	338
6.3.3. Adding Custom Filters for Moderation View	340
6.3.4. Emails	341
6.3.5. Resend Registration Confirmation Mail from <i>Studio</i>	343
6.3.6. Curated transfer	343
6.3.7. reCAPTCHA	344
6.3.8. Sign Cookie	344
6.4. Adaptive Personalization	346
6.4.1. Key Integration Points	347
6.4.2. Adaptive Personalization Extension Modules	347
6.4.3. CAE Integration	349
6.4.4. Studio Integration	352
6.5. Third-Party Integration	356
6.5.1. Optimizely	356
6.5.2. Open Street Map Integration	357
6.5.3. Google Analytics Integration	358
6.5.4. Salesforce Marketing Cloud Integration	358
6.6. Advanced Asset Management	360
6.6.1. Product Asset Widget	361
6.6.2. Replaced Product and Category Images	363
6.6.3. Extract Image Data During Upload	366
6.6.4. Configuring Asset Management	367
7. Reference	375
7.1. Content Type Model	376

- 7.2. Link Format 379
- 7.3. Predefined Users 385
- 7.4. Database Users 391
- 7.5. Cookies 392
- Glossary 393
- Index 399

List of Figures

2.1. System Overview	20
4.1. CoreMedia CMS's Four-Tier Architecture	61
4.2. CoreMedia CMS's Shared, Application-Specific, and Global Workspaces	62
4.3. Backend Tier Workspace Dependencies	62
4.4. Middle Tier Workspace Dependencies	63
4.5. CoreMedia Extensions Overview	69
4.6. The new sample studio plugin	127
4.7. The sample studio plugin with plugin class and descriptor	127
5.1. Calista (Experience-led) start page for different devices: desktop, tablet, mobile	140
5.2. Hybris (commerce-led) start page for different devices: desktop, tablet, mobile	141
5.3. Chef Corp. start page for different devices: desktop, tablet, mobile	143
5.4. Dynamic list of articles tagged with "Vegetables"	152
5.5. Taxonomy Administration Editor	154
5.6. Taxonomy Property Editor	155
5.7. Taxonomy Studio Settings	156
5.8. Navigation in the Corporate Site	163
5.9. The page grid editor and the Hero placement	169
5.10. An inheriting placement	170
5.11. A locked placement	170
5.12. The layout chooser combo box	171
5.13. Layout Variant selector	182
5.14. CMS Catalog Settings	184
5.15. Default view and teaser view of an Article	186
5.16. Content Type Sitemap	205
5.17. Robots.txt settings	207
5.18. Channel settings with configuration for Robots.txt as a linked setting on a root page	208
5.19. Selection of a sitemap setup	211
5.20. Search Configuration Settings document	213
5.21. Generated topic page for topic "Professionals"	219
5.22. The topic pages administration in Studio	221
5.23. Settings document for topic pages	222
5.24. A Search Result for a Topic Page	223
5.25. Tag Management Configuration	226
5.26. Multi-Site Interdependence	231
5.27. Locales Administration in CoreMedia Studio	233
5.28. Derive Site: Setting site manager group	236
5.29. Site Indicator: Setting site manager group	237
6.1. Content Query Form	298
6.2. Call-to-Action-Button editor	299
6.3. Call-to-Action button in teaser view	299
6.4. Video Options panel in the DocumentForm of a Video content	299
6.5. Displayed Date editor	300

6.6. Setting a Custom Date	301
6.7. Image Gallery Creation Button	301
6.8. Image Gallery Creation Dialog	302
6.9. Library List View	302
6.10. Bookmarks	303
6.11. External Preview	304
6.12. New content menu on the favorites toolbar	305
6.13. New content dialog	306
6.14. New content dialog for pages	306
6.15. New content dialog as button on a link list toolbar	307
6.16. New content dialog menu on a link list toolbar	308
6.17. Create from template dialog	312
6.18. OpenStreetMap Property Editor	315
6.19. The site selector on the preference tab	316
6.20. The upload files dialog	317
6.21. The slider of the Studio Preview	320
6.22. SFMC Uploadable Properties Setting	324
6.23. Conditions in Personalized Content and Customer Segment documents	353
6.24. Defining artificial context properties using Customer Personas	354
6.25. Selecting Customer Personas to test Personalized Content and User Segment documents	355
6.26. Example for an Open Street Map integration in a website	357
6.27. Product image gallery in HCL Commerce delivered by the CMS	361
6.28. Assign a product to a picture	362
6.29. Define Product Image URLs in Management Center	363
6.30. Screenshot from Adobe Photoshop for a Picture containing XMP Data	366
6.31. Picture linked to XMP Product Reference	367
6.32. Configuration of the download portal	373
6.33. Taxonomy for assets	374
7.1. CoreMedia Blueprint Content Type Model - CMLocalized	377
7.2. CoreMedia Blueprint Content Type Model - CMNavigation	377
7.3. CoreMedia Blueprint Content Type Model - CMHasContexts	378
7.4. CoreMedia Blueprint Content Type Model - CMMedia	378
7.5. CoreMedia Blueprint Content Type Model - CMCollection	378
7.6. A basic absoluteUrlPrefixes Struct	382
7.7. A complete absoluteUrlPrefixes Struct	383
7.8. An initial absoluteUrlPrefixes Struct	384

List of Tables

1.1. Typographic conventions	3
1.2. Pictographs	4
1.3. CoreMedia manuals	7
1.4. Changes	16
3.1. Overview of minimum / recommended Hardware requirements	33
4.1. Packages request mapping	88
4.2. Optional modules and blueprints	91
4.3. Blueprint Extensions and Dependencies	93
4.4. Add-ons and the dependent extensions	100
4.5. Database Settings	105
4.6. Studio Configuration Properties for In-Memory Store	107
4.7. Content type model dependencies	118
4.8. Parameters of the settings* methods	119
5.1. Overview of Content Types for common content	145
5.2. Commerce Content Types	146
5.3. Overview Commerce Content Properties	146
5.4. Overview Common Content Properties	147
5.5. CMMedia Properties	149
5.6. CMTaxonomy Properties	153
5.7. Additional CMLocTaxonomy Properties	153
5.8. CMLinkable Properties for Tagging	154
5.9. Properties of CMLinkable for Settings Management	165
5.10. Collection Types in CoreMedia Blueprint	180
5.11. CMS Catalog: Maven parent modules	183
5.12. Properties of CMTeasable	187
5.13. Properties of CMTemplateSet	189
5.14. Client Code - Properties of CMAbstractCode	191
5.15. Properties for Visibility Restriction	203
5.16. Brand website search settings	214
5.17. Page Grid Indexing Spring Properties	216
5.18. Options of the import-themes tool	225
5.19. Suggested Users and Groups for multi-site	234
5.20. Properties of the Site Model	238
5.21. Placeholders for Site Model Configuration	242
5.22. Example for server export and import for multi-site	246
5.23. Translation Workflow Properties	268
5.24. XLIFF Properties	269
5.25. Publishing documents: actions and effects	275
5.26. Publishing folders: actions and effects	276
5.27. Predefined publication workflow definitions	278
5.28. Predefined publication workflow steps	278
5.29. User options.	280
5.30. Attributes of GetDerivedContentsAction	283
5.31. Attributes of CreateTranslationTreeData	284
5.32. Attributes of FilterDerivedContentsAction	285
5.33. Attributes of GetSiteManagerGroupAction	287

5.34. Attributes of ExtractPerformerAction	287
5.35. Attributes of AutoMergeTranslationAction	288
5.36. Attributes of AutoMergeSyncAction	290
5.37. Attributes of CompleteTranslationAction	291
5.38. Attributes of RollbackTranslationAction	292
6.1. Upload Settings	318
6.2. Root Channel Context Settings	332
6.3. Context Settings for Every Channel	334
6.4. Mail Templates	341
6.5. Adaptive Personalization's main Maven module in detail	348
6.6. Adaptive Personalization contexts configured for CoreMedia Blueprint	349
6.7. Predefined SearchFunctions in <i>CoreMedia Blueprint</i>	350
6.8. Settings for Open Street Map Integration	357
6.9. Path segments in the image URL	364
7.1. CapBlobHandler	379
7.2. CodeHandler	379
7.3. ExternalLinkHandler	379
7.4. PageActionHandler	380
7.5. PageHandler	380
7.6. PageRssHandler	380
7.7. PreviewHandler	380
7.8. StaticUrlHandler	381
7.9. TransformedBlobHandler	381
7.10. Global groups	385
7.11. Global users	386
7.12. Site specific groups for Salesforce Commerce	386
7.13. Site specific users for Salesforce Commerce	386
7.14. Site specific groups for SAP Commerce	387
7.15. Site specific users for SAP Commerce	387
7.16. Site specific groups for <i>HCL Commerce</i>	388
7.17. Site specific users for <i>HCL Commerce</i>	388
7.18. Site specific groups Brand web presence	389
7.19. Site specific users Brand web presence	389
7.20. Database Users	391

List of Examples

4.1. Dependencies for a CoreMedia application	54
4.2. Adding the Base Component	57
4.3. Specify the extension point	68
4.4. plugin.properties	74
4.5. com.acme.myplugin.MyPluginConfiguration	75
4.6. com.acme.myplugin.MyExtension	75
4.7. PluginA plugin.properties	82
4.8. PluginABeansForPluginsContainer	82
4.9. PluginABeansForPlugins	83
4.10. PluginAConfiguration	83
4.11. PluginB plugin.properties	83
4.12. PluginBConfiguration	83
4.13. PluginA plugin.properties	84
4.14. SomeExtensionPointForA	84
4.15. PluginAConfiguration	84
4.16. PluginB plugin.properties	85
4.17. PluginBConfiguration	85
4.18. SomeExtensionPointForAlmpl	85
4.19. my-plugin-7.8.9.json	90
4.20. Remove CoreMedia Elastic Social Extension	102
4.21. Remove CoreMedia Adaptive Personalization Extension	102
4.22. Example for Adaptive Personalization Content in Blueprint	103
4.23. Remove CoreMedia eCommerce Extension	103
4.24. Remove CoreMedia Corporate Extension	103
4.25. Remove CoreMedia Product Asset Management Extension	104
4.26. The Spring Bean Definition for the Map of Settings Finder	120
4.27. Adding Custom Settings Finder	121
4.28. Business Logic API	121
4.29. Settings Address Adapter	122
4.30. Address Proxy	122
4.31. POM file of a new Studio module	125
4.32. Adding custom stub classes	134
5.1. Pagegrid example definition	173
5.2. A robots.txt file	206
5.3. robots.txt file generated by the example settings	209
5.4. A sitemap file	209
5.5. A sitemap index file	209
5.6. Usage of import-themes	225
5.7. Multi-Site Folder Structure Example	229
5.8. Site Folder Structure Example	230
5.9. XML of locale Struct	232
5.10. SiteModel in editor.xml	243
5.11. Versioned Master Link in editor.xml	243
5.12. CMLocalized	244
5.13. CMTeasable	245
5.14. XLIFF fragment	248

5.15. Transforming to Translation Items	249
5.16. Function to Determine Locales	249
5.17. Exporting XLIFF	250
5.18. Importing XLIFF	251
5.19. Importing XLIFF	252
5.20. Example for CapTranslateItemException	253
5.21. TranslatePropertyTransformer for XHTML	254
5.22. Example for CapXliffExportException	255
5.23. PropertyExportHandler for XHTML	255
5.24. XhtmlToXliffConverter	256
5.25. XHTML Example Input	259
5.26. XHTML as XLIFF Example Output	259
5.27. XliffXhtmlPropertyImportHandler	260
5.28. XliffToXhtmlConverter	261
5.29. Attribute Export	263
5.30. XHTML Example Input (Attributes)	264
5.31. XHTML as XLIFF Example Output (Attributes)	264
5.32. XLIFF Validation Error	265
5.33. Custom XLIFF XSD	265
5.34. Custom XLIFF XSD (Bean)	265
5.35. Importing Translatable Attributes	265
5.36. Importing Non-Translatable Attributes	266
5.37. Example for a customTranslationWorkflowDerived ContentsStrategy	267
5.38. translatableExpressions Configuration Example	271
5.39. Usage of GetDerivedContentsAction	284
5.40. Usage of CreateTranslationTreeDataAction	285
5.41. Usage of FilterDerivedContentsAction	286
5.42. Usage of GetSiteManagerGroupAction	287
5.43. Usage of ExtractPerformerAction	288
5.44. Usage of AutoMergeTranslationAction	290
5.45. Usage of AutoMergeSyncAction	290
5.46. Usage of CompleteTranslationAction	292
5.47. Usage of RollbackTranslationAction	293
6.1. Using the content query form	297
6.2. Add content creation dialog to link list with quickCreateLinkList Menu	307
6.3. Predicate Example	325
6.4. Predicate Customizer Example	326
6.5. Dynamic Include Link Scheme Example	327
6.6. Dynamic Include Handler Example	327
6.7. Root Channel Context Settings	333
6.8. Root Channel Context Settings	334
6.9. Context Settings for Every Channel	337
6.10. Rendition Publication Configuration	371
7.1. Configuration of URL prefix type	383

1. Preface

This manual contains the basic knowledge you should have when you want to develop with *CoreMedia Content Cloud*. It describes the basic features and concepts of the development workspace, of the Commerce integration and of the Corporate Blueprint features.

- [Chapter 2, Overview of CoreMedia Content Cloud \[17\]](#) gives you an overview over the modules, functions and architecture of *CoreMedia Content Cloud*.
- [Chapter 3, Getting Started \[29\]](#) shows you step by step how to install and start the components using the *Blueprint* workspace.
- [Chapter 4, Blueprint Workspace for Developers \[52\]](#) explains in depth the concepts and patterns of the *Blueprint* workspace. You will learn how to release and deploy the system and how to develop in the workspace.
- [Chapter 5, CoreMedia Blueprint - Functionality for Websites \[138\]](#) explains the content types, the web functionality, details about localized content management and workflow management of *CoreMedia Content Cloud*.
- [Chapter 6, Editorial and Backend Functionality \[295\]](#) describes the extensions of *CoreMedia Blueprint* to the standard system.
- [Chapter 7, Reference \[375\]](#) contains reference information, such as the tag library, ports, the content type model or Maven profiles.

1.1 Audience

This manual is intended for architects and developers who want to work with *CoreMedia Content Cloud* or who want to learn about the concepts of the product. The reader should be familiar with *CoreMedia CMS*, the commerce system to connect with, *Spring*, *Maven* and *Chef*.

1.2 Typographic Conventions

CoreMedia uses different fonts and types in order to label different elements. The following table lists typographic conventions for this documentation:

Element	Typographic format	Example
Source code	Courier new	cm systeminfo start
Command line entries		
Parameter and values		
Class and method names		
Packages and modules		
Menu names and entries	Bold, linked with	Open the menu entry Format Normal
Field names	Italic	Enter in the field <i>Heading</i>
CoreMedia Components		The <i>CoreMedia Component</i>
Applications		Use <i>Chef</i>
Entries	In quotation marks	Enter "On"
(Simultaneously) pressed keys	Bracketed in "<>", linked with "+"	Press the keys <Ctrl>+<A>
Emphasis	Italic	It is <i>not</i> saved
Buttons	Bold, with square brackets	Click on the [OK] button
Code lines in code examples which continue in the next line	\	cm systeminfo \ -u user

Table 1.1. Typographic conventions

In addition, these symbols can mark single paragraphs:




Pictograph	Description
	Tip: This denotes a best practice or a recommendation.
	Warning: Please pay special attention to the text.
	Danger: The violation of these rules causes severe damage.

Table 1.2. Pictographs

1.3 CoreMedia Services

This section describes the CoreMedia services that support you in running a CoreMedia system successfully. You will find all the URLs that guide you to the right places. For most of the services you need a CoreMedia account. See [Section 1.3.1, "Registration" \[5\]](#) for details on how to register.

NOTE

CoreMedia User Orientation for CoreMedia Developers and Partners

Find the latest overview of all CoreMedia services and further references at:

<http://documentation.coremedia.com/new-user-orientation>



- [Section 1.3.1, "Registration" \[5\]](#) describes how to register for the usage of the services.
- [Section 1.3.2, "CoreMedia Releases" \[6\]](#) describes where to find the download of the software.
- [Section 1.3.3, "Documentation" \[6\]](#) describes the CoreMedia documentation. This includes an overview of the manuals and the URL where to find the documentation.
- [Section 1.3.4, "CoreMedia Training" \[10\]](#) describes CoreMedia training. This includes the training calendar, the curriculum and certification information.
- [Section 1.3.5, "CoreMedia Support" \[10\]](#) describes the CoreMedia support.

1.3.1 Registration

In order to use CoreMedia services you need to register. Please, start your [initial registration via the CoreMedia website](#). Afterwards, contact the CoreMedia Support (see [Section 1.3.5, "CoreMedia Support" \[10\]](#)) by email to request further access depending on your customer, partner or freelancer status so that you can use the CoreMedia services.

1.3.2 CoreMedia Releases

Downloading and Upgrading the Blueprint Workspace

CoreMedia provides its software as a Maven based workspace. You can download the current workspace or older releases via the following URL:

<https://releases.coremedia.com/cmcc-10>

Refer to our [Blueprint Github mirror repository](#) for recommendations to upgrade the workspace either via Git or patch files.

NOTE

If you encounter a 404 error then you are probably not logged in at GitHub or do not have sufficient permissions yet. See [Section 1.3.1, "Registration" \[5\]](#) for details about the registration process. If the problems persist, try clearing your browser cache and cookies.



Maven artifacts

CoreMedia provides its release artifacts via Maven under the following URL:

<https://repository.coremedia.com>

You have to add your CoreMedia credentials to your Maven settings file as described in section [Blueprint Developer Manual \[i\]](#).

License files

You need license files to run the CoreMedia system. Contact the support (see [Section 1.3.5, "CoreMedia Support" \[10\]](#)) to get your licenses.

1.3.3 Documentation

CoreMedia provides extensive manuals and Javadoc as PDF files and as online documentation at the following URL:

<https://documentation.coremedia.com/cmcc-10>

The manuals have the following content and use cases:

Manual	Audience	Content
Adaptive Personalization Manual	Developers, architects, administrators	This manual describes the configuration of and development with <i>Adaptive Personalization</i> , the CoreMedia module for personalized websites. You will learn how to configure the GUI used in <i>CoreMedia Studio</i> , how to use predefined contexts and how to develop your own extensions.
Analytics Connectors Manual	Developers, architects, administrators	This manual describes how you can connect your CoreMedia website with external analytic services, such as Google Analytics.
Blueprint Developer Manual	Developers, architects, administrators	<p>This manual gives an overview over the structure and features of <i>CoreMedia Content Cloud</i>. It describes the content type model, the <i>Studio</i> extensions, folder and user rights concept and many more details. It also describes administrative tasks for the features.</p> <p>It also describes the concepts and usage of the project workspace in which you develop your CoreMedia extensions. You will find a description of the Maven structure, the virtualization concept, learn how to perform a release and many more.</p>
Connector Manuals	Developers, administrators	This manual gives an overview over the use cases of the eCommerce integration. It describes the deployment of the Commerce Connector and how to connect it with the CoreMedia and eCommerce system.
Content Application Developer Manual	Developers, architects	This manual describes concepts and development of the <i>Content Application Engine [CAE]</i> . You will learn how to write JSP or FreeMarker templates that access the other CoreMedia modules and use the sophisticated caching mechanisms of the CAE.
Content Server Manual	Developers, architects, administrators	This manual describes the concepts and administration of the main CoreMedia component, the <i>Content Server</i> . You will learn about the content type model which lies at the heart of a CoreMedia system, about user and rights management, database configuration, and more.

Manual	Audience	Content
Deployment Manual	Developers, architects, administrators	This manual describes the concepts and usage of the CoreMedia deployment artifacts. That is the deployment archive and the Docker setup. You will also find an overview of the properties required to configure the deployed system.
Elastic Social Manual	Developers, architects, administrators	This manual describes the concepts and administration of the <i>Elastic Social</i> module and how you can integrate it into your websites.
Frontend Developer Manual	Frontend Developers	This manual describes the concepts and usage of the Frontend Workspace. You will learn about the structure of this workspace, the CoreMedia themes and bricks concept, the CoreMedia FreeMarker facade API, how to develop your own themes and how to upload your themes to the CoreMedia system.
Headless Server Developer Manual	Frontend Developers, administrators	This manual describes the concepts and usage of the <i>Headless Server</i> . You will learn how to deploy the Headless Server and how to use its endpoints for your sites.
Importer Manual	Developers, architects	This manual describes the structure of the internal CoreMedia XML format used for storing data, how you set up an <i>Importer</i> application and how you define the transformations that convert your content into CoreMedia content.
Operations Basics Manual	Developers, administrators	This manual describes some overall concepts such as the communication between the components, how to set up secure connections, how to start application or the usage of the watchdog component.
Search Manual	Developers, architects, administrators	This manual describes the configuration and customization of the <i>CoreMedia Search Engine</i> and the two feeder applications: the <i>Content Feeder</i> and the <i>CAE Feeder</i> .
Site Manager Developer Manual	Developers, architects, administrators	This manual describes the configuration and customization of <i>Site Manager</i> , the Java based stand-alone application for administrative tasks. You will learn how to configure the <i>Site Manager</i> with property files and

Manual	Audience	Content
		XML files and how to develop your own extensions using the <i>Site Manager API</i> . The Site Manager is deprecated for editorial work.
Studio Developer Manual	Developers, architects	This manual describes the concepts and extension of <i>CoreMedia Studio</i> . You will learn about the underlying concepts, how to use the development environment and how to customize <i>Studio</i> to your needs.
Studio User Manual	Editors	This manual describes the usage of <i>CoreMedia Studio</i> for editorial and administrative work. It also describes the usage of the <i>Adaptive Personalization</i> and <i>Elastic Social</i> GUI that are integrated into <i>Studio</i> .
Studio Benutzerhandbuch	Editors	The Studio User Manual but in German.
Supported Environments	Developers, architects, administrators	This document lists the third-party environments with which you can use the CoreMedia system, Java versions or operation systems for example.
Unified API Developer Manual	Developers, architects	This manual describes the concepts and usage of the <i>CoreMedia Unified API</i> , which is the recommended API for most applications. This includes access to the content repository, the workflow repository and the user repository.
Utilized Open Source Software & Third-Party Licenses	Developers, architects, administrators	This manual lists the third-party software used by CoreMedia and lists, when required, the license texts.
Workflow Manual	Developers, architects, administrators	This manual describes the <i>Workflow Server</i> . This includes the administration of the server, the development of workflows using the XML language and the development of extensions.

Table 1.3. CoreMedia manuals

If you have comments or questions about CoreMedia's manuals, contact the Documentation department:

Email: documentation@coremedia.com

1.3.4 CoreMedia Training

CoreMedia's training department provides you with the training for your CoreMedia projects either in the CoreMedia training center or at your own location.

You will find information about the CoreMedia training program, the training schedule and the CoreMedia certification program at the following URL:

<http://www.coremedia.com/training>

Contact the Training department at the following email address:

Email: training@coremedia.com

1.3.5 CoreMedia Support

CoreMedia's support is located in Hamburg and accepts your support requests between 9 am and 6 pm MET. If you have subscribed to 24/7 support, you can always reach the support using the phone number provided to you.

To submit a support ticket, track your submitted tickets or receive access to our forums visit the CoreMedia Online Support at:

<http://support.coremedia.com/>

Do not forget to request further access via email after your initial registration as described in [Section 1.3.1, "Registration" \[5\]](#). The support email address is:

Email: support@coremedia.com

Create a support request

CoreMedia systems are distributed systems that have a rather complex structure. This includes, for example, databases, hardware, operating systems, drivers, virtual machines, class libraries and customized code in many combinations. That's why CoreMedia needs detailed information about the environment for a support case. In order to track down your problem, provide the following information:

Support request

- Which CoreMedia component(s) did the problem occur with (include the release number)?
- Which database is in use (version, drivers)?
- Which operating system(s) is/are in use?
- Which Java environment is in use?
- Which customizations have been implemented?

- A full description of the problem (as detailed as possible)
- Can the error be reproduced? If yes, give a description please.
- How are the security settings (firewall)?

In addition, log files are the most valuable source of information.

To put it in a nutshell, CoreMedia needs:

Support checklist

1. a person in charge (ideally, the CoreMedia system administrator)
2. extensive and sufficient system specifications
3. detailed error description
4. log files for the affected component(s)
5. if required, system files

An essential feature for the CoreMedia system administration is the output log of Java processes and CoreMedia components. They're often the only source of information for error tracking and solving. All protocolling services should run at the highest log level that is possible in the system context. For a fast breakdown, you should be logging at debug level. The location where component log output is written is specified in its `logback.xml` file.

Log files

Which Log File?

Mostly at least two CoreMedia components are involved in errors. In most cases, the *Content Server* log files together with the log file from the client. If you are able locate the problem exactly, solving the problem becomes much easier.

Where do I Find the Log Files?

By default, log files can be found in the CoreMedia component's installation directory in `/var/logs` or for web applications in the `logs/` directory of the servlet container. See Section 4.7, "Logging" in *Operations Basics* for details.

1.4 Working with CoreMedia Content Cloud

This chapter guides you to the download area, other manuals and training courses depending on your skills and the tasks you want to accomplish. CoreMedia documentation is organized in such a way, that each component manual contains all required information for the configuration, operation and development of the component. Only the user manuals for editors and other users are in separate documents.

Chapters and sections that have only a noun in the title usually contain conceptual information while a title with an "-ing" indicates an instructional chapter.

1.4.1 Getting an Overview

To start with *CoreMedia Content Cloud* you should open the following address in your browser:

<https://releases.coremedia.com/cmcc-10>

Here, you will find a short quick start description and links to all resources for *CoreMedia Content Cloud*. You can download all software artefacts and demo content.

With *CoreMedia Content Cloud* you do not get a program to install and run, but a workspace to develop within, to build and to deploy artifacts from.

- Read the Supported Environments document available at <http://bit.ly/cmcc-10-supported-environments> to learn which databases, browsers, operation systems, Java versions, Portal version and servlet container are supported by *CoreMedia Content Cloud*.
- Read the Deployment Manual to learn how to install CoreMedia components with *CoreMedia Blueprint*.
- Read the [Blueprint Developer Manual] to learn about the *Blueprint* features.
- Read the Operations Basics manual to learn basic operation tasks.
- Read the Utilized Open Source Software & 3rd Party Licenses if you want to know which open source software is used by *CoreMedia Content Cloud*.
- Attend the "CoreMedia Administrator training" at the CoreMedia Training Center, see <https://www.coremedia.com/en/services/training/coremedia-training-program> for the current schedule.

1.4.2 Learning about Components

If you want to get familiar with the concepts and coverage of *CoreMedia Content Cloud*, then this manual is the starting point. Nevertheless, it only gives you a rough insight. If you want to learn more about all the components that comprise *CoreMedia Content Cloud* you should read the following chapters:

- Read the Chapter 2, *Overview* in *Content Server Manual* to learn something about the basic component of the CoreMedia system.
- Read the "Overview" chapter in the manual of every component you are interested in.
- Attend the "CoreMedia Fundamentals" training at the CoreMedia Training Center, see <https://www.coremedia.com/en/services/training/coremedia-training-program> for the current schedule.

1.4.3 Working with the GUI

CoreMedia Content Cloud comes with different GUIs that support different tasks, such as managing content and user generated content or personalize the output. Their usage is described in separate manuals or chapters shown below. All these manuals are intended for editors and other non-technical staff.

CoreMedia Studio

CoreMedia Studio is the editor tool for all users. It is web based and requires no installation. Its easy-to-use interface with instant preview and form based editing makes content creation easier than ever. All other CoreMedia components integrate their GUI into *CoreMedia Studio*. Create new content, access your catalog data, manage your website or user generated content or publish new content to your customers.

- Read the Studio User Manual for details.

Elastic Social

The *Elastic Social* GUI is integrated with *CoreMedia Studio*.

- Read Chapter 8, *Working with User Generated Content* in *Studio User Manual* for details.

Adaptive Personalization Management

CoreMedia Adaptive Personalization comes with a management GUI that bases on the same technology as *CoreMedia Studio*. It lets you define selection rules, test user profiles and customer segments.

- Read Chapter 7, *Working with Personalized Content* in *Studio User Manual* for details.

1.4.4 Operating the System

The components of *CoreMedia Content Cloud* are configured using properties and you can use JMX to manage them. In addition, *CoreMedia Content Cloud* contains tools to monitor the status of its components. The following chapters are intended for operators and administrators but developers should read the chapters as well.

- Read the Operations Basics for some operational concepts and tasks.
- Each component manual contains a configuration chapter. Read this chapter if you want to learn details about a component's configuration.

1.4.5 Extending the System

CoreMedia Content Cloud is a very flexible software system, which you can adapt to all your needs. It integrates nicely with a Maven based development environment. CoreMedia is shipped with manuals that cover general development concepts such as the workspace and the *Unified API* and with manuals that cover the development with specific components.

General Concepts

- Read the [Blueprint Developer Manual] to learn how to develop extensions using *Blueprint* workspace.
- Read the Unified API Developer Manual in order to learn how to use the most fundamental CoreMedia API.
- Read Chapter 4, *Developing a Content Type Model* in *Content Server Manual* in order to learn how to define your own content types.

Developing editorial components

If you want to develop components for editorial purpose, you might refer to one of the following manuals:

- Read the Studio Developer Manual in order to learn how to extend *CoreMedia Studio*.
- Read the Unified API Developer Manual in order to learn how to develop client applications from the scratch accessing the *CoreMedia CMS* via the *Unified API*.
- Attend the *CoreMedia Studio Customization* training in order to learn how to extend *CoreMedia Studio*, see <https://www.coremedia.com/en/services/training/coremedia-training-program> for details.

Developing workflows

CoreMedia CMS contains a customizable *Workflow Server* that you can adapt to your needs. *CoreMedia CMS* is delivered with workflows that support publishing tasks, but the *Workflow Server* can support much more complicated processes.

- Read the Workflow Manual in order to learn how to define your own workflows.

Developing websites

CoreMedia CMS is a web content management system and its main purpose is to deliver content to various devices. Not only to a PC but to all gadgets such as mobile phones or tablet PCs.

- Read the Content Application Developer Manual in order to learn how to develop fast, dynamic websites that support sophisticated caching. Learn how to use the *CAE*.
- Read the Frontend Developer Manual in order to learn to write FreeMarker applications using the Frontend Workspace.
- Read the Headless Server Manual in order to learn how to access CoreMedia content via the *Headless Server* for your websites written with the framework of your choice.
- Read the Elastic Social Manual in order to learn how to extend your websites with user generated content, such as comments or ratings.
- Read the Adaptive Personalization Manual in order to learn how to deliver personalized content.
- Read the Search Manual in order to learn how to make your websites searchable.
- Attend the *Content Application Engineering* training, in order to get hands-on experience in the development of CAE applications. See <https://www.coremedia.com/en/services/training/coremedia-training-program> for details.
- Attend the *Frontend Development* training, in order to learn how to implement a new theme with FreeMarker, JavaScript and CoreMedia components. See <https://www.coremedia.com/en/services/training/coremedia-training-program> for details.
- Attend the *CoreMedia Headless* training, in order to learn how to implement sites with content from the Headless Server using GraphQL. See <https://www.coremedia.com/en/services/training/coremedia-training-program> for details.

1.5 Change Chapter

In this chapter you will find a table with all major changes made in this manual.

Section	Version	Description
---------	---------	-------------

Table 1.4. Changes

2. Overview of CoreMedia Content Cloud

CoreMedia Content Cloud is the next-generation experience management platform from CoreMedia that lets you build highly engaging, multi-channel branded eCommerce experiences as well as corporate sites for your global customers.

Now, you can easily bridge the gap between a pure eCommerce system which is focused on the more transactional aspects of the buying process and content-driven brand sites that focus on engaging user experiences.

CoreMedia Studio allows your business users to efficiently create and manage engaging digital experiences across the customer journey by adding editorial content and media assets from the CoreMedia CMS and by enriching the basic product information with storytelling by adding editorial content and media assets from the CoreMedia CMS. You can seamlessly blend catalog content and CMS content to any degree and on any delivery channel - and ensure brand-consistency through multi-language and multi-site localization tools.

The *CoreMedia Content Cloud* platform bundles all components to help you manage every aspect of your blended digital experiences from content to commerce:

- CoreMedia CMS platform
- *CoreMedia Studio*
- CoreMedia Blueprints for eCommerce and corporate sites
- *CoreMedia Commerce Hub and eCommerce Connectors*
- *CoreMedia Site Manager*
- *CoreMedia Headless Server*
- *CoreMedia Elastic Social*
- *CoreMedia Adaptive Personalization*
- *CoreMedia Advanced Asset Management*

CoreMedia Content Cloud was designed to empower your team in creating and managing highly relevant and engaging experiences for your customers from a single, easy-to-use business user interface. Customers should always get the information they need, independent of the device they use or the time they connect - delivered in an optimized fashion for the current customer's context.

CoreMedia Studio allows business users to create and manage experiences based on context and to define and test rules and customer segments for personalization in real-time. Content can be easily mixed with eCommerce catalog items. Editors can intuitively

select the products and categories from the catalog and place them on the site just as they are accustomed from other web content.

CoreMedia Content Cloud ships with CoreMedia Blueprints for eCommerce and corporate sites that provide a high-level of prefabrication of common features and use cases. The source code is provided for easy customization to your specific needs for competitive differentiation.

Built upon industry-leading best practices with a fully responsive and adaptive mobile first design plus a wealth of ready-to-use layout modules, your development team can jump start on a strong foundation proven in many customer projects whilst retaining full flexibility. A predefined Maven based development environment is provided.

Leveraging the CoreMedia CAE technology, you can dynamically and contextually combine relevant content from CoreMedia CMS, *CoreMedia Elastic Social* and your eCommerce system and deliver the combined experience in real-time on all channels with utmost performance using the sophisticated caching.

Headless Server allows you using *CoreMedia Content Cloud* in a headless way. *Headless Server* delivers content from the repository as JSON data over a GraphQL endpoint and is fully integrated in *CoreMedia Studio*. Therefore, you can preview and edit all changes in Studio.

Elastic Social allows your end users to contribute user-generated content such as product reviews, comments and ratings - whilst providing an intuitive moderation interface to your business users that also allows for editorial re-purposing of user-generated content.

CoreMedia Site Manager is the administration console for user and rights management.

2.1 Components and Architecture

CoreMedia Content Cloud has been developed to provide a universal solution for the creation and management of content.

The use of modern development tools and open interfaces enables the system to be flexibly adapted to enterprise requirements. For this purpose, worldwide standards for information processing, such as XML, HTML, HTTP, REST, Ajax, CORBA and the Java Platform are used or supported.

CoreMedia Content Cloud is a distributed system, that consists of several components for different use cases.

- *CoreMedia Content Server*
 - Content Management Server
 - Master Live Server
 - Replication Live Server
- *CoreMedia Workflow Server*
- *CoreMedia Content Application Engine*
- *CoreMedia Headless Server*
- *CoreMedia Importer*
- *CoreMedia Search Engine*
 - CoreMedia Content Feeder
 - CoreMedia CAE Feeder
- *CoreMedia Commerce Hub*
- eCommerce Connectors
- *CoreMedia Studio*
- *CoreMedia User Changes web application*
- *CoreMedia Site Manager*
- *CoreMedia Elastic Social*
- *CoreMedia Adaptive Personalization*
- *CoreMedia Advanced Asset Management*
- *CoreMedia Blueprints*

In addition, *CoreMedia Content Cloud* relies on some third-party systems:

- An *HCL Commerce Server* or *SAP Commerce Server* or *Salesforce Commerce Cloud* or *commercetools* for Commerce
- A relational database to store the content and user data
- A MongoDB NoSQL database to store the user generated content
- An LDAP server for user management

Conceptually, a CoreMedia system can be divided into the *Content Management Environment* where editors create and manage the content and the *Content Delivery Environment* where the content is delivered to the customers. Some components are used

in both environments, mostly to give you a realistic preview of your websites. **Figure 2.1, “System Overview”** [20] provides an overview of a *CoreMedia Content Cloud* system with all components installed:




Figure 2.1. System Overview

The following sections describe in short the aim of all components, some main technologies used in *CoreMedia Content Cloud* and give a short overview over the communication between the components.

2.1.1 Content Management Environment

The Content Management Environment is the place where you create and manage your website with the *Content Management Server* and *Studio* at its heart. A freely adaptable content model allows you to manage and deliver every type of digital content including text, video, images, music and many more.

The following components are solely located in the Content Management Environment:

CoreMedia Content Management Server

The *Content Management Server* manages the content in *CoreMedia Content Cloud*.

CoreMedia Studio

Studio is a web application. It integrates the complete workflow used by online editors from the creation, over management to preview publication of digital experiences with

contextual content. *Studio* is a web application that bases on modern standards such as Ajax. Therefore, it can be used like a common desktop application; fast, reliable but without installation. *Studio* integrates the *CoreMedia Adaptive Personalization* and *Elastic Social* GUI and has an integrated preview window where you can see your content in its context. You can even see the effects of personalization or time-dependent publication.

With the use of eCommerce Connectors, *CoreMedia Studio* lets you access the content of the eCommerce system. Content can be mixed easily with commerce catalog items. Editors can intuitively select the items from the catalog and place them on the site just as they are accustomed from other web contents.

CoreMedia User Changes application

The *CoreMedia User Changes* application is a listener, which shows the current work of the logged-in editor in *Studio*. This web application supports the functionality of Control Room in *Studio*.

CoreMedia Site Manager

CoreMedia Site Manager is a Java based rich client for administrators. It offers additional functionality to *Studio*.

CAUTION

The Site Manager is deprecated for editorial work.



CoreMedia Importer

You can use the Importer to import content from external sources into the management system. A freely adaptable importer framework based on JAXP is used to build content sets and pipelines and to invoke content transformations, using XSL, DOM and Streams.

CoreMedia Workflow Server

The *CoreMedia Workflow Server* is an application that executes and manages workflows. *CoreMedia Content Cloud* comes with predefined workflows for publication, translation and synchronization, but you can also define your own workflows.

CoreMedia Content Feeder

The *Content Feeder* is an application that collects the content from the *Content Management Server* and delivers it to the *Search Engine* for indexing. Thus, the *Content Feeder* is necessary to make content searchable in *Studio*. The *Content Feeder* listens for changes in the content and triggers the indexing of the changed or newly created content.

With the use of eCommerce Connectors, the *Content Feeder* lets you access items of the eCommerce system. This is needed if commerce issues should be integrated into the search in *Studio* as filter option. In this way, for example, invalid references to eCommerce items can be tracked down.

2.1.2 Content Delivery Environment

The Content Delivery Environment of *CoreMedia CMS* may consist of the *Master Live Server*, several *Replication Live Servers* (which are optional), the *CoreMedia CAE*, the *Headless Server*, *CoreMedia Elastic Social*, the *Search Engine* and *Adaptive Personalization*. It manages the approved and published online data and adds user generated content.

CoreMedia Master Live Server

The *Master Live Server* manages the CoreMedia repository in the Content Delivery Environment. It receives this content from the *Content Management Server* during publication. The *Content Application Engine* or the *Headless Server* fetches the content from the *Master Live Server* or from the *Replication Live Servers*.

CoreMedia Replication Live Server

The optional *Replication Live Servers* replicate the content of the *Master Live Server* in order to enhance reliability and to add scalable performance.

2.1.3 Shared Components

Some components of *CoreMedia Content Cloud* are used in both environments. The *Commerce Hub*, for example, is used in the Management Environment to manage content from the eCommerce system in *Studio* and in the Delivery Environment to include content from the eCommerce system into the pages generated by *Content Application Engine*.

Other components, like the *Content Application Engine*, are used to provide the editor with a preview of the live site.

Commerce Hub

Commerce Hub in combination with the eCommerce Connectors connects the CoreMedia CMS with the eCommerce server. It provides functionality to read catalog items, such as products or marketing spots, and to display them on web pages. You can also display price information and availability of products on the site. All commerce functions are provided by a commerce Java API that enables you to extend your shop application.

The eCommerce bridge also enables you to enrich pages rendered by the eCommerce system with content delivered by the CAE of *CoreMedia Content Cloud*. This way, you can enhance your shop pages with more engaging content.

Finally, the *CoreMedia eCommerce Bridge for IBM WebSphere Commerce* synchronizes user sessions between the *HCL Commerce* system and the CoreMedia system, so that users only have to sign in once.

CoreMedia Headless Server

CoreMedia Headless Server allows you to access CoreMedia content as JSON through a GraphQL endpoint. It provides clean APIs and easy access to content for all sorts of native apps, browser-based single-page applications or progressive web applications.

CoreMedia Studio integrates a preview of content delivered by the Headless Server.

With the use of eCommerce Connectors, the *CoreMedia Headless Server* lets you access items of the eCommerce system. This is mainly needed to compute page grid placements for commerce pages along the category hierarchy and to serve a mixed navigation.

CoreMedia Content Application Engine (CAE)

The *CoreMedia Content Application Engine* represents a stack for building client applications with *CoreMedia CMS*. It is a web application framework which allows fast development of highly dynamic, supportable and personalizable applications and websites. Sophisticated caching mechanisms allows for dynamic delivery even in high-load scenarios with automatic invalidation of changed content.

The *CoreMedia Content Application Engine* combines content from all CoreMedia components, from your eCommerce system and other third-party systems in so-called content beans and delivers the content to your customers in all formats. The preview in *Studio* and the website visited by your customers is delivered by the CAE

CoreMedia Search Engine

A *CoreMedia CMS* system comes with Apache Solr as the default search engine, which can be used from the editors on content management site and from the applications on content delivery site. The editor, for example, can perform a fast full text search in the complete repository. The pluggable search engine API allows you to use other search engines than Apache Solr for the website search.

CoreMedia CAE Feeder

The *CAE Feeder* makes content beans searchable by sending their data to the *Search Engine* for indexing.

CoreMedia Adaptive Personalization

CoreMedia Adaptive Personalization enables enterprises to deliver the most appropriate content to users depending on the 'context' – the interaction between the user, the device, the environment and the content itself. *CoreMedia Adaptive Personalization* is a powerful personalization tool. Through a series of steps it can identify relevant content for individuals. It can draw on a user's profile, commerce segment, preferences and even social network behavior. Use *CoreMedia Adaptive Personalization* to deliver highly relevant and personalized content to users, at any given moment in time.

The GUI is integrated into *CoreMedia Studio* for easy creation and testing of customer segments and selection rules.

CoreMedia Elastic Social

CoreMedia Elastic Social enables enterprises to engage with users, entering a conversation with them and stimulating discussion between them. Use *Elastic Social* to enable Web 2.0 functionality for Web pages and start a vibrant community. It offers all the features it takes to build a community – personal profiles, preferences, relationships, ratings and comments. *CoreMedia Elastic Social* is fully customizable to reflect the environment you want to create, and offers unlimited horizontal scalability to grow with the community and your business vision. It also integrates with *CoreMedia Studio* so you can manage comments and external users right from your common workplace.

CoreMedia Advanced Asset Management

CoreMedia Advanced Asset Management is a module that adds asset management functionality to the system. Digital assets, such as images or documents, and their licenses can be managed in *CoreMedia Studio*. From an asset, you can create common content items that can be used in the eCommerce system.

CoreMedia Blueprint

For a quick start, *CoreMedia Content Cloud* is delivered with two fully customizable blueprint applications including best practices and example integration of available features. *CoreMedia Blueprint* contains a ready-made content model for navigation and multi-language support. It contains for instance solutions for eCommerce items, taxonomy, rating, integration with web analytics software and user created page layouts. *CoreMedia Blueprint* comes as a Maven based workspace for development.

The workspace is the result of CoreMedia's long year experience in customer projects. As *CoreMedia Content Cloud* is a highly customizable product adaptable to your specific needs, the first thing you used to do when you started to work with *CoreMedia Content Cloud* was to create a proper development environment on your own. *CoreMedia Content Cloud* addresses this challenge with a reference project in a predefined working environment that integrates all CoreMedia components and is ready for start.

CoreMedia Blueprint workspace provides you with an environment which is strictly based on today's de facto standard for managing and building Java projects by using Maven.

Maven based environment

For details on each component, please refer to the individual manuals. Online documentation for all these components is available online at <https://documentation.core-media.com/cmcc-10>.

2.1.4 User Management

CoreMedia Content Cloud has an integrated user management, but also supports an LDAP server for user management.

Lightweight Directory Access Protocol (LDAP) is a set of protocols for accessing information directories. It is based on the standards within the X.500 standard, but is significantly simpler. Unlike X.500, LDAP supports TCP/IP, which is necessary for any type of Internet access. Because it's a simpler version of X.500, LDAP is sometimes called X.500-lite.

2.1.5 Communication Between the Components

Communication between the individual components on both the production side and the *Live Server* is performed via CORBA and HTTP. MongoDB uses the Mongo Wire Protocol. The *Production* and *Live Systems* can be secured with a Firewall if the servers are located on different computers. The servers contact the databases over a JDBC interface,

CoreMedia Content Cloud and the commerce systems communicate over REST interfaces. The concrete communication differs slightly based on the selected deployment scenario which are the *content-led scenario* for *HCL Commerce* and the *commerce-led scenario*.

Processing

On the production side of the CoreMedia system, content is created and edited with *CoreMedia Studio*, with custom clients or imported by the importers. Once editing or import of contents is completed, they are approved and published via the *CoreMedia Workflow*. During the publication process, the content is put online onto the *Master Live Server*. If available, *Replication Live Servers* get noticed and reproduce the changes. Then the content is put online by the *Replication Live Server*. User generated content is produced via *Elastic Social* and is stored in MongoDB. Editors can use the *Studio* plugin to moderate this content.

Content from the commerce server is not copied into the CoreMedia system. Instead, references to the content are hold and are resolved when content is delivered.

The *CoreMedia CAE* in combination with *Adaptive Personalization* and *Elastic Social* creates dynamic HTML pages or any other format (XML, PDF, etc.) from the internal and external content and CoreMedia templates.

Headless Server, on the other hand, delivers content from *CoreMedia Content Cloud* as JSON data via a GraphQL endpoint. This gives you you full flexibility in choosing your frontend technology.

2.2 CoreMedia Blueprint Sites

CoreMedia Content Cloud Experience Platform contains Brand Blueprint and eCommerce Blueprint for a quick start. They come with four different sites that support different use cases.

Aurora Augmentation (en)

This site belongs to the eCommerce Blueprint. It is intended for a company that wants to extend their *HCL Commerce* B2C online shop with engaging assets and content from the CoreMedia system, the so called commerce-led scenario (see Chapter 8, *Commerce-led Integration Scenario* in *Connector for HCL Commerce Manual*). Editors can add inspiring content from the CMS such as images, videos, articles to the standard commerce pages. They do not need to enter the commerce system, but can use *CoreMedia Studio* for their work, taking advantage of the sophisticated preview of *Studio*.

Aurora B2B Augmentation (en)

This site belongs to the eCommerce Blueprint. It is intended for a company that wants to extend their *HCL Commerce* B2B online shop with engaging content from the CoreMedia system, the so called commerce-led scenario (see Chapter 8, *Commerce-led Integration Scenario* in *Connector for HCL Commerce Manual*). This site only works with FEP8. The use case is similar to the one of the Aurora Augmentation site for B2C shops. In addition, the *Studio* preview supports contracts, so that a test persona will only see content related to products from the commerce system which is allowed by their contract.

Calista Augmentation (en)

This site belongs to the eCommerce Blueprint and implements the experience-led hybrid blended scenario, where pages are delivered by both systems, the corporate and the eCommerce system, transparent for the user. Therefore, it is intended for a company that wants to offer their corporate content as well as their eCommerce shop as one engaging experience for its users on all devices with a fully responsive design. You can manipulate the navigation through the catalog pages and add complete new navigation paths. You can augment

	product detail pages with content from the CMS. Categories are rendered from the CAE. However, content and settings are inherited along the catalog category structure.
Hybris Apparel (uk)	This site belongs to the eCommerce Blueprint. It is intended for a company that wants to extend their SAP Hybris Commerce B2C online shop with engaging assets and content from the CoreMedia system, the so called commerce-led scenario (see Chapter 5, <i>Commerce-led Integration Scenario</i> in <i>Connector for SAP Commerce Cloud Manual</i>). Editors can add inspiring content from the CMS such as images, videos, articles to the standard shop pages. They do not need to enter the commerce system, but can use <i>CoreMedia Studio</i> for their work, taking advantage of the sophisticated preview of <i>Studio</i> .
Chef Corp. Site (en/de)	This site belongs to the Brand Blueprint. It is intended for a company that wants to offer their corporate site as an engaging experience for its users on all devices with a fully responsive design. The site contains no eCommerce shop, but the company can use the CoreMedia catalog to manage and present their products on the website.

Removing Sites

You can remove sites and features that you do not need from your workspace.

To remove the Aurora sites or Hybris Apparel site remove the eCommerce extension as described in [Section "Removing the eCommerce Blueprint" \[103\]](#).

To remove the Brand Site, remove the corporate extension as described in [Section "Removing the Brand Blueprint" \[103\]](#).

3. Getting Started

In this chapter you will learn the basics for the quickest way to get started using *CoreMedia Content Cloud*.

- [Section 3.1, “Prerequisites” \[30\]](#) describes the software and hardware requirements that you need to fulfill to work with *CoreMedia Content Cloud*.
- [Section 3.2, “Quick Start” \[35\]](#) describes the fastest way to get a CoreMedia system up and running.

3.1 Prerequisites

In order to work with the *Blueprint* workspace you need to meet some requirements.

NOTE

For an overview of exact versions of the supported software environments (Java, servlet container, databases, operating systems, directory services, web browsers) please refer to the Supported Environments document at <http://bit.ly/cmcc-10-supported-environments>.



CoreMedia Account

In order to get access to the download page, to the CoreMedia contributions repository and to CoreMedia's Maven repository [<https://repository.coremedia.com>], you need to have a CoreMedia account. See [Section 1.3.1, "Registration" \[5\]](#) for details. If in doubt, contact CoreMedia support to validate your permissions (see [Section 1.3.5, "CoreMedia Support" \[10\]](#)).

NOTE

CoreMedia User Orientation for CoreMedia Developers and Partners

Find the latest overview of all CoreMedia services and further references at:

<http://documentation.coremedia.com/new-user-orientation>



Find the current online documentation at:

- <https://documentation.coremedia.com/cmcc-10>

Find the download links at the CoreMedia release page at:

- <https://releases.coremedia.com/cmcc-10>

Internet access

CoreMedia provides the *CoreMedia Content Cloud* components as Maven artifacts. These components in turn depend on many third-party components. If your operator has not yet set up and populated a local repository manager, you need Internet access so that Maven can download the artifacts.

NOTE**Maven Repository and Internet Access**

The *CoreMedia Blueprint* workspace relies heavily on Maven as a build tool. That is, Maven will download CoreMedia artifacts, third-party components and Maven plugins from the private CoreMedia repository and other, public repositories (Maven Central Repository, for example). This might interfere with your company's internet policy. Moreover, if a big project accesses public repositories too frequently, the repository operator might block your domain in order to prevent overload. The best way to circumvent both problems is to use a repository manager like **Sonatype Nexus**, that decouples the development computers from direct Internet access.



Maven Repository Manager

CoreMedia strongly recommends to use a repository manager to mirror CoreMedia's Maven repository, for example **Sonatype Nexus**. Alternatively, if a repository manager is not available, configure your credentials for the CoreMedia Maven repositories in your `~/.m2/settings.xml` file as shown below. Simply replace `USERNAME` and `PASSWORD` with your CoreMedia user name and password. It is strongly recommended, that you do not enter the password in plaintext in the `settings.xml` file but encrypt the password. To do so, follow the instructions at <http://maven.apache.org/guides/mini/guide-encryption.html> or any other available Maven documentation.

```
<?xml version="1.0" encoding="UTF-8"?>
<settings xmlns="http://maven.apache.org/SETTINGS/1.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/SETTINGS/1.0.0
    http://maven.apache.org/xsd/settings-1.0.0.xsd">
  <interactiveMode>false</interactiveMode>
  <servers>
    <server>
      <id>coremedia.external.releases</id>
      <username>USERNAME</username>
      <password>PASSWORD</password>
    </server>
  </servers>
</settings>
```

MAVEN_OPTS

Maven requires the following minimal memory settings:

```
MAVEN_OPTS=-Xmx2048m
```

3.1.1 Developer Setup

These are the prerequisites for your local machine where you develop CAE templates or *CoreMedia Studio* extensions, for example.

Hardware

- At least a dual-core CPU with 2GHz, a quad-core CPU is recommended, because *CoreMedia CMS* code makes heavy use of multithreading.
- The minimum RAM you need is 8 GB which is enough if your locally tested components are connected to remote Test System Setup.

Required Software

- A supported Java SDK (see <http://bit.ly/cmcc-10-supported-environments>). The variable `JAVA_HOME` must be set.
- A supported browser (see <http://bit.ly/cmcc-10-supported-environments>)
- A supported **Maven** installation (see <http://bit.ly/cmcc-10-supported-environments>)
- An IDE. CoreMedia suggests IntelliJ Idea because it has the best support for *CoreMedia Studio* development.
- A supported container environment, see [Section 3.2.2, “Docker Compose Setup” \[40\]](#) and <http://bit.ly/cmcc-10-supported-environments> for details.
- A supported Sencha Cmd release (see <http://bit.ly/cmcc-10-supported-environments>). Install from <https://www.sencha.com/products/extjs/cmd-download/> on your computer. Ensure that Sencha Cmd is available in your `PATH` variable.

Some Maven modules need more memory than Sencha Cmd provides per default. You can pass additional JVM options via the `jangaroo-maven-plugin` in the `pom.xml` of the corresponding module by using the `senchaJvmArgs` configuration. For the `studio-base-app` this value is already set to `-Xms512m -Xmx2048m` and can be overridden via the Maven property `studio-base-app.senchaJvmArgs`.

- If you want to build the workspace with tests, you need an up-to-date version of Google Chrome installed on your computer. It must be contained in your path. Alternatively, you can use other supported browsers (Firefox, Edge, Internet Explorer 11) or PhantomJS. If you wish to do so, see [section “Joo Unit Testing” \[128\]](#).
- CoreMedia license files for starting the various *Content Servers*. If you do not already have the files, request your licenses from the CoreMedia [support](#).

3.1.2 Test System Setup

These are the prerequisites for the machine on which you want to install the Test System Setup

Hardware

CPU	Mem [GiB]	Storage [GiB]
4	16	32

Table 3.1. Overview of minimum / recommended Hardware requirements

Required Software

- A supported container environment (see <http://bit.ly/cmcc-10-supported-environments>).
- A supported Docker Compose release (see <http://bit.ly/cmcc-10-supported-environments>).

3.1.3 Additional Software for eCommerce Blueprint only

Depending on the eCommerce Connector you use, you need one of the following eCommerce systems:

- *HCL Commerce*
- *SAP Hybris Commerce*
- *Salesforce Commerce Cloud*
- *commercetools*

In Connector for HCL Commerce Manual you will learn how to install and configure the CoreMedia software in the *HCL Commerce* system.

In Connector for SAP Commerce Cloud Manual you will learn how to install and configure the CoreMedia software in the *SAP Hybris Commerce* system.

In Connector for Salesforce Commerce Cloud Manual you will learn how to install and configure the CoreMedia software in the *Salesforce Commerce Cloud* system.

In Commercetools Connector Manual you will learn how to install and configure the CoreMedia software in *commercetools*.

NOTE

For an overview of exact versions of the supported software environments (especially the eCommerce systems) please refer to the Supported Environments document at <http://bit.ly/cmcc-10-supported-environments>.



3.2 Quick Start

With *CoreMedia Content Cloud* you do not get a program to install and run, but a workspace to develop within, to build with Maven and to deploy artifacts from. See [Chapter 2, Overview of CoreMedia Content Cloud \[17\]](#) for an overview.

By default, you have two ways to build and deploy the workspace. Both approaches base on the built of the Blueprint Workspace described in [Section 3.2.1, "Building the Workspace" \[35\]](#).

Different deployment scenarios

- The Docker Test System Setup is the recommended way. It uses the Docker images to start the systems components. See [Section 3.2.2, "Docker Compose Setup" \[40\]](#) for details.
- The Deployment Archive. It is a Zip file that contains all application artifacts required to deploy on a supported Linux system. It uses Chef to set up the CoreMedia system.

The subsections guide you through all steps you have to perform in order to get the CoreMedia system running on a machine using the Docker Test System Setup approach. The quick start describes only one path, no options or advanced configurations are described. The "Further Reading" section of each step contains links to additional content, but you do not need to read these chapters for the purpose of the quick start.

NOTE

You need Internet access and a resolvable host name to get everything up and running.



3.2.1 Building the Workspace

What do you get?

When you are finished with all steps, you will have built the CoreMedia Blueprint Workspace and the required Docker images for all CoreMedia applications.

Step 1: Getting a Login for CoreMedia

Goal

You have a login to the CoreMedia software download page, the contributions GitHub repository, the documentation and the CoreMedia artifact repository.

Steps

1. Ask your project manager for your company's account details or contact the CoreMedia support. Keep in mind, that you have to ask explicitly for the access rights to the CoreMedia GitHub contributions repository. See CoreMedia's website for the contact information of the support at <http://www.coremedia.com/support>.

Check

Got to <https://documentation.coremedia.com/cmcc-10> and <https://github.com/core-media-contributions/coremedia-blueprints-workspace> and enter your credentials. You should be able to use the online documentation and see the contributions repository.

Step 2: Getting License Files for the CoreMedia System

Goal

You have licenses for the CoreMedia system.

Steps

Ask your project manager, your key account manager or your partner manager for the CoreMedia licenses.

Check

You have a Zip file that contains three zipped license files. In [Section 3.2.2, "Docker Compose Setup" \[40\]](#) you will learn where to put the license files.

Further Reading

- See Section 4.6, "CoreMedia Licenses" in *Operations Basics* for details about the license file format.

Step 3: Checking the Hardware Requirements

Goal

You are sure, that your computer meets the hardware requirements as described in [Section 3.1, "Prerequisites" \[30\]](#).

Step 4: Checking and Installing all Required Third-Party Software

Goal

All required third-party software (such as Java, Git, Maven, Sencha Cmd ...) is installed on your computer and has the right version.

Steps

1. Open the supported environments document at <http://bit.ly/cmcc-10-supported-environments> and check that you have installed the right version of Java and that you have the right OS. The `JAVA_HOME` variable must be set.
2. Check that a supported Maven version is installed [see <http://bit.ly/cmcc-10-supported-environments>].
3. Check that a supported Sencha Cmd version is installed on your computer [see <http://bit.ly/cmcc-10-supported-environments>].

Some Maven modules need more memory than Sencha Cmd provides per default. You can pass additional JVM options via the `jangaroo-maven-plugin` in the `pom.xml` of the corresponding module by using the `senchaJvmArgs` configuration. For the `studio-base-app` this value is already set to `-Xms512m -Xmx2048m` and can be overridden via the Maven property `studio-base-app.senchaJvmArgs`.

4. Check that a supported container environment is installed on your computer [see <http://bit.ly/cmcc-10-supported-environments>]. See Section “[Docker Installation](#)” [40] for installation instructions.

Further reading

- [Section 3.1, “Prerequisites”](#) [30] describes the required software in more detail.

Step 5: Cloning the Workspace

Goal

You have the *CoreMedia Blueprint* workspace on your hard disk.

Steps

1. Make sure that you have access to <https://github.com/coremedia-contributions/core-media-blueprints-workspace>. If you encounter a 404 error, then you are probably not logged in at GitHub or you do not have sufficient permissions yet.
2. When you use a Windows system, make sure that the Git configuration parameter `core.autocrlf` is set to “input”. Otherwise, some init files will not run properly in your test machine. Because on checkout, Git would change the line endings to Windows style.
3. On your local machine, clone the repository into a directory `blueprint` using Git:

WARNING

Path length limitation in Windows

The *CoreMedia Blueprint* workspace contains long paths and deeply nested folders. If you install the *CoreMedia Blueprint* workspace in a Windows environment, keep the installation path shorter than 25 characters. Otherwise, unzipping the workspace might fail or might lead to missing files due to the 260 bytes path limit of Windows.



```
git clone
https://github.com/coremedia-contributions/coremedia-blueprints-workspace
blueprint
```

4. In the cloned repository, get a list of all tags:

```
git tag
```

5. Create your working branch from the tag you want to use as your starting point:

```
git checkout -b <yourBranchName> <tagName>
```

Check

The Git clone command has succeeded.

Further reading

- [Chapter 4, *Blueprint Workspace for Developers* \[52\]](#) describes the structure of the workspace, the concepts behind the workspace and how you can work with the workspace.
- [Section 4.2.2, "Configuring the Workspace" \[104\]](#) describes further configuration of the workspace which is required for development and deployment.
- On <https://releases.coremedia.com/cmcc-10> click the link to the latest download to find a description on how to download a specific release.

Step 6: Getting the blob Demo Content

The textual content and the themes are already part of the workspace you have cloned before. However, to keep the workspace small, the blob content is supplied in a separate file.

Goal

The workspace contains the blob files of the CoreMedia demo content (videos, images, ...).

Steps

1. Open the releases site <https://releases.coremedia.com/cmcc-10> and click the link to the current release.
2. Click the "content-blobs archive" link on the site and download the file.
3. Extract the archive into the workspace you have cloned in step 5.

Step 7: Configuring the Repository Settings and Check Maven Configuration

Goal

Your Maven `settings.xml` file contains the settings required to connect with the CoreMedia Nexus repository.

Steps

1. Follow the steps described in [Section 3.1, "Prerequisites" \[30\]](#).

Check

When you build the workspace, all artifacts are found.

Step 8: Building the Workspace

Goal

The workspace has been build, so that all artifacts and Docker images are built. The build takes some time. On an Intel i7 processor with 16GB RAM around 20 minutes.

Steps

In the main directory of the workspace call:

```
mvn clean install -DskipTests -Pwith-docker
```

Check

The Maven build ends with message "Build successful".

Further reading

- [Section 4.2.1, "Removing Optional Components" \[91\]](#) describes how you can remove parts of the workspace that you do not need.
- [Section 4.2.4, "In-Memory Replacement for MongoDB-Based Services" \[106\]](#) describes how you can replace MongoDB for Studio services with an in-memory solution.

Now, you have build the Blueprint workspace and the Docker images. Continue with [Section 3.2.2, “Docker Compose Setup” \[40\]](#) in order to configure and start the Docker deployment.

3.2.2 Docker Compose Setup

This tutorial will guide you through the first steps to start the CoreMedia Content Cloud Services using `docker compose`, which is a tool to simplify the deployment of development environments using docker.

Prerequisites

Docker knowledge is not required, but for first starters with this technology, it is highly recommended to start with simpler projects until the infrastructure is running and basic knowledge about the tooling has been acquired. As a good start, you can play around online in one of the free tutorials on [learndocker](#) or [katacoda](#).

Docker Installation

Colima - Containers in Linux Machines

Colima is a free virtualization tooling for Mac OS to provide the same seamless developer experience as Docker Desktop. It is based on **Lima** (Linux Machines), which is using the same QEMU stack as Docker Desktop. Lima ist also the foundation of **Rancher Desktop**, the Kubernetes developer tooling setup by Rancher.

To install Colima, Docker and Docker Compose run the brew installation formulae for each app:

- [colima](#)
- [docker](#)
- [docker-compose](#)

```
brew install colima docker docker-compose
```

To start Colima run:


```
colima start --cpu 4 --memory 14
```

After the VM has started, you should be able to use the Docker client. Be aware, that instead of `~/.docker/daemon.json`, Colima uses `~/.colima/docker/daemon.json` to configure the runtime.

```
DOCKER_HOST=unix:///Users/<YOUR USER NAME>/.colima/docker.sock
```

Rancher Desktop

A new contender to replace Docker Desktop is **Rancher Desktop**. It is designed to bootstrap Kubernetes developers, but it can be installed using the dockerd runtime from the Moby project to replace Docker Desktop completely. At its core, Rancher Desktop is also based on Lima like Colima, but it adds a nice UI and Kubernetes integration.

Rancher Desktop can be installed using an installer binary and supports not only MacOS but also Linux and Windows. The installation is easy, but you have to make sure to completely uninstall Docker Desktop before installing Rancher Desktop.

After installing Rancher Desktop there are two steps required to make it a full Docker Desktop replacement:

- Uninstall Kubernetes if you don't need it. If you don't uninstall Kubernetes, you will always have those containers listed, when running `docker ps`. Uninstalling can be done by executing the following two calls and wait a couple of minutes until Kubernetes uninstalls its containers.

```
kubect1 config use-context rancher-desktop  
kubect1 delete node lima-rancher-desktop
```

- If you need to customize the `daemon.json` file, you need to workaround Rancher Desktops early stages and lack of UI integration. The `daemon.json` file is only accessible in the Lima VM and to access it you need to install the Lima client and login to the VM and edit the file manually using `vi`.

1. Install Lima

```
brew install lima
```

2. Configure the Lima client to target the Rancher Desktop VM

```
export LIMA_HOME=~/.Library/Application\ Support/rancher-desktop/lima
```

3. Log into the VM

```
limactl ls
# identify the ordinal of the rancher VM, by default it should be 0
limactl shell 0
```

4. In the Lima VM, edit the `daemon.json` file

```
sudo vi /etc/docker/daemon.json
# restart the docker service to apply the configuration changes
sudo service docker restart
```

Windows

- [Installer](#)
- [Getting Started](#)
- Make sure that the following paths and files are excluded from being scanned by any real time virus scanner:
 - The location of Hyper-V :

```
C:\ProgramData\Microsoft\Windows\Hyper-V
```

- The location of your disk image. The defaults are

```
C:\Users\Public\Documents\Hyper-V\Virtual hard disks\MobyLinux.vhxd
```

- The executables for virtualization

```
vmms.exe
vmwp.exe
```

- The file extensions for virtualization files:

```
VHD
VHDX
```

- Make sure that no process is already listening on ports 80 and 443. You may run `net stop http` in an elevated PowerShell to stop these processes. If port 80 is still blocked, you may need to stop the `WWW web publisher service` as well.
- Be careful with hibernation, make sure to stop all containers, before hibernate your workstation.

Docker Configuration

After the installation was successful and Docker has been started, proceed with the following configurations. If you read the getting started documentation of Docker, you should easily find the corresponding settings.

- Increase Disk size to at least 30GB
- Increase RAM to at least 14 GB
- On Windows, you also need to:
 - share the Drive C in the "Shared Drives" settings page.
 - enable the "Expose the daemon without TLS" toggle in the general settings page.

Docker Compose Configuration

Configure your docker compose environment by creating or editing your `.env` file. All environment variable references in the Docker Compose files, can be configured using this file. Be aware, that environment variables in the current process environment have precedence over variables defined in the `.env` file. Below, you will find an example `.env` file.

In the `.env` file you can configure the following properties. All relative paths shown here are relative to the `global/deployment/docker` directory.

- Make sure `compose/development.yml` is included in the `COMPOSE_FILE` variable, it is required to expose the container internal ports to the docker host.
- Make sure `compose/development-local.yml` is included in the `COMPOSE_FILE` variable, it is required for content import from Blueprint and optionally for loading licenses from local `coremedia-licenses` directory.
- For the `docker compose` development setup, make sure that you have the licenses placed at the following locations:

```
coremedia-licenses/cms-license.zip
coremedia-licenses/mls-license.zip
coremedia-licenses/rls-license.zip
```

Zip files added below this directory are by default excluded from Git version control. If you place the license files in this directory, you must not set an environment variable for the license location!

Alternatively, you may define environment variables with license URLs and the server containers will download them at runtime. You will find the corresponding environment variables in the `.env` example below.

- For the development setup, make sure that you have created or provide themes. Set either `THEMES_ARCHIVE_URL` or `THEMES_ARCHIVE_FILE` in the `.env` file. To re-import the themes set `FORCE_REIMPORT_THEMES` to `true`.

If you use the provided CoreMedia themes, you must not set these environment variables because the default setting is sufficient.

- For the development setup, make sure that you have created or provide content. Set either `CONTENT_ARCHIVE_URL` or `CONTENT_IMPORT_DIR` in the `.env` file. To re-import the content set `FORCE_REIMPORT_CONTENT` to `true`.

If you use the provided CoreMedia test data, you must not set these environment variables because the default setting is sufficient.

- Depending on the eCommerce system[s] you want to connect to, you will need to set these additional variables:

HCL WebSphere Commerce

```
SPRING_PROFILE=dev-wcs
COMPOSE_FILE=compose/default.yml:compose/development-wcs.yml
WCS_HOST=your.wcs.host
```

SAP Hybris

```
COMPOSE_FILE=compose/default.yml:compose/development-hybris.yml
```

Salesforce Commerce Cloud

```
COMPOSE_FILE=compose/default.yml:compose/development-sfcc.yml
```

By default, you can start with this file:

```
# This sets the compose path separator to ":" for all OS.
COMPOSE_PATH_SEPARATOR=:

# Configure a list of compose files you want to apply and
# separate them using the value of the COMPOSE_PATH_SEPARATOR.
# Be advised that ordering is crucial and last definitions
# override preceeding ones.
# compose/default.yml - unconfigured services
# compose/development.yml - development configuration
# compose/development-local.yml - local licenses / content
#
# for most cases this should be your default.
COMPOSE_FILE=compose/default.yml:compose/development.yml:compose/development-local.yml

# Optional properties

# With this variable, you can set the prefix of the image repository.
# Set this to use images from a remote registry, that is,
# REPOSITORY_PREFIX=my.registry/cmcc would result in a studio-server
# image my.registry/cmcc/studio-server
# REPOSITORY_PREFIX=my.registry/cmcc

# With this variable, you can set the prefix of the image repository for
# the Commerce Adapter Docker images. Set this to use images from a remote
# registry.
# COMMERCE_REPOSITORY_PREFIX= my.registry/cmcc
```

```
# The version tags of the commerce adapter service images to be used.
# COMMERCE_ADAPTER MOCK_VERSION=1.2.3
# COMMERCE_ADAPTER_SFCC_VERSION=1.2.3
# COMMERCE_ADAPTER_HYBRIS_VERSION=1.2.3
# COMMERCE_ADAPTER_WCS_VERSION=1.2.3

# The environment fully qualified domain name to use for the system.
# If not set, docker.localhost will be used.
# ENVIRONMENT_FQDN=docker.localhost

# enable debug agent for all spring boot apps. If you want to enable
# this only for a single service, you need to set the environment
# variable explicitly at that service.
# JAVA_DEBUG=true

# Service Specific variables

# The license url/path for the content-management-server
# CMS_LICENSE_URL=/coremedia/licenses/cms-license.zip

# The license url/path for the master-live-server
# MLS_LICENSE_URL=/coremedia/licenses/mls-license.zip

# The license url/path for the replication-live-server
# RLS_LICENSE_URL=/coremedia/licenses/rls-license.zip

# The mail server for elastic social registration mails
# ELASTIC_SOCIAL_MAIL_SMTP_SERVER=localhost

# Theme Import

# Themes can be imported from a file location or from an URL
# pointing to an zip archive containing the themes.
# By default, the variable points to the path
# /coremedia/import/frontend.zip within the management-tools
# container. To pass in an archive from your hosts file system
# include the development-local.yaml file in your
# COMPOSE_FILE environment variable and configure only the path
# on your host system using the THEMES_ARCHIVE_FILE env var.
# If you don't configure that variable, the default will point
# to the frontend.zip in your workspace.
# THEMES_ARCHIVE_URL=
# THEMES_ARCHIVE_FILE=

# Force reimport of themes when set to true
# FORCE_REIMPORT_THEMES=false

# Content Import

# The directory from which the content should be imported. By default,
# this points to the content/test-data/target/ directory of the test-data
# module
# in the CoreMedia Blueprints workspace.
# CONTENT_IMPORT_DIR=

# Forces the reimport of the content when set to true
# FORCE_REIMPORT_CONTENT=false

# The url of a webserver, serving all content blobs during the
# server-import. If you added the content blobs to the workspace,
# you can leave this field empty. This is a CI development
# optimization to keep content image blobs out of the VCS history.
# BLOB_STORAGE_URL=

# The url to a zip archive containing content, users and optionally
# themes for import. The layout in the archive should be the same
# as the test-data module creates. This is a CI development feature
# to import content from a separated build process.
# CONTENT_ARCHIVE_URL=
```

```
# Skips the whole content and theme import when set to true
# SKIP_CONTENT=false
```

Note that you cannot set arbitrary environment variables in the `.env` file and expect, that they will be picked up by the CoreMedia Spring Boot applications. Only the variables, being referenced in compose files, can be used here.

For more information about this tooling option, visit the official [Docker Compose](#) documentation.

DNS Configuration

To access the applications, you need to configure your hosts DNS resolution. Changing this requires admin rights.

Without Administrator rights: Without administrator rights, you need to set the following environment variables in the `.env` file to the DNS resolvable host name of your computer:

- `ENVIRONMENT_FQDN`
- `CMS_ORB_HOST`
- `MLS_ORB_HOST`
- `WFS_ORB_HOST`

With Administrator rights: With administrator rights edit the configuration file for the host mappings at the following locations:

- On Linux / Mac OS `/etc/hosts`
- On Windows `%SystemRoot%\System32\drivers\etc\hosts`

Make sure that it contains the following mappings:

```
# Development names to connect from Maven / IDEA
127.0.0.1 workflow-server
127.0.0.1 content-management-server

# Administrative Hosts
127.0.0.1 docker.localhost
127.0.0.1 overview.docker.localhost
127.0.0.1 monitor.docker.localhost

# Corporate Hosts
127.0.0.1 corporate-de.docker.localhost
127.0.0.1 corporate.docker.localhost

# Management Hosts
127.0.0.1 studio.docker.localhost
127.0.0.1 preview.docker.localhost
127.0.0.1 site-manager.docker.localhost

# Commerce Hosts
```

```
127.0.0.1 helios.docker.localhost
127.0.0.1 calista.docker.localhost
127.0.0.1 apparel.docker.localhost
127.0.0.1 sitegenesis.docker.localhost
127.0.0.1 shop-preview-ibm.docker.localhost
127.0.0.1 shop-ibm.docker.localhost
127.0.0.1 shop-preview-production-ibm.docker.localhost
127.0.0.1 shop-preview-hybris.docker.localhost
127.0.0.1 shop-hybris.docker.localhost
127.0.0.1 shop-preview-sfcc.docker.localhost
127.0.0.1 shop-sfcc.docker.localhost
127.0.0.1 shop-tools-sfcc.docker.localhost
```

Reducing the Setup

If you do not want to start the whole stack, you can start only the required components. All services define their dependencies using the `depends_on` directive. Running a simple `docker compose up -d content-management-server workflow-server` therefore will also start `mysql`, `mongodb` and `solr`.

You can get all available services by running `docker compose config --services`

```
docker compose config > docker-compose.yml
```

You can then remove everything you don't want. `docker-compose.yml` is ignored by Git with the default `.gitignore` file. You only have to make sure, that in your `.env` file

```
COMPOSE_FILE=docker-compose.yml
```

is set, otherwise the file won't be loaded.

Of course, there are a lot of toggles for your convenience:

- `JAVA_DEBUG` - default ports XXX06 for JDWP
- `FORCE_REIMPORT_CONTENT` - once imported, the content won't reimport unless forced
- `SKIP_CONTENT` - same as not running the `management-tools` container.

Having multiple backends in parallel or keep multiple backend data volumes

In order to work on multiple tasks in an interleaved mode, you may want to keep the example content of each setup and switch back and forth. In order to do so, you can use the `COMPOSE_PROJECT_NAME`. If set docker compose will prefix all resources with the set value, that is, a volume will be named `JIRA-55_db-data` if `COM`

`POSE_PROJECT_NAME=JIRA-55`. The only thing to keep in mind with this approach is to never use the `-v` flag when running `docker compose down`.

Starting the Docker Setup

Make sure that you have build the workspace and the Docker images. To build the Docker images the Maven profile `with-docker` must be activated. To check whether you have build the images you can list the available images using the following command:

```
docker images
```

The result should look like this but should contain image names like `cae-live` or `content-server`:

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
coremedia/cae-preview	latest	a8f9d245fbbe	10 hours ago	296MB
coremedia/content-server	latest	8f6045472222	10 hours ago	272MB

If there are no images listed, you probably did not activate the Maven profile. To build with the active Maven profile, run the following command:

```
mvn clean install -Pwith-docker
```

After the images have been built, you can change the directory to the docker setup:

```
cd global/deployment/docker
```

Prestart Check

In order to make sure that there are no conflicts with preexisting setups, you can run the following steps to delete all preexisting setups:

- `docker compose down -v` this command should stop and remove all running containers and volumes that are associated with the project defined by the Docker Compose files. The execution of this command needs to be successful to start up a new clean system. The warnings can be ignored, because if the volume does not exist, it cannot be removed.
- `docker ps --format "table {{.Names}}\t{{.Ports}}" -a` this command lists all running containers and their mapped ports. Make sure that these ports do not conflict with the standard port mappings of the CoreMedia applications, when run on a single node.

Start the services

To list the services that will be started execute the following command:

```
docker compose config --services
```

The result should look similar to this, depending on the value of `COMPOSE_FILE`:

```
mysql
mongodb
solr
content-management-server
master-live-server
replication-live-server
workflow-server
content-feeder
cae-feeder-preview
cae-feeder-live
user-changes
elastic-worker
studio-server
studio-client
cae-preview
cae-live
site-manager
headless-server-preview
headless-server-live
traefik
```

Now you can start the services by running the following command:

```
docker compose up -d --build
```

The flag `--build` forces `docker compose` to build the images, which are not included into the Maven build and which are only required in the development setup, such as `mysql`, `mongodb`, `overview`, `traefik` and the commerce proxies. You can omit this flag on subsequent builds, if there aren't any changes to these images.

The result should look like the following output.

```
Creating elastic-worker      ... done
Creating traefik             ... done
Creating mongodb             ... done
Creating management-tools    ... done
Creating master-live-server  ... done
Creating headless-server-preview ... done
Creating studio-client       ... done
Creating cae-live            ... done
Creating cae-preview         ... done
Creating replication-live-server ... done
Creating cae-feeder-live     ... done
Creating solr                ... done
Creating overview            ... done
Creating content-management-server ... done
Creating mysql               ... done
Creating studio-server       ... done
Creating workflow-server     ... done
Creating headless-server-live ... done
Creating content-feeder      ... done
Creating site-manager        ... done
```

```
Creating user-changes          ... done
Creating cae-feeder-preview    ... done
```

Wait until the services are healthy

To make sure that the system is up and running and all services are healthy, you can use the `docker ps` command. By default, it will print out the healthy state for each service.

```
docker ps
```

The result should look like this excerpt:

cae-preview	coremedia/cae-preview	Up	About a minute	(healthy)
cae-live	coremedia/cae-preview	Up	About a minute	(unhealthy)
studio-server	coremedia/studio-server	Up	About a minute	(health:starting)

Now you have to wait until all services are healthy. You can track this by either running a command loop in your shell, or by visiting the overview page in your browser.

Watch health state using the overview page

Open the <https://overview.docker.localhost> and scroll down to the table where the status is shown on the right side. In case the service is healthy or unhealthy, a green or red icon is shown.

Watch health state using the shell

- On Linux / Mac OS

```
watch -n 1 "docker ps"
```

- On Windows (PowerShell)

```
while($true) { Clear-Host; docker ps; sleep 5 }
```

For better visibility of this command, you can configure the formatting by editing/creating the `~/.docker/config.json` with the following content:

```
{  
  "psFormat" : "table {{.Names}}\\t{{.Image}}\\t{{.Status}}"  
}
```

Login to CoreMedia Studio

Click on the **Open Studio** link at the top of the overview page or simply open the link to Studio directly by using the previously configured domain name:

- <https://overview.docker.localhost>
- <https://studio.docker.localhost>

NOTE

The import of the test data may take some time. So, you may not be able to login as one of the predefined users like Rick C or some content is missing.



Cleanup Services

To shut down the services, simply run the following command:

```
docker compose down
```

Cleanup Services and Content

To shut down all services and clear all created volumes including the databases, simply run the following command:

```
docker compose down -v
```

4. Blueprint Workspace for Developers

CoreMedia Blueprint workspace is the result of CoreMedia's long year experience in customer projects. As *CoreMedia CMS* is a highly customizable product that you can adapt to your specific needs, the first thing you used to do when you started to work with *CoreMedia CMS* was to create a proper development environment on your own. *CoreMedia Blueprint* workspace addresses this challenge with a reference project in a predefined working environment that integrates all CoreMedia components and is ready for start.

The CoreMedia workspace contains two blueprints, the eCommerce Blueprint and the Brand Blueprint. Both blueprints can be used together as demonstrated in the example sites [see [Section 2.2, "CoreMedia Blueprint Sites" \[27\]](#)]. However, you can also use both blueprints separately. Deactivate the not used blueprint as described in [Section 4.2.1, "Removing Optional Components" \[91\]](#).

CoreMedia Blueprint workspace provides you with an environment which is strictly based on today's de facto standard for managing and building Java projects by using Maven. You do not get a program to install and run, but a workspace to develop within, to build and to deploy artifacts from.

Maven based environment

NOTE

Unless specified otherwise command line examples are given in Unix style. The path to the root of the *Blueprint* workspace directory will be referenced by the variable `$SCM_BLUEPRINT_HOME`.



4.1 Concepts and Architecture

This chapter describes concepts and architecture of *CoreMedia Content Cloud*.

- [Section 4.1.1, “Maven Concepts” \[53\]](#) describes how the Maven concepts are implemented within the *CoreMedia Blueprint* workspace.
- [Section 4.1.3, “Application Architecture” \[57\]](#) describes how CoreMedia applications are build from library and component artifacts and how deployable artifacts are build with package artifacts.
- [Section 4.1.4, “Structure of the Workspace” \[59\]](#) describes the folder structure of the *CoreMedia Blueprint* workspace.
- [Section 4.1.5, “Project Extensions” \[67\]](#) describes the extensions mechanism which lets you enable and disable extensions in one single location.
- [Section 4.1.6, “Application Plugins” \[72\]](#) describes how you can create plugins for CoreMedia applications.

4.1.1 Maven Concepts

The *Maven* build and dependency system is the foundation of the *CoreMedia Blueprint* workspace. This section will introduce you into the concepts CoreMedia used with *Maven* to provide you with the best development experience as possible.

Packaging Types

By default, *Maven* provides you with several packaging types. The most important ones are the `pom`, `jar` and the `war` type. They should be sufficient for the most common kinds of development modules but whenever you try to either support proprietary formats or try to break whole new ground, those three packaging types aren't sufficient. Using only the `pom` packaging type together with custom executions of arbitrary plugins, gives you flexibility but adding and maintaining your `pom.xml` files is going to be a complex and costly process.

To reduce complexity, but even more important to enforce standards, CoreMedia came up with two custom tailored packaging types for the *CoreMedia Blueprint* workspace. The `coremedia-application` and the `jangaroo` packaging type. The `coremedia-application` type provides a build lifecycle and dependency profile for a proprietary application format, whereas the `jangaroo` type provides both for the *JavaScript* tool chain to build sophisticated and compelling user interfaces like *CoreMedia Studio*.

coremedia-application

The `coremedia-application` packaging type is provided by the `coremedia-application-maven-plugin`. When you take a look at the root `pom.xml` and search for this plugin, you will find two occurrences, one in the `pluginManagement` section and one in the `build` section. The latter definition contains the line `<extensions>true</extensions>` within its plugin body, telling *Maven* that it extends *Maven* functionality. In this case, *Maven* will register the custom lifecycle bound to the custom packaging type.

```
<plugin>
  <groupId>com.coremedia.maven</groupId>
  <artifactId>coremedia-application-maven-plugin</artifactId>
  <extensions>true</extensions>
</plugin>
```

Besides lifecycle, a custom packaging type can also influence if *Maven* dependencies of this type have transitive dependencies or not. Because CoreMedia wanted to keep the `coremedia-application` packaging type to be the pendant of the `war` packaging type, it does not have transitive dependencies either. For your modules to depend on other `coremedia-application` modules and their dependencies as well, this means, that you need to define an additional dependency to the same GAV [groupId, artifactId, version] coordinates but with packaging type `pom`.

```
<dependency>
  <groupId>com.coremedia.cms</groupId>
  <artifactId>probedog-application</artifactId>
  <type>coremedia-application</type>
  <scope>runtime</scope>
</dependency>
<dependency>
  <groupId>com.coremedia.cms</groupId>
  <artifactId>probedog-application</artifactId>
  <type>pom</type>
  <scope>runtime</scope>
</dependency>
```

Example 4.1. Dependencies for a CoreMedia application

You may know this pattern from working with `war` overlays if they are skinny too, which means that they contain no further versioned artifacts.

For further information about the `coremedia-application-maven-plugin`, you should visit the plugins documentation site at [CoreMedia Application Plugin](#).

Jangaroo

Like the `coremedia-application-maven-plugin`, the `jangaroo-maven-plugin` defines a *Maven* extension with a custom packaging type

`jangaroo`, which introduces a custom lifecycle. This lifecycle binds the standard phases known from the `jar` packaging type to the corresponding goals for compiling ActionScript to JavaScript, running JooUnit tests and packaging the compilation result. Because *Jangaroo* artifacts and dependencies are of type `jar`, transitive dependencies are automatically added to the compile scope, making it easy to create and maintain modularity throughout your project.

For further information on the *Jangaroo Maven* build process, visit the corresponding documentation in the [Jangaroo Tools Wiki](#).

BOM files

BOM stands for "bill of material" and defines an easy way to manage your dependency versions. The BOM concept depends on the `import` scope introduced with *Maven 2.0.9*, that allows you to merge or include the `dependencyManagement` of a foreign POM artifact in your POMs `dependencyManagement` section without inheriting from it.

```
<dependency>
  <groupId>com.coremedia.cms</groupId>
  <artifactId>core-bom</artifactId>
  <version>CURRENT_RELEASE_VERSION</version>
  <type>pom</type>
  <scope>import</scope>
</dependency>
```

The inclusion or merge is done before the actual dependency resolution of your project is done. By the time the actual resolution starts *Maven* does not see any BOM imports but only the merged or included dependencies.

For projects using a framework that provides many artifacts like *CoreMedia* does, this means, that you can fix the versions for all dependencies that are part of that BOM, by simply declaring one dependency.

Of course there are pitfalls when using BOMs and the `import` scope, but the benefits of using BOMs overcome any disadvantages. To prevent you from falling into one of the pitfalls, the following paragraphs will show you how to use the BOM approach correctly.

Chaining BOMs and artifact procurement

Artifact procurement is a feature that some repository management tools like *Nexus* or *Artifactory* offer you to allow your project to use only explicitly configured versions of their dependencies. In addition to the local dependency management in your POM files, artifact procurement is done remotely in your artifact repository. Because of this fact, artifact procurement is much stricter and most commonly only applied in organizations, where securing build infrastructure has the highest priority.

When you chain BOM files, which means that the BOM you import, imports another BOM and so forth, you cannot achieve complete artifact procurement if any POM enforces a different version of a BOM than the version that is used within that chain of its predecessors. This problem stems from the fact that all import scoped dependencies must be resolved in any case, even if your topmost project enforces a different version. Luckily this only affects POM artifacts, you cannot compile against or which have no effect when deployed to the classpath.

BOM import order

Because the import scope is more likely an `xinclude` on XML basis, ordering of these imports is crucial if the BOMs content is not disjoint, which is most likely the case in presence of chained BOMs.

As a result, it is important to list the BOM imports in reverse order of the BOM import chain. To make sure your update is correct you should therefore always create the effective POM and check the resulting `dependencyManagement` section. To do so execute:

```
$mvn help:effective-pom -Doutput=effective-pom.xml
```

4.1.2 Blueprint Base Modules

CoreMedia Content Cloud introduces a new way of providing default features for *CoreMedia Blueprint*, *Blueprint Base Modules*. Step by step CoreMedia will move features from the *Blueprint* workspace to the *Blueprint Base Modules*. All features of the *Blueprint Base Modules* will be described by a public API. The reasons why CoreMedia decided to do so are:

- Less source code means faster Maven builds.
- Less source code in *Blueprint* workspace leads to easier migration paths when updating to new versions.

As its name implies, this new module contains Blueprint logic and thus depends on the Blueprint's content model. The content model is still part of the Blueprint workspace, hence you may customize it. Be aware, that some changes will break the Blueprint Base modules. Read [Section "Content Type Model Dependencies" \[118\]](#) for the list of Blueprint Base dependencies to the Blueprint content type model.

NOTE

Read [Section 4.4.1, "Using Blueprint Base Modules" \[117\]](#) for a detailed description of how to develop with the various *Blueprint Base Modules*.



4.1.3 Application Architecture

CoreMedia applications are based on Spring Boot and as such support [Spring Java configuration](#), [Spring Boot auto-configuration](#), and [Spring Boot configuration properties](#).

The recommended way to develop, extend, and configure CoreMedia applications is to follow the Spring Boot conventions. However, for backward-compatibility reasons, the CoreMedia component loader may still be used to activate component XML bean definitions and to load component properties files.

NOTE

The rest of this section describes the component loader and related topics. This is mostly relevant for projects migrating from an old CoreMedia version to a recent one.



To activate the component loader, add the following dependency to your component or web application module `pom.xml` file:

```
<dependency>
  <groupId>com.coremedia.cms</groupId>
  <artifactId>base-component</artifactId>
  <scope>runtime</scope>
</dependency>
```

Example 4.2. Adding the Base Component

CoreMedia applications are hierarchically assembled from artifacts:

- Library artifacts are used by
- Component artifacts which are used by
- Application artifacts.

Library Artifacts

Library artifacts contain JAR artifacts with Java classes, resources and Spring bean declarations.

An example is the artifact `cae-base-lib.jar` that contains *CAE* code as well as the XML files which provide Spring beans.

Component Artifacts

Component artifacts provide a piece of business (or other high level) functionality by bundling a set of services that are defined in library artifacts. Components follow the naming scheme `<componentKey>-component.jar`. The component artifact `cae-component.jar` for example, bundles all services that are typically required by a *CAE* web application based project.

Component artifacts are automatically activated on application startup, in contrast to library artifacts. That is, Spring beans and properties are loaded into the application context and servlets and so on will be instantiated. Therefore, you can add a component by simply adding a Maven dependency. No additional steps (such as adding an import to a Spring file) are necessary.

The following files allow you to declare services for a component which are automatically activated:

- `/META-INF/coremedia/component-<componentname>.xml`:

An entry point for all component Spring beans. Either declared directly or imported from library artifacts.

- `/META-INF/coremedia/component-<componentname>.properties`:

All configuration options of the component as key/value pairs. These properties might be overridden by the concrete application.

Redundant Spring Imports

NOTE

This section is about Spring XML configuration files. The recommended way to configure Spring bean definitions is to use Spring Java configuration.



Due to the design of the Spring Framework and the CoreMedia component loader, it may often be necessary to declare many `<import/>` elements in Spring XML configuration files, often pointing to the same resource. This slows down the startup of the `ApplicationContext`.

Unfortunately, `org.springframework.beans.factory.xml.XmlBeanDefinitionReader` does not track imported XML files, so redundant `<import/>` elements will lead to Spring parsing the same XML files over and over

again [in most cases, those XML files will contain more `<import/>` elements leading to even more parsing, ...] After moving to Servlet 3.0 resources, for each `<import/>`, the JAR file containing the XML file has to be unpacked. Also, every time that an XML file is completely parsed, Spring reads all Bean declarations, creates new `org.springframework.beans.factory.config.BeanDefinition` instances, overwriting any existing bean definitions for the same bean ID.

The optional `Spring Environment` property `skip.redundant.spring.imports` controls handling of redundant imports. If set to `true`, the first `<import/>` element will be used and all following, duplicate `<import/>` elements pointing to the same resource will be ignored. The property is `true` by default. The time saved depends on the number of duplicated `<import/>` elements.

CAUTION

Even though this setting is recommended, it may change which bean definitions are loaded. (As explained above, normally, bean definitions may be overwritten by subsequent imports, depending on how `<import/>` elements are used in a web application).



4.1.4 Structure of the Workspace

Starting with *CoreMedia Content Cloud* major version 10 (CMCC 10), this repository has been restructured to better reflect that the overall software system consists of several applications.

Overview

Since CoreMedia applications have been developed monolithically for years, there are lots of dependencies and shared code between the applications. Also, the build process of different applications was not independent, because they shared build configuration (through parent POMs).

The new *CoreMedia Blueprint* workspace structure is modular in the sense that it consists of many (sub-)workspaces that can be built independently, only interacting through Maven artifacts. Shared code still exists, and shared workspaces must be built before application workspaces, but workspaces of different applications are independent.

Besides shared workspaces (`shared/*`) and application-specific workspaces (`apps/*`), there are global Workspaces (`global/*`) that depend on several to all applications.

Workspace Concepts and Terminology

Workspaces

To reduce build-time dependencies and allow modular builds, the concept of workspaces has been introduced. A workspace is a Maven multi-module project that can be built independently, only relying on artifacts from the Maven repository, but not on anything else being present in the same Git repository. This means one Git repository hosts several workspaces. Since a workspace is a group of Maven modules and each module only belongs to one workspace, dependencies between modules of different workspaces lead to dependencies between their workspaces. In other words, workspaces are a coarsening of Maven modules and their dependencies, just like modules (and their dependencies) are a coarsening of classes (and their dependencies).

Applications (Apps) and Shared Code

CoreMedia Content Cloud is a software system that consists of several applications. Here, an application is a piece of software running in the same execution environment (usually a JVM), serving a certain (business) objective, and communicating with other applications via remote calls. Examples of CoreMedia applications are CAE, Studio Server, Studio Client (execution environment: browser!), Content Server, and all Commerce Adapters.

An application consists of one or more application-specific workspaces and reuses shared code from arbitrary many other workspaces, but not from other application workspaces. This means that all code and resources used by more than one application must not be located in an application-specific workspace, but in a shared code workspace.

Putting all shared code into one workspace would have been too coarse-grained. One has to consider that shared code changes are much more expensive, since they potentially affect any application, thus after changes, all applications have to be rebuilt, re-tested, redeployed, and re-released.

CoreMedia CMS has a four-tier architecture: Between frontend and persistent data storage, unlike most architectures that use one "backend" tier, CoreMedia CMS features two tiers. The backend tier consists of Content Server, Workflow Server and Search (a specifically configured Solr). The middle tier acts as a frontend façade to the backend for delivery (CAE, Headless Server), editorial interface (Studio Server, User Changes, Studio Package Proxy, Site Manager), search (CAE Feeder, Content Feeder), and other tasks (Elastic Worker).




Figure 4.1. CoreMedia CMS's Four-Tier Architecture

Analyzing code reuse between applications in our code base validated the assumption that this four-tier architecture has a major influence on code sharing. Middle-tier servers share code not reused by backend servers, and vice versa. Computing the set of shared modules, it turned out that there was only one module shared by the backend servers (`cap-serverbase`), so CoreMedia decided not to create a workspace with just one module and ended up with two shared code workspaces:

- shared/middle - contains all modules shared by two or more middle-tier servers, but not by backend server
- shared/common - all other shared code, shared by two or more servers of any tier

Global Modules

Despite the clear separation of application development, there is the need to unite all applications to a complete CoreMedia CMS software system. There are two use cases for doing so:

- Run system tests. A system (integration) test is a test that verifies the interaction of two or more applications and as such cannot be located in any application-specific workspace (and of course is not shared code, either).
- Deploy a complete CMS software system.

CoreMedia offers prefabrication for setting up the complete system of all applications in form of a Docker compose file.

The system deployment workspace is called `global/deployment`.

All Workspaces

The following diagram shows all workspaces, grouped into shared, apps, and global.




Figure 4.2. CoreMedia CMS's Shared, Application-Specific, and Global Workspaces

Dependency Management

Putting applications into focus leads to the idea that dependency management can also be done modularly, namely for each application, because each runs in its own execution environment. Since application-specific code only runs in one execution environment, there are application-specific external dependencies that are managed centrally for each application. This means that not every (sub-)workspace needs its own external dependency management.

However, shared code needs to run in all applications that use it, so by reusing shared code, an application also inherits the shared code's dependency management.

Maven implements reused dependency management through "bill of material" (BOM) POMs. This means that there are third-party dependency management BOM POMs for each shared workspace and for each application.




Figure 4.3. Backend Tier Workspace Dependencies




Figure 4.4. Middle Tier Workspace Dependencies

Enforcer

For global management of banned dependencies a customized `BannedDependencies` Enforcer rule is used that reads the banned dependencies from a configuration file on the classpath. The configuration file for the CMS comes with the dependency on `com.coremedia.cms:common-banned-dependencies`. It is an XML file which contains the `bannedDependencies` configuration element that you would normally include in the configuration of the enforcer plugin. It is also possible to add additional includes and excludes directly in the custom rule element.

A new Enforcer rule called `ModularOneRepoEnforcerRule` has been added which mainly enforces that one workspace always manages its dependencies on other workspaces. You should always manage this kind of dependencies by importing the BOM of the other workspace instead of using a versioned dependency directly. On the other hand, for dependencies inside one workspace you should use `project.version`. If you have to violate these rules (for a hotfix, for instance), you can ignore certain dependencies, by adding an `ignoredDependencies` element to the rule, which works the same way as in the `maven-dependency-plugin`. The filter syntax is: `[groupId]:[artifactId]:[type]:[version]` where each pattern segment is optional and supports full and partial `*` wildcards. An empty pattern segment is treated as an implicit wildcard.

Following this pattern enables you to build the workspaces independently and to even use different versions for the separate workspaces.

Remark on Group and Artifact IDs

With the introduction of separate workspaces some aggregator and parent modules have to be copied to more than one workspace (`blueprint-parent`, for instance). To make the Maven coordinates unique the artifact IDs of these modules were prefixed with the name of the workspace (for example, `cae.blueprint-parent`), while the directory of the modules stayed as they were (for example, `blueprint-par`

Banned Dependencies

ModularOneRepoEnforcerRule

ent/). The `groupId` could have been used for this, which would have been the more natural solution, but in order to get consistent group IDs for a workspace this would have meant new group IDs for every single artifact, which was refrained from changing for now.

There are some exceptions where the modules are copied to many workspaces, but got a real distinct artifact ID and directory (for example, `cae-core-bom`). These modules distinguish themselves as they are also relevant outside of a workspace, in contrast to the parents and aggregators, where the focus is put more on the similarity to the old structure and the other workspaces.

Development Use Cases

The new repository structure encourages working on a single workspace at a time, or at least on few workspaces.

Currently, you have to build workspace common and in most cases, that is when working on a middle tier app, workspace middle. Later, there should be a CI that produces SNAPSHOT artifacts for all modules from branch master, so that you can let Maven fetch artifacts from there and only do local builds of workspaces you actually work on.

Working with Application-Specific Code Only

When your task only involves one application, build common, (if it is a middle tier app) middle, and the application's workspace on the command line:

```
for ws in shared/common shared/middle apps/<some-app>; do mvn clean
source:jar install -f $ws -DskipTests <more-options>; done
```

Then, open only the application's workspace in IDEA. The goal `source:jar` allows browsing sources of shared code, even though they are not part of the IDEA project.

All Java applications (except Site Manager) are Spring Boot applications and can be started locally like so:

```
mvn spring-boot:run -pl :<someapp>[-<variant>]-app
```

Adding the option `-Dinstallation.host=<FQDN>` connects your local application to a CI reference system. For details, see the README file in the Spring Boot folder. Alternatively, you copy the IDEA run configuration provided in the `ideaRunConfiguration` subfolder of the Spring Boot folder to `.idea/runConfigurations`, as also described in that README.

Working with Shared Code Only

This use case is quite similar to the first one.

When working with `shared/middle`, you have to build `shared/common` first.

When working with shared/common, nothing needs to be built before.

Keep in mind that changes in shared code have impact on many, sometimes even all CoreMedia applications. Treat shared code like public API!

- Refrain from unnecessary breaking changes.
- Write unit tests for new functionality.
- If a change in shared code passes unit tests, but CI alerts you that it breaks an application, write a regression test before fixing shared code.
- Document what you change.
- If possible, put shared code changes and application code changes in separate commits.

Working with Application-Specific and Shared Code

There is still a lot of shared code, so it might happen more often than not that part of the code you must touch to implement an application feature is located in a shared workspace. The advantage of the new multi-workspace structure is that you can immediately tell that code is shared by the fact that it is located under a path starting with `shared/`.

The idea of modularization is to not fall into monolithic development mode (see below) just because you change shared code. In an ideal world, all shared code's contracts would be checked by unit tests. So if you change shared code in a non-breaking fashion and no tests fail, you can use new API in the application you actively work on and need not worry about other applications also using the changed code.

Even if you do not have sufficient unit tests coverage of shared code, you might have integration tests that should detect shared code changes that break other applications. Thus, if you push your shared code changes and your application-specific changes to a feature branch, your local CI should take care of validating that no other applications are (negatively) affected by your changes. Treat shared code as having an API, and you should be fine.

Working in IDEA, the most convenient way is to add the needed shared code workspace(s) to the application's IDEA project.

After that, you have to run "Reimport Maven Projects" to update the dependencies on shared code from references into your local Maven repository to references to the corresponding IDEA modules. This enables a fast development turn-around after changes in shared code, including source-level debugging and hot deploy.

Working with (Almost) All Code

If your task requires global changes, for example, a shared third-party library is updated to a new (major) version, you can still use the multi-workspace repository like the old monolithic workspace.

You can simply build the whole workspace through the root POM and then open it in IDEA.

Now, having one big IDEA project, you can do global refactorings or search and replace.

It is not recommended to work like this for normal feature implementation, because importing the large overall project into IDEA takes quite some time, and after switching to a different branch or merging in master, this process has to be repeated over and over again.

Even if you have to perform application-spanning changes, try to find a subset to work on:

- Do the changes affect Java code "only"? Even though most of your code is Java, when restricting the IDEA project to Java workspaces, you can leave out Studio Client, Frontend, and Content. Although these are only three workspaces, they use quite different tooling and in case of Studio Client a custom IDEA Maven import process, which you may be glad to avoid.
- Are the changes located in backend-tier servers only? If so, you can leave out `shared/middle`, which contains a large fraction of the workspace modules and code.

The *CoreMedia Blueprint* workspace contains the `modules` and `test-data` top level aggregator modules.

modules

Almost every workspace, be it an application, shared or global workspace, has a `modules` top-level aggregator module which is the most important space for project developers. All code, resources, templates and the like is maintained here. You can start all components locally in the modules area.

The `modules` hierarchy consists of modules that build libraries and modules that assemble these libraries to applications. Library modules are being built with the standard Maven *jar* packaging type or with the *swc* packaging type, which is a custom packaging type to package *CoreMedia Studio* client libraries and plugins.

Most applications created by the modules below the `modules` folder are Spring Boot applications using the standard Maven *jar* packaging type. The *CoreMedia Studio* client is an Ext JS browser application with the special packaging type *jangaroo-app*. All other applications are command line tools built with the custom *coremedia-application* packaging type. *coremedia-application* modules are built with the *coremedia-application-maven-plugin*, a custom plugin tailored to the CoreMedia *.jpf* based application runtime.

The `modules` folder is structured in sub-hierarchies by grouping modules due to their functionality. There is a dedicated group `cmd-tools` for command line tools and functional groups like `ecommerce`. Since the introduction of application-oriented workspaces, the groups for these applications (`cae`, `studio`, ...) are mostly redundant, but kept for structural similarity to previous releases of *CoreMedia Content Cloud*. The

same holds true for the group named `shared`, whose modules now are in most cases part of one of the two `shared` workspaces. The remaining two groups `extension-config` and `extensions` are required for the extensions functionality of *CoreMedia Blueprint* workspace.

By default, *CoreMedia Blueprint* workspace ships preconfigured with many extensions such as *Adaptive Personalization* or *Elastic Social*. Typically, extensions do not extend one, but many applications. *CoreMedia Project Extensions* decouple the application from the dependencies it is extended by and lets you automatically manage these dependencies. Not all extensions will be used in a project right from the start. In this case, the *CoreMedia Extension Tool* allows you to easily deactivate features that you do not need. See [Section 4.1.5, "Project Extensions" \[67\]](#) for details.

test-data

The `content/test-data` folder contains test content to run *CoreMedia Blueprint* with. It can be imported into the content repository by using the *CoreMedia serverimport* tool. Extensions may contain additional test-data folders.

4.1.5 Project Extensions

One of the main goals of *CoreMedia Content Cloud* is to offer a developer friendly system with a lot of prefabricated features, that can simply be extended modularly. To this end, CoreMedia provides the Maven based *CoreMedia Blueprint* workspace and the extensions mechanism.

An extension adds new features to one or more CoreMedia applications. Assume, for example, that a feature requires a new content type. In this case the extension affects at least three applications:

- The Content Server needs the new content type
- The CAE needs according content beans
- Studio needs according document forms

Manually enabling or disabling a feature in all the affected applications would be cumbersome, tedious and error-prone. Therefore, CoreMedia provides the extensions mechanism, which allows you to enable or disable a feature for all affected applications by a single configuration switch. The extensions mechanism is based on Maven modules and runtime dependencies. Adhering to some structural conventions enables you to use the *CoreMedia Extension Tool* to manage those dependencies.

Extensions Mechanism Structure

The extension mechanism structure consists of two parts:

- extensions which extend different applications to provide a new feature
- extension points of CoreMedia applications to which the features are added.

Extensions and extension points are separated for each application workspace [apps/*]. In each workspace, extension points (usually one) can be found at the local path `./modules/extension-config/*-extension-dependencies` and extensions are located below `./modules/extensions`.

Any Maven module with an artifact ID using the pattern `{prefix}-extension-dependencies` constitutes an extension point, for example the artifact ID `studio-server-extension-dependencies` defines an extension point named `studio-server`. This name serves as an ID by which an extension point can be referenced from an extension.

extension points

In the new version of *CoreMedia Content Cloud*, the extension point names have been aligned with the application (workspace) names. For backwards compatibility, the old extension point names may still be used, but are deprecated.

*extension point names
backwards compatibility*

Extensions points collect runtime dependencies on app extensions. Applications have explicit dependencies on extension points, so they get transitive dependencies on the actual app extensions.

Since an extension extends several applications, it consists of so-called application extensions or for short app extensions, where one app extension uses exactly one extension point and thus extends exactly one CoreMedia application. The desired extension point is marked in the `pom.xml` by the property named `coremedia.project.extension.for` and has the name of the extension point as value.

extensions and application extensions

```
<properties>
<coremedia.project.extension.for>studio-client</coremedia.project.extension.for>
</properties>
```

Example 4.3. Specify the extension point

In previous versions of *CoreMedia Content Cloud*, one module was allowed to use several extension points. Since now, a clear separation of applications is enforced and only one extension point may be used. To migrate a multi-extension-point extension, you must move the extension module to a shared code location (`shared/middle/modules/extensions/...`) and create two app extensions that both have a dependency on the shared-code module.

Short overview of the extensions structure of each application workspace `apps/{application}`:

- `./modules/extensions` - contains application extensions as Maven submodules
 - one extension - aggregator of all application extensions (usually only one per workspace)
 - one application extension - Maven module with property `coremedia.project.extension.for`
 - another application extension - Maven module with property `coremedia.project.extension.for`
 - extension library - Maven module with application-specific code that is used by one or more of the application extensions
- `./modules/extension-config` - Maven aggregator module
 - `{extension-point-name}-extension-dependencies` - extension point for application with the identifier `{extension-point-name}`
- `./spring-boot/{application}-app` - has a runtime dependency on `{extension-point-name}-extension-dependencies`.




Figure 4.5. CoreMedia Extensions Overview

Usually, each workspace below `apps /` contains exactly one application with exactly one extension point. However, there are two exceptions to this one-to-one rule.

The CAE comes in two application "flavors", `cae-preview-app` and `cae-live-app`, and consequently offers two extension points. Because only preview allows dedicated extensions, the extension points are called `cae-preview` (preview only) and `cae` (both preview and live).

The second exception is *CoreMedia Studio* client: The `studio-app` (an Ext JS app, not a Spring Boot app) allows statically linked as well as dynamically linked extension modules. Depending on your choice, use the extension point `studio-client` or `studio-client-dynamic`.

Extension points do not contain any code or configuration directly and should never be edited manually, because they are modified by the *CoreMedia Extension Tool* to contain all collected dependencies on active application extensions.

Usage of the *CoreMedia Extension Tool*

Within the extension mechanism structure, the extensions and the dependencies from the applications onto the extension points are maintained manually. The extension point modules must already be present and are updated by the *CoreMedia Extension Tool*. The tool lets you synchronize the dependencies from the extension points to application extensions by their status (enabled/disabled). You can disable, enable, remove and add prefabricated and custom extensions.

Usage of the Core-Media Extension Tool

For convenience, the *CoreMedia Extension Tool* is implemented as a Maven plugin, which is preconfigured for usage in the *CoreMedia Blueprint* workspace in the Maven POM file `workspace-configuration/extensions/pom.xml`. The tool is used by invoking it through this POM, by running Maven either from that directory or from the project root directory, adding `-f workspace-configuration/extensions`. All relevant use cases and command line examples can be found in `workspace-configuration/extensions/README.md`. The most important advice is to call `mvn -f workspace-configuration/extensions extensions:help` to see full usage instructions of all available goals (commands) and their options (parameters). Especially the extensive help text of goal `sync` is important to understand how the tool works.

When disabling or removing extensions, note that extensions may depend on each other. Therefore, when you enable an extension all the extensions it depends on must also be enabled. For example, `es-p13n` makes only sense if `es` and `p13n` are enabled too. Otherwise, you would encounter runtime errors like missing Spring beans.

To prevent such situations, the *CoreMedia Extension Tool* does not allow enabling or disabling extensions that would result in such an inconsistent state. The tool will stop with an error message that tells you exactly what went wrong and how to fix the problem. For example, if you try to disable the extension `alx`, the tool outputs the following error (the concrete list of dependent modules may vary in future releases):

```
[ERROR] Inconsistent set of extensions to disable/remove. These extensions
would need to be
  disabled or removed, too:
  [alx-google, alx-webtrends]
```

Implementing a Custom Extension

The following steps summarize how to add a custom extension to the *CoreMedia Blueprint* workspace. Let's call the extension `my-feature`.

1. Plan your feature: Which applications (workspaces) do you need to extend? Do you have shared code? Let's assume you need to extend cae and studio-server and want to have one shared code module.
2. For shared code, add a new Maven module at `shared/middle/modules/extensions/my-feature/`. Its parent must be set to `com.coremedia.blueprint.middle.extensions:1-SNAPSHOT`. If you have multiple shared modules, add an aggregator module at that location and place the other shared modules below that aggregator.
3. For each application you want to extend, here cae and studio-server, create a new Maven module in its application workspace at `apps/{application}/modules/extensions/my-feature`. Its parent must be set to `com.coremedia.blueprint:{application}.extensions:1-SNAPSHOT`. Again, if you have multiple application-specific modules, instead create an aggregator at that location and place all modules below that aggregator.
4. Set the `coremedia.project.extension.for` property in the `pom.xml` file of all application extension modules, that is all modules that are supposed to be added as `{extension-point}-extension-dependencies`. Usually, there is exactly one such module per extension point/application.
5. This would be a good time to do a VCS commit. This helps you to see what modifications the *CoreMedia Extension Tool* applies in the next step, and if anything goes wrong, allows you to revert to this state.
6. Run the *CoreMedia Extension Tool* with goal `sync` (`mvn -f workspace-configuration/extensions extensions:sync` and enable your new extension by adding `-Denable=my-feature`).
7. Use `mvn -f workspace-configuration/extensions extensions:list` to check that your extension has been added (`my-feature` appears in the list) and activated (it does *not* start with a hash ("`#`").
8. Check the changes the tool has applied to each affected workspace:
 - Your extension's workspace-specific root module is added as a `<module>` to the corresponding workspace extensions aggregator, `{workspace}.extensions/pom.xml`.
 - All affected extension points `{extension-point}-extension-dependencies/pom.xml` files should now contain dependencies on your application extensions.
 - All modules of your extension that now belong to this workspace are added to the workspace's extensions BOM, `{workspace}-extensions-bom/pom.xml`, so that their version is managed for others who import this BOM.
9. Rebuild your project, at least all affected workspaces.

If your extension becomes obsolete, you can disable it:

1. Run the *CoreMedia Extension Tool* with goal `sync` and option `-Ddisable=my-feature`.
2. Checkpoint: In all affected workspaces, all three types of POMs (extensions aggregator, extension point, extensions BOM) no longer refer to any of your extension modules.
3. Rebuild your project, at least all affected workspaces.

If you want to reactivate your extension, just call the `sync` goal with `-Denable=my-feature` again and rebuild your project. Otherwise, if you are sure that you will never need your extension again, rerun the *CoreMedia Extension Tool* with goal `sync` and option `-Dremove=my-feature`, which removes all files of your extension from all workspaces.

NOTE

Removing is not recommended for extensions that come with the Blueprint, because when updating to a new Blueprint release, deleted files lead to merge conflicts for all files updated by CoreMedia.



Best Practice

In a particular project the set of active extensions is usually not changed frequently. Therefore, CoreMedia recommends applying the *CoreMedia Extension Tool* only manually and to check in all changed files into the VCS. You should then call the tool's `sync` goal without any additional parameters on a regular basis to check that all generated extension dependencies are in a consistent state.

Alternatively, you could integrate the tool into the CI and synchronize the extension points in every build. However, since the result is almost always the same, this would unnecessarily increase the roundtrip time.

4.1.6 Application Plugins

Application Plugins are another way to extend *CoreMedia Content Cloud* applications. The focus of plugins are clear APIs and strong isolation to increase reusability and decrease maintenance effort.

In contrast to classic Blueprint Extensions (see [Section 4.1.5, "Project Extensions" \[67\]](#)), which are usually part of a project's Blueprint and are built together with the application, plugins are meant to be developed and released separately. This way plugins can be packaged with the application at a later time, for example when creating a Docker image or even later, when deploying the application.

Difference between extensions and plugins

Similar to Blueprint Extensions, to implement some feature through plugins, it must be decomposed into parts that plug into exactly one CoreMedia application, and optional parts that are reused in different application plugins (called shared code). The plugin artifacts resulting from these parts can then be bundled via a *Plugin Bundle Descriptor* [see [Section “Plugin Bundles” \[89\]](#)].

NOTE

Currently, only Content Hub Connectors can be implemented via the plugin mechanism. More possibilities to convert classic Blueprint extensions to plugins by creating the corresponding extension points and providing the needed Spring beans to plugins will follow in upcoming releases.



For Content Hub Connectors, the Content Hub API in *Studio-Server* provides an extension point for plugins, and for the localization part, it is now possible to add Studio Client plugins as "dynamic packages" at runtime. Therefore, without adding a Maven dependency to the Studio Client application. More possibilities to convert classic Blueprint Extensions to plugins by creating the corresponding extension points and providing the needed Spring beans to plugins will follow in upcoming releases.

The technology to implement plugins is different for *Studio Client* than for the other Java based applications, so there are dedicated sections for these two types of plugins, followed by a section explaining how to bundle plugins that together implement some feature.

- [Section “Plugins for Java Applications” \[73\]](#)
- [Section “Plugins for Studio Client” \[85\]](#)
- [Section “Plugin Bundles” \[89\]](#)

Plugins for Java Applications

Some CoreMedia Java applications provide *extension points* which are interfaces for which you can provide implementations (*extensions*, see [Section “Extensions” \[75\]](#)) via a *plugin*.

For the integration of plugins with an application the Spring framework is used. Every plugin has its own application context with its own class loader which has the app's class loader as parent and resolves classes in the plugin first. A plugin cannot access the application context of the application directly, but only use a well-defined subset of beans that the application has copied into the plugin context [see [Section “Application Beans in Plugins” \[76\]](#)]. The application also takes care of starting the plugin's context and then collects all Beans of extension point types. A plugin extension is very similar to a service provider, but based on beans (instances) instead of classes.

Plugins and their application context

Creating Plugins

A plugin is a (zipped) folder with the following structure:

<code>classes/</code>	The classes of your plugin
<code>lib/</code>	Third-party dependencies (JAR files) used by your plugin
<code>plugin.properties</code>	File for plugin configuration and metadata

The `plugin.properties` file provides metadata of your plugin. Most importantly, the properties give your plugin an identifier and configure a Spring configuration class that will be registered with the application context. These are the supported properties:

<code>plugin.id</code>	The ID of the plugin, must be unique, for example, MyPlugin
<code>plugin.version</code>	The version of the plugin following the Semantic Versioning Specification , for example, 1.2.3 or 1.0.0-SNAPSHOT
<code>plugin.configuration-class</code>	The Spring Configuration class, for example, com.acme.myplugin.MyPluginConfiguration
<code>plugin.provider</code>	The provider/author of the plugin, for example, ACME
<code>plugin.dependencies</code>	(optional): Comma-separated list of plugin IDs, for example, some-plugin,some-other-plugin . See Section “Plugin Dependencies” [8] for details.
<code>plugin.add-on-for</code>	(optional): The plugin ID of the plugin that this plugin is an add-on for, for example, some-plugin
<code>plugin.requires</code>	A version range of supported CMS versions (a single version means greater or equal to that version), for example, 10.2010.1, >=10.2010.2 & <10.2101.1

Example

```
plugin.id=MyPlugin
plugin.version=1.2.3
plugin.configuration-class=com.acme.myplugin.MyPluginConfiguration
plugin.provider=ACME
```

Example 4.4. plugin.properties

```
@Import("SomePluginBeansConfig.class")
@Configuration(proxyBeanMethods = false)
public class MyPluginConfiguration {
    @Bean
    public MyExtension myExtension(SomeBean someBean) {
        return new MyExtension(someBean);
    }
}
```

Example 4.5. *com.acme.myplugin.MyPluginConfiguration*

```
public class MyExtension implements SomeCoremediaExtensionPoint {
    public MyExtension(SomeBean someBean) {
        ...
    }
    ...
}
```

Example 4.6. *com.acme.myplugin.MyExtension*

Extensions

Plugin extensions must not be confused with *CoreMedia Project Extensions* [see [Section 4.1.5, “Project Extensions” \[67\]](#)]. Project extensions are just normal Maven modules in your CoreMedia Blueprint project and have no isolation. They use the same dependencies, Spring application context and class loader as the rest of the application and all other extensions. Plugin extensions only use an explicit set of beans from the application, can bring their own dependencies and do not interfere with other parts or plugins of the application.

Extension Points

Extension points are CoreMedia interfaces or classes which are annotated as `com.coremedia.cms.common.plugins.plugin_base.ExtensionPoint`.

Typically, extension points are strategies like content hub adapters or validators. A plugin provides instances of extension points as Spring beans in its configuration class. The plugin framework detects them at runtime by their type and passes them to the components that apply them.

Extension Points Reference

CoreMedia Content Cloud features the following extension points:

- `CapTypeValidator`

- `Validator`
- `ContentHubAdapterFactory`
- `FeedbackHubAdapterFactory`
- `FeedbackProviderFactory`
- `JobFactory`

For details, consult the API documentation of the particular extension point.

Application Beans in Plugins

Each plugin has its own Spring application context. However, in order to implement your feature, you might need some services from the application, for example the `CapConnection`.

The applications of *CoreMedia Content Cloud* expose dedicated sets of beans for usage in plugins, which are provided as Spring configuration classes that you can import in your plugin's configuration class. These configuration classes are annotated with `com.coremedia.cms.common.plugins.plugin_base.BeatnsForPlugins`.

Other plugins can also provide such configuration classes. To access them, you have to add these plugins as dependencies.

NOTE

Be aware to **not** use scope `provided` for dependencies on the jars containing the `BeatnsForPlugins` configuration classes, as these are not loaded by the application.



Beans for Plugins Reference

The following `BeatnsForPlugins` are currently available:

- `CommonBeatnsForPluginsConfiguration` (Available in all apps with extension points)

The API documentation of the `BeatnsForPlugins` classes shows the actual beans they provide.

Application Properties

All Spring properties are passed from the application to its plugins, including those from application.properties, system properties, environment variables, etc. You can access these properties in your Plugin's ApplicationContext for example via `@Value` or `ConfigurationProperties` as usual.

Although it is technically possible, you should not rely on existing properties of the application but instead create new dedicated properties for your plugin.

CoreMedia / Third-party Dependencies

Each plugin has its own class loader and can bring its own third-party libraries. This gives you control over the versions of the third-party libraries you use and makes you independent of third-party version changes in the particular *CoreMedia Content Cloud* application, so that your plugin will reliably continue to work with *CoreMedia Content Cloud* updates. The plugin's libraries are included in the plugin ZIP file, where the plugin class loader discovers them and loads the classes from.

Plugins have their own class loader

However, at runtime your extensions are integrated into the particular *CoreMedia Content Cloud* component which features the extension point. Technically, this requires some classes (especially the *Spring Framework*) to be shared with the application.

Shared classes

Moreover, some frameworks like *slf4j* have application wide aspects, which do not work with objects of classes from different class loaders. And last but not least, any *CoreMedia Content Cloud* classes must be shared with the application. Even if it would work to use a particular *CoreMedia Content Cloud* feature just like an independent third-party library, CoreMedia does not guarantee this for updates, so just don't do it.

The following subsections describe how you can handle these issues.

Dependencies in Practice

Plugin developers must handle the difference between plugin libraries and shared classes appropriately. You have to develop your plugin in a Maven project. Each extension has its own module. Add a `dependencyManagement` section with at least the following entries to your POM file:

- The BOM that manages the extension point
- The BOM that manages the shared classes for the particular application (Each application with extension points provides such a BOM.)

Now, if you add a new dependency to your POM file, check whether it is managed by this dependency management. If it is not, it does not need to be shared, and you can simply declare the version of your choice in the dependency. Otherwise, omit the version and set the dependency scope to `provided`. Scoping all shared dependencies as `provided`, you can easily use the *maven-dependency-plugin* and the *maven-assembly-plugin* to build the plugin zip file including the non-shared libraries.

For example, a POM file for a *studio-server* plugin looks like this:

```
<project>
  <!-- [...] -->

  <dependencyManagement>
    <dependencies>

      <!-- For the extension point, e.g. ContentHubAdapterFactory -->
      <dependency>
        <groupId>com.coremedia.cms</groupId>
        <artifactId>studio-server-core-bom</artifactId>
        <version>${studio-server.version}</version>
        <type>pom</type>
        <scope>import</scope>
      </dependency>

      <!--
        For the third-party classes that must be
        shared with the studio-server application
      -->
      <dependency>
        <groupId>com.coremedia.cms</groupId>
        <artifactId>studio-server-thirdparty-for-plugins-bom</artifactId>
        <version>${studio-server.version}</version>
        <type>pom</type>
        <scope>import</scope>
      </dependency>
    </dependencies>
  </dependencyManagement>

  <dependencies>
    <!-- An independent third-party library, managed right here. -->
    <dependency>
      <groupId>com.sun.activation</groupId>
      <artifactId>jakarta.activation</artifactId>
      <version>1.2.2</version>
    </dependency>

    <!-- coremedia dependencies must always be shared. -->
    <dependency>
      <groupId>com.coremedia.content-hub</groupId>
      <artifactId>content-hub-api</artifactId>
      <scope>provided</scope>
    </dependency>

    <!--
      The Spring framework is managed by
      studio-server-thirdparty-for-plugins-bom,
      thus, it must be shared by the plugin.
    -->
    <dependency>
      <groupId>org.springframework</groupId>
      <artifactId>spring-web</artifactId>
      <scope>provided</scope>
    </dependency>
  </dependencies>

  <!-- [...] -->
</project>
```

```
</project>
```

More Dependency Subtleties

Further dependency problems might occur when you try to link instances of plugin classes with objects of application classes. The following example illustrates this. Assume, that you want to use the FasterXML Jackson libraries in your plugin. Those are not managed in the `studio-server-thirdparty-for-plugins-bom`, so you add a normal dependency to your pom:

```
<dependencies>
  <dependency>
    <groupId>com.fasterxml.jackson.core</groupId>
    <artifactId>jackson-databind</artifactId>
    <version>2.12.6</version>
  </dependency>

  <dependency>
    <groupId>com.coremedia.content-hub</groupId>
    <artifactId>content-hub-api</artifactId>
    <scope>provided</scope>
  </dependency>

  <dependency>
    <groupId>org.springframework</groupId>
    <artifactId>spring-web</artifactId>
    <scope>provided</scope>
  </dependency>

  <!-- [...] -->

</dependencies>
```

You code your plugin, you build your plugin, you run your plugin. Everything works fine.

The next change in your plugin involves Spring's `MappingJackson2HttpMessageConverter`:

```
import com.fasterxml.jackson.databind.ObjectMapper;
import
org.springframework.http.converter.json.MappingJackson2HttpMessageConverter;

private HttpMessageConverter<Object> createMessageConverter() {
    ObjectMapper objectMapper = new ObjectMapper();
    MappingJackson2HttpMessageConverter mc = new
MappingJackson2HttpMessageConverter();
    mc.setObjectMapper(objectMapper);
    return mc;
}
```

You code your plugin, you build your plugin, you run your plugin. Everything wor... but wait, what's this?

```
the class loader org.pf4j.PluginClassLoader @227b4be7 of the current class,
com/acme/my/famous/StudioPlugin,
and the class loader 'app' for the method's defining class,
org/springframework/http/converter/json/AbstractJackson2HttpMessageConverter,
```

```
have different Class objects for the type  
com/fasterxml/jackson/databind/ObjectMapper
```

The `MappingJackson2HttpMessageConverter` class is shared with the application (because the `spring-web` dependency has the scope `provided`) and is loaded by the application class loader. `MappingJackson2HttpMessageConverter` references `ObjectMapper` as a method argument, so the application class loader also loads the `ObjectMapper` class.

Your plugin declares an ordinary (scope `compile`) `jackson-databind` dependency. Thus, the plugin class loader also loads the `ObjectMapper` class, independently of the application. Now, you invoke `MappingJackson2HttpMessageConverter.setObjectMapper`. The argument is an instance of the plugin's `ObjectMapper`, but the method expects an instance of the application's `ObjectMapper`. These two classes are not assignment compatible, not even if the plugin and the application use the same version of the `jackson-databind` library! This causes the observed error.

The solution is to set the scope `provided` for the `jackson-databind` dependency, in order to share the `ObjectMapper` class with the application, even though `jackson-databind` is not managed by `studio-server-thirdparty-for-plugins-bom`. However, this has some drawbacks that you know already from the CoreMedia Extensions:

- You are bound to the particular version of `jackson-databind` that is used by Spring, so you cannot use the new features of later versions.
- Other *CoreMedia Content Cloud* versions may use other Spring/Jackson versions, which may differ in functionality and make your plugin less portable.

This combination of Spring and Jackson is just an example. You might have to use other libraries with scope `provided` too. CoreMedia refrained from adding all such transitive dependencies to the `thirdparty-for-plugins` BOMs, because of the following reasons:

- The appropriate scope depends on the particular usage of the library. It is not generally `provided`. As long as you use a library only with other plugin classes, you can use a `compile` scope dependency.
- Normally, BOMs do not list transitive dependencies explicitly, so CoreMedia adheres to this convention.

Due to the drawbacks mentioned above, CoreMedia recommends that you use scope `compile` for dependencies that are not managed by the `thirdparty-for-plugins` BOMs whenever possible, and only switch to `provided` when necessary.

Maven Archetype

As a starting point for the development of a new plugin CoreMedia recommends to use the CoreMedia `plugin-archetype`. The created Maven project contains a descriptor and an example configuration class and manages necessary dependencies. On building, a plugin ZIP file will be created and attached which is ready to be deployed with the given application.

The archetype has the following additional parameters:

application	The targeted application (for example, studio-server). The value is the artifact ID of the root POM of the workspace. It is also possible to set this to <code>common</code> or <code>middle</code> to create a plugin that could be used in different applications.
cms-version	The version of the CoreMedia platform that you compile and test your plugin against (for example, 2101.1).

Example: Creating a *Studio Server* plugin

```
mvn archetype:generate \
  -DarchetypeGroupId=com.coremedia.maven \
  -DarchetypeArtifactId=plugin-archetype \
  -DarchetypeVersion=1.0.0 \
  -DgroupId=com.acme.plugins \
  -DartifactId=myplugin-studio-server \
  -Dversion=0.1.0-SNAPSHOT \
  -Dpackage=com.acme.plugins.myplugin.studio_server \
  -Dapplication=studio-server \
  -Dcms-version=2101.1
```

Using Plugins

To use your plugins, you have to provide the paths to the directories containing plugins for the application with the Spring property `plugins.directories`.

If you put a zipped plugin in there, it will be automatically extracted on the first start of the application and the extracted directory is used afterwards. See [Section 4.3, “Build and Run the Applications” \[109\]](#) for how to configure and run CoreMedia Java applications.

Plugin Dependencies

Plugins can also have dependencies on other plugins to make use of their classes and beans. Dependencies are declared in the property `plugin.dependencies`. You

can declare just the dependent plugin's ID or a specific version or version range separated by @. Multiple dependencies can be declared separated by commas.

Examples

- `some-plugin`
- `some-plugin@1.0.0`
- `some-plugin@>=1.0.0 & <2.0.0`

Providing Beans to Dependents

The configuration classes described in [Section "Application Beans in Plugins" \[76\]](#) are a kind of public beans API for your plugin. For each of those configuration classes, you need to create a class implementing the `BeansForPluginsContainer` marker Interface. This implementation serves as a container for your Beans and is injected into the dependents application context.

For every Bean definition in the Configuration class there should be a field, a constructor argument and a getter in the `BeansForPluginsContainer` class. The configuration class should have a field and a constructor with one argument of the concrete `BeansForPluginsContainer` type, so it can delegate to this field in its Bean defining methods. This way Spring can resolve the bean dependencies for the `BeansForPluginsContainer` classes and dependents of your plugin get a simple IDE supported way to find and inject your beans.

Example

PluginB depends on PluginA; PluginA provides a bean of type `SomeBeanFromA` to its dependencies and PluginB uses this bean.

PluginA

```
plugin.id=pluginA
plugin.version=1.2.3
plugin.configuration-class=com.acme.plugin_a.PluginAConfiguration
```

Example 4.7. PluginA plugin.properties

```
// Used to collect beans to be injected into dependent plugins
public class PluginABeansForPluginsContainer implements
BeansForPluginsContainer {
    private final SomeBeanFromA someBeanFromA;

    public PluginABeansForPluginsContainer(SomeBeanFromA someBeanFromA) {
        this.someBeanFromA = someBeanFromA;
    }

    public SomeBeanFromA getSomeBeanFromA() {
        return someBeanFromA;
    }
}
```

```

    }
}

```

Example 4.8. *PluginABeansForPluginsContainer*

```

// Defines a public API of Beans to be used by dependents
// and provides convenient access to beans from
PluginABeansForPluginsContainer.
@BeansForPlugins
@Configuration(proxyBeanMethods = false)
public class PluginABeansForPlugins {
    private final PluginABeansForPluginsContainer
pluginABeansForPluginsContainer;

    @SuppressWarnings("SpringJavaInjectionPointsAutowiringInspection")
    public PluginBeansAConfiguration(PluginABeansForPluginsContainer
pluginABeansForPluginsContainer) {
        this.pluginBeansA = pluginABeansForPluginsContainer;
    }

    @Bean
    public SomeBeanFromA someBeanFromA() {
        return pluginABeansForPluginsContainer.getSomeBeanFromA();
    }
}

```

Example 4.9. *PluginABeansForPlugins*

```

...
@Bean
SomeBeanFromA someBeanFromA() {
    return new SomeBeanFromA();
}

// Beans of type PluginBeans will be collected and injected into
// dependents by the framework.
@Bean
PluginBeansA pluginBeansA(SomeBeanFromA someBeanFromA) {
    return new PluginBeansA(someBeanFromA);
}
...

```

Example 4.10. *PluginAConfiguration*

PluginB

```

plugin.id=pluginB
plugin.version=0.1.0
plugin.configuration-class=com.acme.plugin_b.PluginBConfiguration
plugin.dependencies=pluginA

```

Example 4.11. *PluginB plugin.properties*

```

@Import(PluginABeansForPlugins.class)
@Configuration(proxyBeanMethods = false)
class PluginBConfiguration {
    ...
    @Bean
    SomeBeanForB someBeanForB(SomeBeanFromA someBeanFromA) {
        return new SomeBeanForB(someBeanFromA);
    }
}

```

```

    }
    ...
}

```

Example 4.12. PluginBConfiguration

Add-Ons

Plugins can also extend other plugins. To this end plugins can define extension points for which they collect implementing beans from *add-on* plugins using the `AddOnManager`.

A plugin can have multiple dependencies but can only be an add-on for one other plugin. Add-ons can also inject beans from the extended plugin in the same way as if the add-on had a dependency on the extended plugin. The `AddOnManager` can be injected by importing the configuration class `com.coremedia.cms.common.plugins.plugin_framework.addons.AddOnConfiguration`.

Example

PluginB is an add-on for PluginA and provides an extension for PluginA's extension point.

PluginA

```

plugin.id=pluginA
plugin.version=1.2.3
plugin.configuration-class=com.acme.plugin_a.PluginAConfiguration

```

Example 4.13. PluginA plugin.properties

```

public class SomeExtensionPointForA {}

```

Example 4.14. SomeExtensionPointForA

```

@Import(AddOnConfiguration.class)
@Configuration(proxyBeanMethods = false)
class PluginAConfiguration {
    @Bean
    UsageOfExtensionPoints usageOfExtensionPoints(AddOnManager addOnManager)
    {
        return new
        UsageOfExtensionPoints (addOnManager.getExtensions (SomeExtensionPointForA.class));
    }
}

```

Example 4.15. PluginAConfiguration

PluginB

```
plugin.id=pluginB
plugin.version=0.1.0
plugin.configuration-class=com.acme.plugin_b.PluginBConfiguration
plugin.add-on-for=pluginA
```

Example 4.16. *PluginB plugin.properties*

```
...
@Bean
SomeExtensionPointForAImpl someExtensionPointForAImpl() {
    return new SomeExtensionPointForAImpl();
}
...
```

Example 4.17. *PluginBConfiguration*

```
public class SomeExtensionPointForAImpl extends SomeExtensionPointForA {}
```

Example 4.18. *SomeExtensionPointForAImpl*

Plugins for Studio Client

The word *plugin* is already used in the *Studio Client* world and the already existing `StudioPlugin` and `EditorPlugin` are of course still used to customize the *Studio Client* [See Section 7.1, “Studio Plugins” in *Studio Developer Manual*]. The *plugins* that are described here are merely a new packaging around these, so that you are able to add customizations at deployment time similar to the Java applications.

Creating Plugins

A *Studio Client Plugin* is just a normal `swc` project containing your standard `StudioPlugin` and optionally additional modules. One limitation is that all modules must be usable as *dynamic packages*, leading [section “Adding Studio Client Modules as Blueprint extensions” \[129\]](#) The only specialty of the plugin Maven project is that you execute the goal `package-plugin` of the `jangaroo-maven-plugin` that will package your code together with your dependencies into a zip file which is very similar to a `jangaroo-app-overlay.jar`.

NOTE

It is important to set the scope of all CoreMedia dependencies that you use in your plugin and that are already part of the `studio-app` to `provided` to prevent them from being packaged with your plugin redundantly.



The created ZIP file contains a directory `packages` that contains all packages as subfolders.

Maven Archetype

As a starting point for the development of a new plugin it is recommended to use CoreMedia's `studio-client-plugin-archetype`. The created Maven project consists of a single `swc` project with some common dependencies. During the build, a plugin ZIP file will be created and attached which can be used by a *Studio Client* container after unpacking. It also adds some convenience to run the local development state of your Studio Client Plugin [see [Section "Working with the Plugin Workspace" \[86\]](#) for details.

The archetype has the following additional parameter:

cms-version The version of the CoreMedia platform that you compile and test your plugin against (for example, **2101.1**).

Example: Creating a *Studio Client* plugin

```
mvn archetype:generate \
  -DarchetypeGroupId=com.coremedia.maven \
  -DarchetypeArtifactId=studio-client-plugin-archetype \
  -DarchetypeVersion=1.0.0 \
  -DgroupId=com.acme.plugins \
  -DartifactId=myplugin-studio-client \
  -Dversion=0.1.0-SNAPSHOT \
  -Dpackage=com.acme.plugins.myplugin.studio_client \
  -Dcms-version=2101.1
```

Working with the Plugin Workspace

Like the Maven workspaces for the other (Java) CoreMedia applications, the workspace resulting from the Studio Client plugin archetype can be built independently from the Blueprint workspace. For example, it does not reuse a parent POM of the Blueprint workspace. This is important, so that your plugin can be updated and released independently of your Blueprint customizations and a concrete CoreMedia release.

All dependencies on Studio modules that are already part of `studio-app` must be set to `provided`. For Studio Client, you will only use non-provided dependencies, that is `compile` dependencies [which is the default value for `scope`], for the following cases:

- For plugin-specific third-party modules
- For splitting a large Studio plugin into several modules
- For a utility module reused by different plugins

Note that unlike plugins for Java applications, Studio Client does not support dedicated class loading per plugin, and thus all plugins use the same version of a shared code module.

If you have two plugins that use a common shared code module, but can be used independently of one another, each of them must bundle the shared code module (that is, specify a `compile` dependency on that module, so that it is added to the plugin's ZIP artifact). It is allowed to use plugins with "overlapping" modules, but consider that when all plugins are extracted into a common folder, only one copy can "win". Thus, using different versions of shared code modules is strongly discouraged, as it may lead to spurious errors at runtime.

Apart from this special treatment of dependencies, a Studio plugin workspace is used just like a normal Studio plugin in the Blueprint workspace. You build it with `mvn install`, resulting in JavaScript files and resources in the `target` directory and an `swc` artifact. What is different is that by specifying the goal `package-plugin` in the POM, all resources needed by the plugin are gathered in the subfolder `target/app` and an additional artifact (a `zip`) is created that contains all these resources. This artifact is installed, deployed and released like any other Maven artifact, so it can be used to produce a "binary" release of your Studio Client plugin.

The POM created by the archetype also contains configuration to conveniently test the local development state of your plugin. You need a ready-to-run Studio Client as described in [Section 4.3, "Build and Run the Applications"](#) [109].

If the feature you develop as a plugin also plugs into Studio Server (which is a common case), take care that this Studio Client is connected to a Studio Server including the corresponding plugin. To activate your Studio Client plugin, you have two options:

- If you want to use the Studio Client Docker image, you only need to mount your plugin's `target/app` directory as a volume under the path configured in the Nginx server running in Docker, namely `/coremedia/additional-packages/plugins`. Then, run the Docker image, and Studio Client will pick up your plugin.
- If you want to run Studio Client from your Blueprint workspace via Maven, you must configure the path to your plugin's `target/app` directory via the system property `additionalPackagesDirs`, for example like so:

Provided and non-provided dependencies

No dedicated class loading per plugin

Building the Studio plugin workspace

Configuration for testing

Activating Studio client plugin

```
mvn jangaroo:run
-DadditionalPackageDirs=~/.workspace/my-plugin/studio-client/target/app
```

You may specify multiple additional package directories as a comma-separated list.

Plugin Discovery

The Studio Client app supports dynamic packages that can be added without rebuilding the app itself. When dynamic packages were introduced, you still had to create an "application overlay" Maven module (packaging type `jangaroo-app-overlay`) to add dynamic packages. This is how the `studio-app` module in the Blueprint workspace adds all dynamic packages to `studio-base-app`.

However, using application overlays is not flexible enough for plugins, so the mechanism to "discover" dynamic packages has been enhanced. To use this enhanced mechanism, you can just use the Maven archetype described in [Section "Maven Archetype" \[86\]](#) and the Docker image created by the `apps/studio-client` workspace, and it will work out of the box. Read on if you'd like a deeper understanding of how plugin (or to be more precise: dynamic package) discovery in Studio Client works, for example for debugging purpose in case your plugin does not load.

The package loading of the `studio-app` has been extended to look for additional packages at the URL path `/additional-packages/`. There, it expects a directory listing from the web server. Currently the only supported format is the JSON format of the [NGINX autoindex module](#). The Studio Client Docker image contains an Nginx server with the necessary configuration.

Extended package loading

To support multiple additional package directories, the package discovery protocol expects further subdirectories at this level, which then contain the content of all package directories of your plugins. The package loader only uses these paths to find the packages. For the actual loading it expects the packages themselves to be served at the standard path `/packages/package-name`. This way you can dynamically add packages to your `studio-app` without rebuilding it, just with some web server magic.

Example: Packages request mapping

Path	Description
<code>/packages/dynamic-packages.json</code>	Listing of built-in packages
<code>/packages/additional-packages/</code>	Directory listing of further package locations
<code>/packages/additional-packages/plugins/</code>	Directory listing of packages from the plugins directory

Path	Description
/packages/additional-packages/plugins/com_acme__myplugin	An additional package from the plugins directory
/packages/additional-packages/more-plugins/	Directory listing of packages from the directory more-plugins
/packages/com_coremedia__a_built_in_package	Built-in packages are loaded from /packages/
/packages/com_acme__myplugin	Additional packages are also loaded from /packages/ ; the web server also looks at the plugins directory and will deliver /packages/additional-packages/plugins/com_acme__myplugin

Table 4.1. Packages request mapping

The *Studio Client* NGINX image configures NGINX to create directory listings for the path /additional-packages/ and /additional-packages/plugins/. Additionally, the /packages/ location is extended to also try the /additional-packages/plugins/ path. This way a *Studio Client* container will automatically load all packages from the directory mounted at /coremedia/additional-packages/plugins/.

Plugin Bundles

As a feature often requires the extension of multiple applications, a JSON file is used to bundle up plugins for different applications. If you write plugins only for a specific project, you probably do not need to create such a file. But if you want to provide plugins for others or want to use plugins provided by CoreMedia or partners, this file is intended to be the entry point to access those plugins.

The file simply lists all individual plugins by their targeted applications. The plugins are referenced by their Maven coordinates, where the type is always zip. The JSON file should follow the schema at <https://releases.coremedia.com/plugins/plugin-schema-1.0.0.json>.

There is no automated out-of-the-box deployment process that would distribute the individual plugins into the respective applications. You could include them as a dependency into your Maven project, for example, when building your docker images, or download them manually or via `mvn dependency:copy -Darti`

`fact=g:a:v:zip -DoutputDirectory=.` and deploy them with your applications directly.

Example

```
{
  "$schema": "https://releases.coremedia.com/plugins/plugin-schema-1.0.0.json",
  "plugins": {
    "studio-server": {
      "maven": {
        "groupId": "com.acme.plugins",
        "artifactId": "my-plugin-studio-server",
        "version": "1.2.3"
      }
    },
    "studio-client": {
      "maven": {
        "groupId": "com.acme.plugins",
        "artifactId": "my-plugin-studio-client",
        "version": "4.5.6"
      }
    }
  }
}
```

Example 4.19. my-plugin-7.8.9.json

As you can see in the example, the individual plugins can have different versions and the JSON descriptor itself should also be versioned, so that you can release new versions without breaking anything. Of course all plugins and the JSON descriptor could share the same version if you release everything together.

4.2 Configuring the Workspace

Before you can start with development, you have to do some configurations, in part, depending on the Blueprint you want to work with.

- Remove the Blueprints and modules that you do not want to use as described in [Section 4.2.1, “Removing Optional Components” \[91\]](#).
- Adapt your Maven settings to the required repositories as described in [Section 3.1, “Prerequisites” \[30\]](#).
- Adapt the workspace to your own project as described in [Section 4.2.2, “Configuring the Workspace” \[104\]](#). Configure, for example, groupId, version, deployment repositories and CoreMedia licenses.
- If you want to use a local setup, then you have to do some database configuration and host mapping as described in [Section 4.2.3, “Configuring Local Setup” \[105\]](#).

4.2.1 Removing Optional Components

The *CoreMedia Content Cloud* workspace contains a complete CoreMedia system with all the core components and optional modules which have to be licensed separately. See [Section 2.1, “Components and Architecture” \[19\]](#) for an overview of all components. Before you start with development, remove all modules that you do not need.

Name	Description	Removal
<i>CoreMedia Adaptive Personalization</i>	Module for the work with personalized content and personas.	See Section “Removing the Adaptive Personalization Extension” [102]
<i>CoreMedia Elastic Social</i>	Module for the work with external users and user generated content, such as ratings or comments.	See Section “Removing the Elastic Social Extension” [101]
<i>Advanced Asset Management</i>	Module for the work with assets, such as images or documents.	See Section “Removing the Advanced Asset Management Extensions” [103]
eCommerce Blueprint	Blueprint for the integration with an eCommerce system.	See Section “Removing the eCommerce Blueprint” [103]

Name	Description	Removal
Brand Blueprint	Blueprint for a brand website with responsive templates.	See Section “Removing the Brand Blueprint” [103]

Table 4.2. Optional modules and blueprints

[Section “Extensions and Their Dependencies” \[92\]](#) lists all extensions and their mutual dependencies.

As described in [Section 4.1.5, “Project Extensions” \[67\]](#) the *CoreMedia Blueprint* workspace provides an easy way to enable or disable existing extensions in one place. This chapter shows you how to disable and remove extensions from the *Blueprint*.

The command is always the same, only the list of extension names differs depending on the feature to remove. There are two different commands to deactivate an extension:

disable	Removes the dependencies from applications to any extension modules, but keeps the modules in the Maven aggregator(s) in a profile named <code>inactive-extensions</code> .
remove	Removes the dependencies from applications to any extension modules, but keeps the modules in the Maven aggregator(s) in a profile named <code>inactive-extensions</code> .

All commands in the following sections use `disable`, which can be replaced by `remove` according to your needs. All `mvn` commands have to be executed in directory `workspace-configuration/extensions`.

Extensions and Their Dependencies

This section sums up the existing extensions in *CoreMedia Blueprint* and shows their mutual dependencies and their dependencies with licensed product add-ons. This information is required when removing extensions completely or when you want to know the licences required for some extensions.

To obtain a list of all extensions in the *CoreMedia Blueprint* workspace, invoke the extensions tool with the following command:

```
mvn -f workspace-configuration/extensions extensions:list -q -DshowDependencies
-Dverbose
```

More information on how to use the extensions tool can be found in the `README.md` in `workspace-configuration/extensions`.

Dependencies between extensions and licences

alx	
Description	General Analytics Integration
Required by Extension	alx-google, alx-webtrends, es-alx, alx-p13n
Required licences	No add-on licence required
alx-google, alx-webtrends	
Description	Specific Analytics Integration for Google Analytics and Webtrends. These extensions can be enabled or disabled independently.
Required by extension	None
Required licences	None
alx-p13n	
Description	Personalization plugin for Analytics, exposes personalization info (for example, segment) for tracking
Required by extension	alx-google, alx-webtrends, es-alx
Required licences	Adaptive Personalization
am	
Description	<i>CoreMedia Asset Management</i> allows you to store digital assets (for example high-resolution pictures of products) in the content repository.
Required by extension	None

Required licences	Advanced Asset Management
-------------------	---------------------------

catalog

Description	Internal catalog.
-------------	-------------------

Required by extension	corporate
-----------------------	-----------

Required licences	None
-------------------	------

corporate

Description	Extension with the features for the Brand Blueprint.
-------------	--

Required by extension	None
-----------------------	------

Required licences	None
-------------------	------

content-hub-default

Description	Content Hub
-------------	-------------

Required by extension	None
-----------------------	------

Required licences	Content Hub
-------------------	-------------

content-hub-default-adapters

Description	Content Hub adapters
-------------	----------------------

Required by extension	None
-----------------------	------

Required licences	Content Hub
-------------------	-------------

create-from-template

Description	Create a Page in Studio with predefined content.
-------------	--

Required by extension	None
-----------------------	------

Required licences None

custom-topic-pages

Description Create custom topic pages in Studio.

Required by extension None

Required licences None

ecommerce-adapter

Description eCommerce Adapter

Required by extension None

Required licences Commerce Hub

ecommerce-ibm

Description *HCL Commerce* implementations and features for eCommerce and demo content

Required by extension None

Required licences Commerce Hub, Connector for HCL Commerce

headless-search

Description Search integration for headless-server

Required by extension lc-asset, ec-augmentation

Required licences None

ec-augmentation

Description eCommerce augmentation extension for headless-server

Required by extension none

Required licences Commerce Hub

hybris

Description SAP Hybris specific demo content

Required by extension None

Required licences Commerce Hub, Connector for SAP Commerce Cloud

ecommerce-sfcc

Description Salesforce Commerce Cloud specific demo content

Required by extension None

Required licences Commerce Hub, Connector for Salesforce Commerce Cloud

ecommerce-commercetools

Description commercetools specific demo content

Required by extension None

Required licences Commerce Hub, Connector for commercetools

es

Description CoreMedia Elastic Social Integration

Required by extension es-p13n, lc-es, sfmc-es-p13n

Required licences Elastic Social

es-alx

Description Extension to retrieve and cache computed data from Analytics. The data is persisted using CoreMedia Elastic Core.

Required by extension	None
Required licences	No add-on licence required
es-controlroom	
Description	Extension that enables the collaborative features and supports MongoDB as the database for collaborative components.
Required by extension	None
Required licences	No add-on licence required
es-p13n	
Description	Extension to retrieve data from CoreMedia Elastic Social for use in the Adaptive Personalization Extension.
Required by extension	None
Required licences	Adaptive Personalization, Elastic Social
external-preview	
Description	Adds the external preview functionality to Studio and CAE. The external preview is a Studio utility that supports to use one or more additional displays for Studio's preview.
Required by extension	None
Required licences	No add-on licence required
feedback-hub	
Description	Feedback Hub
Required by extension	None
Required licences	Experience Feedback Hub

lc	
Description	Generic eCommerce Extension
Required by extension	ecommerce-ibm, hybris, lc-es, lc-p13n, lc-asset, ec-augmentation
Required licences	Commerce Hub
lc-asset	
Description	Feature allows you to manage images and image variants (or crops) for categories, products and products variants (products for short) in the CoreMedia system. These extensions depend on <i>CoreMedia Commerce</i> .
Required by extension	ec-augmentation
Required licences	Advanced Asset Management, Commerce Hub
lc-es	
Description	Elastic Social features for eCommerce
Required by extension	None
Required licences	Elastic Social, Commerce Hub
lc-p13n	
Description	Personalization features for eCommerce
Required by extension	None
Required licences	Adaptive Personalization, Commerce Hub
notification-elastic	
Description	Notifications
Required by extension	None

Required licences	None
-------------------	------

optimizely

Description	Optimizely Integration
-------------	------------------------

Required by extension	None
-----------------------	------

Required licences	None
-------------------	------

osm

Description	OpenStreetMap Integration
-------------	---------------------------

Required by extension	None
-----------------------	------

Required licences	None
-------------------	------

p13n

Description	CoreMedia Adaptive Personalization Integration
-------------	--

Required by extension	es-p13n, alx-p13n, lc-p13n, sfmc-p13n, sfmc-es-p13n
-----------------------	---

Required licences	Adaptive Personalization
-------------------	--------------------------

sfmc

Description	Salesforce Marketing Cloud basics
-------------	-----------------------------------

Required by extension	sfmc-p13n, sfmc-es-p13n
-----------------------	-------------------------

Required licences	Marketing Automation Hub, Connector for Salesforce Marketing Cloud
-------------------	--

sfmc-p13n

Description	Salesforce Marketing Cloud Personalization
-------------	--

Required by extension	None
-----------------------	------

Required licences	Adaptive Personalization, Marketing Automation Hub, Connector for Salesforce Marketing Cloud
sfmc-es-p13n	
Description	Salesforce Marketing Cloud Personalization
Required by extension	None
Required licences	Adaptive Personalization, Elastic Social, Marketing Automation Hub, Connector for Salesforce Marketing Cloud
taxonomy	
Description	Taxonomy
Required by extension	taxonomies required by alx-p13n, am, custom-topic-pages, es-p13n, lc-p13n, p13n, sfmc-p13n
Required licences	No add-on licence required

Table 4.3. Blueprint Extensions and Dependencies

Add-on licences and their corresponding extensions

The following Table 4.4, “ Add-ons and the dependent extensions ” [100] shows the CoreMedia add-on licences and the extensions which need this license.

NOTE

This section only describes the technical dependencies between add-ons and extensions. If you can use a CoreMedia system in a specific configuration, depends on your contract.



Add-On	Extensions
Adaptive Personalization	alx-p13n, es-p13n, lc-p13n, p13n, sfmc-p13n, sfmc-es-p13n
Elastic Social	es, es-p13n, lc-es, sfmc-es-p13n

Add-On	Extensions
Content Hub	Up to three Content Hub adapters, including the default ones, are already included in the product. Content Hub adapters use extension <code>content-hub-default</code> . Default adapters are packages in extension <code>content-hub-default-adapters</code> .
Experience Feedback Hub	<code>feedback-hub</code>
Commerce Hub	A general commerce hub license is required for any of CoreMedia's vendor-specific commerce adapters as well as to implement a custom commerce adapter, based on extension <code>ecommerce-adapter</code> . The license for a vendor-specific commerce adapter allows using the corresponding extension:
Connector for HCL Commerce	<code>ecommerce-ibm</code> (starting with CMCC 2004: demo content only, adapter ships separately)
Connector for SAP Commerce Cloud	<code>hybris</code> (demo content only, adapter ships separately)
Connector for Salesforce Commerce Cloud	<code>ecommerce-sfcc</code> (demo content only, adapter ships separately)
Connector for commercetools	<code>ecommerce-commercetools</code> (demo content only, adapter ships separately)
Marketing Automation Hub	Not yet sold separately / no corresponding extension yet.
Connector for Salesforce Marketing Cloud	<code>sfmc</code> , <code>sfmc-es-p13n</code> , <code>sfmc-p13n</code>

Table 4.4. Add-ons and the dependent extensions

Removing the Elastic Social Extension

This section describes the required steps to remove the *CoreMedia Elastic Social* extension from *Blueprint*.

NOTE

Removing the Elastic Social Integration is optional. Even if you have no license or if you do not want to use it, you can leave the extension in the workspace.



1. Remove the listed extensions from the managed extensions.

```
mvn extensions:sync -Ddisable=es,es-p13n,lc-es,sfmc-es-p13n
```

Example 4.20. Remove CoreMedia Elastic Social Extension

2. Some documents of the demo content may have references to extension specific documents [CMMail, CMUserProfile, CMP13NSearch, CMSelectionRules]. After removing the extension, this may lead to errors in the CoreMedia components. The content has to be adapted not to use extension specific content any longer.

Either exclude any documents of types defined in `elastic-social-plugin-doctypes.xml` or manually add those content types to your *Content Server*.

3. Disable or remove the frontend brick `elastic-social` and make sure, it is not used in any existing theme.

Removing the Adaptive Personalization Extension

This section describes the required steps to remove the *CoreMedia Adaptive Personalization* extension from *CoreMedia Blueprint*.

1. Remove the listed extensions from the managed extensions.

```
mvn extensions:sync -Ddisable=p13n,alx-p13n,es-p13n,lc-p13n,sfmc-p13n,sfmc-es-p13n
```

Example 4.21. Remove CoreMedia Adaptive Personalization Extension

2. The *Adaptive Personalization* integration brings along specific content types. If you disable the Adaptive Personalization Integration the *Content Server's* configuration will be affected as well. In this case you have to drop the databases of the *Content Servers* during the next deployment. Furthermore, you have to remove the documents of this content types from the demo content before importing or manually deploy the relevant content types to your content server.

Either exclude any documents of types defined in `personalization-doc-types.xml` or manually add those content types to your *Content Server*.

Example 4.22. Example for Adaptive Personalization Content in Blueprint

Removing the eCommerce Blueprint

This section describes the required steps to remove the *CoreMedia eCommerce* Blueprint from the *CoreMedia Blueprint* workspace depending on your eCommerce Connector.

1. Remove the listed extensions from the managed extensions.

```
mvn extensions:sync
-Ddisable=lc,lc-asset,lc-es,lc-pl3n,ecommerce-ibm,hybris,ecommerce-sfcc,
ecommerce-adapter,ec-augmentation
```

Example 4.23. Remove CoreMedia eCommerce Extension

2. Delete the following themes: `aurora-theme`, `calista-theme`, `hybris-theme`, `sfra-theme`, `sitegenesis-theme` in the frontend module `[themes]`.

Removing the Brand Blueprint

This section describes the required steps to remove the *CoreMedia Brand* Blueprint from the *CoreMedia Blueprint* workspace.

1. Remove the listed extensions from the managed extensions.

```
mvn extensions:sync -Ddisable=corporate
```

Example 4.24. Remove CoreMedia Corporate Extension

2. Delete the `corporate-theme` in the Frontend Workspace `[themes]`.

Removing the Advanced Asset Management Extensions

This section describes the required steps to remove *Advanced Product Asset Management* from *CoreMedia Blueprint*. *Advanced Asset Management* consists of two extensions.

1. Remove the listed extensions from the managed extensions.

```
mvn extensions:sync -Ddisable=lc-asset,am
```

Example 4.25. Remove CoreMedia Product Asset Management Extension

2. If you use the CoreMedia example content, you also have to remove the links to Asset content in the CMPicture files. You can use a tool like sed.
3. Disable or remove the frontend brick `download-portal` and make sure, it is not used in any existing theme.

4.2.2 Configuring the Workspace

The *Blueprint* workspace comes ready to use. However, there are some environment specific configurations to be adjusted at the very beginning of a project. You may skip these steps only if you are just going to explore the workspace, you will neither share your work with others nor release it, and you will start over from scratch again with your actual project.

Changing the group IDs and versions

The groupId of the *CoreMedia Blueprint* workspace is `com.coremedia.blueprint`. While this works from the technical point of view, you have to change it to a project specific groupId, because CoreMedia reserves the possibility to provide versioned artifacts of this groupId.

Since the groupId is needed to denote the parent POM file, it cannot be inherited but occurs in every `pom.xml` file. CoreMedia provides a script for this task. It does not only change the group ID in the POM files but also in the deployment environment when necessary. Execute the following command in the workspace:

```
./workspace-configuration/scripts/set-blueprint-groupId.sh <YourGroupId>
```

You can use the script `set-blueprint-version.sh` to also change the versions.

4.2.3 Configuring Local Setup

Relational Database Setup

You need to create different databases and users used by the various *CoreMedia CMS* components (see [Section 3.1, "Prerequisites" \[30\]](#)). In the `workspace-configuration/database` folder of the *Blueprint* workspace you will find SQL scripts for creating and dropping all database entities needed for the relational database.

The scripts are suitable for a local MySQL instance in a developer environment. You can easily adapt them for other databases or remote users. There are also Bash scripts and Windows batch files to apply the SQL scripts. If the MySQL server is running and the `mysql` command line client is executable via the `PATH` variable, you only need to execute the following in order to prepare the databases for *CoreMedia Content Cloud*.

Windows:

```
> cd $CM_BLUEPRINT_HOME\workspace-configuration\database\mysql\
createDB.bat
```

Linux:

```
$ cd $CM_BLUEPRINT_HOME/workspace-configuration/database/mysql
./createDB.sh
```

The command was successful if the following databases have been created:

Database	User	Password	Description
cm_management	cm_management	cm_management	Database for the <i>Content Management Server</i>
cm_master	cm_master	cm_master	Database for the <i>Master Live Server</i>
cm_replication	cm_replication	cm_replication	Database for the <i>Replication Live Server</i>
cm_mcafeeder	cm_mcafeeder	cm_mcafeeder	Database for the <i>CAE Feeder</i> connected to the <i>Content Management Server</i>
cm_cafeeder	cm_cafeeder	cm_cafeeder	Database for the <i>CAE Feeder</i> connected to the <i>Master Live Server</i>

Database	User	Password	Description
cm_editorial_comments	cm_editorial_comments	cm_editorial_comments	Database for the <i>Studio Server</i> that runs the editorial comments feature

Table 4.5. Database Settings

MongoDB Database Setup

Several CoreMedia core features like *CapLists*, *Notifications* and *Projects* require MongoDB as a persistence layer. A default local MongoDB installation is sufficient, because the CoreMedia components connect through the default port with no user credentials, by default. If required, see Section 4.5, “Collaborative Components” in *Operations Basics* for more MongoDB configuration.

4.2.4 In-Memory Replacement for MongoDB-Based Services

Several CoreMedia core features like *CapLists*, *notifications* and *projects/to-dos* use *MongoDB* as a persistence layer. Although not recommended, it is possible to substitute *MongoDB* with an *in-memory* persistence layer.



NOTE

There is no *in-memory* replacement for the persistence layer of the *Elastic Social* extension. *MongoDB* is required for that.

Besides not supporting *Elastic Social* there are other functional limitations to the *in-memory* approach. Collaboration based on projects/to-dos will not work properly with more than one *Studio* server.

In the following, you find how to activate the in-memory persistence for *Studio* and *Workflow server*

In-Memory configuration for Studio

The easiest way is to use the Maven profile `in-memory` when starting the *Studio* web app. This will take care of setting all the required system properties accordingly.

Alternatively (or if using the profile is not an option for some reason) you can take care of setting the required properties yourself. You need the following:

```
elastic.core.persistence=memory
mongodb.models.create-indexes=false
repository.capi.list.connect=true
repository.capi.list.factory-class-name=com.coremedia.cotopaxi.list.memory.MemoryCapListConnectorFactory
```

Furthermore, you can configure your *Studio* server with the following properties so that the *in-memory* store is read / written from the given file upon application context startup / shutdown. To limit memory usage of the in-memory store, the size per collection map is configured. To be robust against data loss, the in-memory store can be persisted periodically in a given interval.

Property	Default	Description
repository.params[memory.collection.serialization.file]	null	In-memory store persistence file name.
repository.params[memory.collection.size]	5000	Number of in-memory map entries per collection.
repository.params[memory.collection.serialization.interval]	360000	Interval in ms in which the in-memory store is persisted periodically to the configured file. If 0, periodic persistence is disabled.
repository.params[memory.collection.selfclearing.names]	notifications	A comma separated list of collection names, which will be periodically deleted and re-created, when <code>memory.collection.size</code> is reached. Fast growing collections, which do not contain critical data should be configured as self-clearing collections, for example, notifications.

Table 4.6. Studio Configuration Properties for In-Memory Store

In-Memory configuration for the Workflow Server

In the *in-memory* deployment the *Workflow Server* sends pending and finished processes to *Studio*, where they are persisted in the *Studio*'s *in-memory* persistence layer. In order to connect to *Studio*, the *Workflow Server* needs a *Studio* connection and an authorized user.

The recommended way to enable the in-memory configuration for *Workflow Server*, is to create a Spring application configuration file, like `application-in`

`memory.properties`, add the necessary configuration properties and start the *Workflow Server* web app with the corresponding Spring profile name (in this case with the profile name `inmemory`).

The configuration file has to contain these settings:

```
elastic.core.persistence=memory

studio.host=localhost
studio.http.port=41080
studio.context=studio

studio.user=admin
studio.password=admin

repository.caplist.connect=false
```

Alternatively, the properties above also can be set using corresponding environment variables (written in upper case, appropriate for Spring relaxed binding). This approach may come in handy in a container environment like docker. The blueprint workspace contains a docker compose YAML file, which may serve as a starting point: `global/deployment/docker/compose/in-memory.yml`

Please note, that you may need to adapt the values for `studio.host`, `studio.http.port` and `studio.context`.

4.3 Build and Run the Applications

The Blueprint workspace provides Maven modules to build Spring Boot applications for Blueprint applications.

Prerequisites

Before you can run the applications, you have to build the [CoreMedia Blueprint Workspace](#) in advance:

```
mvn clean install -Pwith-docker
```

See [Section 3.2.1, “Building the Workspace” \[35\]](#) for more details.

Workspace Structure

- `apps/<app-name>/spring-boot` - below this folder there is a Maven module for each service application. Each of these modules will build a single Spring Boot application packaged as a JAR file.
- `shared/common/spring-boot/blueprint-spring-boot-autoconfigure`, this module encapsulates common configuration aspects for all Spring Boot service modules.

See [Section 4.1.4, “Structure of the Workspace” \[59\]](#) for more details.

Application Structure

Each Spring Boot application module is structured the same way:

- A source folder containing at least the application starter class. It could also contain other classes implementing Spring configuration classes.
- A resources folder containing the properties files and the logging configuration file.

Spring Configuration

Each application can define properties in multiple Spring Boot profiles:

- The **default** profiles with properties defined in `application.properties`.
- The **development** profiles defined in `application-dev*.properties`.
- The **local** profiles with properties defined in `application-*.local.properties`. These properties can contain paths only available on a local workstation.

The default local profile is named `local` and should be used when starting the application using either IDEA or Maven.

The Docker specific Spring Boot profiles can be found under `apps/<app-name>/docker/src/docker/config`, like

- Commerce specific settings:
 - `application-dev-wcs.properties`
- **Development profiles** activating development features for local and CI environments.
 - The default development profile is named `dev` and should be used when starting the application using either IDEA or Maven.

Logging

The overall logging setup is configured in the configuration files `logback-common.xml` and `logback-elk.xml` located in the module `blueprint-spring-boot-autoconfigure`. Note that these files are declared as `included` and must be referenced in the concrete `logback-spring.xml` file of each application. This way, every application can configure its own default log level and appenders.

Developing with CoreMedia Blueprint applications

Currently there are two different approaches to start the Spring Boot apps you want to develop locally:

- using the `spring-boot-maven-plugin`
- using IntelliJ IDEA run configurations together with the Run Dashboard

The apps you don't want to alter, can be provided using either:

- a remote deployment of any kind using the Spring Boot apps, that is Docker or Chef.
- a local Docker deployment for complete isolation or running offline.

Application Configuration Facade

To configure the locally started applications, Spring Boot profiles are being used:

- `dev` - this profile activates development features like actuators, monitoring etc. and should not add filesystem or localhost features. This profile will be active by default if you include the `development.yml` in the docker compose setup included with this workspace.

- `local` - this profile configures local paths within the workspace like paths to licenses or source folders of other modules. This profile should only be activated for locally started apps using Maven or IDEA but not the docker compose setup.

To configure which application should be used from a remote system, there is a list of convenience host properties, forming a simple configuration facade. The intent of these properties is to use them only on the command-line or in IDEA run configurations when you are developing locally. Do not use these properties outside of the `application-local.properties` files.

The main property is `installation.host` which when set implicates all other services / endpoints are running remotely. By default, all other convenience host properties derive their default from `installation.host`. If you start more than one service locally, lets say `studio-server` and `preview`, then you need to tell `studio-server` to use the locally started `preview` instead of a remote one and you have to set `cae-preview.host` to `localhost`.

```
- installation.host
  |- db.host
  |- mongodb.host
  |- solr.host
  |- content-management-server.host
  |- master-live-server.host
  |- workflow-server.host
  |- cae-preview.host
  |- cae-live.host
  - wcs.host
```

4.3.1 Starting Applications using IntelliJ IDEA

Since IDEA 2018.2 Spring Boot applications are natively supported in the *Run* dashboard.

CoreMedia delivers predefined run configurations for the apps with all required settings. In order to use these configurations, do as follows:

1. Copy the predefined files from `apps/<app-name>/spring-boot/ideaRunConfigurations` into the `.idea/runConfigurations` folder in your Blueprint workspace. You can use the script `spring-boot/copy-run-configurations.sh` to copy all configurations at once.

If you copy the configuration files manually, you might have to create the `'runConfigurations'` folder.

2. Close and open IDEA, so that it finds the new run configurations.

Now, you can edit the run configurations in IDEA by setting the `installation.host` or any of the other convenience properties.

Services/Run Dashboard not Visible

In order to see the run configurations in IDEA's *Services* dashboard (in version 18 called *Run Dashboard*) you might have to do some configuration. Open the *Run* menu and select *Edit Configurations*. Select the *Templates* folder, and add *Spring Boot* to the *Configurations available in Services* field in the main field of the window.

4.3.2 Starting Applications using Maven

As an alternative to the IDEA integration, you can start most of the applications using the [spring-boot-maven-plugin](#).

Exception: The Studio Client must be started via a local Jetty Server

Using CoreMedia's configuration facade makes it very simple to use remote services when developing a single app. Simply run

```
mvn spring-boot:run -Dinstallation.host=<FQDN>
```

If more than one app is started locally, simply add the required convenience host properties to the command-line.

NOTE

Please activate the Maven profile `dev`, that is, `mvn spring-boot:run -Pdev`, when you start the following Spring Boot apps locally:

- `cae-preview-app` and `cae-live-app`
- `workflow-server-app`
- `studio-packages-proxy-app`
- `content-server-app`



Starting the Studio Client

You have two possibilities, either start the `studio-packages-proxy-app` or use the `jangaroo:run` Maven goal.

Studio Packages Proxy App

This Spring Boot application delivers your local static Studio Client resources.

Working Directory:

```
apps/studio-packages-proxy/spring-boot/studio-packages-proxy-app
```

You have two possibilities to connect your Studio Client with a Studio server:

1. Connect Remote Studio Server

Start the Studio Packages Proxy and connect against a remote Studio server running at `<FQDN>` via

```
mvn spring-boot:run -Pdev -Dinstallation.host=<FQDN>
```

2. Connect Local Studio Server

First step: Start Studio Server locally. Then start the Studio Packages Proxy via

```
mvn spring-boot:run -Pdev
```

Limitations

Unfortunately, with this approach, it is not possible to deliver static resources from a single, local Maven modul only and proxy all other static resources from a remote Studio Server.

This is only possible using the `jangaroo:run` approach

Links

- [Studio](#)
- [Actuators](#)

Studio Client using a local Jetty Server

This approach delivers your local static Studio Client resources via a Jetty Server started with the Maven goal `jangaroo:run`.

Working Directory:

```
apps/studio-client/modules/studio
```

You have the following possibilities to connect your Studio Client [plugin] with a Studio server.

Connect Remote Studio Server

Start the Studio Client and connect against a remote Studio running at `v`<FQDN>`` via

```
mvn jangaroo:run -pl :studio-app -Dinstallation.host=<FQDN>
```

With this command line call, only Rest requests are proxied to/from the remote Studio Server. No remote static Studio Client resources are proxied, that is, all Studio Client resources are served locally.

Proxy Remote Studio Server and remote Studio Client Resources

This case is interesting if you develop a custom Studio Client plugin, for example, `my-studio-module` and want to proxy the static resources of the Studio Client as well as the Rest requests.

To proxy all request to/from the remote Studio, you need to start the Studio Client via

```
mvn jangaroo:run -pl :my-studio-module \  
-DjooProxyPathSpec=/* \  
-DjooProxyTargetUri=http://studio.<FQDN>:41080
```

or

```
mvn jangaroo:run -pl :my-studio-module \  
-DjooProxyPathSpec=/* \  
-Dinstallation.host=<FQDN>
```

Now, all Rest requests are proxied from/to the remote Studio Server as well as the Studio Client resources from the remote Studio.

Connecting with Local Studio Server

First: Start Studio Server locally.

Then just start the Studio Client via

```
mvn jangaroo:run -pl :studio-app
```

With this command line call, the Rest requests are proxied to/from the locally started Studio Server.

Connecting with Local CAE

When you want to connect Studio Client with a local CAE instance, start Studio Client as above but add `-Dcae-preview.host=localhost` and/or `-Dcae-live.host=localhost` to the Maven call.

Links

- [Studio](#)

Starting the Studio Server

Working Directory:

```
apps/studio-server/spring-boot/studio-server-app
```

Start Studio Server locally via

```
mvn spring-boot:run -Dinstallation.host=<FQDN>
```

Connecting with Local CAE

When you want to connect Studio Server with a local CAE instance, start Studio Server as above but add `-Dcae-preview.host=localhost` and/or `-Dcae-live.host=localhost` to the Maven call.

Links

- [Actuators](#)

Starting the CAE Preview App

Working Directory:

```
apps/cae/spring-boot/cae-preview-app
```

Start CAE Preview locally via

```
mvn spring-boot:run -Pdev -Dinstallation.host=<FQDN>
```

Links

- [Actuators](#)
- [CAE Preview](#)
- [Log File](#)

Starting the CAE Live App

Working Directory:

```
apps/cae/spring-boot/cae-live-app
```

Start CAE Live locally via

```
mvn spring-boot:run -Pdev -Dinstallation.host=<FQDN>
```

- [Actuators](#)
- [CAE Live](#)
- [Log File](#)

Links

- [Studio Client](#)
- [Studio Server Actuators](#)

4.3.3 Local Docker Test System

For the setup of a local Docker test system see [Section 3.2.2, "Docker Compose Setup" \[40\]](#).

4.4 Development

This chapter describes how you can customize your CoreMedia system in the *CoreMedia Blueprint* workspace. However, it does not describe how you, for example, write a *Studio* plugin or a *CAE* template; this is explained in the component's specific manual. Instead, it describes how you can use the workspace mechanisms to include your extensions and where you can add your own code or configuration.

- [Section 4.2.1, “Removing Optional Components” \[91\]](#) describes how you can add and remove extensions using the *CoreMedia Project Maven Build Extension*. The extensions mechanism is explained in detail in [Section 4.1.5, “Project Extensions” \[67\]](#).
- [Section 4.4.2, “Extending Content Types” \[123\]](#) describes how you can add your own content types. You will find more details on content types in the Content Server Manual.
- [Section 4.4.3, “Developing with Studio” \[125\]](#) describes how you can add Studio modules to the list of studio plugins.
- [Section 4.4.4, “Developing with the CAE” \[129\]](#) describes how you can add extensions to the CAEs.
- [???](#) describes how you can add the default structure components for logging and JMX to your own web applications.
- [Section 4.4.6, “Handling Personal Data” \[132\]](#) describes how you can document and check personal data usage in Java code.

4.4.1 Using Blueprint Base Modules

This section describes how the *Blueprint Base Modules* are integrated into *CoreMedia Blueprint* and how a developer might customize and configure all the various modules or even replace certain modules completely.

NOTE

CoreMedia Blueprint uses *Blueprint Base Modules* as binary Maven dependencies but CoreMedia provides access to the source code via Maven source code artifacts. IDE's like JetBrains IntelliJ Idea are able to download those sources automatically for a certain class by evaluating its correspondent Maven POM file.



Content Type Model Dependencies

As its name implies, the *Blueprint Base Modules* contain Blueprint logic and thus depend on the Blueprint's content type model. The content type model is still part of the Blueprint workspace, hence you may customize it. Be aware, that changes might affect or even break the *Blueprint Base Modules*. The following table shows an overview of the content types which are relevant for the *Blueprint Base Modules*. Details are explained in the sections about the particular modules.

Content Type [Properties]	Module
CMLinkable [localSettings, linkedSettings]	Settings
CMTeaser [target]	Settings
CMNavigation	Settings
CMSettings	Settings

Table 4.7. Content type model dependencies

The Settings Service

Settings are a flexible way to enable editors to configure application behavior via content changes within *CoreMedia Studio* without the need to redeploy a web application. *CoreMedia Blueprint* uses the `com.coremedia.blueprint.base.settings.SettingsService` to read certain settings from various different sources. This section describes how you can use the settings service in your own projects.

NOTE

Read [Section 5.4.3, "Settings" \[165\]](#) for a description of why you want to use settings and how to do it from an editors perspective.



The setting* Methods

```
public interface SettingsService {
    <T> T setting(
        String name,
        Class<T> expectedType,
        Object... beans);

    <T> T settingWithDefault([...]);

    <T> List<T> settingAsList([...]);

    <K, V> Map<K, V> settingAsMap([...]);

    [...]
}
```

All `setting*` methods are actually just variants of the basic `setting` method. Some provide additional convenience like `settingWithDefault`, others have complex return types which cannot be expressed as a simple type parameter, for example `settingAsList`. All `setting*` methods have some common parameters which are described in [Table 4.8, “Parameters of the settings* methods” \[119\]](#). For detailed descriptions of the `setting*` methods please consult the API documentation of the `SettingsService`.

Parameter	Description
<i>name</i>	The name (or key) of the setting to fetch.
<i>expectedType</i>	The type of the returned object. This parameter allows for type safety and prevents you from unchecked casts of the result. For the <code>settingAsList</code> method, the <code>expectedType</code> parameter determines the type of the list entries, not the list itself. <code>settingAsMap</code> has separate type arguments for keys and values of the result map.
<i>beans</i>	Settings are always fetched for one or multiple targets, which are passed by the <i>beans</i> <code>vararg</code> parameter. In the <i>Blueprint</i> 's default configuration the <code>SettingsService</code> supports content objects, content beans, pages, sites and some other kinds of beans.

Table 4.8. Parameters of the settings* methods

Configuring the Default Settings Service via SettingsFinders

The *Blueprint Base Modules* not only defines the interface of how to evaluate settings but also provides an implementation and a Spring bean.

```
<beans>
  <bean id="settingsService"
        class="c.c.b.base.settings.impl.SettingsServiceImpl">
    <property name="settingsFinders" ref="settingsFinders"/>
  </bean>

  <util:map id="settingsFinders">
  </util:map>
</beans>
```

The plain `SettingsService` has no lookup logic for settings at all, but it must be configured with `SettingsFinders`. A `SettingsFinder` implements a strategy how to determine settings of a particular type of bean. *CoreMedia Content Cloud* provides some preconfigured `SettingsFinders` for popular beans like content objects. It can be modified and enhanced with custom `SettingsFinders` for arbitrary bean types. As you can see, the default settings service only needs one property, which is a map named `settingsFinders`. The keys of that map must be fully qualified Java class names and its values are references to concrete `SettingsFinder` beans.

```
<util:map id="settingsFinders">
  <entry key="com.coremedia.cap.content.Content"
        value-ref="cmlinkableSettingsFinder"/>
  <entry key="com.coremedia.cap.multisite.Site"
        value-ref="siteSettingsFinder"/>
</util:map>

<bean id="cmlinkableSettingsFinder"
      class="c.c.b.base.settings.CMLinkableSettingsFinder">
  <property name="cache" ref="cache"/>
  <property name="hierarchy" ref="navigationTreeRelation"/>
</bean>

<bean id="siteSettingsFinder"
      class="c.c.b.base.settings.SiteSettingsFinder"/>
```

Example 4.26. The Spring Bean Definition for the Map of Settings Finder

The example above shows a map with two settings finders. One is supposed to be used for target beans of type `com.coremedia.cap.content.Content` and the other for targets of type `com.coremedia.cap.multisite.Site`.

In order to determine the appropriate settings finder for a given target bean the settings service calculates the most specific classes among the keys of the settings finders

map which match the target bean. For the above example this is trivial, since `Content` and `Site` are disjointed. The lookup gets more interesting with content beans which usually constitute a deeply nested class structure. Assume, you configured settings finders for `CMLinkable` and `CMTaxonomy`. If you invoke the settings service with a `CMTaxonomyImpl` bean, only the settings finder for `CMTaxonomy` is effective. There is no automatic fallback to the `CMLinkable` finder. If you need such a fallback, let your special settings finder extend the intended fallback finder and call its `setting` method explicitly.

The easiest way to provide a custom way of fetching settings for certain documents or even for objects that do not represent a CoreMedia document, is, to add a corresponding settings finder, that does the trick. Therefore, you should use CoreMedia's Spring bean customizer, that you can use anywhere within your Spring application context as follows:

```
<beans>
  <customize:append id="mySettingsFinders" bean="settingsFinders">
    <map>
      <entry key="example.org.MyClass" value-ref="mySettingsFinder"/>
    </map>
  </customize:append>
</beans>
```

Example 4.27. Adding Custom Settings Finder

Via Spring you can configure one settings finder per class. This is a tradeoff between flexibility and simplicity which is sufficient for most use cases. However, on the Java level the `SettingsServiceImpl` provides the method `addSettingsFinder(Class<?>, SettingsFinder)` which allows you to add multiple settings finders for a class.

Typed Settings Interfaces

The `SettingsService` is a powerful multi-purpose tool. However, genericity always comes at the price of abstraction. Assume, there is some business logic which is based on a domain specific interface `Address`:

```
public interface Address {
    String getName();
    String getCity();
}

public class Messages {
    public static String getHelloMessage(Address address) {
        return "Hello " +
            address.getName() +
            ", are you living in " +
            address.getCity() + "?";
    }
}
```

```

    }
}

```

Example 4.28. Business Logic API

If your actual address data is provided by the `SettingsService`, it must be adapted to the address interface.

```

class SettingsBackedAddress implements Address {
    // [...] constructor and fields for service and provider bean
    public String getName() {
        return settingsService.setting("name", String.class, bean);
    }
    public String getCity() {
        return settingsService.setting("city", String.class, bean);
    }
}

```

Example 4.29. Settings Address Adapter

Cumbersome, isn't it? Especially, if the interfaces are larger or not yet final. Fortunately, you don't need to implement such interfaces manually, but `SettingsService.createProxy` does the job for you:

```

class MyCode {
    private SettingsService settingsService;

    void doSomething(BusinessBean beanWithSettings) {
        Address address = settingsService.createProxy(Address.class,
            beanWithSettings);
        String message = Messages.getHelloMessage(address);
    }
}

```

Example 4.30. Address Proxy

Internally the default settings service intercepts the call to `getName()` and `getCity()`. The operation `getCity()` is translated to `settingsService.setting("city", String.class, bean)`. Note: The property name "city" will be derived from the operation `getCity()` in the interface. Be aware of this dependency when choosing names for your settings properties and for the operations of your business objects if you want to use the proxy mechanism.

Content types Requirements

The `SettingsService` itself does not depend on particular content types, since the actual lookup strategies are implemented in `SettingsFinders`. `CoreMedia` Blueprint provides (among others) the `LocalAndLinkedSettingsFinder`, which fetches settings from the `localSettings` and `linkedSettings` properties of `Content` objects. It is a naming convention that originates from the `CMLinkable` content type, but applies also to other content types, for example `CMSite`.

`CoreMedia` recommends to yield the `localSettings` and `linkedSettings` properties exclusively to the `SettingsService`. If you need struct data which is not to be handled by the `SettingsService`, do not put it into `localSettings` and `linkedSettings`, but add new struct properties to the content type model.

`CMNavigation` documents inherit their settings along the hierarchy up to the root navigation. `CMTeaser` documents inherit the settings of their targets. If you rename these content types, this functionality gets lost.

4.4.2 Extending Content Types

Developing a new software almost always starts by analyzing the domain model. This is not different for *CoreMedia CMS*. Here the domain model is the source for modeling the content type model. The content type model is the backbone of *CoreMedia CMS* as it describes what content means to you. Read Chapter 4, *Developing a Content Type Model* in *Content Server Manual* for details on the content types.

Basically, there are two places within the *Blueprint* workspace you may use if you define your own content type model or extend the *Blueprint*'s one. You will learn both of them by defining a new content type `CMHelloWorld` as a child of `CMTeaser` within a new file `mydoctypes.xml` as follows:

```
<?xml version="1.0" encoding="ISO-8859-1" ?>
<DocumentTypeModel
  xmlns="http://www.coremedia.com/2008/documenttypes"
  Name="my-doctypes">

  <ImportGrammar Name="coremedia-richtext-1.0"/>
  <ImportDocType Name="CMTeaser"/>

  <DocType Name="CMHelloWorld" Parent="CMTeaser">
    <StringProperty Name="message" Length="32"/>
  </DocType>
</DocumentTypeModel>
```

```
</DocType>
</DocumentTypeModel>
```

Defining content types in contentserver-blueprint-component

The first and a little easier way of defining CMHelloWorld is to put the new file `mydoctypes.xml` shown above into the directory `apps/content-server/modules/server/contentserver-blueprint-component/src/main/resources/framework/doctypes/my/`. It is good style to create a subfolder under `doctypes` for your customization, here named "my".

After doing so, you can test your new content type. To do so, you have to build the `contentserver-blueprint-component` module and the `content-server-app` module as follows. Remember to stop the server if you have not already.

```
$ cd apps/content-server/modules/server/contentserver-blueprint-component
$ mvn clean install
$ cd apps/content-server/spring-boot/content-server-app
$ mvn clean install
```

Now, start the *Content Management Server* application and take a look into its log file. You should see the following message, telling you that the *Content Server* created a new database table for the new content type.

```
[INFO] SQLStore - DocumentTypeRegistry: creating table:
CREATE TABLE CMHelloWorld( id INT NOT NULL, version INT NOT NULL,
isApproved TINYINT, isPublished TINYINT, editorId INT,
approverId INT, publisherId INT, editionDate DATETIME,
approvalDate DATETIME, publicationDate DATETIME,
"locale" VARCHAR(32), "masterVersion" INT, "keywords" VARCHAR(1024),
"validFrom" DATETIME, "validFrom tz" VARCHAR(30), "validTo" DATETIME,
"validTo tz" VARCHAR(30), "segment" VARCHAR(64), "title" VARCHAR(512),
"teaserTitle" VARCHAR(512), "notSearchable" INT, "message" VARCHAR(32),
PRIMARY KEY (id_, version_), FOREIGN KEY (id_) REFERENCES Resources(id_))
```

Using a Separate Module in the Context of an Extension

The second possibility is the more flexible way. You build your own module in the context of an extension. The following steps assume that an extension module `my-extension` already exists and requires a new content type. Proceed as follows:

1. Create a new subfolder `my-extension-server` in the `apps/content-server/modules/extensions/my-extension` directory.
2. Create a `pom.xml` file and add the following contents.:

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
```

```

<parent>
  <groupId>com.coremedia.blueprint</groupId>
  <artifactId>my-extension</artifactId>
  <version>${project.version}</version>
  <relativePath>../pom.xml</relativePath>
</parent>

<artifactId>my-extension-server</artifactId>

<properties>
  <coremedia.project.extension.for>
    server
  </coremedia.project.extension.for>
</properties>
</project>

```

3. Adjust the `groupId` and `artifactId` of the parent declaration according to your project settings.
4. Add this module's Maven coordinates to the Extension Descriptor of the extension.
5. Create the subfolder `src/main/resources/framework/doctypes/my-extension`.
6. Copy the content type definition file from above into the folder created in the last step.
7. Refer to [Section 4.2.1, "Removing Optional Components" \[91\]](#) to enable the extension.

4.4.3 Developing with Studio

New *CoreMedia Studio* modules can be added to the project using the Blueprint extensions mechanism or by adding them as direct dependencies of the `studio-base-app` or `studio-app` module. Using the extension mechanism is the preferred way. But as it is based on the same steps of adding a module directly, this is firstly covered and the additional required steps for adding *Studio modules* as extensions are described at the end of the section.

Maven Configuration

First, add the new plugin module, say `sample-studio-plugin`, to the `modules` section of the `apps/studio-client/modules/studio/pom.xml` file.

Next, create the child folder of the new module and its `pom.xml` file.

```

<project>
  <modelVersion>4.0.0</modelVersion>

  <parent>
    <groupId>com.coremedia.blueprint</groupId>

```

```

    <artifactId>studio-client.studio</artifactId>
    <version>1-SNAPSHOT</version>
    <relativePath>../pom.xml</relativePath>
  </parent>

  <artifactId>sample-studio-plugin</artifactId>
  <packaging>swc</packaging>

  <description>Sample Plugin for the CoreMedia Studio</description>

  <dependencies>
    <dependency>
      <groupId>com.coremedia.ui.toolkit</groupId>
      <artifactId>ui-components</artifactId>
    </dependency>

    <dependency>
      <groupId>com.coremedia.ui.sdk</groupId>
      <artifactId>editor-components</artifactId>
    </dependency>

    <dependency>
      <groupId>net.jangaroo</groupId>
      <artifactId>ext-as</artifactId>
    </dependency>
  </dependencies>

  <build>
    <plugins>
      <plugin>
        <groupId>net.jangaroo</groupId>
        <artifactId>jangaroo-maven-plugin</artifactId>
        <extensions>true</extensions>
      </plugin>
    </plugins>
  </build>
</project>

```

Example 4.31. POM file of a new Studio module

The module contains the packaging `swc` which is necessary so that during the Maven build time, the module is recognized as a Studio module.

After reimporting the Maven project, IntelliJ IDEA should display the new plugin module as a Flash/Flex module (tiny letter "f" on the module node in the project tree). Now the module must be added as a dependency to the Studio application. Open the `pom.xml` of the `studio-base-app` module and add the following dependency:

```

<dependency>
  <groupId>${project.groupId}</groupId>
  <artifactId>sample-studio-plugin</artifactId>
  <version>${project.version}</version>
  <scope>runtime</scope>
</dependency>

```

Your module should have the following structure by now:




Figure 4.6. The new sample studio plugin

Source Files and Folders

A Studio plugin module contains at least two files: the plugin descriptor file located in the module root folder [package.json] and the initializing plugin class [SampleStudioPlugin.as].

The plugin class only implements the `init` method of the `EditorPlugin` interface:

```
package com.coremedia.blueprint.studio.sample {
import com.coremedia.cms.editor.sdk.EditorPlugin;
import com.coremedia.cms.editor.sdk.IEditorContext;

public class SampleStudioPlugin implements EditorPlugin {
    public function init(editorContext:IEditorContext):void {
    }
}
}
```

Add the class to the corresponding package, created in the subfolder `src/main/joo`. After reimporting the Maven project, IntelliJ IDEA should display the newly created `joo` folder in blue, indicating that it was recognized as source folder. Moreover, it should show the formatted package name of the new ActionScript class.




Figure 4.7. The sample studio plugin with plugin class and descriptor

Now it's time to create the file `package.json`. The plugin descriptor specified therein is read after a user logs in to the Studio web app. It contains the ActionScript class name and a user-friendly name of the Studio plugin.

```
{
  "studioPlugins": [
    {
```

```

    name: "Sample Plug-in",
    mainClass: "com.coremedia.blueprint.studio.sample.SampleStudioPlugin"
  }
}

```

Each JSON object in the `studioPlugins` array may use the attributes defined by the class `EditorPluginDescriptor`, especially `name` and `mainClass` as shown above. In addition, the name of a group may be specified using the attribute `requiredGroup`, restricting access to the plugin to members of that group.

Additional CSS files or other resources required for the plugin can be declared in the configuration of `jangaroo-maven-plugin` in the module's `pom.xml`.

When set up correctly, your project structure should build successfully using

```
mvn install -DwithoutJangarooApp
```

Using the `withoutJangarooApp` flag is recommended for development mode. Building *CoreMedia Studio* in "Jangaroo App" mode takes substantially longer and is only needed for deployment, not for local testing.

NOTE

Additional steps would be adding resource bundles and plugin rules to your plugin. For more details about this and developing Studio plugins and property editors have a look at the Studio Developer Manual.



Joo Unit Testing

The *jangaroo-maven-plugin* supports unit testing of ActionScript classes inside the Studio modules. Please refer to [Jangaroo Tools Wiki, chapter "Unit Testing"](#). To run the tests, you need to meet one of the following preconditions:

- Google Chrome is installed
- Another supported browser (`firefox`, `edge`, `ieexplorer`) is installed and is specified by property `-DjooUnitWebDriverBrowser=...`
- PhantomJS version 2.1.1 is installed and available on your `PATH` or its location is specified by property `phantomjs.bin`. PhantomJS is discontinued, so using it is discouraged.

If none of the preconditions are met, you can still build by skipping Jangaroo unit tests by activating Maven profile `skip-joo-unit-tests`.

The test results are gathered in the `/target/surefire-reports` directory of modules containing Joo unit tests. To debug the Joo unit tests, run


```
mvn jangaroo:run
```

within the appropriate module and open the printed-out test URL with the browser.

Adding Studio Client Modules as Blueprint extensions

How to work with *Blueprint* extensions is described in detail in Section [Section 4.1.5, "Project Extensions"](#) [67]. For *Studio* client modules there exist two extension points: `studio` and `studio-dynamic`.

The *Studio* client modules are packaged into *apps*. CoreMedia distinguishes between so-called *base apps* and *app overlays*. A base app is a Sencha ExtJs app and includes the ExtJs framework, *Studio* core modules and generally all modules that participate in theming. Modules of a base app are included in the *Sencha Cmd* build of the Sencha ExtJs app and are thus *statically* linked into the app. An app overlay in contrast references a base app and adds further modules to this base app. These modules are not included in the *Sencha Cmd* build of the Sencha ExtJs app and instead can be loaded at runtime into the app. Consequently, they are *dynamically* linked into the app.

The *CoreMedia Blueprint* features one *Studio* base app, namely the `studio-base-app` module with Maven packaging type `jangaroo-app`. In addition, there is one app overlay, namely the `studio-app` module with Maven packaging type `jangaroo-app-overlay`. It references the `studio-base-app`. If something is wrong with the overall *Studio* app, it is typically sufficient to just re-compile `studio-base-app`.

Both apps come with their own extension points. Use the extension point `studio` (for the `studio-base-app`) for new modules that do theming and the extension point `studio-dynamic` (for the `studio-app`) for modules that come without theming. Also, note that there must never be a dependency of a `studio` module to a `studio-dynamic` module.

Adding Studio Server Modules as Blueprint extensions

Additional modules for the *Studio* REST Service use the `studio-lib` extension point.

4.4.4 Developing with the CAE

The *CAE* can be extended with new capabilities by using the *Blueprint* extension mechanism or by just creating a new module with the required resources. In both cases the extension will be activated by adding a Maven dependency on the new module. This section describes how to add a new Blueprint module which contains an additional view template and a new view repository using this template.

Maven Configuration

First you have to create a new module which contains the required resources. The location of the new module inside the workspace is not important to enable the new features provided by the module. But to keep cohesion in the aggregation modules of the *Core-Media Blueprint* workspace the new module should be created next to other CAE functions. In this example the new module `sample-cae-extension` will be created in the `apps/cae/modules/cae` module.

1. First, add a new module entry named `sample-cae-extension` to the modules section of the `cae pom.xml` file:

```
<modules>
  <module>cae-base-lib</module>
  <module>cae-base-component</module>
  <module>cae-live-webapp</module>
  <module>cae-preview-webapp</module>
  <module>contentbeans</module>

  <!-- add module -->
  <module>sample-cae-extension</module>
</modules>
```

2. After that create a new subdirectory `sample-cae-extension` and add the `pom.xml`.

```
<?xml version="1.0" encoding="UTF-8"?>
  <project xmlns="http://maven.apache.org/POM/4.0.0"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>

    <parent>
      <groupId>com.coremedia.blueprint</groupId>
      <artifactId>cae</artifactId>
      <version>BLUEPRINT_VERSION</version>
      <relativePath>../pom.xml</relativePath>
    </parent>

    <artifactId>sample-cae-extension</artifactId>
    <packaging>jar</packaging>

    <dependencies>
      <dependency>
        <groupId>com.coremedia.cms</groupId>
        <artifactId>coremedia-spring</artifactId>
        <scope>runtime</scope>
      </dependency>
    </dependencies>

  </project>
```

Now the basic structure for the extension exists.

Enabling the Extension

To enable the extension the target component has to depend on the created extension module.

To enable the new capabilities in all CAEs add the following dependency to the `pom.xml` of the `cae-base-component` module:

```
<dependency>
  <groupId>${project.groupId}</groupId>
  <artifactId>sample-cae-extension</artifactId>
  <version>${project.version}</version>
</dependency>
```

Creating Source Files and Folders

The sample extension for the CAE provides a new view template for the content type `CMArticle` to display external content and a new view repository configuration which includes this view template.

1. Create the new view template `CMArticle.jsp` in the module `sample-cae-extension` in the directory `src/main/resources/META-INF/resources/WEB-INF/templates/external-content-view-repository/com.coremedia.blueprint.common.contentbeans`.
2. To include the new view repository add a Spring boot auto configuration defining the following beans:

```
@Configuration(proxyBeanMethods = false)
static class AddSampleViewRepositories {
    @Bean
    @Customize(value = "viewRepositories", mode = Customize.Mode.PREPEND)

    List<String> sampleViewRepositories() {
        // Add repository name, relative to /WEB-INF/templates/
        return ImmutableList.of("sample-cae-extension");
    }
}
```

4.4.5 Customizing the CAE Feeder

Before customizing the *CAE Feeder*, you should be familiar with the content of [Section 4.4.4, "Developing with the CAE" \[129\]](#) about the *CAE* modules. Details about how the *CAE Feeder* works and how it may be customized are presented in the Search Manual.

4.4.6 Handling Personal Data

NOTE

All features how to handle personal data, from annotations to Maven profiles are in experimental stage. For details what this means to you read the API documentation of the `@Experimental` annotation.

Note, that feedback on this feature set is very welcome.



Personal data needs to be handled carefully, as it can be subject to regulations such as the European Union's General Data Protection Regulation (GDPR). Therefore, it is important to know how and where personal data is used in your code.

CoreMedia provides annotations to mark personal data and document the flow of personal data in Java code. You can also enable compile-time checks to validate that personal data is not passed accidentally to methods or libraries that are not prepared for personal data. Compile-time checking can be enabled with a Maven profile as described in [Section "Running Personal Data Checker" \[133\]](#).

CoreMedia public Java API and *CoreMedia Blueprint* code already use personal data annotations, especially in the context of *Elastic Social*. Note that applied annotations are not necessarily complete; there can be more places where personal data is used. The personal data annotations and the corresponding checker are tools to help to document and restrict access to personal data, but they cannot solve this for each and every case. The existing annotations also do not state whether some data is personal data in the sense of some legal act or regulation.

The annotations for personal data are:

- `@PersonalData`,
- `@PolyPersonalData` and
- `@NonPersonalData`

of package `com.coremedia.common.personaldata` in module `com.coremedia.cms:coremedia-personal-data`. Please read the [API documentation](#) of that annotations first. It describes the usage of these annotations with examples in detail. Below you will find more details like [Section "Running Personal Data Checker" \[133\]](#), [Section "Annotating Third-Party Libraries" \[134\]](#) and more.

Running Personal Data Checker

To run the *Personal Data Checker* in *Blueprint* you need to enable the Maven profile `checkPersonalData` while compiling. This profile is defined in module `blueprint-parent`.

NOTE

As of version 2.5.3 the *Checker Framework* has the following limitation:

- You must not build in parallel while running Checker (issue [typetools/checker-framework#1771](#)).



The checker for personal data will analyze all modules with a direct or transitive dependency to Maven module `coremedia-personal-data`. In your Maven output you will recognize the message `Checking @PersonalData` once such a module is found in your Maven build.

By default, the *Checker Framework* will trigger a failure once it detects a violation in using personal data objects. To change the behavior to print only warnings instead, add the compiler argument `-Awarns`. Configure the `maven-compiler-plugin` for the `checkPersonalData` profile in `blueprint-parent` module accordingly. For more configuration options have a look at the documentation at [checkerframework.org](#).

Using Personal Data Annotations

You can find documentation and examples how to use the annotations for personal data in the [API documentation](#). This section covers some further best practices.

Logging Personal Data

You might want to take extra care of logging personal data, which is either to prevent it from being logged or to ensure that such log entries go to a secured environment.

To do so, you may use markers of the *Simple Logging Facade for Java* (SLF4J). Markers enable filtering your logs by cross-cutting concerns, such as authentication and authorization or for log entries which contain personal data. Find more about filtering in the [corresponding Logback documentation](#).

The CoreMedia API provides a set of predefined markers also for personal data. You will find them as part of `com.coremedia.common.logging.BaseMarker` which are:

- `PERSONAL_DATA`,
- `UNCLASSIFIED_PERSONAL_DATA` and

Read the corresponding documentation for more details how and when to use them.

In order to log personal data explicitly it is recommended to use the logger `com.coremedia.common.logging.PersonalDataLogger`. It provides the very same logging methods as a standard SLF4J Logger having its parameters already annotated with `@PersonalData`. For details and usage examples have a look at the [API documentation](#).

Logging Exceptions

To log exceptions which might (or will) contain personal data, you should consider using the helper class `com.coremedia.common.logging.PersonalDataExceptions`. It will log the original exception securely, using the markers mentioned above and rethrow a new exception which is directly under your control. The tool will ensure that there is a reference between the new exception and the logged one which eases tracing the exceptions although the cause hierarchy is not available by intention.

Annotating Third-Party Libraries

When handing over personal data to third-party dependencies, you will most likely get a compile time error raised by the *Checker Framework*. You have two options then: Either suppress the check as stated in the Javadoc or add so-called stub classes as described in [The Checker Framework Manual](#).

CoreMedia Personal Data Checker already comes with some predefined stub classes. But they may not be sufficient for your needs. Adding your own stub classes can extend or even override the predefined stub classes as your explicitly mentioned stubs have a higher priority. And more: You may add stub classes for CoreMedia API as well.

To add custom stubs, just extend the annotation processor arguments in the `check-PersonalData` profile. In the example [Example 4.32, "Adding custom stub classes" \[134\]](#) you see how you may add two directories which will then be scanned for files named `*.astub`. Using `${path.separator}` ensures that your path will work across multiple platforms.

```
<profile>
  <id>checkPersonalData</id>
  <build>
```

```

<plugins>
<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-compiler-plugin</artifactId>
  <executions>
    <execution>
      <id>default-compile</id>
      <!-- ... -->
      <configuration>
        <compilerArgs>
          <!-- ... -->
          <arg>-Astubs=/stubs/a${path.separator}/stubs/b</arg>
        </compilerArgs>
      </configuration>
    </execution>
  </executions>
</plugin>
</plugins>
</build>
</profile>

```

Example 4.32. Adding custom stub classes

Stubbing: Best Practices

You can use stub files to add annotations to classes and methods which are not part of your source code, that is especially third-party API and of course CoreMedia API.

Below you will find some practices which have proven to ease managing such stub files.

Naming Convention

While you may put all your stubs into one file, it is recommended to split it into smaller chunks to ease maintenance. For example, create a stub file for each third-party library.

A possible naming pattern is to use the Maven group and artifact ID within the filename. So for the artifact `mongodb-driver-legacy` within group `org.mongodb` a stub filename could be: `org.mongodb.mongodb-driver-legacy.astub`.

Stub Structure

Start with imports and especially start with importing the personal data annotations:

```
import com.coremedia.common.personaldata.*;
```

Then add packages and their classes, each in alphabetical order. Add methods in alphabetical or logical order to group getters and setters for example.

Stubbing Rules

- In general, do not annotate parameters of methods that are intended for override. This may cause errors for existing code.

```
class Collection<E> {
    boolean contains(@PersonalData Object o); // BAD!
}
```

While this sounds useful, it actually breaks existing code. Custom Collection implementations would cause errors as long as their parameter is not annotated as well. Because of that, it is better to use `@SuppressWarnings("PersonalData")` at usages of `Collection#contains`.

- The stub parser of the ignores method bodies and modifiers and it is recommended to omit them for readability. However, adding `static` and `final` modifiers to methods and classes will make it easier to think about possible overrides (see previous rule). Parameters of static or final methods or final classes can easily be annotated because there cannot be any overrides.
- There is no need to annotate all methods of a class or interface. However, it often makes sense to annotate similar methods equally. Overloaded convenience methods which just differ in the number of parameters should be annotated together to avoid confusion.
- Sometimes it makes sense to annotate classes itself when instances of this class contain personal data and are passed to third-party methods.

```
package java.security;

@PersonalData interface Principal {
    @PersonalData String getName();
}
```

Reasoning: A `Principal` may be passed to some third-party method, which then possibly calls `getName()` internally. Because third-party internals are not subject to checking, you should already check the transfer of the `Principal` object to third-party libraries and either avoid it or allow it with `@SuppressWarnings("PersonalData")`.

Note that this rule just applies to stubbing: It does not make sense to use `@PersonalData` at interface source files when all code that uses that interface can be checked for personal data use. It is easier to just annotate method return values then. However, if a custom class or interface extends a third-party class/interface that is already annotated with `@PersonalData`, then the extending class/interface needs to be annotated in the same way:

```
@PersonalData class MyPrincipal implements Principal {
    @Override
    public @PersonalData String getName() {
        return name;
    }
}
```



```
}  
  // ...  
}
```

5. CoreMedia Blueprint – Functionality for Websites

This chapter describes all aspects of *CoreMedia Blueprint* that you can use to manage your web sites.

- [Section 5.1, “Overview of eCommerce Blueprint” \[139\]](#) gives a short overview of the *eCommerce Blueprint* frontend.
- [Section 5.2, “Overview of Brand Blueprint” \[142\]](#) gives an overview of the *Brand Blueprint* frontend.
- [Section 5.3, “Basic Content Management” \[144\]](#) describes aspects of the content type model of *CoreMedia Blueprint*.
- [Section 5.4, “Website Management” \[161\]](#) describes all features relevant for website management, such as layout, search and navigation.
- [Section 5.5, “Localized Content Management” \[227\]](#) describes all aspects of localized content management.
- [Section 5.6, “Workflow Management” \[273\]](#) describes all aspects of multi-site management.

5.1 Overview of eCommerce Blueprint

The *eCommerce Blueprint* provides a modern, appealing, highly visual website template that can be used to start a customization project. It demonstrates the capability to build localizable, multi-national, experience-driven eCommerce web sites. Integration with HCL Commerce, SAP Hybris Commerce and Salesforce Commerce Cloud ships out of the box. Other eCommerce systems can be integrated via the CoreMedia eCommerce API as a project solution.

The following integration patterns are available with the product:

- Commerce-led fragment-based approach like the Hybris example
- Experience-led hybrid blended approach shown in the Calista store example

Based on a fully responsive, mobile-first design paradigm, the *eCommerce Blueprint* leverages most of our bricks and the FreeMarker templating framework. It scales from mobile via tablet to desktop viewport sizes and uses the CoreMedia Adaptive and Responsive Image Framework to dynamically deliver the right image sizes in the right aspect ratios and crops for each viewport.

NOTE

For more information about the themes please see the Section 6.1, “Example Themes” in *Frontend Developer Manual*






Figure 5.1. Calista [Experience-led] start page for different devices: desktop, tablet, mobile




Figure 5.2. Hybris [commerce-led] start page for different devices: desktop, tablet, mobile

The responsive navigation can blend commerce as well as content categories and content pages seamlessly and in any user-defined order that does not have to follow the catalog structure. Navigation nodes with URLs to external sites can be added in the content.

5.2 Overview of Brand Blueprint

The *Brand Blueprint* provides a modern, appealing, highly visual website template that can be used to start a customization project. It demonstrates the capability to build localizable, multi-national, non-commerce web sites.

Based on a fully responsive, mobile-first design paradigm, the *Brand Blueprint* leverages most of our bricks and Design framework for easy customization and adaptation by frontend developers. It is a child theme, inherited from the Shared-Example Theme.

NOTE

For more information about the themes please see the Section 6.1, "Example Themes" in *Frontend Developer Manual*



It scales from mobile via tablet to desktop viewport sizes and uses the CoreMedia Adaptive and Responsive Image Framework to dynamically deliver the right image sizes in the right aspect ratios and crops.




Figure 5.3. Chef Corp. start page for different devices: desktop, tablet, mobile

5.3 Basic Content Management

The basis of the information structure of a CoreMedia system are content types. Content types organize your content and form a hierarchy with inheritance.

See the Content Server Manual, [Developing a Content Type Model](#) and [Section 7.1, "Content Type Model" \[376\]](#) for more details.

CoreMedia Blueprint comes with a comprehensive content type model that covers the following topics:

- Common content such as Articles or Pictures.
- Placeholder types that you can use to link to commerce content
- Taxonomies are used to tag content.

5.3.1 Common Content Types

Requirements

An appealing website does not only contain text content but has also images, videos, audio files or allows you to download other assets such as brochures or software.

In addition, current websites aim to reuse content in different contexts. An article about the Hamburg Cycloclassics might appear in Sports, Hamburg and News section, for example. An image of the St. Michaelis church (the "Hamburger Michel") on the other hand might appear in Articles about sights in Hamburg or religion. Nevertheless, it's not a good idea to copy the article to each section or the image to each article because this is error prone, inefficient and wastes storage.

Therefore, content should be reusable across different contexts (different sites, customer touchpoints for instance) by just applying the context specific layout and without having to duplicate any content. This increases the productivity by reducing redundancy and keeps management effort at a minimum.

Solution

CoreMedia Blueprint is shipped with content types that model common digital assets such as articles, images, videos or downloads. All these types inherit from a common parent type and can be used interchangeably. In addition, none of these types has fixed information about its context so that it can be used repeatedly and everywhere in your site. The context is first determined through the page which links to the document or

through the position in the folder hierarchy of the website [see [Section 5.4.2, "Navigation and Contexts"](#) [163] for more details).

Common Content Types

CoreMedia Blueprint defines the following types for common content. Using CoreMedia's object oriented content model projects can define their own content types or add to the existing ones.

CMArticle	
UI Name	Article
Description	Contains mostly the textual content of a website combined with images.
CMPicture	
UI Name	Picture
Description	Stores images of the website. The editor can define different crops of the image which can be used in different locations of the website.
CMVideo	
UI Name	Video
Description	Stores videos which can be viewed on the website.
CMAudio	
UI Name	Audio
Description	Stores audio/podcast information which can be heard on the website.
CMDownload	
UI Name	Download
Description	Stores binary data for download. You can add a description, image and the like.
CMGallery	
UI Name	Gallery

Description	Aggregates images via a linklist. You can add a description, teaser text and the like.
-------------	--

Table 5.1. Overview of Content Types for common content

eCommerce Placeholder Types

Blueprint comes with some additional content types required to build representations of entities of a commerce system.

CMProductTeaser	
UI Name	Product Teaser
Description	A teaser for products of the commerce system. It inherits from CMTeasable
CMMarketingSpot	
UI Name	e-Marketing Spot
Description	A placeholder for an e-Marketing spot. It inherits from CMTeasable.
CMExternalChannel	
UI Name	Category Placeholder
Description	Documents of this type are used to build a CMS representation of commerce categories. It inherits from CMAbstractCategory which in turn inherits from CMChannel.
CMExternalPage	
UI Name	Placeholder for other shop pages such as Help pages or the main page.
Description	Documents of this type are used to build a CMS representation of other commerce pages. It inherits from CMChannel.

Table 5.2. Commerce Content Types

Commerce Content Properties

A short description of the properties provided for eCommerce scenarios is provided below.

externalId	
UI Name	External ID

Description	The ID of the corresponding entity in the commerce system. For a <code>CMProductTeaser</code> this id is the technical id of the product in the catalog.
<code>localSettings.shopNow</code>	
UI Name	'Shop Now' flag
Description	This Boolean flag is stored in the local settings of the document types <code>CMProductTeaser</code> and <code>CMExternalChannel</code> and is used in the content-led scenario. If enabled the 'Shop Now' overlay is visible for product teasers. This configuration is extendable via <code>CMExternalChannels</code> and may be overwritten for every <code>CMProductTeaser</code> .

Table 5.3. Overview Commerce Content Properties

Common Content Properties

All common content types extend the abstract type `CMTeasable` to share common properties and functionality. Teasable means that you can show for each content that inherits from `CMTeasable` a short version that "teases" the reader to watch the complete article, site or whatever else.

A short description of the core properties of content is provided below. Properties specific for certain Blueprint features such as teaser management etc. are described in their respective sections (follow the link in the *Description* column).

<code>title</code>	
UI Name	[Asset] Title
Description	The name or headline of an asset, for example the name of a download object or the headline of an article.
<code>detailText</code>	
UI Name	Detail Text
Description	A detailed description, for example the article's text, a description for a video or download.
<code>teaserTitle, teaserText</code>	
UI Name	Teaser Title and Text

Description	The title and text used in the teaser view of an asset. See Section 5.4.9, “Teaser Management” [186] .
-------------	--

pictures

UI Name	Pictures
---------	----------

Description	A reference to <code>CMPicture</code> items that illustrate content. Examples include a photo belonging to the article, a set of images from a video etc. Usage of the pictures depends on the rendering. In <i>Blueprint</i> the pictures are used for teasers and detail views of content.
-------------	--

related

UI Name	Related Content
---------	-----------------

Description	The related content list refers to all items that an editor deems related to the content. For an article for a current event this list could include a video describing of the event, a download with event brochure, an audio/podcast file with an interview with the organizers, an image gallery with photos of the previous event and many more.
-------------	--

keywords

UI Name	Keywords
---------	----------

Description	Keywords for this content. <i>CoreMedia Blueprint</i> currently uses keywords as meta information for the HTML <code><head></code> .
-------------	--

subjectTaxonomy

UI Name	locationTaxonomy
---------	------------------

Description	Tags for this content. See Section 5.3.3, “Tagging and Taxonomies” [151] for details.
-------------	---

viewType

UI Name	Layout Variant
---------	----------------

Description	The layout variant influences the visual appearance of the content on the site. It contains a symbolic reference to a view that should be used when the content is rendered. For more information see Section 5.4.7, “View Types” [180]
-------------	---

segment	
UI Name	URL Segment
Description	A descriptive segment of a URL for this content. Used for SEO on pages displaying the content. See Section 5.4.15, “URLs” [201]
locale, master, masterVersion	
UI Name	Locale, Master, Master Version
Description	See Section 5.5, “Localized Content Management” [227] for details. Properties for the Localization of this asset.
validFrom, validTo	
UI Name	Valid From, Valid To
Description	Meta information about the validity time range of this content. Content which validity range is not between validFrom and validTo will not be displayed on the website. See Section 5.4.17, “Content Visibility” [203] for details.
notSearchable	
UI Name	Not Searchable Flag
Description	Content with this flag will not be found in end user website search. See Section 5.4.21, “Website Search” [212] for details.

Table 5.4. Overview Common Content Properties

Media Content

The abstract content type `CMMedia` defines common properties for all media types. Media types for content such as pictures (`CMPicture`), video (`CMVideo`), audio (`CMAudio`), and HTML snippets (`CMHTML`) inherit from `CMMedia`.

data	
UI Name	Data
Description	The core data of the content. Either a <code>com.coremedia.cap.common.Blob</code> or in the case of <code>CMHTML</code> a <code>com.coremedia.xml.Markup</code> .

copyright	
UI Name	Copyright
Description	Allows you to store arbitrary copyright information in a string property.
alt	
UI Name	Alternative Representation
Description	Allows managing alternative representations of an image, for example a description of an image that can be used to enable a website accessible for the visually impaired.
caption	
UI Name	Caption
Description	The caption of a content. Unused property in <i>Blueprint</i> .

Table 5.5. CMMedia Properties

A common feature of all `CMMedia` objects is the ability to generate and cache transformed variants of the underlying object (see `CMMedia#getTransformedData`). This ability is extensively used for rendering images without the need to store image variants and renditions as distinct blobs in the system.

5.3.2 Adaptive Personalization Content Types

Adaptive Personalization extends *Blueprint* with the following content types:

- Personalized Content (`CMSelectionRules`)
Personalized Content enables an editor to explicitly determine under which conditions a certain Content is shown. Conditions can be combined with **AND** and **OR** operators to create complex expressions. At runtime, theses Conditions are evaluated against the provided contexts.
- Personalized Search (`CMP13NSearch`)
Personalized Search documents can be used to augment search engine queries with context data. The result is a dynamic list of Content.

- Customer Segments [`CMSegment`]

Customer Segments let an editor predefine sets of conditions to be (re-)used in Personalized Content, thereby grouping your website's visitors. For example one can imagine a User Segment called "Teenage Early Birds". This could then aggregate the conditions

- "[logged in] user is older than 14"
 - "[logged in] user is younger than 20"
 - "It is earlier than 10 am"
- Test User Profiles [`CMUserProfile`]

Test User Profiles are artificial contexts under the control of the editors. They can be used to test the CAE's rendering when creating Personalized Content. Typically, Test User Profiles are used to simulate certain website visitors containing the corresponding context properties.

5.3.3 Tagging and Taxonomies

Requirements

Most websites define business rules that require content to be classified into certain categories. Typical examples include use cases such as "Display the latest articles that have been labeled as press releases" or "Promote content tagged with 'Travel' and 'London' to visitors of pages tagged with 'Olympic Games 2012'" etc.

Keywords or tags are common means to categorize content. Employing a controlled vocabulary of tags can be more efficient than allowing free-form keyword input as it helps to prevent ambiguity when tagging content. Furthermore, a system that supports the convenient management of tags in groups or hierarchies is required for full editorial control of the tags used within a site.




Figure 5.4. Dynamic list of articles tagged with "Vegetables"

Solution

Blueprint currently uses tag information in various ways:

- It is possible to use the taxonomies of a content item as conditions for dynamic lists of content (such as "5 latest articles tagged with 'London'").
- In CoreMedia Adaptive Personalization tags can be used to gather information about the topics a site visitor is interested in (see `TaxonomyInterceptor`).
- In CoreMedia Adaptive Personalization tag information representing the interests of visitors can be used to define Customer Segments, conditions for personalized selection rules and personalized searches.
- It is possible to display related content for a content item based on content that shares a similar set of tags (see `CMTeasableImpl#getRelatedBySimilarTaxonomies`).

In *CoreMedia Blueprint* tags are represented as `CMTaxonomy` content items which represent a controlled vocabulary that is organized in a tree structure. *CoreMedia Blueprint* defines two controlled vocabularies: Subject and location taxonomies that can be associated with all types inheriting `CMLinkable`.

Taxonomy Management

Subject taxonomies can be used to tag content with "flat" information about the content's topic (such as Olympic Games 2012). They can also enrich assets with hierarchical categorization for fine-grained drill down navigation (such as Hardware / Printers / Laser Printer).

Subject Taxonomies are represented by the content type `CMTaxonomy` which defines the following properties:

value	
Type	String
Description	Name of this taxonomy node
children	
Type	Link list
Description	References to subnodes of this taxonomy node
externalReference	
Type	String
Description	Reference of an equivalent entity in an external system in the form of an ID / URI etc.

Table 5.6. CMTaxonomy Properties

Location taxonomies allow content to be associated with one or more locations. Location taxonomy hierarchies can be used to retrieve content for a larger area even if it is only tagged with a specific element within this area ("All articles for 'USA'" would include articles that are tagged with the taxonomy node North America / USA / Louisiana / New Orleans).

Location taxonomies are represented by the content type `CMLocTaxonomy` which inherits from `CMTaxonomy` and adds geographic information for more convenient editing and visualization of a location.

latitudeLongitude	
Type	String

Description	Latitude and longitude of this location separated by comma
postcode	
Type	String

Description	The post code of this location
-------------	--------------------------------

Table 5.7. Additional CMLocTaxonomy Properties

The taxonomy administration editor can be used to create a taxonomy and build a tree of keywords.




Figure 5.5. Taxonomy Administration Editor

The taxonomy administration editor displays taxonomy trees and provides drag and drop support and the creation and deletion of keywords.

Taxonomy Assignment

To enable tagging of content two properties are available the `CMLinkable` content type.

subjectTaxonomy	
Type	Link list
Description	Subject[s] / topic[s] of that content item
locationTaxonomy	

Type	Link list
Description	Geographic location(s) of that content item

Table 5.8. CMLinkable Properties for Tagging

Editors can assign taxonomies to content items using *CoreMedia Studio* and the Blueprint taxonomy property editor. It allows for the following:

- adding/removing references to taxonomy
- autocompletion
- suggestions




Figure 5.6. Taxonomy Property Editor

The user can add taxonomy keywords to the corresponding property link list using the taxonomy property editor. The editor also provides suggestions that are provided by the *OpenCalais* integration or a simple name matching algorithm. The strategy type can be configured in the preferences dialog of *CoreMedia Studio*.




Figure 5.7. Taxonomy Studio Settings

How taxonomies are loaded

A Blueprint taxonomy tree is built through content items located in a specific folder of the content repository. The default taxonomy resolver will then look for a "_root" settings document inside these folders and uses the taxonomy documents linked inside the LinkListProperty "roots" as top level nodes. If the "_root" document is not found, the taxonomy resolver checks for empty referrers of all taxonomy documents inside a taxonomy folder, to determine which node is a top level node of the given taxonomy tree. In that case, top level node documents must be placed directly within the root folder. Taxonomies of subsequent levels can also be placed in subfolders. The name of the folder in which the taxonomy tree is placed defines the name of the taxonomy tree and is visible as a root node in the taxonomy administration UI.

The lookup folders for taxonomies and the strategy used to build the tree are configured in the Spring configuration class `TaxonomyConfiguration` of the `shared/taxonomies` module. The bean properties

```
siteConfigPath
```

and

```
globalConfigPath
```

of the `strategyResolver` bean configure the folders that are used to find taxonomies. `TaxonomyResolverImpl` implements the `TaxonomyResolver` interface so that it is possible to implement other taxonomy detection strategies.

WARNING

The default taxonomy implementation (`DefaultTaxonomy.java`) checks the taxonomy folder for write permissions. If these permissions are not granted, the taxonomy won't appear in *Studio*. Therefore, ensure that taxonomy administrators have `Folder` rights for taxonomy folders.



How to implement a new taxonomy resolver strategy

The `TaxonomyResolverImpl` implements the interface `TaxonomyResolver` and is injected to the `TaxonomyResource` in the `component-taxonomies.xml`. For every taxonomy request, the `TaxonomyResource` instance looks up the corresponding `Taxonomy` object using the resolver instance. To change the resolver strategy, inject another instance of `TaxonomyResolver` to the `TaxonomyResource`.

How to configure the document properties used for semantic strategies

The document properties that are used for a semantic evaluation are configured in the method `SemanticTaxonomyConfiguration#semanticDocumentProperties` of the `shared/taxonomies` module. The Spring configuration declares the abstract class `AbstractSemanticService` that new semantic service can extend from. The default properties used for a semantic suggestion search are:

- `title`
- `teaserTitle`
- `detailText`
- `teaserText`

How to implement a new suggestion/semantic strategy

To add a new semantic strategy to *Studio*, it is necessary to implement the corresponding strategy for it and add it to *CoreMedia Studio*.

A new semantic strategy can easily be created by implementing the interface `SemanticStrategy`. The result of a strategy is a `Suggestions` instance with several `Suggestion` instances in it. Each `Suggestion` instance must have a corresponding content instance in the repository whose content type matches that one used for the taxonomy. *Blueprint* uses `CMTaxonomy` documents for keywords of a taxonomy, so suggestions must be fed with these documents. Additionally, a float value `weight` can be set for each suggestion, describing how exactly the keyword matches from 0 to 1. After implementing the semantic strategy, the implementing class must be added to the Spring configuration, for example:

```
<customize:append id="semanticStrategyExamplesCustomizer"
bean="semanticServiceStrategies" order="1000">
  <list>
    <ref bean="myMatching"/>
  </list>
</customize:append>
```

Next the new suggestion strategy has to be added to *Studio*, so that is selectable in *CoreMedia Studio*.

1. Open the file `TaxonomyStudioPlugin.mxml`
2. Add an entry to the configuration section that configures the `AddTaggingStrategyPlugin`:

```
<taxonomy:AddTaggingStrategyPlugin serviceId="{TAXONOMY_NAME_MATCHING_KEY}"
label="{resourceManager.getString('com.coremedia.blueprint.studio.taxonomy.TaxonomyStudioPlugin',
'TaxonomyPreferences_value_nameMatching_text')}" />
```

Make sure that the `serviceId` matches the one you configured for the implementation of the `SemanticStrategy`.

How to remove the OpenCalais suggestion strategy

If you want to disable the OpenCalais integration, simply remove the corresponding `AddTaggingStrategyPlugin` entry from the `TaxonomyStudioPlugin.mxml` configuration section.

How to add a site specific taxonomy

The logic how a site depending taxonomy tree is resolved is implemented in the `TaxonomyResolver#getTaxonomy(String siteId, String taxonomyId)` method.

To create a new site depending taxonomy proceed as follows:

1. Open *Studio*, create and select the site specific folder `Options/Taxonomies/` from the library.

2. Create a new sub folder with the name of the new taxonomy.

The location for the new taxonomy has been created now.

3. To identify the type of taxonomy (such as `CMTaxonomy` or `CMLocTaxonomy`) you have to create at least one taxonomy document in the new folder. Alternatively, create a `_root` settings document and link a newly created `CMTaxonomy` document to the `StructList roots` to it.

Once the taxonomy has been set up, additional nodes can be created using the taxonomy manager. If the new taxonomy does not appear as new element in the column on the left, press the reload button. It ensures that the `TaxonomyResolver` rebuilds the list of available taxonomy trees. The new taxonomy is shown in the root column afterwards, include the site name it is created in.

Creating site specific taxonomies allows you to overwrite existing ones. For example you create a new taxonomy tree called `Subject` for site X and open an article that is located in a sub folder of site X, the regular `Subject` taxonomy property editor on the `Taxonomies` tab in *CoreMedia Studio* will access the `Subject` taxonomy of your new site, not the one that is located in the global `Settings` folders. The suggestions and the chooser dialog will also work in the new taxonomy tree.

How to configure the taxonomy property editor for a taxonomy

CoreMedia Blueprint comes with two types of taxonomies: `Subject` and `Location`. The name of the taxonomy matches the folder name they are located in, which is `/Settings/Taxonomies`. When the taxonomy property editor for a *Studio* form is configured, these IDs are passed to the property editor, for example

```
<taxonomy:taxonomyPropertyField propertyName="subjectTaxonomy"
                                taxonomyId="Subject"/>
    <taxonomy:taxonomyPropertyField itemId="locTaxonomyItemId"
                                    propertyName="locationTaxonomy"
                                    taxonomyId="Location"/>
```

As mentioned in the previous section, it is possible to overwrite the existing location or subject taxonomy with a site depending variant. In this case, it is *not* necessary to change the configuration for the property field. The taxonomy property editor will always try to identify the site depending taxonomy with the same name first. If this one is not found, the global taxonomy with the given id will be looked up and used instead. For custom site-specific taxonomy trees, the attribute value `taxonomyId` must match the name of the newly created taxonomy folder.

How to configure access to the taxonomy content / taxonomy administration

The taxonomy *Studio* plugin reads configuration values from global document `/Settings/Options/Settings/TaxonomySettings`. The configuration docu-

ment `TaxonomySettings` contains the name of the user groups that are allowed to administrate taxonomies. Additional configuration files with the same name can be put in the folder `Options/Settings` (Relative paths will be concatenated with the root folder of the active site.). The entries of the files will be added to the existing configuration. Below the default taxonomy settings are shown.

```
<Struct xmlns="http://www.coremedia.com/2008/struct"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <StringListProperty Name="administrationGroups">
    <String>global-manager</String>
  </StringListProperty>
</Struct>
```

To ensure that the taxonomies are working properly, ensure that the user has the corresponding read and write rights to the settings and taxonomy folders. For taxonomy folders, ensure that also the *Folder* rights are set.

5.4 Website Management

Website management comprises different features. For example:

- Layout
- Navigation
- Search

5.4.1 Folder and User Rights Concept

It is good practice to organize the content of a content management system in a way that separates different types of content in different locations and to have user groups that attach role depending rights to these locations. This fits with CoreMedia access rights, which are assigned to groups and grant rights to folders and their content, including all sub folders, to all members of that group.

See Section 3.15, "User Administration" in *Content Server Manual* for details about the CoreMedia rights system.

CoreMedia Blueprint comes with demo sites that provide a proposal on how to structure content in a folder hierarchy and how to organize user groups for different roles. A more fine grained folder and group configuration can easily be built upon this base.

For details on site specific groups and roles have a look at [Groups and Rights Administration for Localized Content Management \[233\]](#) and for a set of predefined users for that groups and roles see [Reference - Predefined Users \[385\]](#).

CoreMedia Blueprint distinguishes between the following types of content in the repository:

- **Content:** These are the "real" editorial contents like Articles, Images, Videos, and Products. They are created and edited by editorial users. In a multi-site environment editors are usually working on one of the available sites and they can only access that site's content.
- **Navigation and page structure:** These types represent the site's navigation structure - both the main navigation and the on-page navigation elements like collections or teasers linking to other pages. They are readable by every editorial user, but only the site manager group may maintain them.
- **Technical content types** like options, settings and configuration: These types provide values for drop down boxes in the editorial interface, like view types. They also bundle reusable sets of context settings, for example API keys for external Services. These

*Different content types
for different uses*

types are readable by every editorial user but can only be created and edited by Administrators or other technical staff.

- **Client code:** Consists of JavaScript and CSS and is maintained by technical editors.

CoreMedia Blueprint comes with a folder structure that simplifies groups and rights management in that way that users taking specific roles only get rights to those contents they are required to view or change. Most notably you will find a `/Sites` folder which contains several sites and several other folders which contain globally used content like global or default settings.

For details on the structure of the `/Sites` folder have a look at [Section "Sites Structure" \[229\]](#).

Commonly used content is stored below dedicated folders directly at root level. Web resources like CSS or JavaScript is stored under `/Themes`. Global settings, options for editorial interfaces, and the like are stored under `/Settings`.

Site-Independent Groups

Along with the site specific groups which are described in [Groups and Rights Administration for Localized Content Management \[233\]](#) there are also groups representing roles for global permissions required by some of the predefined workflows. These workflows are especially dedicated to the publication process and are bound to the following roles:

- composer-role

This site-independent group allows members to participate in a workflow as a composer, that is each member of this group may compose a change set for a publication workflow.

- approver-role

This site-independent group allows members to participate in a workflow as an approver, that is each member of this group may perform approval operations within a publication workflow.

- publisher-role

This site-independent group allows members to participate in a workflow as a publisher, that is each member of this group may publish the content items involved in a workflow.

For details on these groups and how to connect them to a LDAP server have a look at [Workflow Manual](#).

5.4.2 Navigation and Contexts

Requirements

Websites are structured into different sections. These sections frequently form a tree hierarchy. For example, a news site might have a Sports section with a Basketball sub-section. The website of a bank might have different sections for private and institutional investors with the latter having subsections for public and private institutions.

Sections are also often called "navigation" or "context". Usually the sections of a site are displayed as a navigable hierarchy (a "navigation" or "site map"). The current location within the tree is often displayed as a "breadcrumb navigation".




Figure 5.8. Navigation in the Corporate Site

Additionally, efficient content management requires reuse of content in different contexts.

For example, reuse of an article for a different section, a mobile site or a micro site should not require inefficient and error-prone copying of that article.

Solution

A site section (or "navigation" or "context") is represented by a content item of type `CMChannel` or `CMExternalChannel` which is a child of `CMChannel`. Sections

span a tree hierarchy through the child relationships of `CMChannel#children`. If a `CMChannel` is referenced by a `CMSite` item it is considered a root channel, that is an entry into a channel hierarchy representing a website. The `CMChannel` content items fulfill the following purposes:

- **Hierarchy:** They form a hierarchy of site sections which can be displayed as a navigation, sitemap, or bread crumb. Each site consists of exactly one section tree.
- **Context:** They function as contexts for content. Content can be reused within different contexts in different layouts and visual appearance. For example, an article's layout may differ in a company's blog section from its layout in the knowledge base.
- **Page:** Each `CMChannel` can be rendered as an overview page of the section it represents. Therefore, the `CMChannel` contains information about the page structure (the "grid") for this overview page and the pages generated when content items are displayed in the content of the `CMChannel`.

For more information on how web pages are assembled in *Blueprint* also refer to the [Section 5.4.4, "Page Assembly" \[167\]](#) section.

- **Configuration:** `CMChannel` content items contain settings which configure various aspects of the site section they represent. Each `CMChannel` can override parent configuration by defining its own layout settings, content visibility, and other context settings. If for example, the "News" section of a site is configured for post-moderation of comments this configuration can be overwritten to premoderation in the subsection "News/Politics".

For more information on settings see the section [Section 5.4.3, "Settings" \[165\]](#).

The context in which a content should be displayed is determined whenever a URL to the content is created. In a simple website with no content reuse all contents only have a single context and link building is very simple. For more complex scenarios *Blueprint* includes a `ContextStrategy` for the following purposes:

- Generate a list of the available contexts for a content (the `ContextFinder`).
- Determine the most appropriate context for the specific link to be built (the `ContextSelector`).

The `DefaultContextStrategy` in *Blueprint* uses a list of `ContextFinders` to retrieve all possible contexts for a content item and a single `ContextSelector` to determine the most appropriate one from the list.

Most notably, there is a `ContextFinder` that utilizes special configuration contents, so-called "folder properties". Its logic to retrieve contexts is as follows:

1. Determine the folder of the content item.

2. Traverse the folder hierarchy starting from the folder in step 1 to the root folder looking for a content item of type `CMFolderProperties` named `_folderProperties`.
3. Return the contents of the linklist property `contexts` of the found `CMFolderProperties` document.

The `ContextSelector` in *CoreMedia Blueprint* is the `NearestContextSelector`. From the list of possible contexts for a content it selects the context closest to the current context.

5.4.3 Settings

Requirements

Editorial users must be able to adjust site behavior by editing content without the need to change the code base and redeploy the application. For example:

- Enable/disable comments for a certain section or the whole site.
- Set the number of dynamically determined related content items that are shown in an article detail view.
- Configure the refresh interval for content included from an external live source.

Administrative users must be able to adjust more technical settings through content, for example:

- Manage API keys for external services
- Image rendering settings
- Localization of message bundles

Solution

CoreMedia Blueprint uses Markup properties following the CoreMedia Struct XML grammar to store settings. Struct XML offers flexible ways to conveniently store typed key-value pairs where the keys are Strings and the values can be any of the following: String, Integer, Boolean, Link, Struct (allows for nested sub Structs).

For more information on the Structs and CoreMedia Struct XML see Section 4.4.4, "Structs" in *Unified API Developer Manual*.

Settings can be defined on all content types inheriting from `CMLinkable`.

```
localSettings
```

UI Name	Local Settings
Description	The settings defined specifically on this CMLinkable.
linkedSettings	
UI Name	Linked Settings
Description	A list of reusable CMSettings documents that contain a bundle of settings.

Table 5.9. Properties of CMLinkable for Settings Management

The local settings are easiest to edit. However, if you want to share common settings across multiple contents, you should spend the few extra steps to put them into a separate `Settings` document and add it to the linked settings in order to facilitate maintenance and ensure consistency. Some projects make use of settings quite extensively.

Multiple `Settings` documents are a good instrument to structure settings of different aspects. You can still override single settings in the local settings, which have higher precedence.

The application also considers settings of the content's page context. If you declare a setting in a page, it is effective for all contents rendered in the context of this page.

Settings are inherited down the page hierarchy, so especially settings of the root page are effective for the whole site, unless they are overridden in a subpage or a content.

For more detailed information and customization of the settings lookup strategy see [Section "The Settings Service" \[118\]](#) and the `SettingsService` related API documentation.

Settings as Java Resource Bundles

In a typical web application there is the need to separate text messages (such as form errors or link texts) from the rendering templates as well as rendering them according to a certain locale. The Spring framework provides a solution for these needs by the concepts of `org.springframework.context.MessageSource` for retrieving localized messages and by `org.springframework.web.servlet.LocaleResolver` for retrieving the current locale. Certain JSP tags such as `<form:error>`; or `<spring:message>` are built on top of these concepts.

In *CoreMedia Blueprint*, localized messages are stored as settings in Struts as described above and can be accessed as `java.util.ResourceBundle` instances.

A handler interceptor (`com.coremedia.blueprint.cae.web.i18n.ResourceBundleInterceptor`) is used to make these content backed messages (as well as the current locale) available to the rendering engine: They are extracted from the content and passed to a special Spring `MessageSource`, the `RequestMessageSource` by storing it in the current request. As a consequence, using JSP tags like `<spring:message>`, `<form:error>` or `<fmt:message>` will transparently make use of these messages.

5.4.4 Page Assembly

Requirements

Requirements

For a good user experience a website should not layout each and every page in a different fancy manner but limit itself to a few carefully designed styles. For example, most pages consist of two columns of ratio 75/25, where the left column shows the main content, and the right column provides some personalized recommendations.

In the best case an editor needs to care only for the content of a page, while the layout and collateral contents are added automatically, determined by the context of the content. However, there will always be some special pages, so the editors must be able to change the layout or the collateral contents. For example for a campaign page which features a new product they may omit the recommendations section and choose a simple one-column layout without any distracting features. In order to preserve an overall design consistency of the site, editors are not supposed to create completely new layouts. They can only choose from a predefined set.

Solution

CoreMedia Blueprint addresses these requirements with the concept of a page grid and placements.

The page grid does not handle overall common page features such as navigation elements, headers, footers and the like. Those are implemented by Page templates with special views. Neither does the page grid control the layout of collections on overview pages. This is implemented by `CMCollection` templates with special views and view types.

You can think of a page grid as a table which defines the layout of a page with different sections. Each section has a link to a symbol document which will later be used to associate content with the section. Technically, the layout of a page is defined in form of rows, columns and the ratio between them. A page grid contains no content and can be reused by different pages. So you might define three global page grids from which an editor can select one, for instance.

Page grid defines layout of a page

The content for the page grid on the other hand, is defined in a `CMChannel` document in so called placements, realized as link lists in structs. Each placement is associated with a specific position of the page grid through a link to a symbol document. The editor can add content to the placement, collections for example, which will be shown at the associated position of the page grid.

CMChannel contains content for page

Placements can also be shared between channels because a child inherits the placements of its parent. A prerequisite for inheritance is that the page grids of the parent and child page must have sections with the same name. For example, the parent channel has a two-column layout with the sections "main" and "sidebar". The child channel has a three-column layout with the sections "main", "sidebar" and "leftcolumn".

Inheriting placements

For the placements this means:

- The child must fill a placement with content for the "leftcolumn" section, because the parent has no such section.
- The child will override the placement for the "main" section with its content. Inheritance makes no sense for the "main" section.
- The child does not need to declare a "sidebar" placement but can inherit the "sidebar" placement of the parent, even though it uses a different layout.

Before going into the implementation details of the page grid, you will see how to work with page grids in *CoreMedia Studio*.

Page grids in CoreMedia Studio

Editors can manage pages directly by editing the "placements" in the page grid in `CMChannel` documents (localized as `Page` in *CoreMedia Studio*). A placement is a specific area on a page such as the navigation bar, the main column or the right column.

Inheriting placements and locking

A `CMChannel` can inherit page grid placements of its parent channel. For example, the Sports/Football section of a site can inherit the right column from the Sports section. Editors can also choose to "lock" certain placements and thus prevent subchannels from overwriting them. Each page grid editor provides a combo box to choose between different layouts for a page. Depending on the selected layout, placement may inherit their content if the same placement is defined in the layout of the parent page.

Each placement link list can configure a view type. The view type determines how the placement is rendered.

Layout of placement via view type

To define which placement view types are available for a page in some site, view type (`CMViewtype`) documents are placed in view type folders under a site-relative path or at global locations. The default paths are the site-relative path `Options/Viewtypes/` and the absolute path `/Settings/Options/Viewtypes/`. This can be configured via the application property `pagegrid.viewtype.paths`, which contains a comma-separated list of repository paths. Each path may start with a slash

['/'] to denote an absolute path or with a folder name to denote a path relative to a site root folder. When changing these values, please make sure that the existing view type documents are moved or copied to the new target location.

Web pages are represented in the CAE using the `com.coremedia.blueprint.common.contentbeans.Page` object which consists of two elements: the content to be rendered and the context in which to render the content.

Pages where the content to be rendered is the same as the context (for example, section overview) display the page grid of the context. Pages where content items (such as Articles) are displayed within a context use display the context's page grid but replace the "main" placement with the content item.




Figure 5.9. The page grid editor and the Hero placement

Each placement contains a link list and several additional buttons on top of it. The order of the linked elements can be modified using drag and drop.

Instead of adding own content, a placement can inherit the linked content from a parent's page placement. If you inherit the content, you cannot edit the placement in the child page. You have to deactivate the "override" button to change the content of the placement.

Placement structure

Inheriting content from parent page



Figure 5.10. An inheriting placement

A placement can be locked using the "lock" button. In this case all child placements are not able to overwrite this placement with own content.

Locking placement




Figure 5.11. A locked placement

The page grid editor provides a combo box with predefined layouts to apply to the current page. After changing the layout, the *Studio* preview will immediately reflect the new page layout.

▼ Placements




Figure 5.12. The layout chooser combo box

The layout of a parent page grid may be changed so that it does not fit anymore with the layout of a child page which inherits some settings. A child may use a three-column layout and inherit most of its content from its parent page that also uses a three-column layout. Then, the layout of the parent may be changed to another layout with a single column that doesn't contain any of the needed layout sections. The child configuration is invalid in this case and the user has to reconfigure all child pages.

Currently there is no kind of detection for these cases in *Studio*, so the user has to check manually if the child configurations are still valid.

Inconsistency between parent and child page grid

No check for inconsistency

How to configure a page grid editor

The Blueprint base module `bpbases-pagegrid-studio-plugin` provides an implementation of the page grid editor shown above through the config class `pageGridPropertyField` in the package `com.coremedia.blueprint.base.pagegrid.config`. In many cases, you can simply use this component in a document form by setting only the standard configuration attributes `bindTo`, `forceReadOnlyValueExpression`, and `propertyName`.

If you want to adapt the columns shown in the link list editors for the individual section, you can also provide fields and columns using the attributes `fields` and `columns`, respectively. The semantics of these attributes match those of the `linkListPropertyField` component.

How to configure the layout location

Pages look up layouts from global and site specific folders. By default, the site specific page grid layout path will point to `Options/Settings/Pagegrid/Layouts`.

and the global one to `/Settings/Options/Settings/Pagegrid/Layouts`. This can be changed via the application property `pagegrid.layout.paths`, which contains a comma-separated list of repository paths. Each path may start with a slash (`'/'`) to denote an absolute path or with a folder name to denote a path relative to a site root folder. When changing these values, please make sure that the existing page layout documents are moved or copied to the new target location. Also, mind that when looking for the default page layout (see below), paths mentioned first take precedence, so it usually makes sense to start with site-relative paths and continue with absolute paths.

CAUTION

The default layout settings document `PagegridNavigation` must be present in at least one of the available layout folders. The page grid editor will show an error message if the document is not found.



CAUTION

If several layout folders are used, make sure that the layout settings documents have unique names.



How to configure a new layout

Every `CMSettings` document in a layout folder is recognized as a layout definition. The `settings` struct property defines a table layout with different sections. The struct defines two integer properties with the overall row and column count. The struct data may also contain two string properties `name` and `description`, which are used for the localization of page grid layout documents (see [section "How to localize page grid objects" \[178\]](#)).

The `items` property contains a list of substructs, each defining a section of the page grid. The order in which the sections appear in the struct list matches the order in which the link lists of the individual sections are shown by the page grid editor.

The sections are represented by `CMSymbol` documents. The layout definition is inspired by the HTML table model, even though *CoreMedia Blueprint*'s default templates do not render page grids as HTML tables but with CSS means. The sections support the following attributes:

- `col`: The column number where the section is placed or, if the `colspan` attribute is set, the column number of the leftmost part of the section.
- `row`: The row number where the section is placed or, if the `rowspan` attribute is set, the row number of the topmost part of the section.

- *colspan*: The number of columns spanned by the section.
- *rowspan*: The number of rows spanned by the section.
- *width*: The width of this section in percent of the total width.
- *height*: The height of this section in percent of the total height.

The *col*, *row* and *rowspan* attributes of the section must match the grid layout defined by the *colCount* and *colRow* attributes (see [Example 5.1, "Pagegrid example definition" \[173\]](#)). That is, when *colCount* and *colRow* are "3" and "4", for example, then you have 12 cells in the page grid table layout which must all be filled by the sections. No cell can be left empty, and no section can overlap with other sections.

The height attribute is only used for the preview of the layout in the page form. It has no impact on the delivered website.

The default PagegridNavigation layout settings document with a 75%/25% two column layout looks as follows:

```
<Struct xmlns="http://www.coremedia.com/2008/struct"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <IntProperty Name="colCount">2</IntProperty>
  <IntProperty Name="rowCount">1</IntProperty>
  <StructListProperty Name="items">
    <Struct>
      <LinkProperty Name="section" xlink:href="coremedia:///cap/content/550"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
      <IntProperty Name="row">1</IntProperty>
      <IntProperty Name="col">1</IntProperty>
      <IntProperty Name="height">100</IntProperty>
      <IntProperty Name="width">75</IntProperty>
      <IntProperty Name="colspan">1</IntProperty>
    </Struct>
    <Struct>
      <LinkProperty Name="section" xlink:href="coremedia:///cap/content/544"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
      <IntProperty Name="row">1</IntProperty>
      <IntProperty Name="col">2</IntProperty>
      <IntProperty Name="height">100</IntProperty>
      <IntProperty Name="width">25</IntProperty>
      <IntProperty Name="colspan">1</IntProperty>
    </Struct>
  </StructListProperty>
  <StringProperty Name="name">2-Column Layout (75%, 25%)</StringProperty>
  <StringProperty Name="description">Two column layout with main and sidebar
sections</StringProperty>
</Struct>
```

Example 5.1. Pagegrid example definition

CAUTION

The main content of a document will always be rendered into the main section of a layout. Therefore, every layout must define a main section.



How to configure a read-only placement

The page grid layout definition provides the possibility to declare a read-only section. Such sections are typically filled with content from third-party integrations. If unspecified, a section is editable. In order to disable editing, you have to declare the Boolean property `editable` for the `struct` element of the corresponding section and set it to "false", for example:

```
<Struct>
  <LinkProperty Name="section" xlink:href="coremedia:///cap/content/120"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
  <IntProperty Name="row">2</IntProperty>
  <IntProperty Name="col">1</IntProperty>
  <IntProperty Name="colspan">1</IntProperty>
  <IntProperty Name="height">75</IntProperty>
  <IntProperty Name="width">25</IntProperty>
  <BooleanProperty Name="editable">false</BooleanProperty>
</Struct>
```

The section that matches the given symbol will be shown as disabled in *Studio*. The matching placements will not appear in the editor.

How to disable the inheritance of the placement

The page grid layout definition provides the possibility to declare a section for which the inheritance of placements is disabled. For such section the placement will be never inherited from parent but must be provided for each children. In order to disable the inheritance, you have to declare the Boolean property `disableInheritance` for the `struct` element of the corresponding section and set it to "true", for example:

```
<Struct>
  <LinkProperty Name="section" xlink:href="coremedia:///cap/content/120"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
  <IntProperty Name="row">2</IntProperty>
  <IntProperty Name="col">1</IntProperty>
  <IntProperty Name="colspan">1</IntProperty>
  <IntProperty Name="height">75</IntProperty>
  <IntProperty Name="width">25</IntProperty>
  <BooleanProperty Name="disableInheritance">true</BooleanProperty>
</Struct>
```

For the section that matches the given symbol the inheritance and locking in the *Studio* are disabled.

You can also disable the inheritance for all sections for a given layout by declaring the Boolean property `disableInheritance` to 'true' in the first level as shown in the following example:

```
<Struct xmlns="http://www.coremedia.com/2008/struct"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <IntProperty Name="colCount">2</IntProperty>
  <IntProperty Name="rowCount">1</IntProperty>
  <BooleanProperty Name="disableInheritance">true</BooleanProperty>
  <StructListProperty Name="items">
    <Struct>
      <LinkProperty Name="section" xlink:href="coremedia:///cap/content/550"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
      <IntProperty Name="row">1</IntProperty>
      <IntProperty Name="col">1</IntProperty>
```

```

<IntProperty Name="height">100</IntProperty>
<IntProperty Name="width">75</IntProperty>
<IntProperty Name="colspan">1</IntProperty>
</Struct>
<Struct>
<LinkProperty Name="section" xlink:href="coremedia:///cap/content/544"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
<IntProperty Name="row">1</IntProperty>
<IntProperty Name="col">2</IntProperty>
<IntProperty Name="height">100</IntProperty>
<IntProperty Name="width">25</IntProperty>
<IntProperty Name="colspan">1</IntProperty>
</Struct>
</StructListProperty>
<StringProperty Name="name">2-Column Layout (75%, 25%)</StringProperty>
<StringProperty Name="description">Two column layout with main and sidebar
sections</StringProperty>
</Struct>

```

How to disable the default inheritance of the placement

For a new page grid the placement is per default inherited from a parent. You can declare a section for which the inheritance of placements is not default. For such section the placement will be empty first before you activate the inheritance or fill the placement on your own. In order to make the non-inheritance default, you have to declare the Boolean property `defaultInheritance` for the struct element of the corresponding section and set it to "false", for example:

```

<Struct>
  <LinkProperty Name="section" xlink:href="coremedia:///cap/content/120"
LinkType="coremedia:///cap/contenttype/CMSymbol"/>
  <IntProperty Name="row">2</IntProperty>
  <IntProperty Name="col">1</IntProperty>
  <IntProperty Name="colspan">1</IntProperty>
  <IntProperty Name="height">75</IntProperty>
  <IntProperty Name="width">25</IntProperty>
  <BooleanProperty Name="defaultInheritance">false</BooleanProperty>
</Struct>

```

You can also make the non-inheritance default for all sections for a given layout by declaring the Boolean property `defaultInheritance` to 'false' in the first level - similar as the `disableInheritance`.

CAUTION

For an existing layout which is used for many page grids changing the flags `disableInheritance` and `defaultInheritance` will change the contents of the page grids. Especially if the page grids are indexed by the *CAE Feeder* they all be re-indexed. Use the flags with caution.



How to populate a page grid with content

Page grids are defined in the struct property `CMNavigation.placement` of a channel. Such structs are typically created using the page grid editor shown above. Example:

```
<Struct xmlns="http://www.coremedia.com/2008/struct"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <StructListProperty Name="placements">
    <Struct>
      <LinkProperty Name="section"
LinkType="coremedia:///cap/contenttype/CMSymbol"
xlink:href="coremedia:///cap/content/550"/>
      <LinkProperty Name="viewtype"
LinkType="coremedia:///cap/contenttype/CMViewtype"
xlink:href="coremedia:///cap/content/1784"/>
      <LinkListProperty Name="items"
LinkType="coremedia:///cap/contenttype/CMArticle">
        <Link xlink:href="coremedia:///cap/content/134"/>
        <Link xlink:href="coremedia:///cap/content/498"/>
      </LinkListProperty>
    </Struct>
    <Struct>
      <LinkProperty Name="section"
LinkType="coremedia:///cap/contenttype/CMSymbol"
xlink:href="coremedia:///cap/content/544"/>
      <LinkListProperty Name="items"
LinkType="coremedia:///cap/contenttype/CMArticle">
        <Link xlink:href="coremedia:///cap/content/776"/>
      </LinkListProperty>
    </Struct>
  </StructListProperty>
  <StructProperty Name="placements_2">
    <Struct>
      <LinkProperty Name="layout"
LinkType="coremedia:///cap/contenttype/CMLayout"
xlink:href="coremedia:///cap/content/3488"/>
    </Struct>
  </StructProperty>
</Struct>
```

A placement struct contains a list of section structs `placements`. The `placements_2` struct contains another struct, `placements` and a link property `layout`, which determines the layout for this channel.

The `placements` struct property consists of substructs for the single placements, each of which refers to a section and lists its contents in the `items` property. Additionally, each placement can declare a view type.

Layouts and placements are connected by the section documents. Let's assume you have two sections, "main" and "sidebar". Your channel declares some latest news for the main section and some personalized recommendations for the sidebar. The layout definition consists of one row with two columns, the left column refers to the "main" section, the right column refers to the "sidebar". This will make your channel be rendered with the main content left and the recommendations on the right. If you don't like it, you can simply choose another layout, for example with a different width ratio of the columns or with the sidebar left to the main section.

The rendering of a page grid is layout-driven, because the sections of the table-like layout model must be passed to the template in an order which is suitable for the output format [usually HTML]. CoreMedia Blueprint's web application processes a page grid as follows:

1. The `PageGridServiceImpl` determines the layout document of the channel. If there is no layout link in the `placements_2` struct, a fallback document `PagegridNavigation` is used. This name can be configured by setting the application property `pagegrid.layout.defaultName`. The fallback layout document can be located in any of the configured layout folders (see "layout locations"), usually it will be located under the site relative path `Options/Settings/Pagegrid/Layouts`. The layout definition is evaluated and modeled by a `ContentBackedStyleGrid`.
2. The `PageGridServiceImpl` collects the placements of the channel itself and the parent channel hierarchy. The precedence is obvious, for example a channel's own placement for a section ("sidebar" for instance) overrides an ancestor's placement for that section.
3. Both layout and placements are composed in a `ContentBackedPageGrid` which is the backing data for a `PageGridImpl`. `PageGridImpl` implements the `PageGrid` interface and prepares the data of the `ContentBackedPageGrid` for access by the templates. Basically
 - it wraps the content of the placements into content beans,
 - it arranges the placements in rows and columns, according to the layout
 - it replaces the channel's main placement with the requested content.

Blueprint's default templates [namely `PageGrid.ftl`] do not render page grids as HTML tables but as nested `<div>` elements and suitable CSS styles. The beginning of a rendered page grid looks like this:

```
<div id="row1" class="row">
  <div id="main" class="col1 column col1of2 width67">
```

The outer `<div>` elements represent the rows of the page grid, the inner `<div>` elements represent the columns. The ids of the rows are generated by the template as an enumeration. The ids of the columns are the section names of the placements. The column `<div>` elements are rendered with several class attributes:

- `column`: A general attribute for column `<div>` elements
- `col1`: The absolute index of the column in its row
- `col1of2`: The *colspan* of this column [1] and the absolute number of columns of the page grid [2]
- `width67`: The relative width of this column

You can use these attributes to define appropriate styles for the columns. *CoreMedia Blueprint*'s default CSS provides styles which reflect the width ratios of some typical multi-column layouts. You find them in the document `/Themes/basic/css/basic.css` in the content repository where you can enhance or adapt them to your needs.

In the inner `<div>` elements the placements are included, and their section names determine the views. For example a "sidebar" placement is included by the `PageGrid.Placement.sidebar.jsp` template.

How to localize page grid objects

To localize a layout name, create a resource bundle entry with the key `<layoutname>_text` in the resource bundle `PageGridLayouts_properties`, where `<layoutname>` is the name of the layout document or, preferably, the `name` property of the settings struct of the layout. Similarly, a layout description can be localized with entries of the form `<layoutname>_description`. If no corresponding resource bundle entries are found, the `description` property of the settings struct of the layout is used. If that property is empty, too, the name is used as the description. The resource bundle is available in the package `com.coremedia.blueprint.base.pagegrid` of module `bpbse-pagegrid-studio-plugin`.

For the purposes of localization, placements are treated as pseudo-properties and localized according to the standard rules for content properties as described in the Studio Developer Manual. The name of the pseudo-property is `<structname>-<placementname>`, where `<structname>` is the name of the struct property storing the page grid and `<placementname>` is the name of the section document. For example, a placement with the name `main` that is referred from the standard page grid struct `placement` of a `CMChannel` document would obtain its localization using the key `CMChannel_placement-main_text`. You can add localization entries to the resource bundle `BlueprintDocumentTypes_properties` of module `blueprint-forms`, which is applied to the built-in resource bundle `ContentTypes_properties` at runtime.

To localize a view type name or a view description, you can add a property `<viewtype name>_text` or `<viewtypename>_description` to the bundle `Viewtypes_properties`. Here `<viewtypename>` is the name of the view type document or, preferably, the string stored in its `layout` property. Because view types are also used in other contexts, this bundle has been placed in the package `com.coremedia.blueprint.base.components.viewtypes` of module `bpbse-studio-components`.

CoreMedia Blueprint defines three resource bundles `BlueprintPageGridLayouts_properties`, `BlueprintPlacements_properties`, and `BlueprintViewtypes_properties`. Entries of these bundles are copied to the bundles described above, providing a convenient way to add custom entries.

5.4.5 Overwriting Product Teaser Images

NOTE

Feature is only supported in *eCommerce Blueprint*



Requirements

You have put a product teaser on your home page, which is displayed with the default product image coming from the eCommerce system but you want to highlight that teaser by changing its default image to a more engaging one.

Solution

CoreMedia Content Cloud allows you to either use the content from the eCommerce database or overwrite this image with your own image in the *Teaser* content type.

5.4.6 Content Lists

Requirements

Websites frequently display content items that share certain characteristics as lists, for example, the top stories of the day, the latest press releases, the best rated articles or the recommended products. Some of these lists are managed editorially while others should be compiled dynamically by business rules defined by editors. It is a common requirement to reuse these content lists across different web pages and use common functionality to place lists on pages and assign different layouts to lists.

Solution

CoreMedia Blueprint defines different content types for lists of content which differ in how they determine the content items. Leveraging CoreMedia's object oriented content

modeling these lists can reuse view templates and can be placed interchangeably on web pages.

Type	Purpose
CMCollection	A common base type for lists, which all other list types extend. It provides functionality for editorially managed lists.
CMGallery	A distinct content type for lists of CMMedia content items which should be displayed as a gallery.
CMQueryList	Dynamic lists that are based on content metadata, such as "latest 5 articles in sport".
CMSelectionRules (part of Adaptive Personalization)	Dynamic lists that are based on context information with rules defined by editorial users, such as "if a visitor is interested in notebooks, display this product, otherwise display something else."
CMP13NSearch (part of Adaptive Personalization)	Dynamic lists based on content metadata and context information, such as "display list of articles matching the current visitor's bookmarked taxonomies."
ESDynamicList (part of Elastic Social)	Dynamic lists that are based on Elastic Social metadata, such as "5 best rated articles in news."
CMALXPageList (part of Analytics)	Dynamic lists that are bases on analytics data, such as "10 most viewed articles in business."

Table 5.10. Collection Types in CoreMedia Blueprint

5.4.7 View Types

Requirements

A common pattern for CoreMedia projects is to reuse content and display the same content item on various pages in different layouts and view variants. A content list, for example, could be rendered as simple bulletin list or as a list of teasers with thumbnails. Similarly, an article can be displayed in a default ("full") view or as a teaser.

Usually the rendering layer decides what view should be applied to a content item in different use cases. For example, the view rendering results of a search on the website could use the `asListItem` view to render the found items.

Editors still need a varying degree of control to influence the visual appearance of content in specific cases. They might want to decide whether a list of content items should be displayed as a teaser list or a collapsible accordion on a page, for example.

Solution

A dedicated content type called `CMViewtype` is available that can be associated with all `CMLinkable` content types.

During view lookup a special `com.coremedia.objectserv`
`er.view.RenderNodeDecorator`, the `ViewTypeRenderNodeDecor`
`ator`, augments the view name by the `layout` property of the view type referenced by the content item.

The `BlueprintViewLookupTraversal` then evaluates this special view name and falls back to the default view name without the view type if the view could not be resolved.

In the example above the template responsible for rendering search results would include all found content with the `asListItem` view. If the content is of type `CMArticle` there would be a lookup for a `CMArticle.asListItem.ftl` (among others in the content object's type hierarchy, see Section 4.3.3, "Views" in *Content Application Developer Manual* for more CoreMedia's object oriented view dispatching). If the article has a view type assigned (such as `breakingnews`) there would be a lookup for `CMArticle.asListItem[breakingnews].ftl` before falling back to `CMArticle.asListItem.ftl`. This allows for very fine grained editorially driven layout selection for any created content.

Selecting a view type in CoreMedia Studio

You can use the view type selector which is associated with the view type property to select a specific view type for a document, a collection for instance. The view type selector is implemented as a combo box providing an icon preview and a description text about the view type. View types can be defined globally or site specific. If the view type item is configured for a site, the name of the site is also displayed in the combo box item.




Figure 5.13. Layout Variant selector

How to configure a view type selector

There are several document forms that include the view type selector form. The `ViewTypeSelectorForm` bundles the view type selector combo box and its configuration parameters. The parameter `paths` defines which items are shown in the combo box. The combo box assumes that each of the items (`CMViewtype` here) has a property `icon` that contains the thumbnail view of the view type.

```
<bpforms:ViewTypeSelectorForm propertyName="viewtype"
  paths="{['/Settings/Options/Viewtypes/CMTeasable',
    'Options/Viewtypes/CMTeasable']}" />
```

In this example all `CMViewtype` documents of the folders `/Settings/Options/Viewtypes/CMTeasable` and `Options/Viewtypes/CMTeasable` (site depending) are shown in the view type selector combo.

An additional view type selector form is the class `ContainerViewTypeSelectorForm`. It inherits from `ViewTypeSelectorForm` and sets the `paths` parameter to `['/Settings/Options/Viewtypes/CMChannel/', 'Options/Viewtypes/CMChannel/']`.

How to localize view types for the view type selector

The view type selector displays two fields of a view type: The name (which is the name of the document in the repository) and the `description` property. These string can be localized as described earlier in [section "How to localize page grid objects" \[178\]](#).

5.4.8 CMS Catalog

Requirements

Some companies do not run an online store. They do not need a fully featured shopping system. Nonetheless, they want to promote some products on their corporate site.

Solution

CoreMedia Content Cloud provides the *CMS Catalog*, an implementation of the *eCommerce API*, which is backed only by the CMS and does not need a third-party eCommerce system. It allows maintaining a smaller number of products and categories for presentation on the website. It does not support shopping features like availability or payment. The *CMS Catalog* is based on *Blueprint* features. It is already integrated in the *Corporate* extension, so you can use it out of the box.

Maven Module	Description
<code>com.coremedia.blueprint.base:bpbase-ecommerce</code>	Contains the <i>eCommerce API</i> implementation for the CMS. The implementation is content type independent.
<code>com.coremedia.blueprint:ecommerce</code>	Contains the content types, content beans and the studio catalog component.
<code>com.coremedia.blueprint:corporate</code>	Example usage of the catalog in the corporate page.

Table 5.11. CMS Catalog: Maven parent modules

Content Types

In the *CMS Catalog* products and categories are modeled as content. There are two new content types, *CMProduct* and *CMCategory*, which extend the well known *Blueprint* document types *CMTeasable* and *CMChannel*, respectively. So you can seamlessly integrate categories into your navigation hierarchy and place products on your pages, just like any other content. In order to activate the new content types you have to add a Maven runtime dependency on the `catalog-doctypes` module to your Content Server components.

Content Beans

The modules `catalog-contentbeans-api` and `catalog-contentbeans-lib` provide content beans for `CMProduct` and `CMCategory`. The content beans integrate into the class hierarchy according to their content types, that is they extend `CMTeasable` and `CMChannel`, respectively. The content beans do not implement the *eCommerce API* interfaces `Product` and `Category`, though. Instead, they provide delegates via `getProduct` and `getCategory` methods. While this may look inconvenient at first glance, it has some advantages concerning flexibility:

- The content bean interfaces remain independent of future changes in the *eCommerce API*.
- You have better control over the view lookup by explicitly including the content bean or the delegate.

Configuration

First, you need three settings in the root channel to activate a CMS Catalog for your site. *Blueprint Base* provides a commerce connection named `cms1` which is backed by the content repository. You can activate this connection by the `livecontext.connectionId` setting. Moreover, your catalog needs a name, which is specified by the `livecontext.store.name` setting. Finally, your catalog needs a root category, which is specified by the `livecontext.rootCategory` setting. In case you didn't choose a root category, you need to reload the site to complete the linking of the settings to the site.




Figure 5.14. CMS Catalog Settings

Although the catalog indicator is a `CMCategory` document, it does not represent a category but serves only as a technical container for the actual top categories [see *eCommerce API*, `CatalogService#findTopCategories`]. The concept resembles the site indicator, which is the point of entry to the navigation without being part of it.

In a multi-site project sites may have different commerce connections. In order to make `DefaultConnection#get` work correctly regarding to the site a particular request refers to, you need to declare a Maven runtime dependency on the `bpbase-ec-cms-component` module and import some magic into the CAE Spring configuration:

```
<import resource="classpath:/com/coremedia/blueprint/ecommerce/cae/ec-cae-lib.xml"/>
```

While the product → category relation is modeled explicitly with the `contexts` link list, the reverse relation uses the search engine. Therefore, you need to extend the *contentfeeder* component with some Spring configuration from the `bpbase-ec-cms-contentfeeder-lib` module:

```
<import resource="classpath:/framework/spring/bpbase-ec-cms-contentfeeder.xml"/>
```

Templating

You can use both, `Product` or `CMProduct` templates. You can also use a mixture of both for different views or fallback to `CMTeasable` templates for views that do not involve `CMProduct` specific features.

Using `Product` templates you can easily switch to a third-party eCommerce system later, since the interface remains the same. Otherwise, you are more flexible with `CMProduct` templates:

- You can easily enhance the `CMProduct` content type and interface and access the new features immediately.
- You benefit from all the inherited features (like multi-language) and fallback capabilities along the content type driven interface hierarchy.
- You can easily switch from `CMProduct` to `Product` just by calling `CMProduct#getProduct` anywhere you need a `Product` object. The reverse direction is more cumbersome.

5.4.9 Teaser Management

Requirements

Most websites present short content snippets as "teasers" on various pages. Content and layout for teasers should be flexible but manageable with minimum effort.



Figure 5.15. Default view and teaser view of an Article

It is a common requirement to automatically derive abbreviated content teasers without the need to duplicate any content items. In some cases, editors wish to create distinct teasers for a content item that don't reuse any information from that item.

Example: An editor wants to point to an article using a specific image that is not part of that article. Or: An editor wants to promote an article on a page with a teaser that is not the default teaser (using different text, image, or layout).

Solution

In *CoreMedia Blueprint* all content types for content and pages extend from the abstract content type `CMTeasable`. It defines common properties and business rules which provide all types inheriting from `CMTeasable` with a default behavior when displayed as a teaser.

Type	Purpose
<code>teaserTitle</code>	The title of the content item when displayed as a teaser.
<code>teaserText</code>	The text of the content item when displayed as a teaser.

Table 5.12. Properties of `CMTeasable`

Fallbacks to automatically display the shorter teaser variant of properties are implemented in the content bean implementation for `CMTeasable`. For example, the `teaserText` of a content reverts to the `detailText` if no `teaserText` has been entered by an author.

For distinct teasers *CoreMedia Blueprint* includes a `CMTeaser` content type that can be used for this purpose. It provides all properties required to display a teaser and can be linked to the content that it promotes. Teasers without a link are also supported to create non-interactive brand promotions etc.

5.4.10 Dynamic Templating

Requirements

In order to quickly implement microsites, campaigns, or specialized channels with unique template requirements, templates can be updated without interrupting the service or requiring a redeployment of the application.

Solution

Views can be implemented as FreeMarker templates and uploaded to the Content Repository in a container file, preferably a JAR. For details, consult the Section "Loading Templates from the Content Repository" in *Content Application Developer Manual*.

Prerequisites

In order for the CAE to find the FreeMarker templates, the property `delivery.local-resources` must be set to "false".

Create the archive containing the templates

A template set archive, preferably a JAR file, can contain FreeMarker templates which must be located under the path: `/META-INF/resources/WEB-INF/templates/siteName/packageName/`

The easiest way to create the JAR is to create a new Maven module with a POM like this one:

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
http://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <groupId>org.example.groupId</groupId>
  <artifactId>templates</artifactId>
  <version>--insert version here--</version>
  <packaging>jar</packaging>
  <description>
    CAE templates to be uploaded to a CMTemplateSet document in
    /Themes/*my.package*/templates/ with name *my.package*-templates.jar.

    Use the *my.package* as a reference in a Page's
    "viewRepositoryNames" settings (list of strings).
  </description>

  <build>
    <plugins>
      <plugin>
        <groupId>org.apache.maven.plugins</groupId>
        <artifactId>maven-jar-plugin</artifactId>
        <version>2.4</version>
        <configuration>
          <archive>
            <addMavenDescriptor>true</addMavenDescriptor>
          </archive>
        </configuration>
      </plugin>
    </plugins>
  </build>
</project>
```

Put your templates below the path `src/main/resources/META-INF/resources/WEB-INF/templates/--themeName--/--packageName--/`, for example `src/main/resources/META-INF/resources/WEB-INF/templates/corporate/com.coremedia.blueprint.common.contentbeans/Page.ftl`

Upload the template set

CoreMedia Blueprint provides the content type `Template Set` (`CMTemplateSet`) which is used for this purpose. Create a document of type `Template Set` in folder `/Themes/--themeName--/templates` and upload the JAR to its `archive` property. Its name is significant and is used to reference template sets from channel settings, as explained see below.

Name	Description
description	A description of the purpose / contents of the code.
archive	blob property that contains the archive (preferably a JAR) that contains the templates.

Table 5.13. Properties of `CMTemplateSet`

Add the template set to a page

A Page context can be configured to add additional template sets to all pages rendered in its context. The names of additional template sets are configured in a string list setting `viewRepositoryNames` of a Page. Like all settings, a Page will inherit this list of names from its parent context, if it is not set. See [Section 5.4.11, “View Repositories” \[190\]](#) for more details.

NOTE

The CAE will resolve view repository names automatically according to the predefined name pattern. For instance, if a Page sets its `viewRepositoryNames` to the list `["christmas", "campaigns"]`, each page rendered in this context will use templates implemented in the Template Sets `/Themes/christmas/templates/christmas-templates.jar` and `/Themes/campaigns/templates/campaigns-templates.jar` before falling back to the default templates defined for the web application.



5.4.11 View Repositories

Requirements

A CoreMedia deployment can host multiple sites which frequently differ in layout and functionality. It is a common requirement to use different view templates for those sites but still be able to define reused templates across sites flexibly.

Solution

The *CoreMedia CAE* offers a very flexible view selection mechanism by providing the `ViewRepositoryNameProvider` and `ViewRepositoryProvider` abstraction [see Section 4.3.3, "Views" in *Content Application Developer Manual*].

CoreMedia Blueprint offers the `BlueprintViewRepositoryNameProvider` implementation which for each lookup of model and view generates a list of view repository names to query. The list is created based on

- the specific view repository names defined in the String list setting `viewRepositoryNames` of the navigation context of the provided model,
- the view repository names defined via Spring in the property `commonViewRepositoryNames` on the `BlueprintViewRepositoryNameProvider` Java bean.

This allows for more fine-grained control of the used view repositories as view repositories can be configured not only specific for a site but also for each site section.

CoreMedia Blueprint uses the standard CAE `TemplateViewRepositoryProvider` to create from the list of view repository names the list of actual view repositories to query. *CoreMedia Blueprint* configures the following `templateLocationPatterns` for the `TemplateViewRepositoryProvider`:

- `jar:id:contentproperty:/Themes/%1$s/templates/%1$s-templates.jar/archive!/META-INF/resources/WEB-INF/templates/%1$s`
- `jar:id:contentproperty:/Themes/%1$s/templates/%1$s-templates.jar/archive!/META-INF/resources/WEB-INF/templates/sites/%1$s`
- `/WEB-INF/templates/sites/%s`
- `/WEB-INF/templates/%s`

Example: For a content of the corporate site the `BlueprintViewRepositoryNameProvider` yields the view repository names "corporate". The `TemplateViewRepositoryProvider` would then return the following view repositories which are queried for the responsible view:

- A FreeMarker template view repository in the CMS located in the `/Themes/corporate/templates/corporate-templates.jar` (a `CMTemplateSet`) content item's blob property `archive`
- A FreeMarker or JSP file system view repository below `/WEB-INF/templates/sites/corporate`
- A FreeMarker or JSP file system view repository below `/WEB-INF/templates/corporate`

5.4.12 Client Code Delivery

Requirements

Client code such as JavaScript and CSS is changing more rapidly than frontend templates and backend business rules. To deliver JS and CSS changes conveniently it is a common pattern to consider those as content and use the common editorial workflow (create, approve, publish) to deploy these to the live environment.

Solution

CoreMedia Blueprint provides the content types `CMCSS` and `CMJavaScript` which both inherit from the common super type `CMAbstractCode`.

Name	Description
description	A description of the purpose / contents of the code.
code	The code stored in a CoreMedia XML property following the CoreMedia Rich-Text schema. This allows for embedding images directly in a code fragment and enables quick fixes of client code in the standard CoreMedia editing tools.
disableCompress	Prevents the CAE from compressing the code. This flag only has any effect if a corresponding <code>com.coremedia.blueprint.cae.view.processing.Minifier</code> is provided to the <code>com.coremedia.blueprint.cae.view.MergeableResourcesView</code> that handles the given content type. If this is the case, setting this flag is recommended if the code is either already compressed or if it is not compatible with the

Name	Description
	compression engine. The <i>Theme Importer</i> automatically set this flag if the file extension is <code>.min.js</code> or <code>.min.css</code> .
<code>include</code>	Other code elements that should be deployed together with this one.
<code>dataUrl</code>	An (optional) URL of the code on an external system. Allows to also manage all code included from third-party servers as if it was part of the CoreMedia repository.

Table 5.14. Client Code - Properties of *CMAbstractCode*

Client code is associated with themes or site sections. *CMTheme* and *CMNavigation* content items contain references to the CSS and JavaScript items to be used within the section. Child sections inherit code from their parent if this code is defined in a theme. They can extend it to refine their section layout. This enables editorial users to quickly associate new design to sections that stand out from the rest of the page, or even roll out a site wide face lift without having to redeploy the application itself.

NOTE

CSS and JavaScript added to a page will only apply to this page and will not be inherited. To apply layout changes to all subpages of a page, it is recommended to create a new theme.



Additional web resources for preview and fragment preview

Additional resources for preview

NOTE

For preview and fragment preview settings and resources it is recommended to manage them in the theme, since it is now possible to define settings there. For more information see Frontend Developer Manual.

Settings to add re-sources for preview



Additional CSS and JavaScript can be added to sites for use in *CoreMedia Studio* and the embedded preview. CSS will be included in `Page._additionalHead.ftl` and JavaScript in `Page._bodyEnd.ftl` after the regular web resources.

The settings are organized as linklist properties. The name of the `linklist` for CSS itself must be `previewCss` and `previewJs` for JavaScript. The settings must be attached to the root channel of a site.

WARNING

In earlier versions the `css/preview.css` and `js/preview.js` of the theme were attached via this setting as well. This is no longer needed as the theme build mechanism will handle adding preview related resources itself.



Additional resources for fragment preview

Additional CSS and JavaScript can be added to sites for use in *CoreMedia Studio* and the embedded preview for fragments, for example, Articles. CSS will be included in `Page._additionalHead.ftl` and JavaScript in `Page._bodyEnd.ftl` before the regular web resources.

The settings are organized as linklist properties. The name of the `linklist` for CSS itself must be `fragmentPreviewCss` and `fragmentPreviewJs` for JavaScript. The settings must be attached to the root channel of a site.

Settings to add re-sources for fragment preview

NOTE

Keep in mind: The CSS and JavaScript for preview are loaded **after** the regular web resources and the ones for the fragment preview are loaded **before** them! Both additional web resources can be combined.



Web Performance Optimization

Besides the concepts for managing and deploying client code from within the content repository, *CoreMedia Blueprint* also features mechanisms to both speed up site loading and reduce request overhead during the delivery of web resources.

Reducing the overhead of both client request count and data transfer sizes for client codes and web resources such as JavaScript and/or CSS.

Minification

In order to reduce the data transfer to the client, JavaScript and CSS files are usually minified, meaning, that all unnecessary characters are removed from the source code. This results in smaller files, hence reduces the amount of data that needs to be transferred to the client. This can especially be useful for mobile clients. Each needed source file is processed by a minifier. The minifier strips all comments, whitespaces and any other unwanted information from the source code and compresses it. The ideal result will be a source file with just a single line of code.

Themes build with the Frontend Workspace will automatically be minified. If for any reason you only want to minify the client code on delivery side you can implement the `com.coremedia.blueprint.cae.view.processing.Minifier` interface and provide your minifier to the corresponding bean of type `com.coremedia.blueprint.cae.view.MergeableResourcesView`.

Merging

CoreMedia Blueprint also offers a merging process which compresses all JavaScript and CSS files into a single one each. The merging, if turned on, immediately follows the minification step. Client codes are also combined by default. As a matter of fact, both features cannot be turned on or of separately.

CAUTION

The process of minification and merging only applies to source files, that don't have a set IE Expression or Data URL property. If an IE Expression or Data URL is set, the file will be skipped in both process steps and result in each file rendered separately into the source code of the page.



Configure minification and merging

For debugging purposes during the development, it might come in handy to disable the minification and merging feature. You do that by turning on the `delivery.developer-mode` property switch, either provided with a standard property file, or via a Maven switch. Inside the `cae-preview-webapp` module, all you have to do is to start the preview CAE web application locally using the Maven Tomcat plugin.

In some cases it might be useful or even necessary to avoid the minification and merging of JavaScript and CSS files without enabling the developer mode. For this you can use the `cae.merge-code-resources` property switch to control the behavior. If set to true (which is not the default), code resources are merged when development mode is off, that is, if no developer is given to construct a page.

WARNING

Merging code resources improves website performance and is generally recommended for live sites.



5.4.13 Managing End User Interactions

Requirements

For a truly engaging experience website visitors need to be able to interact with your website. Interactions can reach from basic ways to search content, register and give feedback to enabling user-to-user communication and facilitating business processes such as product registration and customer self care.

End user interactions should be configurable in the editorial interface by non-technical users in the editorial interface of the system. It should, for example, be possible to place interaction components such as Login and Search buttons on pages just like any other content, configure layout and business rules etc.

Solution

For the Blueprint website, the term "action" denotes a functionality that enables users to interact with the website.

Examples:

- Search: The "search" action lets user to enter a query into a form field. After processing the search, a search result is displayed to the user.
- Login: This action can be used by users to login to the website by adding user name and password credentials. A successful login changes the state web application's state for the user and offers him additional actions such as editing his user profile.

From an editor's perspective, all actions are represented by content objects of type `CMAction`. This enables an editor to add an action content to a page, for example by inserting it to the navigation `linklist` property. When rendering the page, this action object is rendered by a certain template that (for example) renders a search form. The submitted form data (the query, for instance) is received by a handler that does some processing (passing the query to the search engine, for instance) and that provides a model containing the search action result.

This section demonstrates the steps necessary to add new actions to *CoreMedia Blueprint*. It also helps to understand the currently available actions.

Standard Actions

As stated above, all actions are represented as `CMAction` contents in the repository. These contents can be used as placeholders in terms of the "substitution" mechanism

described in the Content Application Developer Manual. An example for adding a new action: Consider an action where users can submit their email addresses in order to receive a newsletter.

1. Create a bean that represents the subscription form and add an adequate template.

```
public class SubscriptionForm {
    public String email;

    public void setEmail(String email) {
        this.email = email;
    }

    public String getEmail() {
        return email;
    }
}
```

SubscriptionForm.asTeaser.jsp

```
<%@ taglib prefix="form"
uri="http://www.springframework.org/tags/form"%>
<!--@elvariable id="self" type="com.mycompany.SubscriptionForm"-->
<!--@elvariable id="subscriptionForm" type="com.mycompany.SubscriptionForm"-->
<!--@elvariable id="cmpage"
type="com.coremedia.blueprint.common.contentbeans.Page"-->
<cm:link target="${cmpage.linkable}" var="redirectUri"/>
<cm:link target="${self}" var="subscriptionUri">
    <cm:param name="return" value="${redirectUri}"/>
</cm:link>
<form:form id="subscriptionForm" modelAttribute="subscriptionForm"
    action="${subscriptionUri}" method="post">
    <form:input path="email"/>
    <input type="submit"/>
</form:form>
```

2. Add a handler that is able to process the subscription as well as a link scheme that builds links pointing to the handler.

```
@Link
@RequestMapping
public class SubscriptionHandler {

    @RequestMapping(value="/subscribe", method=RequestMethod.POST)
    public ModelAndView handleSubscription(@RequestParam(value="return",
        required=true) String redirectUri,
        @ModelAttribute("subscriptionForm")
        SubscriptionForm form,
        HttpServletRequest request,
        HttpServletResponse response)
        throws IOException {
        doSubscribe(request.getSession(), form.getEmail());
        response.sendRedirect(redirectUri);
        return null;
    }

    @Link(type=SubscriptionForm.class, parameter="return", uri="/subscribe")
    public UriComponents createSubscriptionLink(UriComponentsBuilder uri,
```

```

Map<String,Object> parameters) {
    return uri.queryParam("return", (String)
parameters.get("return")).build();
}

...
}

```

Don't forget to register this class as a bean in the Spring application context.

3. Define an action substitution.

```

public class SubscriptionHandler {
    ...
    @Substitution("com.coremedia.subscription",
modelAttribute="subscriptionForm")
    public SubscriptionForm createSubscriptionSubstitution(CMAAction original,
HttpServletRequest request) {
        return new SubscriptionForm();
    }
    ...
}

```

Notes

- The parameters `original` as well as `request` are optional and might be omitted here. But in a more proper implementation it might be useful to have access to the original bean and the current request.
- The optional `modelAttribute` causes the substitution to become available as a request attribute `subscriptionForm`. This is useful when using dealing with the Spring form tag library (see above).

4. Create a newsletter action content

- Create a content of type `CMAAction`
- Set the `id` property to value `com.coremedia.subscription`
- Insert this content to a page's teaser link list.

Here is what happens when opening the page by sending an HTTP request:

1. The request will be accepted by the `PageHandler` that builds a `ModelAndView` containing the `Page` model. This model's tree of content beans contains the new `CMAAction` instance.
2. The model will be rendered by initially invoking `Page.jsp` for the `Page` bean.
3. When the `CMAAction` is going to be rendered in the teaser list, the template `CMAAction.asTeaser.jsp` is invoked. This template substitutes the `CMAAction` bean by invoking the `cm:substitute` function while using the ID `com.coremedia.subscription`.
4. The substitution framework invokes the method `#createSubscriptionSubstitution` after checking whether `SubstitutionRegistry#register`

has been invoked by any handler for his ID (which hasn't happened here). As the result, the substitutions result is a bean of type `SubscriptionForm`.

5. The above mentioned template `CMAction.asTeaser.jsp` therefore delegates to `SubscriptionForm.asTeaser.jsp` then.
6. While rendering `SubscriptionForm.asTeaser.jsp`, a link pointing to this form bean is going to be built. The method `#createSubscriptionLink` is chosen as a link scheme so that the link points to the handler method `#handleSubscription`.
7. After the user has received the rendered page, he might enter his email address and press the submit button.
8. This new (POST) request is accepted by the mentioned handler method `#handleSubscription` that performs the subscription and redirects the original page then so that the first step of this flow is repeated.

Of course, a more proper implementation could mark the subscription state (subscribed or not) in a session/cookie and would return an `UnsubscribeForm` from `#createSubscriptionSubstitution` depending on this state.

Webflow Actions

Spring Webflow (<http://www.springsource.org/spring-web-flow>) is a framework for building complex form based applications consisting of multiple steps. Webflow based actions can be integrated into *Blueprint* as well. This section describes the steps of how to integrate this kind of actions.

In *CoreMedia Blueprint* the `PageActionHandler` takes care of generally handling Webflow actions. The flow's out coming model is automatically wrapped into a bean `WebflowActionState`. A special aspect of this bean is that it implements `HasCustomType` and therefore is able to control the lookup of the of the matching template.

1. Place your flow definition file somewhere below a package named `webflow` somewhere in the classpath. The name of the flow definition file should be `<action_id>.xml`. Example: For an action `com.mycompany.MyFlowAction` you might create a file `com.mycompany.MyFlowAction.xml` that can be placed below a package `com.coremedia.blueprint.mycompany.webflow`.
2. For every flow view (such as "success" or "failure") create a JSP template. The template name needs to match the action id. Example: The action `com.mycompany.MyFlowAction` requires templates to be named `.../templates/com.mycompany/MyFlowAction.<flowView>.jsp`. These templates will be invoked for the mentioned beans of type `WebflowActionState`.

3. Create (and integrate) a new document of type `CMAction` and set the property `id` to the action id (such as `com.mycompany.MyFlowAction`) and the property `type` to **webflow**.

5.4.14 Images

Requirements

For a website images are required in different sizes and formats. For example, teaser need a small image with an aspect ratio of 1:1 in the sidebar and an aspect ratio of 4:3 in the main section. Images in articles and galleries are shown in 5:2 or 4:3 with a large size. And even these sizes are different on mobile devices and desktop displays.

Solution

CoreMedia Blueprint supports different formats combined with different sizes. It comes with four predefined cropping definitions.

- `portrait_ratio3x4` (aspect ratio of 3:4)
- `portrait_ratio1x1` (aspect ratio of 1:1)
- `landscape_ratio4x3` (aspect ratio of 4:3)
- `landscape_ratio16x9` (aspect ratio of 16:9)

A list of sizes can be defined for each format in the `Responsive Image Settings`, located in the `Options/Settings/CMChannel` folder of the site. If no site specific setting is defined, the global setting `Responsive Image Settings` from `/All Content/Settings/Options/Settings` will be taken. The website will automatically choose the best matching image depending of the viewport of the client's browser.

How to configure image sizes

The struct `responsiveImageSettings` contains a list of string properties. This string must contain the name of a cropping format. For example `portrait_ratio1x1`. Each format contains a list of string properties, representing one size of this format. The name and the order of this list is not important and will be ignored. Every size must contain two integer properties `width` and `height`.

If site specific image variants are enabled, the `Responsive Image Settings` will be used for the image editor as well. In this case the additional integer property fields `widthRatio`, `heightRatio`, `minWidth` and `minHeight` must be

defined. Additionally, the field `previewWidth` and/or `previewHeight` should be defined to define the preview size in Studio.

For example a `Responsive Image Settings` with two formats. `portrait_ratio1x1` with just one size and `landscape_ratio4x3` with three sizes.

```
<Struct xmlns="http://www.coremedia.com/2008/struct"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <StructProperty Name="responsiveImageSettings">
    <Struct>
      <StructProperty Name="portrait_ratio1x1">
        <IntProperty Name="widthRatio">1</IntProperty>
        <IntProperty Name="heightRatio">1</IntProperty>
        <IntProperty Name="minWidth">200</IntProperty>
        <IntProperty Name="minHeight">200</IntProperty>
        <IntProperty Name="previewWidth">400</IntProperty>
      <Struct>
        <StructProperty Name="0">
          <Struct>
            <IntProperty Name="width">60</IntProperty>
            <IntProperty Name="height">60</IntProperty>
          </Struct>
        </StructProperty>
      </Struct>
      <StructProperty Name="landscape_ratio4x3">
        <IntProperty Name="widthRatio">4</IntProperty>
        <IntProperty Name="heightRatio">3</IntProperty>
        <IntProperty Name="minWidth">1180</IntProperty>
        <IntProperty Name="minHeight">885</IntProperty>
        <IntProperty Name="previewWidth">400</IntProperty>
      <Struct>
        <StructProperty Name="0">
          <Struct>
            <IntProperty Name="width">200</IntProperty>
            <IntProperty Name="height">150</IntProperty>
          </Struct>
        </StructProperty>
        <StructProperty Name="1">
          <Struct>
            <IntProperty Name="width">320</IntProperty>
            <IntProperty Name="height">240</IntProperty>
          </Struct>
        </StructProperty>
        <StructProperty Name="2">
          <Struct>
            <IntProperty Name="width">640</IntProperty>
            <IntProperty Name="height">480</IntProperty>
          </Struct>
        </StructProperty>
      </Struct>
    </Struct>
  </StructProperty>
</Struct>
```

CAUTION

Every image cropping format must contain one image size, otherwise the default size and format, defined in `ImageFunctions`, will be used.



High Resolution/Retina Images

CoreMedia Blueprint supports high resolution images. Set the BooleanProperty `enableRetinaImages` to true. If enabled, the JavaScript `jquery.coremedia.responsiveimages.js` is choosing a larger image according to the `devicePixelRatio` of the browser.

For Example the website wants to render an image with an aspect ratio of 4:3 and the best responsive image size is 400px : 300px. With a `devicePixelRatio` of 2, the JavaScript `jquery.coremedia.responsiveimages.js` is now choosing the size of 800px : 600px.

Default JPEG Compression Quality

The default JPEG compression quality is 80% in *CoreMedia Blueprint*. This parameter is configured in `blueprint-handlers.xml` for the `transformedBlobHandler`. For further information consult the "CAE Application Developer Manual", chapter "Image Transformation API".

5.4.15 URLs

Link generation and request handling is based on the concepts of the CAE web application. For further information consult the "CAE Application Developer Manual". *CoreMedia Blueprint* offers a simple mechanism for link building and parsing that is based on regular expressions. The out of the box configuration has been made with "SEO Search Engine Optimization" in mind:

- URLs show to which site section the currently displayed page belongs
- URLs for asset detailed pages – opposed to section overview pages – contain the title of the asset

See [Section 7.2, "Link Format" \[379\]](#) for link schemes and controllers of *CoreMedia Blueprint* as well as existing post processors.

5.4.16 Vanity URLs

Requirements

Editors should be able to define special URLs to special content objects which are easy to remember.

Solution

Vanity URLs are special human readable URLs which do not contain any technical identifiers like document IDs. *CoreMedia Blueprint* provides a means to assign vanity URLs to content objects.

Vanity URLs are configured in channel settings. Typically, there is one Vanity URL settings document for the root channel of a given site. This is the setup chosen for *CoreMedia Blueprint* demo content. To find the Vanity URL settings document, open the root channel of a site and switch to the **Settings** tab. You will find the Vanity URL settings document link inside the **Linked Settings** section.

Vanity URLs are defined as a relative URI path. The path might consist of several segments, but if you would like to keep your Vanity URLs simple, just use only one path segment. The URI path is then prepended with a path segment consisting of the site name. For example, for the site `corporate`, a URI path of `my/special/article` would yield the Vanity URL `/corporate/my/special/article`.

To add a Vanity URL for a document, follow these steps:

1. Select the **StructListProperty** `vanityUrlDefinition` and create a new child Element Struct by clicking the **[Add item to List Property]** symbol in the toolbar.
2. Create a new **LinkProperty** and name it "target".
3. Set the content type field to the type of your target document.
4. Click on the value field, this will open the library window. Drag your target document from the library window into the value field.
5. Create a **StringProperty**, name it "id" and type your vanity URI path inside the value field.

Once the settings document is published, the new Vanity URL is reachable on the live site, and it is used for all generated links referring to the target document.

NOTE

While it is possible to define multiple Vanity URLs for a single target document it might cause confusion when looking on the links of the website. By default, the first "id" in the settings document that refers to the target document will be used for link creation.



NOTE

Defining multiple target documents for a single Vanity URL is not prevented by the Studio but it is usually not desired. A link will be generated for every target but the resulting URL will only point to the document referenced by the first occurrence of the "id" in the settings.



CAUTION

A Vanity URL can overlap with other dynamic URLs on your website. A Vanity URL will always take precedence. Consequently, the document behind the other dynamic URL will not be reachable on the website anymore.



5.4.17 Content Visibility

Requirements

Content should become available online only within a specific time frame. For example, editors need to ensure that a press release only becomes public at a certain day and time or an article should expire after a specific day. In addition, editors want to preview their preproduced content in the context of the website as if it was already available.

Solution

CoreMedia Blueprint supports restricting the visibility of content items by setting the optional `validFrom` and `validTo` date properties of content of type `CMLinkable`.

validFrom	
UI Name	Valid From
Description	Content where the "valid from" date has not been reached yet is not displayed on the site yet.
validTo	
UI Name	Valid To

Description	Content where the "valid to" date has passed is not displayed on the site anymore. By not specifying either of validTo or validFrom, an open interval can be specified to define just a start or end date.
-------------	--

Table 5.15. Properties for Visibility Restriction

Content is filtered in the CAE during the following two stages of request processing:

- The controller is resolving content from a requested URL. See `ContentValidityInterceptor`.
- In the content bean layer whenever references to other content beans that implement `ValidityPeriod` are returned.

In the CAE visibility checking is implemented as part of an extensible content validator concept. The generic `ValidationService` is configured with a `ValidityPeriodValidator` to filter content when it is requested.

To allow editors to preview content for a certain preview date and time a `PreviewDateSelector` component has been added to *Studio*, which sets the request parameter `previewDate`. This parameter is respected by the `ValidityPeriodValidator`.

5.4.18 Content Type Sitemap

Configuration

The content type Sitemap has three fields you can configure:

12

English (United States)

Sitemap

Content

Localization

System

▼ Sitemap

Sitemap Title

Sitemap

Root Page

✕ | ✎ | ✂ | 📁 | 📄

📄

 Chef Corp. USA Home Page

Sitemap Depth

Enter the depth of the sitemap here.

▼ Teaser Text

Sitemap

Figure 5.16. Content Type Sitemap

Enter a Sitemap Title which will be rendered as the headline of the Sitemap section in the site. The Root Page field defines the root node from where the content for the Sitemap will be rendered. Additionally the Sitemap can be rendered to a specific depth which can be set here. This depth is three by default.

5.4.19 Robots File

Requirements

Technical editors should be able to adjust site behavior regarding robots (also known as crawlers or spiders) from search engines like Google. For example:

- Enable/disable crawling of certain pages including their sub pages.
- Enable/disable crawling of certain single documents.

- Specify certain bots to crawl different sections of the site.

To support this functionality most robots follow the rules of `robots.txt` files like explained here: <http://www.robotstxt.org/>.

For example, the site "Corporate" is accessible as `http://corporate.blueprint.coremedia.com`. For all content of this site the robots will look for a file called `robots.txt` by performing an HTTP GET request to `http://corporate.blueprint.coremedia.com/robots.txt`.

A sample `robots.txt` file may look like this:

```
User-agent: Googlebot,Bingbot
Disallow: /folder1/
Allow: /folder1/myfile.html
```

Example 5.2. A `robots.txt` file

Solution

Blueprint's `cae-base-lib` module provides a `RobotsHandler` which is responsible for generating a `robots.txt` file. A `RobotsHandler` instance is configured in `blueprint-handlers.xml`. It handles URLs like `http://corporate.blueprint7.coremedia.com:49080/blueprint/servlet/service/robots/corporate`

This is a typical preview URL. In order to have the correct external URL for the robots one needs to use Apache rewrite URLs that forwards incoming GET requests for `http://corporate.blueprint7.coremedia.com/robots.txt` to `http://corporate.blueprint7.coremedia.com:49080/blueprint/servlet/service/robots/corporate`

The `RobotsHandler` will be responsible for requests like this due to the path element `/robots`. The last path element of this URL (in this example `/corporate`) will be evaluated by `RobotsHandler` to determine the root page that has been requested. In this example "corporate" is the URL segment of the Corporate Root Page. Thus, `RobotsHandler` will use Corporate root page's settings to check for `Robots.txt` configuration.

To add configuration for a `Robots.txt` file the corresponding root page (here: "Corporate") needs a setting called `Robots.txt`




Figure 5.17. Robots.txt settings

Example configuration for a Robots.txt file

The settings document itself is organized as a `StructList` property like in this example:




Figure 5.18. Channel settings with configuration for `Robots.txt` as a linked setting on a root page

For any specified user agent the following properties are supported:

- `User-agent`: Specifies the user agent(s) that are valid for this node.
- `Disallow`: A link list of items to be disallowed for robots. This list specifies a black list for navigation elements or content: Elements that should not be crawled. Navigation elements will be interpreted by "do not crawl elements below this navigation path". This leads to two entries in the resulting `robots.txt` file: one for the link to the navigation element and one for the same link with a trailing '/'. The latter informs the crawler to treat this link as path (thus the crawler will not work on any elements below this path). Single content elements will be interpreted as "do not crawl this document"
- `Allow`: A link list of items to be explicitly allowed for robots. This list specifies navigation elements or content that should be crawled. It is interpreted as a white list. Usually one would only use a black list. However, if you intend to hide a certain navigation path for robots but you want one single document below this navigation to be crawled you would add the navigation path to the disallow list and the single document to the allow list.
- `custom-entries`: This is a String List to specify custom entries in the `Robots.txt`. All elements here will be added as a new line in the `Robots.txt` for this node.

The example settings document will result in the following `robots.txt` file:


```
User-agent: *
Disallow: /corporate/corporate-information/
Allow: /corporate/corporate-information/contact-us

User-agent: Googlebot
Disallow: /corporate/embedding-test
```

Example 5.3. robots.txt file generated by the example settings

5.4.20 Sitemap

Requirements

If you run a public website, you want to get listed by search engines and therefore give web crawlers hints about the pages they should crawl. <http://www.sitemaps.org/> declares an XML format for such sitemaps which is supported by many search engines, especially from Google and Microsoft.

"Sitemap" in terms of <http://www.sitemaps.org/> is not to be mistaken with a human readable sitemap which visualizes the structure of a website [see [Section 5.4.18, "Content Type Sitemap" \[204\]](#)]. It is rather a complete index of all pages of a site. A simple sitemap file looks like this:

```
<?xml version="1.0" encoding="UTF-8"?>
<urlset xmlns="http://www.sitemaps.org/schemas/sitemap/0.9"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://www.sitemaps.org/schemas/sitemap/0.9
http://www.sitemaps.org/schemas/sitemap/0.9/sitemap.xsd">
  <url>
    <loc>
      http://helios.coremedia.com/corporate/spicy-duck-694
    </loc>
  </url>
  <url>
    <loc>
      http://helios.coremedia.com/corporate/share-your-recipes-696
    </loc>
  </url>
  ...
</urlset>
```

Example 5.4. A sitemap file

The size of a sitemap is limited to 50,000 URLs. Larger sites must be split into several sitemap files and a sitemap index file which aggregates the sitemap files. A sitemap index file looks like this:

*Maximum number of
URLs*

```
<?xml version="1.0" encoding="UTF-8"?>
<sitemapindex xmlns="http://www.sitemaps.org/schemas/sitemap/0.9">
```

```
<sitemap>
  <loc>http://helios.coremedia.com/sitemap1.xml.gz</loc>
  <lastmod>2014-03-31T15:33:26+02:00</lastmod>
</sitemap>
...
</sitemapindex>
```

Example 5.5. A sitemap index file

Solution

A sitemap consists of multiple entities (the index and the sitemap files) and has dependencies on almost the whole repository. If a new content is created, which "coincidentally" occurs in the first sitemap file, the entries of all subsequent sitemap files are shifted.

In border cases even the number of sitemap files may change, which affects the sitemap index file. So you cannot generate single sitemap entities on crawler demand, asynchronously and independent of each other, but you must generate a complete sitemap which represents a snapshot of the repository. Moreover, the exhaustive dependencies make sitemaps practically uncacheable, and the generation is expensive. For these reasons *Blueprint* does not render sitemaps on demand but pregenerates them periodically. So you must distinguish between sitemap generation and sitemap service. Both are handled by the live web application, though.

Sitemap Generation

CoreMedia Blueprint features separated sitemaps for each site. Sitemap generation depends on some site specific configuration, like the document types to include or paths to exclude, amongst others. This configuration is specified by `SitemapSetup` Spring beans.

The `lc` and the `corporate` extension each provide a `SitemapSetup` bean suitable for their particular sites. Projects can declare their own sitemap setups. The setups are collected in the `sitemapConfigurations` Spring map.

```
<bean id="livecontextSitemapConfiguration" class="c.c.b.c.s.SitemapSetup">
  <property name="protocol" value="http"/>
  ...
</bean>

<customize:append id="appendLSC" bean="sitemapConfigurations">
  <map>
    <entry key="livecontext" value-ref="livecontextSitemapConfiguration"/>
  </map>
</customize:append>
```

If you want to generate a sitemap for a site, you have to specify the setting `sitemapOrgConfiguration` at the root channel. It is a `String` setting, and the value must be a key of the `sitemapConfigurations` map.




Figure 5.19. Selection of a sitemap setup

By default, the Corporate sites are sitemap-enabled. The Aurora sites are not sitemap-enabled, since the Aurora sites serve only as backend for *HCL Commerce* applications, there is no need for sitemaps.

Sitemaps are generated periodically in the Delivery CAE by a `SitemapGenerationJob`. You can specify the initial start time and the period as application properties `cae.sitemap.starttime` and `cae.sitemap.period-minutes`, respectively. For details about the values see the Javadoc of the setters in `SitemapGenerationJob`. The *Blueprint* is preconfigured to run the sitemap generation nightly at 01:30. You can also trigger sitemap generation for a particular site manually by the URL

```
http://live-cae:49080/blueprint/servlet/internal/corporate-de-de/sitemap-org
```

where `corporate-de-de` stands for the segment of the site's root channel. Note that it is an internal URL which can only be invoked directly on the CAE's servlet container. Sitemap generation is an expensive administrative task, which is not to be exposed to end users. CoreMedia's default Apache rewrite rules block `internal` URLs, see files in the deployment folder `global/deployment/chef/blueprint/cookbooks/blueprint-proxy/templates/default/rewrite`.

The sitemaps are written into the file system under a directory which is specified by the `cae.sitemap.target-root` application property. That means, the CAE needs write permissions for this directory.

Sitemap Service

The generated sitemaps are available by the URL pattern

```
/service-sitemap-siteID-sitemap_index.xml
```

This pattern consists only of a single segment without a path, so there are no path restrictions for the URLs included in the sitemap.

In order to inform search crawlers, the sitemap URLs are included in the `robots.txt` files. Since there is only one robots file per web presence, you will see multiple sitemap entries for the localized sites:

```
User-agent: *  
Disallow: /  
  
Sitemap: http://corporate.acme.com/service-sitemap-ab...ee-sitemap_index.xml  
Sitemap: http://corporate.acme.com/service-sitemap-1c...7a-sitemap_index.xml
```

5.4.21 Website Search

There are two search types in *HCL Commerce* integration scenarios: *HCL Commerce Search* and *CoreMedia CMS Search*. You can view the results of both searches by switching between tabs "shop" or "content".

NOTE

For *HCL Commerce Search* the CMS content must be crawled by the HCL Solr Search engine. Please refer to the HCL documentation. A configuration file for each example site is part of the *HCL Commerce Workspace* archive (for example, `WCDE-ZIP/components/foundation/subcomponents/search/solr/home/droidConfig-cm-aurora-en-US.xml`).



The CoreMedia CMS Search is introduced further in this section.

Requirements

In order to make content more accessible for their audience virtually all websites have full-text search capabilities. To improve the search experience some websites also offer features such as search term autocompletion, suggestions in case of misspelled search terms, more advanced filtering options or even metadata based drilldown navigation in search results.

Solution

CoreMedia CMS has built-in integration with the Apache Solr search engine. *Blueprint* comes with a small abstraction layer that offers unified search access to Solr for all CAE based code. It provides the following features, all based on standard Solr functionality:

- Full text search: Search for content across all fields
- Field based filters: Filter results by metadata such as the content type, the site section it belongs to, etc.
- Facets: Display facets, that is the number of results in a field for certain values
- Spellcheck suggestion: "Did you mean" suggestions for misspelled terms

- Search term highlighting: All words are highlighted in your text
- Validity range filtering: Automatically filter for only visible results (see section [Section 5.4.17, “Content Visibility” \[203\]](#))
- Filter non-searchable: Automatically filter content that should not be part of search results.
- Caching: Search results can be optionally cached for a certain amount of time.

The search integration can be found in the modules `com.coremedia.blue`
`print.cae.search` and `com.coremedia.blue`
`print.cae.search.solr`.

`com.coremedia.livecontext.fragment.CMSearchFragmentHandler` is used in *HCL Commerce* integration scenarios to process *fragment search requests*. The handler requires no specific configuration in content settings and uses the general CAE Search configuration as explained in [Section 5.4.21, “Website Search” \[212\]](#).

Configuring search in content settings

Some aspects of website search are configurable in a site-specific Settings document. The site's root channel links to the Settings document `Search Configuration` with the settings used for that site.

Settings

✕ + String | ▾ ⋮ ⬆ ⬇ ✂ 📄 📁 📂 ✎

Property	Value	Type
▼ ...		Struct
searchChannel	📁 SearchResultPage	Link to 📁 Folder or conte
searchAction	📄 SearchAction	Link to 📄 Action
search.result.hitsPerPage	50	Integer
▼ search.doctypeselect		String List
#1	CMArticle	String
#2	CMAudio	String
#3	CMCategory	String
#4	CMChannel	String
#5	CMDownload	String
#6	CMGallery	String
#7	CMProduct	String
#8	CMSitemap	String
#9	CMVideo	String
caefederSiteConfiguration	corporate	String

Figure 5.20. Search Configuration Settings document

It contains the following settings:

Settings Property	Description
<code>searchChannel</code>	The channel used to render the search result page.
<code>searchAction</code>	Content of type <code>CMAAction</code> with ID "search".
<code>searchResultHitsPerPage</code>	The number of hits shown on the search result page. If not set, default is 10.
<code>searchResultPagination</code>	Boolean parameter to enable pagination instead of "load more" functionality. Default is false.
<code>searchDisableSpellingSuggestions</code>	Boolean parameter to disable the spelling suggestion offered by Solr. Default is false.
<code>searchDoctypeSelect</code>	The content types that appear in the search result. Subtypes must be listed explicitly.
<code>searchChannelSelect</code>	The Categories that appear in the filter panel based on configured channels.
<code>searchFacets</code>	A substruct that maps symbolic search facet names to Solr index field names. This enables search faceting on the website with the possibility to filter search results based on values indexed in the configured fields. You can choose arbitrary names for facets, but note that these names will appear as request parameters in search URLs.
<code>searchFacetLimit</code>	An integer parameter that controls how many values will be displayed for each search facet, if <code>searchFacets</code> is configured. Default is 100.
<code>caefeederSiteConfiguration</code>	Contains the value <code>corporate</code> to select the <i>CAE Feeder Brand Blueprint</i> configuration for indexing content of the site. This enables page grid indexing as described in the next section.

Table 5.16. Brand website search settings

Configuring page grid indexing

The *Brand Blueprint CAE Feeder* feeds CMChannel documents to the search engine so that pages can be found on the website. To this end, the CAE Feeder configuration specifies which parts of a page grid need to be indexed. This includes the configuration of relevant page grid sections, content types of linked contents and their properties.

NOTE

Read section [Section 5.4.4, "Page Assembly" \[167\]](#) for an introduction to page grids.



The *Brand Blueprint CAE Feeder* is configured in the Spring bean definition file `component-corporate-caefeeder.xml` and its accompanied properties file `corporate-caefeeder.properties` in directory `src/main/resources/META-INF/coremedia` of the Blueprint module `apps/caefeeder/blueprint/modules/extensions/corporate/corporate-caefeeder-component`. The Spring XML file imports the content bean definitions and defines the following [FeedablePopulators](#) to index the page grid:

The `PageGridFeedablePopulator` takes properties from content linked in the page grid and adds them to the `textbody` index field when feeding a `CMChannel`. It is configured to feed the teaser properties of linked documents except for articles linked with view type "Detail" in which case the full article text is indexed with the channel. The `PageGridInlineContentFeedablePopulator` ensures that articles that are linked with view type "Detail" are not returned by the website search in addition to their page. To this end, it sets the index field `notsearchable` to `true` for such articles.

If a page grid placement contains a `CMCollection` document, then the contents linked in its `items` property are included as well - just as if they were linked directly in the page grid.

The mentioned FeedablePopulators are only used for documents if their site has a settings document that defines the setting `caefeederSiteConfiguration` with value `corporate`. This is the case for *Brand Blueprint* sites. The Spring application context file `component-corporate-caefeeder.xml` configures the site-specific activation of page grid feeding by adding the FeedablePopulators to the bean `siteSpecificFeedablePopulatorMap` for the value `corporate`.

The *Brand Blueprint* comes with a default configuration for indexing page grids of `CMChannel` documents. If needed, you can change the configuration in `component-corporate-caefeeder.xml` and `corporate-caefeeder.properties`. The following table describes the used Spring properties. All properties start

with the prefix `corporate.search.pageGrid` which is abbreviated with `[c.s.p]` below.

Property	Description
<code>[c.s.p].contentType</code>	The type of the contents with indexed page grid. Default: <code>CMChannel</code>
<code>[c.s.p].name</code>	The name of the struct property that contains the page grid. Default: <code>placement</code>
<code>[c.s.p].excludedSections</code>	Comma-separated list of ignored page grid sections. Default: <code>header, footer, sidebar</code>
<code>[c.s.p].itemContentTypes</code>	Comma-separated list of content types of considered page grid items. Contents of other types that are linked in the page grid are ignored and not indexed with the page grid. Default: <code>CMChannel, CMArticle, CMTeaser, CMCollection, CMVideo, CMDownload, CMExternalLink, CMProduct</code>
<code>[c.s.p].itemTextProperties</code>	The content properties of page grid items with a view type other than "Detail" that are indexed in the index field <code>textbody</code> of the page. This property takes a space separated string of document type properties. For each configured document type, the name of the type followed by an equal sign and a comma-separated list of property names is given. The configuration for the most specific document type of an item decides which item properties are used. The property lists are not merged with configurations for super types. This makes it possible to ignore properties in subtypes. Default: <code>CMTeasable=teaserTitle,teaserText CMProduct=productName,shortDescription</code>
<code>[c.s.p].itemValidFromProperty</code> <code>[c.s.p].itemValidToProperty</code>	The name of the date properties for visibility as described in Section 5.4.17, "Content Visibility" [203] . Content that is not currently visible is not indexed with the page. The <i>CAE Feeder</i> automatically reindexes after visibility has changed. Default: <code>validFrom / validTo</code>

Property	Description
[c.s.p].inlineContentTypes	Comma-separated list of content types used in the page grid with view type "Detail" for which the text properties are indexed with the page grid instead of the teaser properties. Default: <code>CMArticle</code>
[c.s.p].inlineContentViewType	The technical name of the "Detail" view type. Default: <code>full-details</code>
[c.s.p].inlineContentTextProperties	The content properties of page grid items with view type "Detail" that are indexed in the index field <code>textbody</code> of the page. This property takes a space separated string of document type properties. For each configured document type, the name of the type followed by an equal sign and a comma-separated list of property names is given. The configuration for the most specific document type of an item decides which item properties are used. The property lists are not merged with configurations for super types. This makes it possible to ignore properties in subtypes. Default: <code>CMArticle=title,detailText</code>
[c.s.p].collectionContentType	The content type of collection documents used in the page grid. Default: <code>CMCollection</code>
[c.s.p].collectionItemsProperty	The link property of collection documents to get the items of a collection. Default: <code>items</code>
[c.s.p].collectionViewTypeProperty	The link property of collection documents to get the view type for the items of a collection. Default: <code>viewtype</code>
[c.s.p].configId	An identifier that represents the configuration options. Default: <code>corporate</code>

Table 5.17. Page Grid Indexing Spring Properties

NOTE

You must reindex from scratch with an empty *CAE Feeder* database to apply the changes of the above configuration properties to all indexed documents. If it is okay to just apply the changes to newly indexed documents and if you don't reindex with an empty *CAE Feeder* database, then you need to change the value of the `[c.s.p].configId` property to some other string constant, if you've changed one of the following properties (all starting with `[c.s.p].`): `name`, `excludedSections`, `itemContentTypes`, `itemValidFromProperty`, `itemValidToProperty`.



5.4.22 Topic Pages

Requirements

Topic pages are a popular feature on most websites. Usually, topic pages are assembled from existing content which has already been published in another context before. Thus, topic pages should not cause any extra effort for the editors, but be available completely automatic.

Solution

In *CoreMedia Blueprint* topic pages are based on tags. Each tag content can be rendered as a topic page, showing the assets which are tagged with this particular tag. That is, add for example the Professionals tag content to the *Subjects* field of the Metadata tab and you will get a link to the topic page. Clicking this link opens the topic page for the topic "Professionals" in the default topic context of the site. See [section "A Topic Page is a Page" \[219\]](#) for details about context.




Figure 5.21. Generated topic page for topic "Professionals"

Configuration

The topic pages feature needs some configuration which is collected in a settings content. In the *Blueprint* example content this setting is located at `<SiteName>/Options/Settings/TopicPages` content of each site folder. This path must be configured as `topicpageConfigurationPath` for the `topicpageContextFinder` Spring bean in `blueprint-contextstrategy.xml`. Topic page configuration is site specific. Relative paths will be concatenated with the root folder of the active site.

A Topic Page is a Page

Topic pages are based on the well known page concept. Just like any other asset, a tag content needs a context in which it is rendered as a topic page. Ordinary assets like articles have their explicit navigation contexts. For tag content there is a default context for each site. This default context is just another Page content. It must be configured as a `TopicPagePage` link property in the `TopicPages` settings content. This deviating context determination has two reasons:

- It spares your editors the tedious task of assigning a context to each tag
- It allows you to create site specific topic pages for `global.com.coremedia.blueprint.studio.rest.taxonomies` tags

CAUTION

If you create your own default topic page set the Hidden flags (on the *Metadata* tab) of the page to true, and add the page as child to the site root. So it inherits all the JavaScript and CSS which is responsible for the design of the site.



Managed Topic Pages

The default topic page context allows you to generate a topic page for any tag content. This is convenient, but for some very popular topics you might want to provide a thoroughly styled and edited topic page, for example with an introductory text and image. *Studio* comes with a UI that executes the following steps for your custom topic page:

1. Creating a new page document.
2. Adding the page as a child to the default context page in order to inherit its features and preserve the style of the site.
3. Setting the new page as context in the tag document which represents the topic.

When the UI has created and linked the topic page, you only need to care for the layout and the accompanying content of the placements other than main:

1. Select the desired layout for your custom topic page.
2. The main placement is reserved for the content list. Fill the other placements with content of your choice (an introductory article or related topics, for instance).





Figure 5.22. The topic pages administration in Studio

The *Studio* plugin provides a separate preview for the generated topic page too. This preview is more reliable than the one that is rendered for the page, since the preview is parameterized with the selected tag.

For global topics each site can have a specific custom topic page. All custom pages are linked in the topic's `contexts`, and at runtime the CAE determines the custom topic page which matches the context of the request or falls back to the default topic page of the particular site.

Configure target folder of new topic pages

When a custom topic page is created by using the Topic Page *Studio* extension, a new page content is created for the active site in folder `Content/Topic Pages`. The path is configurable in the site specific settings content `TopicPages`, located in the settings folder of the site. The property name for the corresponding string property is `folder`.



Property	Value	Type
...		Struct
TopicPagePage	Topicpage	Link to Page
administrationGroups		String List
#1	manager-c-en-US	String
#2	global-site-manager-c	String
#3	developer	String
folder	Content/Topic Pages	String

Figure 5.23. Settings document for topic pages

Configure access to the topic page administration

The topic page plugin uses the `configurations-rest-extension` module to load configuration values from a settings content. The configuration document `TopicPages` contains the name of the user groups that are allowed to administrate topic pages. It is located in the folder `Options/Settings/` (Relative paths will be concatenated with the root folder of the active site.). An additional configuration file with the same name can be put in the folder `/Settings/Options/Settings/TopicPages`. The entries of the files will be added to the existing configuration. The property name for the corresponding string list property is `administrationGroups`.

URL format

Topic pages are search relevant, so they need SEO friendly URLs. The pattern is the same as for standard pages, and the URLs for topic pages are generated and resolved by the `PageHandler`. Only the sequence of segments is different from ordinary page URLs. It does not manifest a hierarchy but consists of exactly the segments `/<site>/<topicpage>/<topic>/<id>`. `Topicpage` is the segment of the topic page context, `topic` is the value property of the tag content, and `id` is the id of the tag content.

Disable Managed Topic Pages

The Managed Topic Pages are implemented as *CoreMedia Extension* called `custom-topic-pages`. Therefore, you can disable it like any other extension (see [Section 4.1.5, "Project Extensions" \[67\]](#) for details).

```
<dependency>
  <groupId>${project.groupId}</groupId>
```

```
<artifactId>custom-topic-pages-bom</artifactId>
<version>${project.version}</version>
<type>pom</type>
<scope>import</scope>
</dependency>
```

Search for Topic Pages

Topic pages can also be found by *CoreMedia Blueprint*'s search. To get topic pages in the search result list, the topic page name must match the entered search query. Topics which are not used in the current site do not appear in the search results. Topic pages are displayed on top of the search results list with a customizable teaser image as shown in [Figure 5.24, "A Search Result for a Topic Page" \[223\]](#). The capability to search for topic pages can be controlled by settings located in the search action of the particular site.




Figure 5.24. A Search Result for a Topic Page

Feeding Topic Pages

In the *Website Blueprint* topics are represented by *CMTaxonomy* and *CMLocTaxonomy* content. The *Blueprint CAE Feeder* is configured accordingly so they get indexed by the search engine.

Enable and Disable Topic Search

The *CoreMedia Blueprint* searches for topic pages by default. This feature can be enabled and disabled for each site independently. The folder *Options/Actions* contains an action "Search" which has a *StringListProperty* setting *search.topicsdoctypeselect*. The entries define all content type names which should be considered by a topic page search. In case of the *Website Blueprint* the content types *CMTaxonomy* and *CMLocTaxonomy* are required here. To avoid searching for topic pages, this setting has to be removed.

If you change the configuration of `search.topicsdoctypeselect` to a different non-empty list of document type names, then you should also add the setting `search.topicsindexfields` with a string list of search engine index fields that reference assigned tags of a content. These index fields are used to determine the tags that are used in the current site. If not set or empty, the setting defaults to the index fields `subjecttaxonomy` and `locationtaxonomy`, which reference `CMTaxonomy` and `CMLocTaxonomy` contents, respectively. For example, if you set `search.topicsdoctypeselect` to `CMTaxonomy` only, then should also set `search.topicsindexfields` to `subjecttaxonomy` only.

5.4.23 Search Landing Pages

NOTE

Feature is only supported in *eCommerce Blueprint*



Requirements

Using *CoreMedia Content Cloud* the user should have the possibility to define custom page layouts for search terms.

Solution

Search Landing Pages are used to apply a custom page layout for product searches that match specific search terms. This feature is used when CAE fragments should be included to search result pages of an eCommerce system. To provide a new search landing page, do the following:

1. Create a new folder with the name `Search Landing Pages` in one of your sites folders. The folder must be part of a site, global search landing pages are not provided.
2. Create a new page document and add the matching keywords in the input field "HTML Keywords" [CMChannel property "keywords"].
3. Add the newly created page document as navigation child to the root document. Ensure that the search landing page has checked the "Hidden in Sitemap" and "Hidden in Navigation" checkboxes.

When the search landing page is included to the commerce storefront, only the main placement of the page's page grid will be included as fragment.

5.4.24 Theme Importer

With the theme importer you can import themes into the content repository. It is the command line equivalent of uploading themes in Studio as described in the Frontend Developer Manual.

```
usage: cm import-themes -u <user> [other options] [-f <folder>] [-c] [-dm]
      <theme.zip> ...

available options:
-c,--clean           Delete existing theme before import in order
                    to get rid of obsolete code resources.
-d,--domain <domain name> domain for login (default=<builtin>)
-dm,--development-mode Development mode. Creates a user (frontend
                    developer) specific copy of the theme.
-f,--folder <arg>    Folder within CoreMedia where themes are
                    stored. Default is /Themes
-p,--password <password> password for login
-u,--user <user name> user for login (required)
-url <ior url>       url to connect to
```

Example 5.6. Usage of import-themes

The options have the following meaning:

Parameter	Description
-c	Delete existing theme before import in order to get rid of obsolete code resources. This option is only intended for the development workflow. It does not delete published themes.
-dm	Development mode. Creates a user [frontend developer] specific copy of the theme.
-f	Folder within CoreMedia where themes are stored. Default is /Themes

Table 5.18. Options of the import-themes tool

5.4.25 Tag Management

A Tag Management System is a tool to deploy analytics code fragments and others on your website dynamically during runtime. With the user interface of CoreMedia Studio it

is easy to set up tag management systems depending on the configuration defined in the repository.

Configuration

Define a local or linked setting called "TagManagement" with type `Struct List` and add it to the root page of the site. Each struct in this list represents a Tag Management integration which defines its own `Markup` properties for "head", "bodyStart", and "bodyEnd".

The *chefcorp-theme* includes the `brick-tag-management` and the support for tag management systems out of the box.

If the *Google Tag Manager* is your preferred solution, refer to Google's documentation at [Google Tag Manager Overview](#) to retrieve the code snippets for your integration.




Figure 5.25. Tag Management Configuration

5.5 Localized Content Management

One of the primary challenges when engaging in a global market is to reach all customers in different countries.

The first most obvious task is to provide your website contents in different languages. But in addition you may also want to customize your advertised products to local holidays or meet the different legal requirements in different countries.

CoreMedia Content Cloud's Multi-Site concept assists you in meeting these requirements.

NOTE

Also have a look into the Multi-Site Manual. The manual describes different options to design your site hierarchy and gives some guidance to avoid common pitfalls when working with multi-site content.



5.5.1 Concept

There are many possible approaches to fulfill the requirements for providing multiple sites in different countries. *CoreMedia Content Cloud* offers a solution which you can customize to your needs and to the workflows you are used to.

The following chapter will present the basic ideas and concepts of *CoreMedia Content Cloud's* Multi-Site to you.

Terms

The multi-site concept and documentation is based on the following terms. You may skip this section for now and return to it later when these terms are referenced.

Locale

The term locale refers to the concept of translation and localization. Thus, it is in general a combination of a country and a language. So if the country *Switzerland* requires contents to be available in English, Italian, German and Romansh, four locales have to be defined.

locale = country + language

The locale is represented as IETF BCP 47 language tag (*Tags for Identifying Languages*).

IETF BCP 47

Site	<p>A site is a cohesive collection of web pages in a single locale, sometimes referred to as localized site. Technically, a site consists of:</p> <ul style="list-style-type: none">• The site folder• The site indicator,• The site's home page and• Other contents of the site.
Master Site	<p>A master site is a site other localized sites are derived from. A localized site might itself take the role of a master site for other derived sites. This reflects the need that your localized Canadian site (which is in English) needs another localized variant in French.</p>
Site Folder	<p>All contents of a site are bundled in one dedicated folder. A typical example of a site folder is:</p> <pre>/Sites/MySite/Canada/French</pre>
Site Indicator	<p>A site indicator is the central configuration object for a site. It is an instance of the content type <code>CM Site</code>. It explicitly configures:</p> <ul style="list-style-type: none">• The site's home page• The site identifier• The site name• The site's locale• The master site• The site manager groups. <p>It also implicitly defines the root of the site folder.</p>
Home Page	<p>The site's home page is the main entry point for all visitors of a site. Technically it is also the main entry point to calculate the default layout and the contents of a site.</p>
Site Identifier	<p>The site identifier needs to be unique among all sites. It can be used to reference a site reliably also outside the CMS for example in configuration files.</p>
Site Name	<p>The site name is the name of a master site and all derived sites. A derived site inherits the site name from its master site and must not change it.</p>
Site Manager Group	<p>Members of a site manager group are typically responsible for one localized site. The recommendation is to have one dedicated group for each site with appropriate permissions applied for the site folder.</p>

Responsible means that they take care of the contents of that site and that they accept translation tasks for that site. If a site manager is allowed to also trigger translation tasks from the master site to their site, they need to be added to the translation manager role.

While the Site Manager Groups are typically local to their site, thus represent the horizontal layer, *CoreMedia Content Cloud* also introduces a vertical layer referred to as *global site manager*. As a consequence the members of the horizontal layer are sometimes referred to as *local site managers*.

Global site managers have an overview over all sites while local site managers focus on their sites with additionally required access to the particular master site for translation processes.

Global and Local Site Manager

Translation Manager Role

Editors in the translation manager role are in charge of triggering translation workflows either from or to a site.

Sites Structure

CoreMedia Content Cloud assumes that your localized sites are all derived from one master site. The site hierarchy might be nested, thus a site derived from the master site again might have derivatives. You can trigger the localization process from your master site, directly derived sites will adapt and forward changes to their derived sites.

The examples below refer to the default configuration which comes with *CoreMedia Blueprint*. To adapt the structure to your needs you have to configure the `SiteModel` - see also [Section "Site Model and Sites Service" \[237\]](#).

Multi-Site Folder Structure

All elements belonging to a site structure are placed in one dedicated folder. In this folder you will find the master site as well as all derived localized sites.

Another set of master and derived sites could be created in parallel to that site following the same concept.

```
/Sites/  
  MySite/  
    United States/
```

```
English/ master
Spanish/ derived from U.S. English
Canada/
  English/ derived from U.S. English
  French/ derived from Canadian English
MyOtherSite/ another master site structure
```

Example 5.7. Multi-Site Folder Structure Example

The folder structure of the master site and its target sites should be kept equal to avoid the automatic recreation of removed or renamed folders during the translation workflow.

In addition to this common aspects for all sites might be placed outside this folder structure. For details see [Section 5.4.1, "Folder and User Rights Concept" \[161\]](#).

Site Folder Structure

The central entry point into the site folder is the site indicator. It points implicitly to the site's root folder (as it needs to be located at the same folder hierarchy depth among all sites in the system) and points explicitly to the site's home page.

Assuming that your site indicator is always placed in some folder like `Navigation` your site folder structure may look like this:

```
MySite/
  United States/
    English/
      Navigation/
        MySite [Site] site indicator
        MySite site's home page
        ...
```

Example 5.8. Site Folder Structure Example

While the above describes the mandatory folder structure for a site, there are additional structures which adhere to the proposed separation of concerns in [Section 5.4.1, "Folder and User Rights Concept" \[161\]](#), thus within a site you can have several user roles taking care of different aspects of the site as there are:

- **Editorial content:** For example, articles, images, collections etc. This is the real content of a site that is rendered to the web page. They are located in folders `Editorial`, `Pictures` and `Videos`.
- **Navigation content:** Channels that span the navigation tree and provide context information, as well as their page grids (see also [Section 5.4.2, "Navigation and Contexts" \[163\]](#)). These contents are located in a folder named `Navigation`.

- **Technical content:** Site specific, technical documents, like actions, settings, view types, etc. They can be found in folder named `Options`.

Site Interdependence

Having a site derived from its master you will have two layers of interdependence:

1. The site indicator points to its master site indicator.
2. Each derived document points to its master annotated by the version of the master when the derived document retrieved its last update from the master. This information is used in the update process when a new master version requires its derived contents to be translated again.
3. A site indicator inherits the site name from its master. If a site indicator has no master it has to define the site name, which will be used for all derived sites.




Figure 5.26. Multi-Site Interdependence

The `master` property is configured as weak link by default. Thus, you might publish derived sites before (or without) publishing the master site.

Modifying the Site Structure

Whenever possible, the structure of a site should not be changed after it has been set up initially. In particular, you should not:

- Change the id of a site. If you do so, you must at least reindex its entire master site, if any. See Section 5.2, "Configuring the CAE Feeder" in *Search Manual* for details on the reindexing procedure. However, the site id might also be stored in other places that a simple reindexing will not update.

- Move a content to a different site. If you do so, you must at least update the master links of the affected contents to point into the master site of the new site.
- Change the locale of a site. If you do so, you must at least update the locale stored in each individual content of the site.
- Change the master site of a site. If you do so, you must at least update the master links of all contents in the site.

CAUTION

After significant changes of the site structure, you should run the `cm validate-multisite` tool to detect inconsistencies in the content. See Section "Validate Multi-Site" in *Content Server Manual* for details.



5.5.2 Administration

Using *CoreMedia Content Cloud's* Multi-Site concept requires some administrative efforts which are described in this section.

Locales Administration

Each site is bound to a specific locale [see [Locale \[227\]](#)]. In order to ensure a consistent usage of locale strings across multiple sites that might be managed in a single content repository, the entire list of available locales is maintained in a central document of type `CMSettings`.

The document `/Settings/Options/Settings/LocaleSettings` contains in the property `Settings` a String List property `availableLocales` which contains locale strings. [Example 5.9, "XML of locale Struct" \[232\]](#) shows the XML structure of the Struct:

LocaleSettings document for locale configuration

```
<settings>
  <Struct xmlns="http://www.coremedia.com/2008/struct"
    xmlns:xlink="http://www.w3.org/1999/xlink">
    <StringListProperty Name="availableLocales">
      <String>de</String>
    </StringListProperty>
  </Struct>
</settings>
```

Example 5.9. XML of locale Struct

Please make sure, that the path to the `LocaleSettings` is configured in the Studio properties, as described in Section 7.19, "Available Locales" in *Studio Developer Manual*.

For providing a new locale, you can simply open the document `LocaleSettings` and add a new entry to the list of locales. See Section 4.6.4, "Editing Struct Properties" in *Studio User Manual* for details on how to edit a struct property and add items to string lists. [Figure 5.27, "Locales Administration in CoreMedia Studio" \[233\]](#) shows a Studio tab in which the `LocaleSettings` document is being edited.

Sometimes you might want to define locales for a supranational region such as Africa or Latin America. In this case you can add the language code followed by the UN M.49 area code as described in http://en.wikipedia.org/wiki/UN_M.49. For Spanish in Latin America and the Caribbean add, for example, "es-419".

Supranational regions




Figure 5.27. Locales Administration in CoreMedia Studio

Groups and Rights Administration

This chapter describes all groups and users, that have to be defined for localization. There are several explicit groups and one user, that can be configured in the `SiteModel` - see also [Section "Site Model and Sites Service" \[237\]](#). For an overview of predefined editorial users that come with *CoreMedia Blueprint* have a look at [Reference - Predefined Users \[385\]](#).

The translation manager role is defined once in the property `translationManagerRole` of the `SiteModel`. It is a required group for every user that needs to start a translation workflow and to derive a site.

translation manager role

In case, you do not want to allow every translation manager to also derive sites, it is advisable to create an additional global site manager group, that has the right, to make modifications in the global sites folder.

global site manager

Members of a site manager group take care of the contents of one or more sites. They may for example accept translation workflows if they manage the corresponding target site of a workflow. Or they may start a translation workflows from the master site. For the latter, they must also be member of the translation manager role group, which is described above.

site manager group

The site manager groups can be defined in the site indicator. The name of the corresponding property field is defined in the `siteManagerGroupProperty` of the `SiteModel`. If not specified, the group "administratoren" will be used by default. This is also the fallback if the defined group is unset or not available.

You may enter multiple groups separated by comma by default. The separator is configured in `groupPropertyDelimitingRegEx` of the `SiteModel`.

There are two ways to set the site manager group:

- While deriving a new site in the sites window, you can set the group.
- Directly in the site manager group property of the site indicator.

For technical reasons the actual changes during a translation workflow are performed as the translation workflow robot user as configured in the property `translationWorkflowRobotUser` of the `SiteModel`. The user needs read and write access on the sites taking part in a translation workflow. As this user is only technical, access to the editor service should be restricted, which can be done in the file `jaas.conf` in the module `content-management-server-blueprint-config`. (For details see Section "LoginModule Configuration in jaas.conf" in *Content Server Manual*).

translation workflow robot user

Overview of required users and groups for multi-site

Table 5.19, "Suggested Users and Groups for multi-site" [234] shows an example, how the configuration of user groups may look like in *CoreMedia Blueprint*.

Type	Name	Member of	Rights	Remark
group	global-site-manager	approver-role, publisher-role, translation-manager-role	<ul style="list-style-type: none">• /Home (folder: RSF, content: RMDS)• /Settings (folder and content: R)• /System (folder and content: R)• /Sites (folder: RAPSF, content: RMDAPS)	

Type	Name	Member of	Rights	Remark
group	local-site-manager	approver-role, publisher-role, translation-manager-role	<ul style="list-style-type: none"> • /Home (folder: RSF, content: RMDS) • /Settings (folder and content: R) • /System (folder: RF, content: RMD) • /Themes (folder: RAPF, content: RMDAP) • /Sites/<master-site-root-folder> (folder and content: R) 	
group	manager-<language-tag>	local-site-manager	<ul style="list-style-type: none"> • /Sites/<site-root-folder> (folder: RAPF, content: RMDAP) 	Suggested pattern configured in <code>siteManagerGroupPattern</code> of the <code>SiteModel</code>
group	translation-manager-role			Configured in <code>translationManagerRole</code> of the <code>SiteModel</code>
group	translation-workflow-robots		<ul style="list-style-type: none"> • / (folder and content: R) • /Sites (folder: RFAS, content: RMDAS) 	<p>Group for automatic multi-site actions like translation. This group requires supervise permissions in order to assign rights to newly created sites (deriving sites, see Section 5.6.3, "Deriving Sites" [293]).</p> <p>Approve rights are required for translation processing, not for publishing to Master Live Servers. So, publish permissions are not required for this group.</p>
user	translation-workflow-robot	translation-workflow-robots		Configured in <code>translationWorkflowRo</code>

Type	Name	Member of	Rights	Remark
				botUser of the Site Model

Table 5.19. Suggested Users and Groups for multi-site

The rights abbreviations denote:

- R - read
- M - modify / edit
- D - delete
- A - approve
- P - publish
- F - folder
- S - supervise

For further information about the rights, please refer to Section 3.15.2, “User Rights Management” in *Content Server Manual*.

Definition while deriving site

When deriving a new site, a proposal for the name of the site manager group is generated from a predefined pattern. By default, the name starts with *manager* followed by the language tag of the selected target locale (see also [Figure 5.28, “Derive Site: Setting site manager group” \[236\]](#)). This pattern may be configured in the property `siteManagerGroupPattern` of the `SiteModel`.

Derive a New Localized Site

Locale

German (Germany)

URL Segment

chef corp.-de-de

Site Manager Group

manager-de-DE

OK

Cancel

Figure 5.28. Derive Site: Setting site manager group

Adapting site manager group later on

If the site already exists, the names of site manager groups can be set or modified directly in the site indicator (see [Figure 5.29, “Site Indicator: Setting site manager group” \[237\]](#)).




Figure 5.29. Site Indicator: Setting site manager group

If any of the given groups does not exist, the property field will be marked red and the creation of the site or the assignment of the group may not be performed, thus the groups need to have been created before. Read more about users, groups and administration in Section 3.15, “User Administration” in *Content Server Manual*.

5.5.3 Development

CoreMedia Content Cloud's Multi-Site concept contains an example implementation for translation and localization processes. As you might have different requirements, for example defined by a translation agency which does the translation for you, the Multi-Site feature is highly configurable. Read the following sections to learn about the configuration options.

Site Model and Sites Service

The site model and the sites service are strongly connected with each other. While the site model consists of properties defining the site structure, the sites service uses this model to work with sites programmatically.

Sites Service

The sites service is designed to access the available sites and to determine the relation between sites and contents. The site model configures the behavior of the sites service.

For developing multi-site features the main entry point is the sites service.

Site Model

The site model is the centralized configuration of the CoreMedia Multi-Site behavior. Its configuration is required in several applications which are listed below. While [section Site Model Properties](#) lists the configurable properties [exception: *CoreMedia Site Manager* with an extra description in [Site Model in CoreMedia Site Manager](#)] the different configuration locations are explained per application:

- [Site Model in CoreMedia Studio \[242\]](#)
- [Site Model in Content Application Engine \[243\]](#)
- [Site Model in Command Line Tools \[243\]](#)
- [Site Model in CoreMedia Site Manager \[243\]](#)

Site Model Properties

The following table illustrates the configurable site model properties. To get to know more about the properties and patterns used, consult the Javadoc of `com.core-media.cap.multisite.SiteModel`.

sitemodel.site.indicator.documentType	
Description	Specifies the content type of the site indicator document. Each site must only have one instance of that content type.
Default Value	CMSite
sitemodel.site.indicator.depth	
Description	Defines the depth under the root of the site folder, where the site indicator document resides.
Deprecated	Setting will phase out. First it will default to 0 and will be removed completely someday. In the end, the site indicator will always be located in the site root folder.
Default Value	0
sitemodel.site.indicator.namePattern	
Description	Name pattern, which will be used for the name of the site indicator document when deriving a site. Only placeholder { 0 } is available for this property. For an overview of placeholders see Table 5.21, "Placeholders for Site Model Configuration" [242] .

Default Value *{0} [Site]*

```
sitemodel.site.rootdocument.namePattern
```

Description Defines the pattern for the site's home page document name, used while deriving a site. Only placeholder *{0}* is available for this property. For an overview of placeholders see [Table 5.21, "Placeholders for Site Model Configuration" \[242\]](#).

Default Value *{0}*

```
sitemodel.site.manager.groupPattern
```

Description Defines the pattern for responsible default site manager group name when deriving a site. For available placeholders see [Table 5.21, "Placeholders for Site Model Configuration" \[242\]](#)

Default Value *manager-{4}*

```
sitemodel.siteManagerGroupProperty
```

Description Defines the property of the site indicator document holding the site manager group names.

Default Value *siteManagerGroup*

```
sitemodel.groupPropertyDelimitingRegex
```

Description Defines the separator (as regular expression) how to split group names into elements, as for example for the site-manager-groups.

Default Value *comma, including trailing space characters*

```
sitemodel.translationManagerRole
```

Description Defines the group name denoting the role which permits a user to start a translation workflow.

Default Value *translation-manager-role*

```
sitemodel.idProperty
```

Description Defines the property of the site indicator document which contains the site id.

Default Value *id*

`sitemodel.nameProperty`

Description Defines the property of the site indicator document which contains the site name.

Default Value *name*

`sitemodel.localeProperty`

Description Defines the property of translatable content and the site indicator document, which holds the locale of the content.

Default Value *locale*

`sitemodel.masterProperty`

Description Defines the property of translatable content and the site indicator, which contains the link the master document.

Default Value *master*

`sitemodel.masterVersionProperty`

Description Defines the property of translatable content, which contains the version the corresponding master document.

Default Value *masterVersion*

`sitemodel.rootProperty`

Description Defines the property of the site indicator document, which refers to the home page document of this site.

Default Value *root*

`sitemodel.uriSegmentProperty`

Description Defines the property of the site's home page content type, which defines the root URI segment of the site.

Default Value	<i>segment</i>
<code>sitemodel.uriSegmentPattern</code>	
Description	Defines the pattern for the default root URI segment when deriving a site. For available placeholders see Table 5.21, “Placeholders for Site Model Configuration” [242] .
Default Value	<i>{0}-{4}</i>
<code>sitemodel.rootFolderPathPattern</code>	
Description	Defines the pattern to determine the site folder for a new derived site. For available placeholders see Table 5.21, “Placeholders for Site Model Configuration” [242] .
Default Value	<i>/Sites/{0}/{6}/{5}</i>
<code>sitemodel.rootFolderPathDefaultCountry</code>	
Description	Defines the folder name for the country folder, if the locale chosen while deriving a site defines no country explicitly.
Default Value	<i>NO_COUNTRY</i>
<code>sitemodel.translationWorkflowRobotUser</code>	
Description	<div>Defines the user name of the user responsible for creating derived content during a translation workflow.</div> <ul style="list-style-type: none">• The user should have read / write access on all localizable Sites.• The user should not be allowed to use the editor service.
Default Value	<i>translation-workflow-robot</i>

Table 5.20. Properties of the Site Model

Site Model Placeholders

Placehold-er	Description	Example
{ 0 }	site name	<i>MySite</i>
{ 1 }	site locale's language code	<i>en</i>
{ 2 }	site locale's country code (defaults to language code, if not available)	<i>US</i>
{ 3 }	site locale's variant (defaults to country or language code, if not avail-able); using BCP 47 Extensions	<i>u-cu-usd</i>
{ 4 }	site locale's IETF BCP 47 language tag	<i>en-US-u-cu-usd</i>
{ 5 }	site locale's language display name (localized in U.S. English); only available for <code>sitemodel.rootFolderPathPattern</code>	<i>English</i>
{ 6 }	site locale's country display name (localized in U.S. English); only available for <code>sitemodel.rootFolderPathPattern</code>	<i>United States</i>
{ 7 }	site locale's variant with the prefix <code>variantPrefix</code> configured in site model's Spring context; defaults to empty String; only available for <code>sitemodel.rootFolderPathPattern</code> . See IANA Lan-guage Subtag Registry for valid registered variants.	<i>_arevela</i>

Table 5.21. Placeholders for Site Model Configuration

Application Configurations

For details of the configuration in every application, please read the documentation below.

CoreMedia Studio

The site model default properties can be adjusted in the `application.properties` file in the `src/main/resources` directory of the `studio-server` module. See Chapter 3, *Deployment* in *Studio Developer Manual* for further information.

Content Management Server

The site model default properties can be adjusted in the `application.properties` file in the `src/main/resources` directory of the `content-management-server-app` module. See [????](#) for further information.

Content Application Engine

The site model default properties can be adjusted in the `component-blueprint-cae.properties` file in the `src/main/resources/coremedia` directory of the `cae-base-component` module. Thus, the configuration applies to the Live CAE as well as to the Preview CAE. See [Content Application Developer Manual](#) for further information.

Command Line Tools

The site model default properties can be adjusted in the `commandline-tools-sitemodel.properties` file in the `properties/corem` directory of the `cms-tools-application` module.

CoreMedia Site Manager

The *Site Manager* provides only rudimentary support of the multi-site features especially for backwards compatibility to old CoreMedia systems. For the full set of features please use *CoreMedia Studio*.

To migrate from existing multi-site features of *Site Manager* you need to adapt the `editor.xml` for example by adding a `SiteModel`.

[Example 5.10, "SiteModel in `editor.xml`" \[243\]](#) shows an example for adding the `SiteModel` to `editor.xml`.

```
<Editor>
  <!-- ... -->
  <SiteModel
    siteIndicatorDocumentType="CMSite"
    siteIndicatorDepth="0"
    idProperty="id"
    rootProperty="root"
    masterProperty="master"
    localeProperty="locale"/>
  <!-- ... -->
</Editor>
```

Example 5.10. SiteModel in `editor.xml`

Mind that for changing property names of `master` and `masterVersion` you also need to adapt property editors for the versioned master reference as shown in [Example 5.11, "Versioned Master Link in `editor.xml`" \[243\]](#).

```
<Document type="..." viewClass="...">
  <!-- ... -->
  <Property
    name="master"
```

```

    editorClass="hox.corem.editor.toolkit.property.VersionLinkEditor"
    versionProperty="masterVersion"/>
  <Property
    name="masterVersion"
    editorClass="hox.corem.editor.toolkit.property.InvisibleEditor"/>
  <!-- ... -->
</Document>

```

Example 5.11. Versioned Master Link in *editor.xml*

Content Type Model

While you might create your very own content type model, the following description is based on the assumption that you use the content type model of *CoreMedia Blueprint*. For a custom content type model you must meet certain requirements which are described at the end of this section.

Content Types

The base content type for any contents which require to be translated is `CMLocalized`. For further information see [Section 7.1, “Content Type Model” \[376\]](#).

```

<DocType Name="CMLocalized" Parent="CMObject" Abstract="true">
  <StringProperty Name="locale" Length="64"/>
  <LinkListProperty Name="master" Max="1"
    LinkType="CMLocalized"
    extensions:weakLink="true"/>
  <IntProperty Name="masterVersion"/>
  ...
</DocType>

```

Example 5.12. *CMLocalized*

Weak Link Attribute

The contents of each site have to be published and withdrawn independently of their master. Therefore, the `weakLink` attribute of every master property must be set to true - see also Content Type Model - LinkListProperty in *Content Server Manual*.

Attributes for Translation

The attributes `extensions:translatable` and `extensions:automerge`, which can be attached to all properties, affect the translation behavior. `extensions:automerge` also affects the synchronization behavior.

Translatable Properties

The properties that have to be translated to derived sites can be marked as translatable in the content type model by attaching the `extensions:translatable` attribute to the property declaration - see also Content Type Model - Translatable Properties in *Content Server Manual*.

section “[Translatable Predicate](#)” [253] describes other ways to mark a property as translatable, for example to mark nested properties of a Struct property as translatable.

```
<DocType Name="CMTeasable" Parent="CMHasContexts" Abstract="true">
  <LinkListProperty Name="master" Max="1"
    LinkType="CMTeasable"
    Override="true"
    extensions:weakLink="true"/>
  <StringProperty Name="teaserTitle" Length="512"
    extensions:translatable="true"/>
  <XmlProperty Name="teaserText" Grammar="coremedia-richtext-1.0"
    extensions:translatable="true"/>
  <XmlProperty Name="detailText" Grammar="coremedia-richtext-1.0"
    extensions:translatable="true"/>
  ...
</DocType>
```

Example 5.13. CMTeasable

Automatically Merged Properties

Usually all property changes from the master content will be merged automatically to the derived content when a translation task is accepted. To disable automatic merging for a property, set the `extensions:automerge` attribute to `false` as described in Content Type Model - Translatable Properties in *Content Server Manual*.

For a synchronization workflow, all properties are synchronized, by default, between a master content and its derived content. You can disable this behavior by setting `extensions:automerge` to `false` or by unchecking the checkbox *Keep synchronized with Master* of the content in Studio (see Section “[Removing Content Permanently from Synchronization](#)” in *Studio User Manual* for details).

Custom Content Type Models

Even if it is not recommended, you can use your own content type model with the Multi-Site feature of *CoreMedia Content Cloud*. Prerequisite is, that you can configure the Site Model mentioned before to meet the requirements of your own content type model. In addition, you probably need to adapt your document type model to fit the requirements of the multi-site concept.

Therefore, every content type, which may occur in a site must contain all properties, listed below.

- master
- masterVersion

- locale

Please adapt the configuration of each property to the properties of `CMLocalized` in the example above.

ServerImport and ServerExport

Both `serverimport` and `serverexport` have a special handling built in for the `master` and `masterVersion` properties. The export will store the translation state of a derived document and on import efforts are taken to reestablish a comparable translation state.

For the concrete names of the `master` and `masterVersion` properties, the `SiteModel` has to be provided to the tools, which is done via *Spring* in the file `COREM_HOME/properties/corem/commandline-tools-context.xml` (In *CoreMedia Blueprint* this file is added in the `cms-tools-application` module).

Examples:

The examples assume that you export a document and its master and import it afterwards into a clean system. The table uses `#` (hash mark) to denote contents having the given latest version number.

Master (before)	The master version before export. <i>none</i> means that no master link is set.
Version (before)	Value of the master version property of the derived document before export. <i>none</i> means that no version is specified yet which actually marks derived documents as not being up to date with its master document.
State (before)	The translation state of the derived document before export.
Master (after)	The master version after import (actually always <code>#1</code>).
Version (after)	Value of the master version property of the derived document after import.
State (after)	The translation state of the derived document after import.

Mas- ter (be- fore)	Ver- sion (be- fore)	State (before)	Mas- ter (after)	Ver- sion (after)	State (after)	Comment
#5	5	up-to-date	#1	1	up to date	The master and derived document were up to date before export (de-

Master (before)	Version (before)	State (before)	Master (after)	Version (after)	State (after)	Comment
						derived document is most recent localization of its master]. Thus, after import the same state is set.
#5	4	not up-to-date	#1	0	master version destroyed	The master and derived document were not up to date before export. Thus, after import the value of the master version property is set to a special version number denoting that the derived content is not up-to-date. On API level this is regarded as if the referred master version got destroyed meanwhile. For the editor the document will appear as being not up-to-date.
#5	none	not translated yet	#1	none	not translated yet	Derived document was never localized from its master. Thus, the same state applies after import.
none	5	no master	none	5	no master	Corrupted content: No special logic is applied. The overall approach for import and export is defensive thus if the state was invalid before, the fallback is to use the default behavior from import and export keeping the values as is.

Table 5.22. Example for server export and import for multi-site

XLIFF Integration

Translation jobs can be represented using the XLIFF, the *XML Localization Interchange File Format*. XLIFF is an OASIS standard to interchange localizable data for tools as for example used by translation agencies. An XLIFF file contains the source language content of translatable properties from one or more documents. It is then enriched by

a translation agency to contain the translated content, too. *CoreMedia Content Cloud* supports XLIFF 1.2.

XLIFF Structure

An XLIFF file is structured into multiple translation units. While a string property is encoded as a single translation unit, a richtext property is split into semantically meaningful parts, comprising for example a paragraph or a list item. Translation units are then grouped, so that units belonging to a single property are readily apparent.

All properties of a single document are included in a single file section according to the XLIFF standard. A custom attribute `cmxliiff:target` allows the importer to identify the target document that should receive the translation, as supported by the XLIFF standard. Translation tools must preserve this extension attribute when filling the target content into the XLIFF file.

The fragment in [Example 5.14, "XLIFF fragment" \[248\]](#) shows the start tag of a `<file>` element for translating from English to French, indicating the source document 222 and the target document 444.

```
<file
  xmlns:cmxliiff=
    "http://www.coremedia.com/2013/xliiff-extensions-1.0"
  original="coremedia:///cap/version/222/1"
  source-language="en"
  datatype="xml"
  target-language="fr"
  cmxliiff:target="coremedia:///cap/content/444">
```

Example 5.14. XLIFF fragment

The elements to translate are grouped in `<trans-unit>` elements, which consists of a `<source>` element containing the original text and will later contain the translated text inside a `<target>` element.

XLIFF Export

In order to export XLIFF as part of a workflow action, the following actions need to be taken:

1. **Pre-Processing: Translation Items:** extract properties and partial properties (Structs) to be translated, and
2. **Generating XLIFF Document:** transform these properties into an XLIFF representation.

Pre-Processing: Translation Items

A translation item represents a content item during the translation process. It is meant to contain only those properties or partial properties (for Struts) which should be translated. Any filtering for example of empty properties (and deciding what *empty* actually means) is done here.

```
Map<Locale, List<TranslateItem>> getTranslationItemsByLocale(
    Collection<ContentObject> masterContentObjects,
    Collection<Content> derivedContents,
    Function<ContentObjectSiteAspect, Locale> localeMapper) {

    ContentToTranslateItemTransformer transformer =
        getSpringContext()
            .getBean(ContentToTranslateItemTransformer.class);

    return transformer
        .transform(
            masterContentObjects,
            derivedContents,
            localeMapper,
            ITEM_PER_TARGET
        )
        .collect(
            Collectors.groupingBy(TranslateItem::getSingleTargetLocale)
        );
}
```

Example 5.15. Transforming to Translation Items

In [Example 5.15, "Transforming to Translation Items" \[249\]](#) you see a typical example used within some workflow action to generate a representation as translation items. It uses the Spring context of the workflow server (retrieved via `getSpringContext()` from [SpringAwareLongAction](#)) to retrieve a bean of type `ContentToTranslateItemTransformer`.

The `ContentToTranslateItemTransformer` is prepared for typical translation workflow scenarios, where you have a set of master content objects (contents or versions) to translate and a set of target contents which should receive the translation result.

As configuration options the transformation process takes a strategy to determine the language from the master content objects as well as from the derived contents and a flag how to group the results (see [TransformStrategy](#)). For XLIFF export the recommended flag is `ITEM_PER_TARGET`.

The result in the given example will be grouped by target locale, which allows combining all translation items into one XLIFF document for one common target locale.

```
static Locale preferSiteLocale(ContentObjectSiteAspect aspect) {
    Site site = aspect.getSite();
    if (site == null) {
        return aspect.getLocale();
    }
}
```

```

    return site.getLocale();
}

```

Example 5.16. Function to Determine Locales

In [Example 5.16, "Function to Determine Locales" \[249\]](#) you see a recommended function used as `localeMapper` passed to the method defined in [Example 5.15, "Transforming to Translation Items" \[249\]](#) to determine the locale (source as well as target) to set within XLIFF. The method prefers the site locale over the locale within a document.

Generating XLIFF Document

Just as the `ContentToTranslateItemTransformer` the `XliffExporter` bean is available in Spring context.

```

Path exportToXliff(Locale sourceLocale,
                  Map.Entry<Locale, List<TranslateItem>> entry)
    throws IOException {

    XliffExporter xliffExporter =
        getSpringContext().getBean(XliffExporter.class);
    String targetLanguageTag = entry.getKey().toLanguageTag();
    List<TranslateItem> items = entry.getValue();

    // Provide some meaningful name.
    String baseName = ...;

    Path xliffPath =
        Files.createTempFile(
            baseName,
            "." + sourceLocale.toLanguageTag() + "2" +
            targetLanguageTag + ".xliff"
        ).toAbsolutePath();

    try (Writer xliffWriter =
        Files.newBufferedWriter(xliffPath, StandardCharsets.UTF_8)) {
        xliffExporter.exportXliff(
            items,
            xliffWriter,
            XliffExportOptions.xliffExportOptions()
                .option(XliffExportOptions.EMPTY_IGNORE)
                .option(XliffExportOptions.TARGET_SOURCE)
                .build());
    }

    return xliffPath;
}

```

Example 5.17. Exporting XLIFF

In [Example 5.17, "Exporting XLIFF" \[250\]](#) you see how you may transform the translation items generated above into an XLIFF document which you may then upload to the translation service.

The parameter `sourceLocale` is just required to generate some meaningful, easy to debug filename. If your translation service preserves these filenames, it may be useful to generate a name, which can easily be identified later on. That is why the file-

name in the example contains information such as the source as well as the target language.

When invoking the `XliffExporter` you have several options to choose from, to control the output of XLIFF. In the given example empty trans-unit nodes should be ignored (they will not be part of the XLIFF export) and the target nodes will contain the same value as the source node, which is recommended by some translation services. For additional options have a look at [XliffExportOptions](#).

XLIFF Import

In order to import XLIFF and apply the translation to the target documents, you will use the [XliffImporter](#).

```
boolean importXliffFile(InputStream inputStream) {
    XliffImporter importer = getSpringContext()
        .getBean(XliffImporter.class);

    List<XliffImportResultItem> resultItems;

    try {
        resultItems = asRobotUser() -> importer.importXliff(inputStream);
    } catch (CapXliffImportException e) {
        LOG.warn("Failed to import XLIFF.", e);
        return false;
    }

    List<XliffImportResultItem> majorIssues =
        XliffImportResults.getMajorIssues(resultItems);

    if (!majorIssues.isEmpty()) {
        LOG.warn("XLIFF has major issues: {}", majorIssues);
        return false;
    }

    return true;
}
```

Example 5.18. Importing XLIFF

Example 5.18, "Importing XLIFF" [251] shows how you may import a received XLIFF document within a workflow action. The example is used within an action to poll the results from the translation service and which will automatically apply XLIFF results as soon as they are available. The implementation assumes that it should repeat the XLIFF download until the download was successful.

To start get the `XliffImporter` bean from Spring context via `getSpringContext()` from [SpringAwareLongAction](#).

The `XliffImporter` provides two ways to signal problems. While exceptions are typically related to for example I/O problems, internal problems such as missing translations, target documents which are gone, and so on, are reported as major issues. To

help rating and analyzing the issues there is a utility class `XliffImportResults`, which will for example filter any relevant issues for you.

Note, that you may want to store issues in a workflow variable instead to present the information in *CoreMedia Studio* as part of the workflow detail panel.

If the workflow action runs in an automated task, it needs some user to update contents according to the translation result. It depends on your actual design of the action and the workflow process, which user should be taken. In the example, the translation workflow robot user is reused, which is part of the site model.

```
<T> T asRobotUser(Supplier<T> run) {
    User robotUser = getRobotUser();

    // Perform content operations in the name of the robot user.
    CapSession session = getCapSessionPool().acquireSession(robotUser);

    try {
        CapSession oldSession = session.activate();
        try {
            return run.get();
        } finally {
            oldSession.activate();
        }
    } finally {
        getCapSessionPool().releaseSession(session);
    }
}

User getRobotUser() {
    SiteModel siteModel = getSpringContext().getBean(SiteModel.class);
    String robotUserName = siteModel.getTranslationWorkflowRobotUser();
    UserRepository userRepository = getConnection().getUserRepository();

    User robotUser = userRepository.getUserByName(robotUserName);

    // Recommended: Add a check that the robotUser actually exists.

    return robotUser;
}
```

Example 5.19. Importing XLIFF

Example 5.19, "Importing XLIFF" [252] sketches a possible implementation. `asRobotUser` will switch the session to a user session using the `CapSessionPool` provided by `LongActionBase` to execute the given supplier.

`getRobotUser` uses the site model to get the artificial robot user to perform the import action.

XLIFF Customization

You may customize XLIFF handling at various extension points:

- you may modify strategies to identify translatable properties, or

- you may change representation in XLIFF export, or
- you may adapt XLIFF import for special property types.

Assumptions

In here you will see a small use case which leads you through all required adaptations to take to your system. The use case is based on the following assumptions:

- you introduced a markup property `xhtml` with XHTML grammar (<http://www.w3.org/1999/xhtml>) to your content type model,
- you do not support attributes for XHTML elements, and
- only markup properties named `xhtml` should be considered for translation (in other words: you do not use the translatable attribute inside your content type model).

In [section "Handling Attributes" \[262\]](#) this simple example is continued by adding the attributes, as this is an expert scenario which requires taking care of XLIFF validation.

Translatable Predicate

In order to add the property to the translation process, you have to mark it as translatable. There are several ways of doing so, where the default one is to mark the property as translatable within the content type model (using `extension:translatable=true`). As alternative to this you may add a custom bean of type `TranslatablePredicate` to your application context, which will then be ORed with all other existing beans of this type. To completely override the behavior, you need to override the bean named `'translatablePredicate'` in `TranslatablePredicateConfiguration`.

The Blueprint contains a default predicate that can be configured with property `translate.xliff.translatableExpressions` and that makes it possible to mark only certain nested properties of Struct properties as translatable. See [section "XLIFF Configuration Beans" \[271\]](#) for details.

Translation Items

Having marked the property `xhtml` as translatable, as described in [section "Translatable Predicate" \[253\]](#) and trying to export a document containing the `xhtml` property, you will see a `CapTranslateItemException` as in [Example 5.20, "Example for CapTranslateItemException" \[253\]](#).

```
com.coremedia.translate.item.CapTranslateItemException:

Property 'xhtml' (type: MARKUP) of content type 'MyDocument' is configured
to be considered during translation but a corresponding transformer of type
'com.coremedia.translate.item.transform.TranslatePropertyTransformer'
cannot be found.
```

Please consider to add an appropriate transformer bean to your Spring context.

Example 5.20. Example for CapTranslateItemException

The exception tells you which steps to do next, in order to support the `xhtml` property during XLIFF export: You have to add a `TranslatePropertyTransformer` to your Spring context.

Some default transformers for standard CoreMedia property types are configured in `TranslateItemConfiguration`. One of them is the `AtomicRich-textTranslatePropertyTransformer` for CoreMedia RichText properties.

Just as the `AtomicRichTextTranslatePropertyTransformer` the transformer can be based on `AbstractAtomicMarkupTranslatePropertyTransformer` which ends up that you only have to specify how to match the grammar name and to add a predicate to decide if the property should be considered empty or not.

```
public class AtomicXhtmlTranslatePropertyTransformer
    extends AbstractAtomicMarkupTranslatePropertyTransformer {
    private static final String XHTML_GRAMMAR_NAME =
        "http://www.w3.org/1999/xhtml";

    private AtomicXhtmlTranslatePropertyTransformer(
        TranslatablePredicate translatablePredicate,
        Predicate<? super Markup> emptyPredicate) {
        super(
            translatablePredicate,
            AtomicXhtmlTranslatePropertyTransformer::isXhtml,
            emptyPredicate
        );
    }

    public AtomicXhtmlTranslatePropertyTransformer(
        TranslatablePredicate translatablePredicate) {
        this(translatablePredicate,
            AtomicXhtmlTranslatePropertyTransformer::isEmpty);
    }

    private static boolean isEmpty(@Nullable Markup value) {
        return !MarkupUtil.hasText(value, true);
    }

    private static boolean isXhtml(XmlGrammar grammar) {
        return XHTML_GRAMMAR_NAME.equals(grammar.getName());
    }
}
```

Example 5.21. TranslatePropertyTransformer for XHTML

Now you have a ready-to-use strategy to add your `xhtml` property to your translation items.



Property Hints

Transformed properties may hold meta information which are required for later processing. Typical scenarios are to tell the translation service how many characters are allowed within a String or to tell the XLIFF importer which grammar is used for the contained Markup.

For details have a look at [TranslateProperty](#) and [PropertyHint](#).

XLIFF Export

As before, an exception provides further guidance how to continue as can be seen in [Example 5.22, “Example for CapXliffExportException” \[255\]](#).

```
com.coremedia.translate.xliff.exporter.CapXliffExportException:
Missing XLIFF export handler for property
'TranslateProperty[
  id = property:markup:xml,
  propertyHints =
    [GrammarNameHint[value = http://www.w3.org/1999/xhtml]],
  value = <html xml:lang="en" ...>'.

Please consider adding an appropriate handler of type
'com.coremedia.cap.translate.xliff.handler.XliffPropertyExportHandler'
to your Spring context.
```

Example 5.22. Example for CapXliffExportException

You now have to implement a strategy to transform XHTML into a representation which contains the texts to translate as XLIFF `<trans-unit>` elements. The strategy is created by implementing [XliffPropertyExportHandler](#).

```
public class XliffXhtmlPropertyExportHandler
    implements XliffPropertyExportHandler {
    private static final String XHTML_GRAMMAR_NAME =
        "http://www.w3.org/1999/xhtml";

    @Override
    public boolean isApplicable(TranslateProperty property) {
        return property.getValue() instanceof Markup &&
            property.getGrammarName()
                .map(XHTML_GRAMMAR_NAME::equals)
                .orElse(false);
    }

    @Override
    public Optional<Group> toGroup(TranslateProperty property,
        Supplier<String> idProvider,
        XliffExportOptions xliffExportOptions) {
        return Optional.ofNullable(
            toGroup(property.getId(),
                (Markup) property.getValue(),
                idProvider,
```

```

        xliiffExportOptions
    );
}

@Nullable
private static Group toGroup(String id,
                             Markup value,
                             Supplier<String> idProvider,
                             XliiffExportOptions xliiffExportOptions) {
    if (!MarkupUtil.hasText(value, true) &&
        xliiffExportOptions.isEmptyIgnore()) {
        // Don't add anything to translate for empty XHTML.
        return null;
    }

    Group markupGroup =
        new XhtmlToXliiffConverter(idProvider, xliiffExportOptions)
            .apply(value);

    Group result = new Group();
    // Required: Set the property name. This is important for
    // the import process later on, to identify the property
    // to change.
    result.setResname(id);
    result.setDatatype(DatatypeValueList.XHTML.value());

    result.getGroupOrTransUnitOrBinUnit().add(markupGroup);

    return result;
}
}

```

Example 5.23. *PropertyExportHandler* for XHTML

Example 5.23, “*PropertyExportHandler* for XHTML” [255] contains the base for such a handler. It especially creates an XLIFF group object, which contains the property name. For mapping XHTML to XLIFF the handler delegates to another class in this case, as this is the most complex task during XLIFF export.

```

public class XhtmlToXliiffConverter implements Function<Markup, Group> {
    private final Supplier<String> transUnitIdProvider;
    private final XliiffExportOptions xliiffExportOptions;

    public XhtmlToXliiffConverter(Supplier<String> transUnitIdProvider,
                                 XliiffExportOptions ) {
        this.transUnitIdProvider = transUnitIdProvider;
        this.xliiffExportOptions = xliiffExportOptions;
    }

    @Override
    public Group apply(Markup markup) {
        XhtmlContentHandler handler = new XhtmlContentHandler();
        markup.writeOn(handler);
        return handler.getResult();
    }

    private class XhtmlContentHandler extends DefaultHandler {
        // First element in stack is the currently modified element.
        private final Deque<Object> xliiffStack = new LinkedList<>();
        private Group result;

        @Override
        public void startElement(String uri,

```



```

        String localName,
        String qName,
        Attributes attributes) {
    String typeId = localName.toLowerCase(Locale.ROOT);
    Group elementWrapper = new Group();
    if (result == null) {
        result = elementWrapper;
    }
    elementWrapper.setType(getType(typeId));
    addElement(elementWrapper);
}

private void addElement(Object elementWrapper) {
    Object first = xliFFStack.peekFirst();
    if (first instanceof ContentHolder) {
        ContentHolder contentHolder = (ContentHolder) first;
        contentHolder.getContent().add(elementWrapper);
    }
    xliFFStack.push(elementWrapper);
}

@Override
public void endElement(String uri,
        String localName,
        String qName) {
    // remove element from xliFFStack

    while (!xliFFStack.isEmpty()) {
        Object object = xliFFStack.pop();
        if (object instanceof TypeHolder) {
            TypeHolder typeHolder = (TypeHolder) object;
            if (getType(localName).equals(typeHolder.getType())) {
                break;
            }
        }
    }
}

@Override
public void characters(char[] ch,
        int start,
        int length) {
    String content = new String(ch, start, length);

    TransUnit transUnit = requireTransUnit();

    transUnit.getSource().getContent().add(content);
    if (xliFFExportOptions.getTargetOption() ==
        XliFFExportOptions.TargetOption.TARGET_SOURCE) {
        transUnit.getTarget().getContent().add(content);
    }
}

private TransUnit requireTransUnit() {
    Object first = xliFFStack.peekFirst();
    TransUnit transUnit;
    if (first instanceof TransUnit) {
        transUnit = (TransUnit) first;
    } else {
        transUnit = new TransUnit();
        transUnit.setId(transUnitIdProvider.get());
        transUnit.setSource(new Source());
        addElement(transUnit);
        if (xliFFExportOptions.getTargetOption() !=
            XliFFExportOptions.TargetOption.TARGET_OMIT) {
            transUnit.setTarget(new Target());
        }
    }
    return transUnit;
}

```

```

private String getType(String typeId) {
    return "x-html-" + typeId.toLowerCase(Locale.ROOT);
}

private Group getResult() {
    // possibly check that the result is actually set
    return result;
}
}

```

Example 5.24. *XhtmlToXliffConverter*

Example 5.24, “XhtmlToXliffConverter” [256] is a very basic implementation of such a converter [it ignores for example any attributes]. It contains the most relevant aspects, that you have to take into account while generating XLIFF structures.

Elements of XhtmlToXliffConverter

<code>transUnitIdProvider</code>	Each <code><trans-unit></code> has to get a unique ID. This ID is supplied by the <code>transUnitIdProvider</code> .
<code>xliffExportOptions</code>	The options will especially tell you, how to deal with target nodes. You may for example have to create empty target nodes in <code><trans-unit></code> elements or you have to copy the value contained in the source node to the target node.
<code>XhtmlContentHandler</code>	Markup can be written to a SAX <code>ContentHandler</code> . Use this handler, for going through the elements and creating a parallel XLIFF structure. For convenience you use the implementation <code>SAXDefaultHandler</code> , so that you only have to implement the methods you are interested in.
<code>startElement</code>	For any element in XHTML, you need to create a representation in XLIFF. Regarding the type identifier you can use any String value - you need this value later on to create the corresponding XHTML element. Thus, it makes sense, that the ID contains a reference to the corresponding XHTML element.
<code>addElement</code>	The XLIFF JAXB Classes contain some convenience methods and interfaces such as <code>ContentHolder</code> to easily identify XLIFF elements which may have some content.
<code>endElement</code>	This method just updates the element stack, so that new elements get added at the expected location.

characters

Obviously, characters are those elements of your XHTML which you want to translate. Thus, you need to add the characters to a `<trans-unit>` node. Depending on the configured XLIFF export options, you also need to add them to the target node.

Do not forget to set the `<trans-unit>` ID here.

Marshalling Failures

If marshalling the XLIFF structure fails, ensure that you check that your generated XLIFF structure is valid. The JAXB wrapper classes do not provide much support there. Thus, it is always recommended having your XLIFF 1.2 specification at hand.



If everything is implemented correctly, an XHTML property as in [Example 5.25, "XHTML Example Input" \[259\]](#) will be transformed to XLIFF as in [Example 5.26, "XHTML as XLIFF Example Output" \[259\]](#), which again will be part of the XLIFF file representing the content containing the property.

```
<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <title>abcdefg</title>
  </head>
  <body>
    <p>abcdefg</p>
  </body>
</html>
```

Example 5.25. XHTML Example Input

```
<group datatype="xhtml" resname="property:markup.xml">
  <group restype="x-html-html">
    <group restype="x-html-head">
      <group restype="x-html-title">
        <trans-unit id="12">
          <source>abcdefg</source>
          <target>abcdefg</target>
        </trans-unit>
      </group>
    </group>
    <group restype="x-html-body">
      <group restype="x-html-p">
        <trans-unit id="13">
          <source>abcdefg</source>
          <target>abcdefg</target>
        </trans-unit>
      </group>
    </group>
  </group>
</group>
```

Example 5.26. XHTML as XLIFF Example Output

XLIFF Import

Having implemented all the above, let's handle the XLIFF import now. Without further changes, the just exported property will be ignored on XLIFF import, and no change will be applied to the target document.

Extending XLIFF Schema

XLIFF 1.2 specification may be extended by custom attributes. If you have enabled XLIFF schema validation for XLIFF importer, and if you generated extended attributes you may have to add additional XLIFF schema sources. For details have a look at [section "Handling Attributes" \[262\]](#).



In order to import the `xhtml` property, you have to implement an `XliffProperty-ImporterHandler` and add it as bean to the Spring context.

```
public class XliffXhtmlPropertyImporterHandler
    implements XliffPropertyImporterHandler {

    private static final String XHTML_GRAMMAR_NAME =
        "http://www.w3.org/1999/xhtml";

    @Override
    public boolean isAccepting(CapPropertyDescriptor property) {
        if (property.getType() != CapPropertyDescriptorType.MARKUP) {
            return false;
        }

        XmlGrammar grammar = ((MarkupPropertyDescriptor) property).getGrammar();
        return grammar != null && XHTML_GRAMMAR_NAME.equals(grammar.getName());
    }

    @Nullable
    @Override
    public Object convertXliffToProperty(
        CapPropertyDescriptor descriptor,
        Group group,
        @Nullable Object originalPropertyValue,
        String targetLocale,
        XliffImportResultCollector result) {
        Group markupGroup = (Group) group.getContent().get(0);
        Markup markup = new XliffToXhtmlConverter().apply(markupGroup);

        if (!descriptor.isValidValue(markup)) {
            result.addItem(XliffImportResultCode.INVALID_MARKUP);
        }

        return markup;
    }
}
```

Example 5.27. `XliffXhtmlPropertyImporterHandler`

Example 5.27, “XliffXhtmlPropertyImportHandler” [260] shows a very simplistic implementation of an import handler. It decides if it is responsible for importing into the given property, and if it is, the method `convertXliffToProperty` will be called. Many of the arguments provide context information which may be used for further validation. You only use the `group` to parse the XLIFF and the `descriptor` to validate the resulting value. The `group` handed over is the group node you added before, which contains the reference to the property. Thus, the relevant content for you to parse is the first group contained in it.

As you can see, it is important that XLIFF export and import go hand in hand, to understand each other. Adapting XLIFF export almost always means to adapt the XLIFF import, too.

The `XliffXhtmlPropertyImportHandler` delegates further processing to a converter which will now generate the Markup as can be seen in **Example 5.28, “XliffToXhtmlConverter” [261]**.

```
public class XliffToXhtmlConverter
    implements Function<Group, Markup> {
    private static final String XHTML_GRAMMAR_NAME =
        "http://www.w3.org/1999/xhtml";

    @Override
    public Markup apply(Group group) {
        Document document = MarkupFactory.newDocument(
            XHTML_GRAMMAR_NAME,
            elementName(group),
            null
        );
        Element documentElement = document.getDocumentElement();
        documentElement.setAttribute("xmlns", XHTML_GRAMMAR_NAME);

        processContents(group, documentElement);

        return MarkupFactory.fromDOM(document);
    }

    private static void processContents(ContentHolder contentHolder,
        Element parent) {
        for (Object content : contentHolder.getContent()) {
            if (content instanceof String) {
                processString(parent, (String) content);
            } else if (content instanceof Group) {
                processGroup(parent, (Group) content);
            } else if (content instanceof TransUnit) {
                TransUnit transUnit = (TransUnit) content;
                processContents(transUnit.getTarget(), parent);
            }
        }
    }

    private static void processGroup(Node parent, Group group) {
        Document document = parent.getOwnerDocument();
        Element node = document.createElement(elementName(group));
        parent.appendChild(node);
        processContents(group, node);
    }

    private static void processString(Node parent, String text) {
        Document document = parent.getOwnerDocument();
        Node node = document.createTextNode(text);
        parent.appendChild(node);
    }
}
```

```

    }

    private static String elementName(TypeHolder group) {
        return group.getType().replace("x-html-", "");
    }
}

```

Example 5.28. XliffToXhtmlConverter

Methods of XliffXhtmlPropertyImportHandler

<code>apply</code>	Create a document from the main group which you may later transform to Markup.
<code>processContents</code>	Steps through the elements of a <code>ContentHolder</code> (again a convenience interface for XLIFF) and decides based on the (XLIFF) class type what to do. Strings will be the translated text. Groups represent nested elements and <code>TransUnits</code> contain the translated text in their target nodes.

The other methods just create the corresponding nodes for elements or texts.

Backward Compatibility

Especially for the import handler it is important to respect backward compatibility if necessary. The import handler may have to deal with XLIFF documents which were sent to a translation service weeks or month before.



Done

Having all this, you are done with this initial example and you got to know most of the API entry points you will need for customized XLIFF export. You learned about the initial filtering, the transformation to XLIFF and the transformation from XLIFF to your new translated property value.

Handling Attributes

In the previous sections, handling attributes was skipped in order to keep the example simple. But when it comes to attributes, you not only need to decide which of them should be translatable and which not, you also need to care of XLIFF validation, if you turned XLIFF validation on.

Start extending [Example 5.24, "XhtmlToXliffConverter" \[256\]](#) by a method to map arguments.

```

public class XhtmlToXliffConverter implements Function<Markup, Group> {
    /* ... */

    private class XhtmlContentHandler extends DefaultHandler {
        /* ... */

        @Override
        public void startElement(String uri,
                                String localName,
                                String qName,
                                Attributes attributes) {
            /* ... */
            mapAttributes(attributes, elementWrapper);
            addElement(elementWrapper);
        }

        private void mapAttributes(Attributes attributes, Group elementWrapper)
        {
            for (int i = 0; i < attributes.getLength(); i++) {
                String localName = attributes.getLocalName(i);
                String attributeValue = attributes.getValue(i);

                switch (localName) {
                    case "title":
                    case "alt":
                    case "summary":
                        elementWrapper
                            .getContent()
                            .add(
                                createTransUnit(
                                    "x-html-attr-" + localName,
                                    attributeValue
                                )
                            );
                        break;
                    default:
                        // Wraps the attribute to a custom namespace.
                        QName xliifAttrQName =
                            new QName(
                                "http://www.mycompany.com/custom-xliff-1.0",
                                localName
                            );
                        elementWrapper.getOtherAttributes().put(xliifAttrQName,
attributeValue);
                }
            }
        }

        private TransUnit createTransUnit(String resType, String value) {
            TransUnit transUnit = new TransUnit();
            transUnit.setId(transUnitIdProvider.get());
            transUnit.setType(resType);

            Source source = new Source();
            transUnit.setSource(source);
            source.getContent().add(value);

            if (xliifExportOptions.getTargetOption() !=
                XliifExportOptions.TargetOption.TARGET_OMIT) {
                Target target = new Target();
                transUnit.setTarget(target);
                if (xliifExportOptions.getTargetOption() ==
                    XliifExportOptions.TargetOption.TARGET_SOURCE) {
                    target.getContent().add(value);
                }
            }
            return transUnit;
        }
    }
}

```

```

    /* ... */
  }
}

```

Example 5.29. Attribute Export

In [Example 5.29, “Attribute Export”](#) [263] a new method `mapAttributes` is added, which distinguishes between attributes to translate, and attributes not to translate.

Translatable Attributes: For translatable attributes you just add a `<trans-unit>` element which also specifies a `restype` attribute. This attribute has to be resolved later on to a property. The rest is very similar to the `characters` method in the initial example.

Non-Translatable Attributes: Non-translatable attributes, are represented as custom attributes within XLIFF, as XLIFF Schema allows adding such custom attributes at many places. In order to be prepared for XLIFF validation, CoreMedia recommends adding a namespace URI to the attribute, here `http://www.mycompany.com/custom-xliff-1.0`.

```

<html xmlns="http://www.w3.org/1999/xhtml">
  <head>
    <title>abcdefg</title>
  </head>
  <body>
    <p class="some--class" title="some title">abcdefg</p>
  </body>
</html>

```

Example 5.30. XHTML Example Input (Attributes)

```

<group restype="x-html-p"
  ns4:class="some--class"
  xmlns:ns4="http://www.mycompany.com/custom-xliff-1.0">
  <trans-unit id="14" restype="x-html-attr-title">
    <source>some title</source>
    <target>some title</target>
  </trans-unit>
  <trans-unit id="15">
    <source>abcdefg</source>
    <target>abcdefg</target>
  </trans-unit>
</group>

```

Example 5.31. XHTML as XLIFF Example Output (Attributes)

Given an example XHTML like in [Example 5.30, “XHTML Example Input \(Attributes\)”](#) [264] the paragraph will be transformed as given in [Example 5.31, “XHTML as XLIFF Example Output \(Attributes\)”](#) [264]. As you can see, the class attribute is added with a custom namespace, and the title attribute is added as `trans-unit` at first place within the group.


```
[Fatal Error] cvc-complex-type.3.2.2: Attribute 'ns4:class' is not allowed
to appear in element 'group'. (23, 8)
```

Example 5.32. XLIFF Validation Error

XLIFF Validation: If XLIFF validation is turned on, the XLIFF import will fail to recognize the custom workspace and raises an error like in [Example 5.32, “XLIFF Validation Error” \[265\]](#). What you need to do now, is to create a schema defining your new attributes and to add the schema to the Spring application context.

```
<?xml version="1.0" encoding="UTF-8"?>
<xsd:schema xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified"
  targetNamespace="http://www.mycompany.com/custom-xliff-1.0"
  xml:lang="en">

  <xsd:attribute name="class" type="xsd:string"/>

</xsd:schema>
```

Example 5.33. Custom XLIFF XSD

```
@Bean
@Scope(BeanDefinition.SCOPE_SINGLETON)
public XliffSchemaSource<Source> customXliffSchema() {
    return () -> new StreamSource(
        getClass().getResourceAsStream("/custom-xliff-1.0.xsd")
    );
}
```

Example 5.34. Custom XLIFF XSD (Bean)

[Example 5.33, “Custom XLIFF XSD” \[265\]](#) adds the `class` attribute to the new custom namespace. Note, that you have to do this for every attribute, you want to support. In [Example 5.34, “Custom XLIFF XSD \(Bean\)” \[265\]](#) you see, how to add the new schema to the application context, so that it can be used for validation. Having this, you are prepared for the actual XLIFF import handling.

For more details on XLIFF Validation Schemes, see the corresponding Javadoc of [XliffSchemaSource](#) and the configuration class adding standard schema required for validation [XliffSchemaConfiguration](#).

XLIFF Import: Now you are going to extend the `XliffToXhtmlConverter` as given in [Example 5.28, “XliffToXhtmlConverter” \[261\]](#).

```
public class XliffToXhtmlConverter
    implements Function<Group, Markup> {

    /* ... */

    private static void processContents(ContentHolder contentHolder,
        Element parent) {
        for (Object content : contentHolder.getContent()) {
```

```

        if (content instanceof String) {
            processString(parent, (String) content);
        } else if (content instanceof Group) {
            processGroup(parent, (Group) content);
        } else if (content instanceof TransUnit) {
            TransUnit transUnit = (TransUnit) content;
            String type = attributeName(transUnit);
            if (type.isEmpty()) {
                processContents(transUnit.getTarget(), parent);
            } else {
                processTranslatableAttribute(type, transUnit.getTarget(), parent);
            }
        }
    }
}

private static void processTranslatableAttribute(String type, Target target,
Element parent) {
    StringBuilder value = new StringBuilder();
    for (Object content : target.getContent()) {
        value.append(content);
    }
    parent.setAttribute(type, value.toString());
}

private static String attributeName(TypeHolder group) {
    String type = group.getType();
    if (type == null || type.isEmpty()) {
        return "";
    }
    return type.replace("x-html-attr-", "");
}

/* ... */
}

```

Example 5.35. Importing Translatable Attributes

In Example 5.35, “Importing Translatable Attributes” [265] add importing the translatable attributes. Add a branch for `<trans-unit>` elements, to detect that they represent a translatable attribute, if the type is set.

```

public class XliffToXhtmlConverter
    implements Function<Group, Markup> {

    /* ... */

    private static void processGroup(Node parent, Group group) {
        Document document = parent.getOwnerDocument();
        Element node = document.createElement(elementName(group));
        processNonTranslatableAttributes(node, group);
        parent.appendChild(node);
        processContents(group, node);
    }

    private static void processNonTranslatableAttributes(Element node,
        Group group) {
        Map<QName, String> otherAttributes = group.getOtherAttributes();
        for (Map.Entry<QName, String> entry : otherAttributes.entrySet()) {
            QName attributeQName = entry.getKey();
            String localPart = attributeQName.getLocalPart();
            node.setAttribute(localPart, entry.getValue());
        }
    }
}

```

```

/* ... */
}

```

Example 5.36. Importing Non-Translatable Attributes

In Example 5.36, "Importing Non-Translatable Attributes" [266] the custom attributes handed over to the group element are parsed and set as corresponding attribute for the DOM element. Note, that in order to shorten the code, the namespace URI is not checked.

Now you are done, and can support custom attributes, translatable or non-translatable.

Translation Workflow

Translation Workflow Configuration

This section describes general configuration options for translation workflows.

NOTE

The necessary Spring configurations for new custom workflows in Studio are documented within Section 7.23, "Customizing Workflow UI" in *Studio Developer Manual*.



Spring configuration for custom translation workflows

A new custom translation workflow requires a strategy for extracting derived contents from your customTranslation.xml workflow definition. Therefore, you need to introduce a bean definition from the class `com.coremedia.translate.workflow.DefaultTranslationWorkflowDerivedContentsStrategy` and adapt it to your custom workflow (see example below).

NOTE

There is already a default bean with the "id" `defaultTranslationWorkflowDerivedContentsStrategy`, that is defined for the `processDefinitionName` "Translation".



```

<bean id="customTranslationWorkflowDerivedContentsStrategy"
class="com.coremedia.translate.workflow.DefaultTranslationWorkflowDerivedContentsStrategy">

```

```
<description>
  A strategy for extracting derived contents from
  the custom translation.xml workflow definition.
</description>
<property name="processDefinitionName" value="customTranslation"/>
<property name="derivedContentsVariable" value="derivedContents"/>
<property name="masterContentObjectsVariable"
value="masterContentObjects"/>
</bean>
```

Example 5.37. Example for a customTranslationWorkflowDerivedContentsStrategy

The bean needs to be customized in the Workflow Server web application, for example with a Blueprint extension module with Maven property `coremedia.project.extension.for` set to `workflow-server`.

Translation Workflow Properties

studio.translation.showPullTranslationStartWindow	
Description	<p>Use this property to show the workflow start dialog in <i>Studio</i> also for translations into the preferred site (pull translations). The pull translation always uses the first available translation workflow. If you have multiple workflow definitions, it might be necessary to select the appropriate workflow definition from the available workflows.</p> <p>Possible values:</p> <ul style="list-style-type: none">• <i>TRUE</i>: Shows the workflow start dialog in <i>Studio</i> also for translations into the preferred site (pull translations).• <i>FALSE</i>: The workflow is started automatically. No workflow start dialog is shown.
Default Value	<i>FALSE</i>
studio.workflow.translation.extendedWorkflow	
Description	<p>Use this property to define the amount of dependent content, that will be shown in a translation workflow window.</p>
Default Value	<i>100</i>

Table 5.23. Translation Workflow Properties

XLIFF Configuration

XLIFF Configuration Properties

The handling of empty translation units during XLIFF import can be configured using the following properties:

`translate.item.include-unchanged-properties`

Description	Configure whether properties that have not changed since last translation are also included in items for translation. Possible values are: <code>true</code> , <code>false</code> .
-------------	--

Default Value	<code>true</code>
---------------	-------------------

`translate.item.transform.failure.mode`

Description	Configure the strictness of the XLIFF Export pre-processing regarding missing property transformers. If mode is <code>fail</code> , the XLIFF export will fail if a property is marked as translatable where no corresponding <code>TranslatePropertyTransformer</code> has been found for. Possible values are: <code>fail</code> , <code>warn</code> , <code>none</code> .
-------------	---

Default Value	<code>fail</code>
---------------	-------------------

`translate.xliff.export.handler.failure.mode`

Description	Configure the strictness of the XLIFF Export regarding missing property export handlers. If mode is <code>fail</code> , the XLIFF export will fail if a property is marked as translatable where no corresponding <code>XliffPropertyExportHandler</code> has been found for. Possible values are: <code>fail</code> , <code>warn</code> , <code>none</code> .
-------------	---

Default Value	<code>fail</code>
---------------	-------------------

`translate.xliff.import.emptyTransUnitMode`

Description	Configure handling of empty trans-unit targets for XLIFF import. Possible values: <ul style="list-style-type: none">• <i>IGNORE</i>: Empty targets are allowed. On import the empty translation unit will replace a possibly non-empty target and thus delete its contents.• <i>FORBIDDEN</i>: No empty targets are allowed.
-------------	--

	<ul style="list-style-type: none"><i>IGNORE_WHITESPACE</i>: Empty targets are only allowed where the matching source is empty or contains only whitespace characters
Default Value	<i>IGNORE_WHITESPACE</i>
<code>translate.xliff.import.ignorableWhitespaceRegex</code>	
Description	Configure the regular expression that determines which characters are counted as ignorable whitespace. This configuration is only used when <code>translate.xliff.import.emptyTransUnitMode</code> is set to <i>IGNORE_WHITESPACE</i> .
Default Value	<code>[\\s\\p{Z}]*</code>
<code>translate.xliff.import.xliffValidationMode</code>	
Description	<p>Configure XLIFF validation behavior.</p> <p>Possible values:</p> <ul style="list-style-type: none"><i>FAIL_ON_WARNING</i>: XLIFF validation will fail if any warnings or above occurred.<i>FAIL_ON_ERROR</i>: XLIFF validation will fail if any errors or above occurred.<i>FAIL_ON_FATAL_ERROR</i>: XLIFF validation will fail if any fatal errors occurred.<i>DISABLED</i>: XLIFF validation is disabled.
Default Value	<i>FAIL_ON_WARNING</i>
<code>translate.xliff.export.excludeContentName</code>	
Description	<p>Configure the flag that determines, whether the name of content in a translation workflow will be excluded in an XLIFF-Export.</p> <div><p>CAUTION</p><p>Including content names into translation may harm your system. Thus, if you set this property to <code>false</code>, you should be aware that for example some settings documents referenced by name or documents like <code>_folderProperties</code> must not get their names translated.</p></div>

Default Value	true
---------------	------

Table 5.24. XLIFF Properties

XLIFF Configuration Beans

In addition to the properties you can customize the following XLIFF beans in your application context:

`translate.xliff.translatableExpressions`

This is a list bean with string entries. Each entry specifies an expression to identify content type properties which should be marked as translatable and thus will be part of the XLIFF Export. The same property types are supported as for the `extensions:translatable` content type model setting (see Chapter 4, *Developing a Content Type Model* in *Content Server Manual* for details).

While it is recommended to use `extensions:translatable` in favor of these expressions, the `translatable-expressions` provide support for nested Struct property value access, which is not possible within the content type model. Thus, the intended use case is to specify selected elements of Struct properties which should be part of the XLIFF file while the Struct property itself is not translatable.

This bean is available through Maven artifact `com.coremedia.cms:cap-translate-item`, which is by default a transitive dependency of *Blueprint Studio* and *Workflow Server*.

Example:

```
<customize:append
  id="blueprint.translate.xliff.translatableExpressions"
  bean="translate.xliff.translatableExpressions">
  <list>
    <value>CMLinkable.localSettings.callToActionCustomText</value>
    <value>CMLinkable.localSettings['entry.with.dots'].childEntry</value>
  </list>
</customize:append>
```

Example 5.38. `translatableExpressions` Configuration Example

Expression Syntax:

The first two elements of the expression define the content type and the property which should be known as (partially) translatable. Following elements define sub-elements within the property. This is currently only supported for Structs. The content type must be the content type which also defines the property.

The expressions support separate properties either by periods or by strings in square brackets. Thus, `CMLinkable.localSettings` is the same as `CMLinkable['localSettings']`.

Limitations:

Using this mechanism to mark properties inside Structs as being translatable works for String and Markup properties. For the latter, only the grammar `coremedia-richtext-1.0` is fully supported.

Alternatively, you can add the bean `RichtextInStructTranslatablePredicate` to your application context to mark *all* richtext markup properties inside Structs as being translatable.

Translation Workflow Studio UI

The possibilities for UI configurations for new custom workflows in Studio are documented within Section 7.23, “Customizing Workflow UI” in *Studio Developer Manual*.

5.6 Workflow Management

In this chapter you will find a description of the predefined workflows as well as the workflow actions that are needed to customize existing workflows or define new ones.

Predefined workflows described in here:

- workflows covering the publication of resources, see [Section 5.6.1, “Publication” \[273\]](#),
- an example translation workflow, see [Section 5.6.2, “Translation Workflow” \[280\]](#),
- a fixed workflow for initially deriving a site from an existing site, see [Section 5.6.3, “Deriving Sites” \[293\]](#).

5.6.1 Publication

In this chapter you will find a description of publication workflows and a description of the publication semantics.

CoreMedia delivers the listed example workflows. But the workflow facilities are not restricted to those features. They can be tailored to fit all types of business processes.

Approval and Publication of Folders and Content Items

A publication synchronizes the state of the *Live Server* with the state of the *Content Management Server*. All actions such as setting up new versions, deleting, moving or renaming files, withdrawing content from the live site require a publication to make the changes appear on the *Live Server*.

What is and what does a publication?

CoreMedia makes a distinction between the publication of structural and of content changes:

- Content-related changes are changes in document versions such as a newly inserted image, modified links, text.
- Structure-related changes are moving, renaming, withdrawing or deleting of resources. So it becomes possible to publish structural changes separately from latest and approved document versions.

For every publication a number of changes is aggregated in a change set. This change set is normally composed in the course of a publication workflow. The administrator and other users with appropriately configured editors can also execute a direct publication, which provides a simpler, although less flexible means of creating a change set.

Change Set in Direct Publications

When performing a direct publication, the change set is primarily based on the set of currently selected resources or on the single currently viewed resource. As the set of resources does not give enough information for all possible types of changes, three rules apply:

- You cannot publish movements and content changes separately. Whenever applicable, both kinds of changes are included in the change set.
- When a document is marked for deletion or for withdrawal, new versions of that document are not published.
- If the specific version to be published is not explicitly selected, the last approved resource version is included in the change set.

There are also some automated extension rules for the change set, which modify the set of to-be-published resources itself. These rules can be configured in detail. Ask your Administrator about the current settings.

- When new or modified content is published and links to an as yet unpublished resource, the unpublished resource is included in the change set. Depending on the configuration, also recursively linked documents can be included in the change set. Target documents that are linked via a weak link property are not included in the change set.
- When the deletion of a folder is published, all directly and indirectly contained resources are included in the change set.
- When the withdrawal of a folder is published, all directly and indirectly contained published resources are included in the change set.
- When the creation, movement, or renaming of a resource in an unpublished parent folder is published, that folder is included in the change set.

Preconditions

Preconditions for a successful publication are:

- all path information concerning the resource has to be approved too: if the resource is located in a folder never published before, this folder has to be published with the resource. So, add it to the change set or publish the folder before.
- withdrawals and deletions must be approved before publication.
- all documents linked to from a document which is going to be published have to be already published or included in the change set. This is because a publication that would cause dead links will not be performed. This rule does not apply for weak link properties.

Preconditions for a successful publication

- a document which is going to be deleted must not be linked to from other documents or these documents have to be deleted during the same publication. This rule does not apply for weak link properties.

Status and action on the <i>Content Management Server</i>	Effect on the Live Server on publication
<p>A version of the document does not yet exist on the <i>Live Server</i>. The document is not marked for deletion.</p> <p>You approve the version.</p>	<p>The approved version is copied to the <i>Live Server</i>.</p>
<p>The last approved version of a document already exists on the <i>Live Server</i>. The document is not marked for deletion.</p> <p>You start a new publication without any further preparation.</p>	<p>No effect on the <i>Live Server</i>.</p>
<p>The document is published and is not marked for deletion. It therefore exists on both servers.</p> <p>You rename the document and approve the change.</p>	<p>The document is renamed.</p>
<p>The document is published and is not marked for deletion. It therefore exists on both servers.</p> <p>You move the document and approve the change.</p>	<p>The document is moved.</p>
<p>The document is published. It therefore exists on both servers. No links to this document exist.</p> <p>You mark the document for withdrawal and approve the change.</p>	<p>The document is destroyed on the Live Server.</p>
<p>The document is published. It therefore exists on both servers. No links to this document exist.</p> <p>You mark the document for deletion and approve the change.</p>	<p>The document is destroyed on the <i>Live Server</i>. The document is moved into the recycle bin on the <i>Content Management Server</i>.</p>
<p>The document is published. It therefore exists on both servers. Links to this document from other published documents exist.</p> <p>You mark the document for deletion and approve the change.</p>	<p>The deletion cannot be published, since an invalid link would be created. A message is displayed in the publication window. Remove the link in the other document and publish again.</p>

Status and action on the <i>Content Management Server</i>	Effect on the Live Server on publication
<p>The document is published. It therefore exists on both servers. Weak links to this document from other published documents exist.</p> <p>You mark the document for deletion and approve the change.</p>	<p>The document is destroyed on the <i>Live Server</i>. The document is moved into the recycle bin on the <i>Content Management Server</i>.</p>

Table 5.25. Publishing documents: actions and effects

Status and action on the <i>Content Management Server</i>	Effects on the Live Server on publication
<p>The folder is published and is not marked for deletion. It therefore exists on both servers.</p> <p>You rename the folder and approve it.</p>	<p>The folder is renamed.</p>
<p>The folder is published and is not marked for deletion. It therefore exists on both servers.</p> <p>You move the folder and approve the change.</p>	<p>The folder is moved.</p>
<p>The folder is not published and not marked for deletion.</p> <p>You approve the folder.</p>	<p>The folder is created on the <i>Live Server</i>.</p>
<p>The folder is published.</p> <p>You mark it for withdrawal. When queried, you acknowledge the mark for withdrawal of all contained resources. You approve the change.</p>	<p>The folder is destroyed on the <i>Live Server</i>. The withdrawal can only succeed if all resources on the <i>Live Server</i> or <i>Content Management Server</i> that are contained in the folder, and all published resources that link to this folders content via a non-weak link property, are also contained in the change set.</p>
<p>The folder is published.</p> <p>You mark it for deletion. When queried, you acknowledge the mark for deletion of all contained resources. You approve the change.</p>	<p>The folder is destroyed on the <i>Live Server</i>. The folder is moved to the recycle bin on the <i>Content Management Server</i>. The deletion can only succeed if all resources on the <i>Live Server</i> or <i>Content Management Server</i> that are contained in the folder, and all published resources that link to this folders content via</p>

Status and action on the <i>Content Management Server</i>	Effects on the Live Server on publication
	a non-weak link property, are also contained in the change set.

Table 5.26. Publishing folders: actions and effects

Special cases

Special cases

Please keep in mind that:

- Older versions cannot be published.
Example: if a version No. 4 had already been published it is not possible to publish version No. 3 thereafter. To do so, create a version No. 5 from No. 3.
- During a deletion, a resource that has not been published yet is moved to the recycle bin immediately.

In addition, consult the previous tables for effects of a publication depending on the state of the resource. For all examples it is assumed that you have appropriate rights to perform the action.

Withdrawing Publications and Deleting Resources

Delete and withdraw resources

There is only one fundamental difference between withdrawal of publications and deletion: a withdrawal affects only the *Live Server*, whereas the deletion of a resource - folder or document - causes the resource to be moved into the trash folder on the *Content Management Server*.

Before a withdrawal or deletion can be published as described before, a mark for withdrawal or for deletion must be applied using the appropriate menu entries or tool bar buttons. In the case of folders, the contained resources are affected, too. If you have marked a resource for deletion and withdrawal, then the deletion will be executed.

- When a folder is marked for deletion, all contained published resources are marked for deletion, too. Not published resources are immediately moved into the recycle bin without requiring you to start a publication.
- When a folder is marked for withdrawal, all contained published resources are marked for withdrawal, too.
- When a mark for withdrawal or deletion of a folder is revoked, this also affects all contained resources with the same mark.
- If you use direct publication and approve a folder that is marked for withdrawal deletion, that approval is implicitly extended to the contained resources that are also marked for withdrawal or deletion.
- Disapprovals extend to contained resources in the same way.

Predefined Publication Workflows

The predefined workflows for the approval and publication of resources are described in the following table. These workflows can be uploaded using `cm upload -n <filename>`. You can examine their definition and use them as examples for your own definitions, by downloading an uploaded definition using `cm download <ProcessName>`.

Workflow	Definition name
simple publication	Process StudioSimplePublication defined in studio-simple-publication.xml
2-step publication	Process StudioTwoStepPublication defined in studio-two-step-publication.xml

Table 5.27. Predefined publication workflow definitions

Publication workflow steps

The following table compares the working steps which are covered by the predefined workflows.

Step	simple publication	2-step publication
1.	A user creates the workflow with all necessary resources.	A user creates the workflow with all necessary resources.
2.	The resources are published (and implicitly approved) in one step, performed by the same user, who needs 'approve' and 'publish' rights.	A second user (needs 'approval' and 'publish' rights) can explicitly approve resources. In <i>Studio</i> , the second user may also modify the resources before
3.		Publication will be executed when finishing the task after all resources in the change set have been approved.
4.		(If not, the workflow is returned to its 'composer')

Table 5.28. Predefined publication workflow steps

Features of the Publication Workflows

The predefined publication workflows have some features in common, which are described in the following:

Users and Groups

In order to execute tasks within workflows, users have to be assigned to special groups. In the predefined publication workflows, these are the following:

1. *composer-role*: to be able to create (and start) a publication workflow and compose a change set
2. *approver-role*: to be able to approve the resources in the change set
3. *publisher-role*: to be able to publish the resources in the change set

Special groups can be defined and linked to the workflow via the **Grant** element in the workflow definition file.

Read more about users, groups and administration in the *Content Server Manual*.

Note that, when all eligible users for a task reject that task, the task is again offered to all eligible users. So if you are the only user for an *approver-role* group and you start a publication workflow, the second step of the workflow will be escalated. That is because you cannot be the composer and the approver of a resource - and there is no other user than you.

Basic Steps in a Publication Workflow

After a user has created one or more documents, these documents should be proofread, approved and published in a workflow:

1. The user (not necessarily the user who did the editing) starts a workflow. If he selects resources at starting time, these resources will be added to the change set and the compose task will be accepted automatically. Otherwise, he has to add the resources to the change set later.
2. The user completes the 'compose' task.
3. The task 'approve' is automatically offered to all appropriate users (members of the *approver-role* group, but not to the composer - even if he is a member of this group). Somebody accepts the task and approves the resources.

The user has the following options:

option A	option B	option C	option D
The user accepts the task, approves the resource(s)and finishes the task. All resources are approved.	The user accepts the task, does not approve all resource(s) and finishes the task	The user rejects the task.	The user accepts the task but delegates it to somebody else.
The task 'Publication' is offered to all members of the group <i>publisher-role</i> .	The change set is sent back to the user who completed the 'compose' task.	The task is offered all other members of the group approver-role.	The task is automatically accepted by this user.

Table 5.29. User options.

5.6.2 Translation Workflow

A translation workflow can be used to communicate changes in the project of a master site to the derived sites.

CoreMedia Blueprint provides one template translation workflow named *Translation* in the file `translation.xml` in the `wfs-tools-application` module. The workflow is built around an empty action, the `SendToTranslationServiceAction` in the `workflow-lib` module, which is supposed to implement the sending / receiving of contents to / from a translation agency. Without an implementation of this action, the workflow can still be used for manual in-house translation, possibly in conjunction with XLIFF download/upload.

Roles and Rights

The translation workflow process is based on two roles defined for *CoreMedia Content Cloud*'s Multi-Site concept:

- The group `translation-manager-role` contains all users that are allowed to start a translation workflow.

The name of this group has to be configured in the property `translationManagerRole` of the `SiteModel` [see [section "Site Model" \[238\]](#)]. After changing this property, you have to upload the workflows again, because uploading persists the current property value.

- The site manager groups define the users who may accept translation workflows for the content of a site.

[Groups and Rights Administration for Localized Content Management \[233\]](#) describes how to set this property for every site.

Workflow Lifecycle

As described in [Section "Roles and Rights" \[280\]](#), the translation managers start the translation workflow for a set of new or changed contents from the Control Room. Therefore, a new `Process` instance will be created for every site that has been selected as a translation target.

At first, the `Process` instances both run two `AutomatedTasks` that retrieve the manager group and collect / create the derived contents for the target site. For details see [Section "Predefined Translation Workflow Actions" \[282\]](#).

The following `UserTask` called `Translate` is used to let the user choose a next step. This is done by selecting a next step in the radio group of the `workflowForm`. The selected value will then be set as value for the `translationAction` process variable. This variable is then used in a `Switch` task to choose the successor task.

These successor tasks are:

- `SendToTranslationService`: Send / retrieve content to / from translation agency (has to be implemented in the project)
- `Rollback`: Cancel the translation and rollback changes that may have been made to the target content. (E.g.: The `GetDerivedContentsAction` may have created content in the target site derived from the provided master content.)
- `Complete`: Update the `masterVersion` of the target content to indicate, that the translation is completed. This can be used, for example when the user translated the content manually.

While the `Rollback` and `Complete` tasks finish the process, the `SendToTranslationService` task has another `UserTask` successor called `Review`. This task simply gives the user an opportunity to check the content imported from the translation agency. For details on the Actions behind these tasks see [Section "Predefined Translation Workflow Actions" \[282\]](#).

Configuration and Customization

The example translation workflow is meant to be configured to your needs. You might define multiple translation workflows, like translation via translation agency or manual translation performed by the site managers.

The only restriction is that every translation workflow needs a process variable `subject` of type `String`, which will be set by the framework.

In order to reliably track content that is currently "in translation", you also need to define, configure and regularly invoke an instance of the `com.coremedia.translate.workflow.impl.CleanInTranslation` class. An example definition is included in the blueprint source in the `com.coremedia.blueprint.workflow.boot.BlueprintWorkflowServerAutoConfiguration` file, which you may have to adapt.

Be aware, that changes in the process definition will probably lead to changes in the UI, too. If you want to change only small bits of the provided translation workflow like adding another user-selectable `translationAction` and `Task`, this can be done pretty easily through configuration of the `defaultTranslationWorkflowDetailForm` inside the `ControlRoomStudioPlugin`.

But if want to use a workflow completely different to the one provided, be prepared to write your own implementations of the `workflowForms` and start panel used to display your workflow in *Studio*.

For details on customizing workflows see the Workflow Manual. For details on customizing the *Studio* UI for the translation workflows see [Section "Translation Workflow Studio UI" \[272\]](#).

Predefined Translation Workflow Actions

This section describes various actions that can be used to define a translation workflow.

- [Section "GetDerivedContentsAction" \[283\]](#) describes an action that computes, and if necessary creates derived contents from a given set of master contents.
- [Section "CreateTranslationTreeData" \[284\]](#) describes an action that computes the data for the TranslationTree in the Studio Client.
- [Section "FilterDerivedContentsAction" \[285\]](#) describes an action that filters previously computed derived contents.
- [Section "GetSiteManagerGroupAction" \[286\]](#) describes an action that determines a site manager group and stores it in a process variable. If the process variable is

atomic, only the first given site manager group will be set. It is recommended to use an aggregation variable as target, though.

- [Section “ExtractPerformerAction” \[287\]](#) describes an action that identifies the user who executes that current task and stores a user object in a process variable.
- [Section “AutoMergeTranslationAction” \[288\]](#) describes an action that automatically updates properties of derived contents after changes in their master content.
- [Section “AutoMergeSyncAction” \[290\]](#) describes an action that automatically updates properties of derived contents after changes in their master content in the context of a synchronization workflow.
- [Section “CompleteTranslationAction” \[291\]](#) describes an action that finishes a manual translation process.
- [Section “RollbackTranslationAction” \[292\]](#) describes an action that rolls back a translation process, possibly deleting spurious content.

GetDerivedContentsAction

This action retrieves all derived contents from a given list of master contents. If a document already exists in the target site and its `masterVersion` equals to the current version of the master content, it will be ignored for the workflow. Documents that do not exist will be created in the corresponding folder of the target site. All derived contents will be marked as being in translation.

`targetSiteIdVariable`

Required yes

Description The name of the variable that contains the id of the target site

`masterContentObjects`

Required yes

Description The name of the variable that contains the list of content objects in the master site

`derivedContentsVariable`

Required no

Description The name of the variable into which a list of all derived contents is stored

`createdContentsVariable`

Required	no
Description	The name of the variable into which a list of all newly created contents is stored. If the workflow is subsequently aborted, these contents can be deleted by the action described in Section "RollbackTranslationAction" [292]

Table 5.30. Attributes of *GetDerivedContentsAction*

```
<Variable name="siteId" type="String"/>
<AggregationVariable name="masterContentObjects" type="Resource"/>
<AggregationVariable name="derivedContents" type="Resource"/>
<AggregationVariable name="createdContents" type="Resource"/>
...

<AutomatedTask name="GetDerivedContents" successor="FollowUpAction">
  <Action class="com.coremedia.translate.workflow.GetDerivedContentsAction"
    masterContentObjects="masterContentObjects"
    derivedContentsVariable="derivedContents"
    createdContentsVariable="createdContents"
    targetSiteIdVariable="siteId"/>
</AutomatedTask>
```

Example 5.39. Usage of *GetDerivedContentsAction*

CreateTranslationTreeData

This Action will calculate the data for the TranslationTree.mxml Studio component. As a result two maps will be created and stored in the process:

- A map that groups the derived content by its locale
- A map that groups each derived content by its master version

```
translationTreeDataVariable
```

Required	yes
Description	The name of the process variable where the map of the derived contents, grouped by their locale is stored as a blob.

```
premularConfigDataVariable
```

Required	yes
Description	The name of the process variable where the map of the masterVersions, grouped by their derived content is stored as a blob.

```
masterContentObjectsVariable
```

Required	yes
Description	The name of the variable that contains the list of content objects in the master site.
derivedContentsVariable	
Required	no
Description	The name of the variable into which a list of all derived contents is stored.

Table 5.31. Attributes of CreateTranslationTreeData

```
<AggregationVariable name="masterContentObjects" type="Resource"/>
<AggregationVariable name="derivedContents" type="Resource"/>
<Variable name="translationTreeData" type="Blob"/>
<Variable name="premularConfigData" type="Blob"/>
...

<AutomatedTask name="CreateTranslationTreeData"
successor="CheckIfSelfAssigned">
  <Action
class="com.coremedia.translate.workflow.CreateTranslationTreeDataAction"
    masterContentObjectsVariable="masterContentObjects"
    derivedContentsVariable="derivedContents"
    translationTreeDataVariable="translationTreeData"/>
  </AutomatedTask>
```

Example 5.40. Usage of CreateTranslationTreeDataAction

FilterDerivedContentsAction

This action is supposed to follow up `GetDerivedContentsAction`. It filters the derived contents in two ways.

- It checks for each content in the given `derivedContents` whether the content's `masterVersion` is more recent than the corresponding version in the given `masterContentObjects`. In this case, the content is excluded from the `derivedContents`. If a `skippedContentsVariable` is given, all of these excluded contents are stored under this variable of the corresponding process.
- For all remaining contents from `derivedContents`, it checks whether the content has its `ignoreUpdates` property set (see `ContentObject SiteAspect#getIgnoreUpdates()`). If so, this content is also excluded from the `derivedContents` (but not stored under `skippedContentsVariable`).

```
masterContentObjects
```

Required	yes
Description	The name of the variable that contains the list of content objects in the master site
derivedContentsVariable	
Required	yes
Description	The name of the variable into which a list of all derived contents is stored
skippedContentsVariable	
Required	no
Description	The name of the variable into which the list of skipped contents (because of outdated master content object) is stored.

Table 5.32. Attributes of FilterDerivedContentsAction

```
<Variable name="siteId" type="String"/>
<AggregationVariable name="masterContentObjects" type="Resource"/>
<AggregationVariable name="derivedContents" type="Resource"/>
<AggregationVariable name="skippedContents" type="Resource"/>
...

<AutomatedTask name="StartSyncFromParentToTarget"
successor="CheckIfDerivedContentsEmpty">
  <Action class="com.coremedia.translate.workflow.GetDerivedContentsAction"
    masterContentObjectsVariable="masterContentObjects"
    derivedContentsVariable="derivedContents"
    createdContentsVariable="createdContents"
    targetSiteIdVariable="siteId"/>
  <Action class="com.coremedia.translate.workflow.FilterDerivedContentsAction"
    masterContentObjectsVariable="masterContentObjects"
    derivedContentsVariable="derivedContents"
    skippedContentsVariable="skippedContents"/>
</AutomatedTask>
```

Example 5.41. Usage of FilterDerivedContentsAction

GetSiteManagerGroupAction

This action is used to determine the user groups that are responsible for managing the site. The names of these groups are defined in the property `siteManagerGroup` of every site indicator. As this property is not required, the group administrators will be used per default.

Note, that the action transparently deals with atomic and aggregation variables as target variable. If the target variable is atomic, only the first group in `siteManagerGroup` will be taken into account.

siteVariable	
Required	yes
Description	The name of the variable that contains the id of the site
siteManagerGroupVariable	
Required	no
Description	The name of the variable into which the site manager groups are stored

Table 5.33. Attributes of `GetSiteManagerGroupAction`

```
<Variable name="siteId" type="String"/>
<Variable name="siteManagerGroup" type="Group"/>
...
<AutomatedTask name="GetTargetSiteManagerGroup" successor="FollowUpAction">
  <Action class="com.coremedia.translate.workflow.GetSiteManagerGroupAction"
    siteVariable="siteId"
    siteManagerGroupVariable="siteManagerGroup"/>
</AutomatedTask>
```

Example 5.42. Usage of `GetSiteManagerGroupAction`

ExtractPerformerAction

To perform an `AutomatedTask` with the same performer used in a previous `UserTask`, you can store the performer of the `UserTask` to the given workflow variable.

performerVariable	
Required	no
Description	The name of the variable into which the performer of the current user task is stored

Table 5.34. Attributes of `ExtractPerformerAction`

```
<Variable name="performer" type="User"/>
...
<UserTask name="Translate" successor="FollowUpAction">
  ...
  <EntryAction class="com.coremedia.translate.workflow.ExtractPerformerAction"
    performerVariable="performer"/>
  ...
</UserTask>
```

Example 5.43. Usage of ExtractPerformerAction

AutoMergeTranslationAction

This action automatically updates properties of derived contents after changes in their master content since its last translation. See also the API documentation in [AutoMergeTranslationAction](#) and [Content Type Model - Properties for Translation \[244\]](#) for the behavior of the automerge feature.

performerVariable	
Required	yes
Description	The name of the variable that contains the user in whose name this action performed. Typically, the user has been retrieved previously by the action described in Section "ExtractPerformerAction" [287] .
derivedContentsVariable	
Required	yes
Description	The name of the variable that contains all translated documents.
masterContentObjectsVariable	
Required	yes
Description	The name of the variable that contains all master content objects.
resultVariable	
Required	yes

Description	The name of the result variable to store derived contents in, whose properties could not be updated automatically.
autoMergePredicateFactoryName	
Required	no
Description	<p>The name of a custom Spring bean that implements interface <code>AutoMergePredicateFactory</code> and that is used to decide which content properties are updated automatically.</p> <p>If this attribute is not specified, the Spring bean with name <code>defaultAutoMergePredicateFactory</code> is used.</p>
autoMergeStructListMapKeyFactoryName	
Required	no
Description	<p>The name of a custom Spring bean that implements the interface <code>AutoMergeStructListMapKeyFactory</code> and that is used to select the merge algorithm for nested struct list properties. For some struct lists, like the placements of a page grid, a better merge algorithm can be used, which enables automatic updates of a derived content for more types of changes. To this end, the merge algorithm can use a selected property of the struct values to find corresponding values in master and derived contents. The default implementation <code>DefaultAutoMergeStructListMapKeyFactory</code> is configured in the Blueprint Spring application context for some standard properties like the page grid placements.</p> <p>If this attribute is not specified, the default implementation <code>DefaultAutoMergeStructListMapKeyFactory</code> is used, which can be configured in the Spring application context.</p>
translatablePredicateName	
Required	no
Description	<p>The name of a custom Spring bean that implements the interface <code>TranslatablePredicate</code> and that is used to decide if a property is translatable. If the value is an empty string, then an instance of <code>BySchemaAttributeTranslatablePredicate</code> will be used. Translatable properties are handled differently by the merge algorithm, most importantly there won't be warnings about merge conflicts, if the property has also changed in the derived content, because that's the expected state for translated properties.</p>

If this attribute is not specified, the Spring bean with name `translatablePredicate` is used.

Table 5.35. Attributes of `AutoMergeTranslationAction`

```
<AggregationVariable name="derivedContents" type="Resource"/>
<AggregationVariable name="masterContentObjects" type="Resource"/>
<AggregationVariable name="autoMergeConflicts" type="Resource"/>
<Variable name="performer" type="User"/>
...
<UserTask name="Translate" successor="FollowUpAction">
  ...
  <EntryAction
class="com.coremedia.translate.workflow.AutoMergeTranslationAction"
  derivedContentsVariable="derivedContents"
  masterContentObjectsVariable="masterContentObjects"
  resultVariable="autoMergeConflicts"
  performerVariable="performer"/>
  ...
</UserTask>
```

Example 5.44. Usage of `AutoMergeTranslationAction`

AutoMergeSyncAction

This action extends the `AutoMergeTranslationAction` and allows to configure a merge strategy. See Javadoc of [AutoMergeSyncAction](#) for details.

mergeStrategyVariable	
Required	no
Description	The name of the variable into which the merge strategy bean name is stored. The bean name refers to a bean in the Spring application context that is an implementation of <code>ThreeWayMerge</code> .

Table 5.36. Attributes of `AutoMergeSyncAction`

```
<AggregationVariable name="derivedContents" type="Resource"/>
<AggregationVariable name="masterContentObjects" type="Resource"/>
<AggregationVariable name="autoMergeConflicts" type="Resource"/>
<Variable name="performer" type="User"/>
<Variable name="mergeStrategy" type="String"/>

<AutomatedTask name="Synchronize">
  ...
  <Action
class="com.coremedia.translate.workflow.synchronization.AutoMergeSyncAction"
```

```
autoMergePredicateFactoryName="allMergeablePropertiesPredicateFactory"
    derivedContentsVariable="derivedContents"
    masterContentObjectsVariable="masterContentObjects"
    resultVariable="autoMergeConflicts"
    performerVariable="performer"
    escalateOnConflict="true"
    mergeStrategyVariable="mergeStrategy"/>
</AutomatedTask>
```

Example 5.45. Usage of AutoMergeSyncAction

A custom merge strategy for a synchronization workflow can be configured by either by implementing the interface `ThreeWayMerge` or `SyncThreeWayMerge` and adding the bean to the Spring application context. The interface `SyncThreeWayMerge` allows control about whether a property needs to be merged or updated.

The bean name can be passed to the synchronization workflow via the variable `mergeStrategy`. How to add a custom merge strategy to the studio client is decribed in Section 7.23.4, "Synchronization-Specific Customizations" in *Studio Developer Manual*.

CompleteTranslationAction

After successfully completing a translation workflow, the `masterVersion` of all translated contents will be set to the current version of their masters.

performerVariable	
Required	yes
Description	The name of the variable that contains the user in whose name this action performed. Typically, the user has been retrieved previously by the action described in Section "ExtractPerformerAction" [287] .
derivedContentsVariable	
Required	yes
Description	The name of the variable that contains all translated documents.
masterContentObjectsVariable	
Required	yes

Description	The name of the variable that contains all master content objects.
-------------	--

Table 5.37. Attributes of CompleteTranslationAction

```
<Variable name="performer" type="User"/>
<AggregationVariable name="targetContents" type="Resource"/>
...

<AutomatedTask name="Complete" successor="Finish">
  <Action class="com.coremedia.translate.workflow.CompleteTranslationAction"

    derivedContentsVariable="derivedContents"
    masterContentObjectsVariable="masterContentObjects"
    performerVariable="performer"/>
</AutomatedTask>
```

Example 5.46. Usage of CompleteTranslationAction

RollbackTranslationAction

If the master content is not needed in the target site, the translation workflow can be aborted with the RollbackTranslationAction. In this case all documents and folders that were created by the [Section "GetDerivedContentsAction" \[283\]](#) will be deleted. In addition, all target contents will be marked as no longer being in translation.

contentsVariable	
Required	yes
Description	The name of the variable that contains all documents and folders that have to be deleted during while rolling back the translation
derivedContentsVariable	
Required	no
Description	The name of the variable that contains all translated documents. Defaults to "derived-Contents".
masterContentObjectsVariable	
Required	no

Description	The name of the variable that contains all master content objects. Defaults to "master-ContentObjects".
-------------	---

Table 5.38. Attributes of RollbackTranslationAction

```
<AggregationVariable name="createdContents" type="Resource"/>
...
<AutomatedTask name="Rollback" successor="Finish">
  <Action class="com.coremedia.translate.workflow.RollbackTranslationAction"
    derivedContentsVariable="derivedContents"
    masterContentObjectsVariable="masterContentObjects"
    contentsVariable="createdContents"/>
</AutomatedTask>
```

Example 5.47. Usage of RollbackTranslationAction

5.6.3 Deriving Sites

A predefined workflow exists to derive an entire site from an existing site. The derive-site workflow cannot be adapted and is available as a built-in workflow from the module `translate-workflow`. To upload the derive-site workflow, use `cm upload -n /com/coremedia/translate/workflow/derive-site.xml` on the command line.

Typically, the derive site workflow is started as a background process from the sites window of *CoreMedia Studio*. The workflow can be started by all members of the translation manager group, as configured in the property `translationManagerRole` of the `SiteModel` (see [section "Site Model" \[238\]](#)). After changing this property, you have to upload the workflow again, because uploading persists the current property value.

Translation Workflow Robot

Actions performed while deriving a new site are performed as `translation-workflow-robot`. As last step when deriving a site, this user will assign possibly missing rights to the chosen site-managers-groups. This requires supervise permissions to the `/Sites` folder.

For details see [Groups and Rights Administration for Localized Content Management \[233\]](#).



5.6.4 Synchronization Workflow

A predefined workflow exists to synchronize content of an existing site to derived synchronization sites. The synchronization workflow cannot be adapted and is available as a built-in workflow from the module `translate-workflow`.

To upload the synchronization workflow, use

```
cm upload -n /com/coremedia/translate/workflow/synchronization.xml
```

on the command line.

The workflow can be started by all members of the translation manager group, as configured in the property `translationManagerRole` of the `SiteModel` (see [section "Site Model" \[238\]](#)). After changing this property, you have to upload the workflow again, because uploading persists the current property value.

6. Editorial and Backend Functionality

CoreMedia Content Cloud enhances *CoreMedia CMS* with additional functionality that is described in the following sections:

- **Section 6.1, “Studio Enhancements” [296]** describes extensions to *CoreMedia Studio* as the unified editing platform. The editorial usage of the features is described in the Studio User Manual.
- **Section 6.2, “CAE Enhancements” [325]** describes extensions to the *Content Application Engine* the delivery module of *CoreMedia Content Cloud*.
- **Section 6.3, “Elastic Social” [331]** describes extensions to *CoreMedia Elastic Social* that are integrated in *CoreMedia Content Cloud*. The standard functionality of *Elastic Social* is described in the Elastic Social Manual.
- **Section 6.4, “Adaptive Personalization” [346]** describes extensions to *CoreMedia Adaptive Personalization* that are integrated in *CoreMedia Content Cloud*. The standard functionality of *Adaptive Personalization* is described in the Adaptive Personalization Manual.
- **Section 6.5, “Third-Party Integration” [356]** describes the integration of third-party components, such as Optimizely, into *CoreMedia Content Cloud*.

These modules are integrated into *CoreMedia Content Cloud* and the example websites and add extended functionality to their default features.

6.1 Studio Enhancements

CoreMedia Blueprint enhances *CoreMedia Studio* with plugins for better usage. This ranges from improved content editors such as the image list editor, which shows a preview of a selected image, up to a complete taxonomy management.

- Document editors

Content query form, see [Section 6.1.1, "Content Query Form" \[296\]](#).

- Library, see [Section 6.1.5, "Library" \[301\]](#).
- Bookmarks, see [Section 6.1.6, "Bookmarks" \[303\]](#).
- External preview, see [Section 6.1.7, "External Preview" \[303\]](#).
- Content creation, see [Section 6.1.9, "Content Creation" \[305\]](#).
- Create content from template, see [Section 6.1.10, "Create from Template" \[311\]](#).
- Site selection, see [Section 6.1.13, "Site Selection" \[315\]](#).
- Upload dialog, see [Section 6.1.14, "Upload Files" \[316\]](#).
- Upload content to Salesforce Marketing Cloud, see [Section 6.1.16, "Uploading Content to Salesforce Marketing Cloud" \[323\]](#).

6.1.1 Content Query Form

Rather than having to maintain a collection of content items manually, you might want to just specify a search rule that updates a list of content items dynamically as new content gets added to the system. The content query form provides a convenient interface to edit such rules.

For example, you can specify a rule that finds the latest five articles from your site's sports subsection, and displays them on a "latest sports news" section of your site's front page.

In the standard configuration of *Blueprint*, you can use the query form to filter for content items according to the following aspects:

- The content item's document type
- The channel the content item belongs to
- The content item's modification date
- Whether the content item is tagged with a given location or subject tag
- Whether the content is tagged with a tag determined from the context (see [Section "Creating Content Queries" in *Studio User Manual*](#) for more details).

Furthermore, you can order the result set by different criteria, and you can specify a maximum number of hits in order to ensure proper layout on a column-based page design, for example.

Support for dynamic content queries is bundled in the *Studio* plugin, and the main component to use is `ContentQueryForm.mxml`. You can use the editor as shown in the following example.

```
<dcqe:ContentQueryForm bindTo="{config.bindTo}"
    itemId="contentQueryForm"
    forceReadOnlyValueExpression=
        "{config.forceReadOnlyValueExpression}"
    queryPropertyName="localSettings"
    documentTypesPropertyName="documenttype"
    sortingPropertyName="order">

    <dcqe:plugins>
        <ui:VerticalSpacingPlugin modifier=
            "{SpacingBEMEntities.VERTICAL_SPACING_MODIFIER_200}"/>
    </dcqe:plugins>
    <dcqe:conditions>
        <dcqe:ModificationDateConditionEditor bindTo="{config.bindTo}"
            propertyName="freshness"
            group="attributes"
            documentTypes=
                "{['CMArticle','CMVideo','CMPicture','CMGallery','CMChannel']}"
            forceReadOnlyValueExpression="{config.forceReadOnlyValueExpression}"
            sortable="true">
            <dcqe:timeSlots>
                <fx:Object name="sameDay"
                    text="{resourceManager.getString(
                        'com.coremedia.blueprint.base.queryeditor.QueryEditor',
                        'DCQE text modification_date_same_day')}"
                    expression="TODAY"/>
                <fx:Object name="sevenDays"
                    text="{resourceManager.getString(
                        'com.coremedia.blueprint.base.queryeditor.QueryEditor',
                        'DCQE text modification_date_seven_days')}"
                    expression="7 DAYS TO NOW"/>
                <fx:Object name="thirtyDays"
                    text="{resourceManager.getString(
                        'com.coremedia.blueprint.base.queryeditor.QueryEditor',
                        'DCQE text modification_date_thirty_days')}"
                    expression="30 DAYS TO NOW"/>
            </dcqe:timeSlots>
        </dcqe:ModificationDateConditionEditor>
        ...
    </dcqe:conditions>
</dcqe:ContentQueryForm>
```

Example 6.1. Using the content query form

In the example, the editor is configured to allow only for a single condition (a content item's modification date). You may combine the existing condition editors - there are predefined conditions for context, date ranges, and taxonomy links - or even write your own condition editors by extending `ConditionEditorBase.as`. Each condition editor provides the user interface for editing the respective condition, and must persist the actual search query fragment in a string property that will be written to the respective struct property. Also, all condition editors support the configuration of a list of document types that this condition may apply to. See the API documentation for the package

`com.coremedia.blueprint.base.queryeditor.conditions` for details.

When rendering the result of a search query in your CAE application, you can use `SettingsStructToSearchQueryConverter.java` to convert the search component that the editor stores in the struct property to an actual search query. See `CMQueryListImpl.java` for an example.

The screenshot shows the 'Content Query Form' in the CoreMedia Content Cloud interface. The form is divided into several sections:

- Conditions**: A tabbed interface with 'Conditions', 'Content', and 'Metadata' tabs. The 'Conditions' tab is active.
- Selection of Content Types**: A section with checkboxes for 'All', 'Articles' (checked), 'Videos', 'Pictures', and 'Galleries'.
- Search Query**: A section with a 'Delete All Conditions' link and a 'Context' box. The 'Context' box contains 'Events Page' and a '+ Add content by dragging it from the Library here.' button. Below the context box is a 'Tag (Subject)' box with a dropdown menu showing 'Article Type' and 'News', and a 'Events' tag. Below the tag box is an 'Add Condition:' section with a 'Choose' dropdown and a 'Show Help' link.
- Sorting of the Search Results**: A section with a dropdown menu for 'modification date', a 'descending' order selector, and a 'There should be 4 search results in the list.' field.

Figure 6.1. Content Query Form

6.1.2 Call-to-Action Button

If you use teasers in your website, you want to animate the users to a specific action. To make this more explicit, *Brand Blueprint* renders a button on a teaser with a configurable text (see Figure 6.3, "Call-to-Action button in teaser view" [299]). By default, this text reads "Learn more".

▼ Call-to-Action-Button

☐ No Call-to-Action Button

☒ Use Default Call-to-Action Label

☐ Use Custom Call-to-Action Label

Enter a custom call-to-action-button label.

Figure 6.2. Call-to-Action-Button editor

You can either use the default text, define a content specific text or render no button.




Figure 6.3. Call-to-Action button in teaser view

6.1.3 Media Player Configuration

CoreMedia CMS offers the possibility to configure player settings of certain media files in a site. Player settings for Video and Audio contents can be configured in the *Video Options* and *Audio Options* panels of Video and Audio document forms.

▼ Video Options

☒ Autoplay

☐ Mute

☐ Loop

☐ Hide Controls

Figure 6.4. Video Options panel in the DocumentForm of a Video content

NOTE

Please note, that this configuration can be overwritten in the theme's FreeMarker templates. E.g., a setting a player's loop configuration in *CoreMedia Studio* will have no impact for media in a hero teaser if the template for hero teasers sets the loop option explicitly.



Configuration of media files

The following options can be enabled by checking the corresponding checkboxes in the document form of the content item. The configuration will be saved in the content's local settings struct:

Video player settings

- Autoplay
- Mute
- Loop
- Hide Controls

Audio player settings

- Autoplay
- Loop

6.1.4 Displayed Date

When you change already published content, you have to publish this change. Of course, the publication changes the publication date of the content. However, you may want that this content always shows the date of the initial publication (or any other fixed date). To do so, you can set a custom displayed date. *Studio* contains an editor for a displayed date for all CMLinkable types.

This data can also be used, to sort results of a `Query List` (see [Section 6.1.1, “Content Query Form” \[296\]](#)).

▼ Displayed Date

☒ Publication Date

☐ Custom Date

Date

at

Time

▼

Europe - Berlin

▼

[Reset](#)

Figure 6.5. Displayed Date editor

You can either choose that the date of the last publication is used or that a fixed date is shown.




Figure 6.6. Setting a Custom Date

6.1.5 Library

The library plugin uses the extension points of the *Studio* library to extend some basic features of it and to add some new ones.




Figure 6.7. Image Gallery Creation Button




Figure 6.8. Image Gallery Creation Dialog

The image gallery creation dialog allows the user to create a new gallery document from an image selection. The images selected in the library are shown as thumbnails in the dialog when the 'Create Image Gallery' button is pressed. After the creation of the gallery, these images are automatically assigned to the list property of the document.




Figure 6.9. Library List View

The library plugin uses the library list view extension point to show some additional columns in the list view/search results. Additional columns are a site column, where the site name of a content item is displayed and a preview column, where images are shown as thumbnails. If the content item itself is not an image item, a referenced image is shown, such as the first picture of a gallery.

6.1.6 Bookmarks

The user can add and remove bookmarks using the bookmark action available on the preview toolbar, the library toolbar or the library list view's context menu.




Figure 6.10. Bookmarks

6.1.7 External Preview

The external preview is a Studio utility that allows you to use one or more additional displays for Studio's preview based editing. When working with *CoreMedia Studio*, the external preview can be started by clicking on the 'open external preview' button that is located on the toolbar of the preview.




Figure 6.11. External Preview

The dialog shows the options of the external preview. It can be invoked on any browser and device, including tablets to see how the document would look like on this device.

6.1.8 Settings for Studio

In order to use content-based settings not only for Content Application Engine usage but also for Studio, a new utility class `StudioConfigurationUtil` was introduced. Now you can, for example, configure paths used for the *Create Content* dialog [see Section 6.1.9, “Content Creation” [305]] in `CMSettings` content items.

The `StudioConfigurationUtil` class searches for bundles located at `<SITE_ROOT_FOLDER>/Options/Settings`, and falls back to `/Settings/Options/Settings` if no site-specific configuration bundle is found there. Bundle content items can be placed anywhere below these paths, and must be of type `CMSettings`.

You can use the `#getConfiguration(bundle, configuration, context)` method, where `bundle` is the name of the `CMSettings` document, and `configuration` is a path to a respective struct property. Optionally, you can also specify a `context`. The latter can be either a `Content` or a `Site`. If you provide `Content`, the site this content item belongs to is resolved, otherwise, the given site is used as the lookup context. If you omit the `context`, the current user's preferred site is used.

The utility class is fully dependency tracked, which means that you should wrap a `FunctionValueExpression` around returned values and bind the UI components that depend on the setting to this expression.

6.1.9 Content Creation

CoreMedia Blueprint provides additional buttons and actions to create new content besides the regular content creation action in the library. The user can click on the "Create content" menu on the favorites toolbar to open a selection of documents to create. The action is also available for link lists and several dialogs.




Figure 6.12. New content menu on the favorites toolbar

The user selects a content to create from the **Create content** menu of the favorites toolbar. Afterwards, a dialog opens where [at least] the document name and folder can be set.

New Article

Name

Enter name of content item.

Folder

Sites/Chef Corp./United States/English/

Type here to search or drag and drop a folder

Create

Cancel

Figure 6.13. New content dialog

The user can decide if the content should be opened in a tab afterwards. The checkbox for this is enabled by default. The *Name* and *Folder* properties are the mandatory fields of the dialog. Depending on the content type the dialog shows different property editors, for example for *Page* content items, the additional field *Navigation Parent* is configured so that the user can select the navigation parent of the new page.

New Page

Name

Enter name of content item.

Folder

Sites/Chef Corp./United States/English/Content/

Type here to search or drag and drop a folder

Navigation Parent

X | | |

Type here to search or drag and drop content onto this area.

Create

Cancel

Figure 6.14. New content dialog for pages

The dialog can be extended in several ways and plugged into existing components using the predefined menu item or button components which will invoke the dialog. Also, the dialog provides a plugin mechanism for new property editors and allows you to customize the post-processing after the content creation, depending on the type of the created content. The following "How To" sections describe how to configure and customize the dialog.

How to add a 'New Content' menu item to the favorites toolbar

There are already some entries defined for this menu, most of them configured in the class `BlueprintFormsStudioPlugin.xml`. The menu can be extended using the `quickCreateMenuItem`:

```
<bp:newContentMenu>
  <plugins>
    <ui:addItemsPlugin>
    <ui:items>
    <bbp-components:quickCreateMenuItem contentType="MyDocumentType"/>
    ...
  </plugins>
</bp:newContentMenu>
```

Separators can be added by:

```
<menuseparator cls="fav-menu-separator"/>
```

How to add a 'New Content' menu item to link list

There are two ways to add the content creation dialog to link lists. First is using the `QuickCreateToolBarButton` class and apply it to an existing link list using the `additionalToolBarItems` plugin. This will add one button to the toolbar of the link list to create a specific content type, for example creating a new child for the `CMChannel` document hierarchy:

```
<bp:extendedLinkListPropertyField bindTo="{config.bindTo}"
                                   propertyName="children">
  <bp:additionalToolBarItems>
    <tbseparator/>
    <bbp-components:quickCreateToolBarButton contentType="CMChannel" />
  </bp:additionalToolBarItems>
</bp:extendedLinkListPropertyField>
```

Example 6.2. Add content creation dialog to link list with `quickCreateLinkList Menu`



Figure 6.15. New content dialog as button on a link list toolbar

The second variant is that you apply a complete dropdown menu with several content types in it. By default, these content types are configured in the file `QuickCreateSettings.properties` that is part of the `blueprint-base` and overwritten with the file `NewContentSettingsStudioPlugin.properties` (see `BlueprintFormsStudioPlugin.xml`). The file contains a property `default_link_list_contentTypes` which contains the document types to display in a comma separated value format. This default can be overwritten by adding the `contentTypes` attribute to the `quickCreateLinklistMenu` element

when the dropdown elements are declared in exml. The attribute value can have a comma separated format to support multiple content types too:

```
<bp:extendedLinkListPropertyField bindTo="{config.bindTo}"
  propertyName="header">
  <bp:additionalToolBarItems>
    <tbseparator/>
    <bbp-components:quickCreateLinklistMenu bindTo="{config.bindTo}"
      contentTypes="CMArticle,CMTeaser,..."
      propertyName="children" />
  </bp:additionalToolBarItems>
</bp:extendedLinkListPropertyField>
```




Figure 6.16. New content dialog menu on a link list toolbar

How to link new content to a link list

When the dialog is added to the toolbar of a link list by using the button component of the menu, the newly created content is automatically linked to the list. The dialog checks during the post-processing if the parameters *propertyName* and *bindTo* have been passed to it and will link the new content to the existing ones. The dialog always assumes that if these two parameters have been passed, the corresponding property is a link list, so using other properties with other types here will raise an error here.

How to add an event handler to the button or menu item

Both components, the `quickCreateLinkListMenu` and the `quickCreateToolBarButton` provide a configuration parameter called `onSuccess`. The method passed there will be executed after a successful content creation and must provide the signature:

```
method(content:Content, data:ProcessingData, callback:Function)
```

The `ProcessingData` instance "data" contains all the data entered by the user for the mandatory and optional properties of the dialog. The object is a `Bean` instance, so the values can be accessed by using `data.get(<KEY>)` calls. Since the new content dialog has already applied all dialog properties to the content, the retrieved new content instance already contains all inputted data.

CAUTION

Ensure that the callback handler is called once the post-processing is finished. Otherwise, the post-processing of the content can not terminate correctly and steps may be missing.



How to add a content property to the new content dialog

A new property editor that should be mapped to a standard content property can be defined in the file `NewContentSettingsStudioPlugin.properties`. The configuration entry supports a comma separated format in order to apply multiple property fields to the dialog. For example when the configuration entry `item_CMArticle=title,segment` is added to the properties file, each time the dialog is opened for a `CMArticle` document the String properties "title" and "segment" are editable in the dialog and will be applied to the new content.

CAUTION

Currently only text fields are supported, so do not configure a content property here that has a different format than "String".



How to add an event handler for a specific content type

The new content dialog allows you to apply a content type depending success handlers that are executed for every execution of the dialog. The success handler must implement the following signature:

```
method(content:Content, data:ProcessingData, callback:Function)
```

and is applied to the dialog by invoking:

```
QuickCreate.addSuccessHandler(<CONTENT_TYPE>, <METHOD>);
```

CAUTION

Unlike the `onSuccess` handler described in the previous section, these types of event handlers will be executed for every content creation of a specific type, no matter how and where the new content dialog is invoked from.



How to add a custom property to the new content dialog

Sometimes it is necessary to configure a value for the dialog that is not a content property. Instead, the value should be processed in the success handler. The dialog allows you to apply new editors to the dialog that are mapped to a specific field in the `ProcessingData` instance.

To apply a custom editor a corresponding factory method has to be implemented that will create the editor every time the dialog is created. This factory method is applied to the dialog then by invoking:

```
QuickCreate.addQuickCreateDialogProperty(<CONTENT_TYPE>,  
    <CUSTOM_PROPERTY>,  
    function (data:ProcessingData, properties:Object):Component {  
        ..  
        //for example return new CustomEditor(customEditor{properties});  
    });
```

The `ProcessingData` instance is a bean, so it can be used to create `ValueExpressions` that are passed as parameters to the component. The predefined parameters are already applied to the `properties` object that is passed to the factory method. Additional properties can be added to this object, like the `emptyText` of an input field.

CAUTION

Make sure that the name of the custom property is unique and does not match an existing property of the given content type.



Since the new editor is shown for each dialog creation of the specific type, a success handler must be applied to the dialog too that processes the value:

```
QuickCreate.addSuccessHandler(<CONTENT_TYPE>,  
    <myPostProcessingHandler>);
```

The processing handler must implement the same method signature like the ones defined for menu items or buttons:

```
method(content:Content, data:ProcessingData, callback:Function)
```

The custom property can be access in the handler by invoking:

```
data.get (<CUSTOM_PROPERTY>)
```

NOTE

The post-processing of the dialog will execute the following steps:

1. create the new content
2. apply values to property fields (default processing)
3. invoke success handlers for custom processing (methods that have been applied through `QuickCreate.addSuccessHandler`)
4. invoke success handler configured for the button or menu items (methods that have been applied by declaring a value for the `onSuccess` attribute)
5. link content to a link list if parameters are defined
6. open created content
7. open additional content in background



Where do I find some examples?

Check the class `CMChannelExtension.as`. The class adds a `successHandler` for the creation of new `CMChannel` documents that is used to apply a value for the `title` property. Additionally, the newly created `CMChannel` document is also linked to a parent (if available) that may have been provided by the `NavigationLinkFieldWrapper` component that also has been added to the dialog.

6.1.10 Create from Template

As described in [Section 6.1.9, “Content Creation” \[305\]](#) when you create a Page content item in the *Create content* menu or from a link list, you will get a new and empty content item. If you want, on the other hand, create a Page with predefined content, or even a complete navigation hierarchy, you can use the *Create content* → *Create from Template* menu item. This will open a dialog where you can choose your Page from predefined templates.




Figure 6.17. Create from template dialog

As with the standard **Create Page** dialog you can choose a name, the destination folder for the page and the navigation parent. The *Create from Template* dialog adds a template chooser from which you can select the template and a new folder chooser (*Base Folder for Content*) where you can select a destination folder for the editorial content. The folder defined in the *Base Folder for Page* chooser must not contain a folder with the name entered above.

The suggested target paths for editorial content and content used to model the navigation are taken from a content-based setting from the bundle `Content Creation` [see [Section 6.1.8, “Settings for Studio” \[304\]](#) for an explanation of the content-based settings mechanism]. You can modify the settings `paths.editorial` and `paths.navigation` to match your specific content tree.

Location of new template folders

By default, templates will be looked up in the following folders:

- Global: `/Settings/Options/Settings/Templates/CMChannel/`
- Site specific: `Options/Settings/Templates/CMChannel/`

- User's home folder: `{USER_HOME}/Templates/CMChannel/`

The lookup path is configurable in the *Studio* properties file `CreateFromTemplateStudioPluginSettings.properties` by changing the property `pagegrid_template_paths`. Additional entries can be added in a comma separated format.

CAUTION

Keep care when you configure a template path outside the site hierarchy or when you use the global templates location. It is possible that the preconfigured layout of a global template may not be available for the active site. Therefore, the page grid extending mechanism won't work anymore, since the page grid editor can't find the layout definitions of other pages.



How to add a new template folder

Template folders must have a specific format to be detected as template folders. Each template is defined in a separate folder inside the `Templates/CMChannel` folder. The folder must contain a `CMSymbol` document named "Descriptor" that might contain an additional icon and description for the template. The icon is used as a preview in the template chooser and the description will be shown as the template name in the template chooser.

Descriptor content

Each template folder must contain exactly one page document at root level, otherwise the folder will be ignored. If the template consists of several pages, the sub pages should be placed within a subfolder of the template. Editorial content (Article, Images ...) that is contained in these folders and is linked by Page templates will be copied to the destination, defined in the *Create from Template* dialog.

If the name and the description should be internationalized, create an additional `Descriptor` document next to the original descriptor and append the locale to the document name, "Descriptor_de" for the German version, for instance.

Localization

6.1.11 Site-specific configuration of Document Forms

With the `SiteAwareVisibilityPlugin`, you can show or hide document form elements (for example, property fields) depending of the activation of a "feature" for a specific site.

The `SiteAwareVisibilityPlugin` takes a parameter called "feature", which is a name for the feature. You can group two or more plugins by giving them the same feature name.

If you configure any ExtJS Component to use this plugin, that component only becomes visible when this feature is configured to be active for the site that the current content belongs to.

By default, the configuration for features of a site is done in a `CMSSettings` document, which has to be named `<SITE_ROOT_FOLDER>/Options/Settings/Studio Features`

This settings bundle consists of a `StringList` named "features" and contains the string values that in turn need to be configured as desired in the `SiteAwareVisibilityPlugin`.

6.1.12 Open Street Map

Open Street Map is a project that creates and provides free geographic data and mapping. *CoreMedia Blueprint* supports an Open Street Map integration scenario:

- The `OpenStreetMap` property field (`OSMPropertyField.mxml`) offers a convenient method to visually edit geographic coordinates. It displays a map segment, and users can just drag a marker to the location they want to point out. Internally, a pair of geographic coordinates (longitude/latitude) is stored in a string property field

`OpenStreetMap` Support is bundled in a *Blueprint* extension. Note that in order for the integration to work properly, the machine hosting the *CoreMedia Studio* web application needs to have Internet access. On startup, a connectivity check is performed, and when the machine cannot reach the OSM servers, the extension is automatically turned off.

If you have changed the default group id of the Blueprint, the property `osm.groupId` of `OSMStudioPlugin.properties` has to be adapted accordingly. Alternatively, an absolute URL for another marker icon can be specified. In that case, the `osm.groupId` should remain empty or should be removed completely.




Figure 6.18. OpenStreetMap Property Editor

The OpenStreetMap property editor gives the editor the possibility to update the geographic location just by dragging a marker.

6.1.13 Site Selection

Since *CoreMedia Blueprint* provides multisite editing, a default working site can be configured in the settings dialog. If you select from *Preferred Site* for example '**Chef Corp. - German (Germany)**' and then create a new article, it will be moved to a folder like this `/Sites/Chef Corp./Germany/...`




Figure 6.19. The site selector on the preference tab

6.1.14 Upload Files

You can invoke the upload files dialog from the new content menu or the library. The dialog shows a drop area and the folder combo box shows where the uploaded documents will be imported to. You can drag and drop files from the desktop or the file system explorer onto the drag area. After the drop, the files are enlisted with a preview (if supported by the OS), a name text field and a mime type field. The mime type is automatically determined by the OS. After pressing the confirmation button the files are uploaded and corresponding documents are created and checked-in. You may choose to open the documents automatically after the upload is finished.

Upload dialog

Besides the upload dialog, you can simply drag and drop files into a folder of the Library or into a link list. Studio will automatically create the content items based on the MIME type of the file.

Drag and drop of files

The upload of Word documents is a special case. If the Word document contains images, Studio will create articles for the text content as well as pictures for the images in the Word document. The article links automatically to the pictures. *CoreMedia Blueprint* contains a prototype class `WordUploadInterceptor` in the `Validators` extension. The class defines the conversion of Word documents to rich text and images. Use the class to add your own conversion logic.

NOTE

The `WordUploadInterceptor` class is only a prototype that does not support all Word documents and Word formats. Most likely, you have to adapt it to your requirements.




Figure 6.20. The upload files dialog

How to configure the upload settings

The upload settings are stored in the settings document `UploadSettings` in folder `/Settings/Options/Settings`. The default configuration has the following format:

```
<Struct xmlns="http://www.coremedia.com/2008/struct"
xmlns:xlink="http://www.w3.org/1999/xlink">
  <StringProperty Name="defaultContentType">CMDDownload</StringProperty>
  <StringProperty Name="defaultBlobPropertyName">data</StringProperty>
  <IntProperty Name="timeout">30000</IntProperty>
  <IntProperty Name="previewMaxFileSizeMB">32</IntProperty>
  <BooleanProperty Name="previewDisabled">>false</BooleanProperty>
</Struct>
```

```
<BooleanProperty Name="autoCheckin">true</BooleanProperty>
<StructProperty Name="mimeTypeMappings">
  <Struct>
    <StringProperty Name="image">CMPicture</StringProperty>
    <StringProperty Name="application">CMDownload</StringProperty>
    <StringProperty Name="audio">CMAudio</StringProperty>
    <StringProperty Name="video">CMVideo</StringProperty>
    <StringProperty Name="text">CMDownload</StringProperty>
    <StringProperty Name="text/css">CMCSS</StringProperty>
    <StringProperty Name="text/javascript">CMJavaScript</StringProperty>
    <StringProperty Name="text/html">CMHTML</StringProperty>
  </Struct>
</StructProperty>
<StructProperty Name="mimeTypeToMarkupPropertyMappings">
  <Struct>
    <StringProperty Name="text/css">code</StringProperty>
    <StringProperty Name="text/javascript">code</StringProperty>
    <StringProperty Name="text/html">data</StringProperty>
  </Struct>
</StructProperty>
</Struct>
```

For a detailed description about the elements and attributes see table below.

autoCheckin	
Format	String
Description	If set to <i>true</i> , the uploaded contents are checked in after being created.
defaultContentType	
Format	String
Description	The default content type to create if the mime type of a file has no corresponding mime type mapping.
defaultBlobPropertyName	
Format	String
Description	The default blob property name to which the file blob is written to.
previewMaxFileSizeMB	
Format	Number
Description	Files that are dropped to the upload dialog and are larger than this value won't have a preview. This is used to avoid browser crashed for big file and defaults to 32MB.

previewDisabled	
Format	Boolean
Description	Boolean flag to disable the preview of upload items completely, defaults to 'false'.
mimeTypeMappings	
Format	Struct
Description	Depending on the mime type the content type to generate is mapped here. Here the primary type or the whole mime type can be specified.
mimeTypeToMarkupPropertyMappings	
Format	Struct
Description	Depending on the mime type the markup property name to which the file is written.
mimeTypeToBlobPropertyMappings	
Format	Struct
Description	Depending on the mime type the blob property name to which the file is written.
timeout	
Format	Integer
Description	The timeout in milliseconds for uploads, default value is 300000.

Table 6.1. Upload Settings

How to intercept the content's properties before creation

There is an example of a Content Write Interceptor contained in the `Validators` extension:

```
<bean id="pictureUploadInterceptor"
      class="com.coremedia.rest.cap.intercept.PictureUploadInterceptor">
  <property name="priority" value="-1"/> <!-- Ensure that this interceptor
is executed before other blob interceptors -->
  <property name="type" value="CMPicture"/>
</bean>
```

```

<property name="imageProperty" value="data"/>
<property name="widthProperty" value="width"/>
<property name="heightProperty" value="height"/>

<!-- uploadLimit: max image size (width * height) in pixels. Images are
not uploaded if too big to prevent
OutOfMemoryExceptions. -->
<property name="uploadLimit" value="100000000"/>

<!-- maxDimension: max width and height in pixels of stored images in
the database. Images are scaled down
if too big. -->
<property name="maxDimension" value="4000"/>
<property name="blobTransformer" ref="blobTransformer"/>
<property name="extractor" ref="imageDimensionsExtractor"/>
</bean>

```

It is a Content Write Interceptor for the `CMPicture` content type which scales an uploaded image blob to a configurable max dimension and writes the image dimensions to the width and height String property of the image document. It also rejects images that exceeds a total pixel size specified in the `uploadLimit` property to avoid the JVM from running out of memory. See the Studio Developer Manual for Content Write Interceptor. The interceptor class itself is now part of the core. You can find other interceptor sources files in the `Validators` extension, for example, the `WordUploadInterceptor.java` file.

6.1.15 Studio Preview Slider

Introduction

CoreMedia Studio's preview features a `slider` tool. The slider tool was build to let the user choose between devices with different resolutions in order to let the preview perform a responsive transformation of the page in the preview window. This means, that the preview will show the page as if it was to be viewed on a device with a different resolution than a "conventional" desktop display (that is a mobile device for instance).



Figure 6.21. The slider of the Studio Preview

Configuration of preview CAE

In order to enable the responsive slider functionality, you have to enable the use of `metadata` tags within the FreeMarker templates. These tags are used for communication between the CAE and *CoreMedia Studio* in order to exchange meta information about the previewed page. (See *CoreMedia Studio Developer Manual* for more details about metadata tags). The following listing illustrates the enabled setting within the file `cae-preview-app/src/main/resources/application.properties`:

```
cae.preview.metadata-enabled=true
```

NOTE

The settings for the responsive slider can also be configured for each theme individually. Therefore, they are assigned in the theme's settings Json files. For more information see Frontend Developer Manual.



Integration of metadata tags in FreeMarker templates

The following list illustrates the use of metadata tags in the `Page.body.ftl` template.

```
<#ftl strip_whitespace=true>

<!-- responsive design slider information for studio -->
<#assign sliderMetadata={
  "cm_preferredWidth": 1281,
  "cm_responsiveDevices": {
    <!-- list of the devices.
    naming and icons see: BlueprintDeviceTypes.properties
    the default icons are in studio-core, but you can define
    your own style-classes in slider-icons.css.
    -->
    <#-- e.g. iphone4 -->
    "mobile_portrait": {
      "width": 320,
      "height": 480,
      "order": 1,
      "isDefault": true
    },
    <#-- e.g. iphone4 -->
    "mobile_landscape": {
      "width": 480,
      "height": 320,
      "order": 2
    },
    <#-- e.g. nexus7 -->
    "tablet_portrait": {
      "width": 600,
      "height": 800,
      "order": 3
```

```

    },
    <!-- e.g. ipad -->
    "hybrid_app_portrait": {
      "width": 768,
      "height": 1024,
      "order": 4
    },
    <!-- e.g. nexus7 -->
    "tablet_landscape": {
      "width": 960,
      "height": 540,
      "order": 5
    },
    <!-- e.g. ipad -->
    "hybrid_app_landscape": {
      "width": 1024,
      "height": 768,
      "order": 6
    }
  }
}
/>

```

To introduce new devices with even different resolutions, simply extend the content of the file appropriately.

Configuration in Studio

The configuration in Studio has to be made in the appropriate bundle files. The following listing shows the content of the file `apps/studio-client/modules/studio/blueprint-forms/src/main/joo/com/coremedia/blueprint/studio/BlueprintDeviceTypes.properties`.

```

Device_mobile_portrait_icon=Resource(key='channel_mobile_portrait',
bundle='com.coremedia.icons.CoreIcons')
Device_mobile_landscape_icon=Resource(key='channel_mobile_landscape',
bundle='com.coremedia.icons.CoreIcons')
Device_tablet_portrait_icon=Resource(key='channel_tablet_portrait',
bundle='com.coremedia.icons.CoreIcons')
Device_tablet_landscape_icon=Resource(key='channel_tablet_landscape',
bundle='com.coremedia.icons.CoreIcons')
Device_notebook_icon=Resource(key='channel_notebook',
bundle='com.coremedia.icons.CoreIcons')
Device_desktop_icon=Resource(key='channel_desktop',
bundle='com.coremedia.icons.CoreIcons')
Device_hybrid_app_portrait_icon=Resource(key='channel_tablet_portrait',
bundle='com.coremedia.icons.CoreIcons')
Device_hybrid_app_landscape_icon=Resource(key='channel_tablet_landscape',
bundle='com.coremedia.icons.CoreIcons')

Device_mobile_portrait_text=Mobile
Device_mobile_landscape_text=Mobile
Device_tablet_portrait_text=Tablet
Device_tablet_landscape_text=Tablet
Device_notebook_text=Notebook
Device_desktop_text=Desktop
Device_hybrid_app_portrait_text=Hybrid App
Device_hybrid_app_landscape_text=Hybrid App
Device_desktopMode_text=Desktop

```

The configuration, which is relatively straightforward, consists of two parts. The top part of the configuration deals with the appropriate icons, that will be displayed for the according device type in the slider. The bottom part defines the text, that will be shown next to the slider. This configuration can be extended to introduce new device types with new device icons. For configuring the device icons, perform the following step:

- Declare a new class for the configured icon name in the file `apps/studio-client/modules/studio/blueprint-forms/src/main/resources/META-INF/resources/joo/resources/css/slider-icons.css`.

6.1.16 Uploading Content to Salesforce Marketing Cloud

Salesforce Marketing Cloud (SFMC) is a customer relationship management (CRM) tool by Salesforce. *CoreMedia Blueprint* supports pushing CoreMedia content to the SFMC. To enable this feature you have to configure the following settings for SFMC.

- `sfmc-credentials-clientId`: The client ID of the client credential
- `sfmc-credentials-customerId`: The subdomain of the client
- `sfmc-credentials-clientSecret`: The second part of the client credential. The passwords can be encrypted by using the tool `cm encryptpasswords` as described in Section “Encryptpasswords” in *Content Server Manual*.
- `sfmc-push-translations`: Whether to push into SFMC the master language and all translations of the configured text properties, or only the master language. This property can be `true` or `false`

The settings can be configured globally in the application context of the Studio application or in the settings document under the path `/Settings/Options/Settings/Marketing/Salesforce Marketing Cloud`. The SFMC settings can be also configured site-specific in the site settings.

In addition, the uploadable content properties for a given content type have to be configured. This can be done globally in the same settings document as above. To that end add a struct `sfmc-uploadableProperties` to the `settings` property of the document. The credentials can be also configured site-specific in the site settings.

sfmc-push-translations	true	String
▼ sfmc-uploadableProperties		Struct
CMArticle	title,detailText,pictures	String
CMTeaser	teaserTitle,teaserText,pictures	String
CMPicture	data	String

Figure 6.22. SFMC Uploadable Properties Setting

Currently, CoreMedia supports the string, richtext and blob image property. In the configuration example above the string property `title` and the richtext property `detailText` of the document type `CMArticle` and the image blob property `data` of the document type `CMPicture` are configured as uploadable content properties.

6.2 CAE Enhancements

This section describes enhancements of the *Content Application Engine*.

- [Section 6.2.1, “Using Dynamic Fragments in HTML Responses” \[325\]](#) describes how context dependent HTML snippets can easily be used in a *Content Application Engine* application.
- [Section 6.2.2, “Image Cropping in CAE” \[328\]](#) describes how you can use cropped images in the CAE.
- [Section 6.2.3, “RSS Feeds” \[329\]](#) describes how you can generate an RSS feed from content.

6.2.1 Using Dynamic Fragments in HTML Responses

Basic concept

Fragments of responses generated by the *Content Application Engine* may depend on a context, for example session data or the time of day. If fragments of a response may not be valid for every request, and responses are cached by reverse proxies (like Varnish or a CDN), it's necessary to exclude those parts from the response and load them separately using techniques like AHAH / Ajax or ESI.

To load the fragments, a link scheme and a matching handler handling the bean's type are needed.

CAE Implementation

In order to support loading of fragments in a generic and almost transparent way, beans are wrapped in a `[com.coremedia.blueprint.cae.view.DynamicInclude]` bean when they are included in the view layer. Whether the bean is wrapped or not is decided using `Predicate<RenderNode>` implementations that are called with the current `RenderNode`. A `RenderNode` represents the current "self" object and the view it's supposed to be rendered in. If any of the available predicates evaluate to true, the bean and view is wrapped as described above.

```
public class DynamicPredicate implements DynamicIncludePredicate {
    //only use DynamicInclude if view matches.
```

```
private static final String VIEW_NAME="myView";

public boolean apply(RenderNode input) {
    if (input == null) {
        return false;
    } else if (input.getBean() instanceof MyBean
        && VIEW_NAME.equals(input.getView())) {
        return true;
    }
    return false;
}
}
```

Example 6.3. Predicate Example

The predicate has to be added to a predefined Spring bean in order to be evaluated:

```
<customize:append id="addMyDynamicPredicates"
bean="dynamicIncludePredicates">
<list>
<bean id="myPredicate"
class="DynamicPredicate"/>
</list>
</customize:append>
```

Example 6.4. Predicate Customizer Example

Render fragment placeholder

After wrapping the bean, the `DynamicInclude` is then rendered by the *Content Application Engine*.

`DynamicInclude` beans are rendered just as other beans by the *Content Application Engine*. By default, the view `DynamicInclude.ftl` is used to render the beans. It will either add a placeholder DOM element that can be used to load the fragment using AHAH, or an `<esi:include>` tag, depending on whether there is a reverse proxy telling the CAE to do so using the `Surrogate-Capability` header. This is described in the [Edge Architecture Specification](#).

Links to dynamic fragments

In order to generate a link for either AHAH or ESI, a separate link scheme must be created for each bean type that should be included dynamically.

If the fragment depends on the context (for example, Cookies, session or the time of day), the link scheme must have the prefix `/dynamic/` (see `UriConstants$Pre`

fixes} so that a preconfigured interceptor will set all Cache headers necessary that downstream proxies never cache those fragments. Matching Apache and Varnish rewrite rules are provided by *CoreMedia Blueprint*.

```
@Link(type = MyBean.class,
view = "fragment",
uri = "/dynamicfragment/mybean")
public UriComponents buildFragmentLink(Cart cart,
UriTemplate uriPattern,
Map<String, Object> linkParameters,
HttpServletRequest request) {

UriComponentsBuilder result =fromPath(uriPattern.toString());
//parameter "targetView" needs to be added
result.queryParam("targetView",linkParameters.get("targetView"));
return result.build();
}
```

Example 6.5. Dynamic Include Link Scheme Example

Handling dynamic fragments

These links have to be handled by using a handler. The handler has to use the Request Param "targetView" to be able to construct a ModelAndView matching the values as originally intended in the include including the original bean.

```
@RequestMapping(value="/dynamicfragment/{mybean}")
public ModelAndView handleFragmentRequest(
@PathVariable("mybean") String mybean,
@RequestParam(value = "targetView") String view) {

Object myBean = resolve(mybean);

//do not create Page, return bean directly (!)
ModelAndView modelWithView = createModelWithView(myBean, view);
return modelWithView;
}
```

Example 6.6. Dynamic Include Handler Example

Preserve view parameters for dynamic fragments

When including fragments dynamically expect the same behaviour as for server side includes. This means that the view parameters which may include all kinds of objects need to be passed to subsequent templates.

To preserve these parameters a hashed string representation of the parameters will be appended by the `IncludeParamsAppendingLinkTransformer` as `includeParams` query parameter to the asynchronous call. When receiving the call,

the `IncludeParamsFilter` will retrieve the view parameters back from the query parameter.

NOTE

Custom URI paths, considered by the `IncludeParamsAppendingLinkTransformer` may be configured via `cae.link-transformer.uri-paths` property.

A server side secret for the hash generation can be configured via `cae.hashing.secret` property.

Have a look at `CaeLinkTransformerConfigurationProperties` and `CaeSecretConfigurationProperties` for further information.



The following types of view parameters are supported for dynamic fragments:

- primitives (boolean, int, float, long)
- String
- ContentBeans
- Content
- Maps and Collections of the above types.

Additional custom types may be configured via the `cae.link-transformer.serializer-classes` property.



CAUTION

For every custom type an `IdScheme` registered at the `IdProvider` is presumed.

6.2.2 Image Cropping in CAE

As described in Section 7.3.3, "Image Cropping and Image Transformation" in *Studio Developer Manual*, there are predefined crops, which can be applied to image rendering in the CAE. *CoreMedia Blueprint* comes with four predefined cropping definitions.

- portrait_ratio3x4
- portrait_ratio1x1
- landscape_ratio4x3
- landscape_ratio16x9

The necessary settings for the image will be set by *Studio* once you open the image in *Studio*. To render images correctly even if they were not imported through *Studio* but for example by the *Importer*, the CAE provides a default cropping configuration for those images, which don't have the settings explicitly set. You will find these default settings in

```
/modules/shared/image-transformation/src/main/resources/framework/spring/mediatransform.xml
```

In this file, there is a list of the transformations mentioned above. Please refer to the Javadoc of `com.coremedia.cap.transform.Transformation` for all configuration possibilities. New Spring bean definitions of this class will be automatically injected to the `TransformImageService` that is responsible for all variant definitions.

Site Specific Image Variants

For the CAE, the class `TransformImageService` is responsible for loading site specific cropping information. The feature can be enabled by changing/adding the Spring property `imagemettransformation.dynamic-variants` to `true`.

The `TransformImageService` requires a lookup of the Struct that contains the information about the image variants. Therefore, it must be injected with an instance of `VariantsStructResolver` which resolves the global and site specific image variants. The implementation of this interface is part of the `shared` module `image-transformation`, since the lookup is content type specific and therefore can not be part of the core.

For example the Corporate site comes with additional predefined cropping definitions.

- `portrait_ratio20x31`
- `portrait_ratio3x4`
- `portrait_ratio1x1`
- `landscape_ratio4x3`
- `landscape_ratio16x9`
- `landscape_ratio5x2`
- `landscape_ratio4x1`

6.2.3 RSS Feeds

The CAE supports the rendering of RSS feeds for all content beans that implement the interface `FeedSource`. The interface is currently implemented by the classes `CM Navigation` and `CMCollection`. Feeds can be generated by invoking URLs with the following pattern:

```
/service/rss/[SITE_URL_SEGMENT]/[CONTENT_ID]/feed.rss  
for the RSS feed with content id [CONTENT_ID]
```

The programmed view `FeedView` collects all content beans that should be part of the feed and generates the RSS XML that is returned to the browser. The default implementation of the *CoreMedia Blueprint* returns the contents of the `items` list for `CMCollection` beans and the content of the main section for `CMNavigation` beans.

The conversion from a content bean to a feed entry is implemented through `FeedItemDataProviders`. The programmed view `FeedSource` contains a list of `FeedItemDataProvider` instances. If a content bean is applicable to a `FeedItemDataProvider`, the content bean is passed to it and the RSS entry with all required data is returned.

CoreMedia Blueprint comes with the following `FeedItemDataProviders`:

- `TeasableFeedItemDataProvider`
- `PictureFeedItemDataProvider`

The amount of items that should be part of an RSS feed can be limited by setting the `String` struct property `'RSS.limit'` in a settings document that is part of the invoked context.

6.3 Elastic Social

CoreMedia Elastic Social is integrated into *CoreMedia Blueprint*. It includes the following features:

- Comments and Reviews

Comments and reviews are supported for any kind of editorial CMS content items, for example articles and products. It is possible to configure for a context if writing comments or reviews is enabled and if it is allowed for anonymous or registered users. A review includes 5-star ratings with title and text.

Elastic Social provides aggregations like "Most Commented" or "Top Reviewed" content in a defined time interval for a certain context.

- User Profiles

User profiles can be created using a registration flow and can be managed in the *CAE* by the user or in the *Studio* plugin "User Management".

A user profile is activated by a user via a link in a registration confirmation email.

- Moderation

In the moderation of *Elastic Social* comments, reviews and user profiles can be edited, approved or rejected. In case of rejecting, a preconfigured template-based email can be sent directly or be modified by the moderator before sending it. A prioritization for comments, reviews or user profiles can be set. For all items that have to be moderated, premoderation, post-moderation or no moderation can be configured.

- Ratings

Rating is supported for any kind of editorial CMS content item, like articles. Ratings are provided via a five star model. *Elastic Social* calculates average ratings for the star rating model and aggregates "Top Rated" and "Most Rated" content items per channel for a certain time span and context for a channel.

- Registration

A user can register by creating a community user from scratch.

- Authentication

The authentication is handled by *Elastic Social*.

- Password Reset

Password reset is available for registered users who authenticate directly with *Elastic Social*.

- User Management

The *Elastic Social* user management in *Studio* includes a search for community users. The user management allows editing, searching, approving, blocking, ignoring and deleting users, as well as resending registration confirmation emails.

- All Contributions

In the *All Contributions* section in *Studio* a list of all comments and reviews can be displayed. The list can be filtered by user, type, status or search term. Selected comments/reviews can then be edited, remoderated and marked for later editorial use.

- Display custom information in *Studio*

Custom information about users, comments or reviews can easily be integrated into the *Studio* moderation and user management via extension points.

- Emails

An email for a specific event can be sent by implementing the corresponding listener. Email templates can be created and edited in *Studio*.

6.3.1 Configuring Elastic Social

This section describes the configuration of the *Elastic Social* plugin.

Context settings for Elastic Social are defined in the following contexts:

- Root channel: Application context settings can only be defined in the root channel and can not be overwritten
- Every Channel: Channel context settings can be defined in every channel and are inherited or can be overwritten by child channels

Root Channel

The following context settings are defined for the root channel and can not be overwritten:

tenant	
Type	String property
Description	The tenant
Example	elastic
Default Value	
Required	true

userModerationType	
Type	String Property
Description	Moderation type for users
Example	PRE_MODERATION, POST_MODERATION, NONE
Default Value	NONE
Required	false
recaptchaForRegistrationRequired	
Type	Boolean property
Description	Enable/disable captcha for user registration
Example	true, false
Default Value	false
Required	false

Table 6.2. Root Channel Context Settings

The context setting tenant is needed to define which tenant is used for a site.

```
<?xml version="1.0" encoding="UTF-8"?>
<Struct xmlns="http://www.coremedia.com/2008/struct"
  xmlns:xlink="http://www.w3.org/1999/xlink">
  <StructProperty Name="elasticSocial">
    <Struct>
      <StringProperty Name="tenant">
        elastic
      </StringProperty>
      <StringProperty Name="userModerationType">
        POST_MODERATION
      </StringProperty>
      <BooleanProperty Name="recaptchaForRegistrationRequired">
        true
      </BooleanProperty>
    </Struct>
  </StructProperty>
</Struct>
```

Example 6.7. Root Channel Context Settings

```
<?xml version="1.0" encoding="UTF-8"?>
<Struct xmlns="http://www.coremedia.com/2008/struct"
  xmlns:xlink="http://www.w3.org/1999/xlink">
  <StructProperty Name="elasticSocial">
    <Struct>
      <StringProperty Name="tenant">
        elastic
      </StringProperty>
      <StringProperty Name="userModerationType">
        POST_MODERATION
      </StringProperty>
    </Struct>
  </StructProperty>
</Struct>
```

Example 6.8. Root Channel Context Settings

Every Channel

The following context settings can be defined per channel and are inherited or can be overwritten by child channels:

Name	Type	Description	Example	De- fault value
enabled	Boolean Prop- erty	Enable/disable feed- back for the channel. If disabled, all other set- tings are ignored	true, false	false
commentType	String Property	Disable commenting generally by settings this property to DIS- ABLED. Enable reading comments by setting this property to READONLY. Enable only registered users to write comments by settings the property to REGISTERED. Enable all users (registered and anonymous) to write comments by settings the property to AN- ONYMOUS. This prop- erty is only available if enabled is true.	DISABLED, READONLY, REGISTERED, ANONYM- OUS	DIS- ABLED

Name	Type	Description	Example	Default value
<code>reviewType</code>	String Property	Disable reviewing generally by settings this property to DISABLED. Enable reading reviews by setting this property to READONLY. Enable only registered users to write reviews by settings the property to REGISTERED. Enable all users (registered and anonymous) to write reviews by settings the property to ANONYMOUS. This property is only available if enabled is true.	DISABLED, READONLY, REGISTERED, ANONYMOUS	DISABLED
<code>recaptchaForReviewRequired</code>	Boolean Property	Enable reCAPTCHA for Reviews and Ratings.	true, false	false
<code>commentModerationType</code>	String Property	Moderation Type for comments.	<i>PRE_MODERATION, POST_MODERATION, NONE</i>	NONE
<code>reviewModerationType</code>	String Property	Moderation Type for reviews.	<i>PRE_MODERATION, POST_MODERATION, NONE</i>	NONE
<code>reviewDocumentTypes</code>	String List Property	Optional whitelist of technical document type identifiers for reviews. Do not set this configuration if reviews should be available for all subtypes of CMTeasable	<i>CMArticle, CMTeasable</i> , etc.	

Name	Type	Description	Example	De- fault value
<code>commentDocumentTypes</code>	String List Property	Optional whitelist of technical document type identifiers for comments. Do not set this configuration if comments should be available for all subtypes of <i>CMTeasable</i>	<i>CMArticle</i> , <i>CMTeasable</i> , etc.	
<code>likeDocumentTypes</code>	String List Property	Optional whitelist of technical document type identifiers for likes. Do not set this configuration if likes should be available for all subtypes of <i>CMTeasable</i>	<i>CMArticle</i> , <i>CMTeasable</i> , etc.	
<code>ratingDocumentTypes</code>	String List Property	Optional whitelist of technical document type identifiers for ratings. Do not set this configuration if ratings should be available for all subtypes of <i>CMTeasable</i>	<i>CMArticle</i> , <i>CMTeasable</i> , etc.	
<code>defaultNumberOfReviews</code>	Integer Property	Default number of reviews to be displayed initially. If 0, all reviews are displayed.	3	0
<code>maxImageFileSize</code>	Integer Property	Maximum size of uploaded images (in bytes).	512000	512000
<code>userImageHeight</code>	Integer Property	Height of user image in px.	150	150

Name	Type	Description	Example	De- fault value
userImageWidth	Integer Property	Width of user image in px.	200	200
userImageThumb nailHeight	Integer Property	Height of user thumb- nail image in px.	48	48
userImageThumb nailWidth	Integer Property	Width of user thumbnail image in px.	48	48
userImageCom mentThumbnail Height	Integer Property	Height of user thumb- nail image in px, dis- played for a comment.	48	48
recaptchaPub licKey	String Property	ID of your registered re- CAPTCHA app	ABCD123...	
re captchaPrivateKey	String Property	Secret authentication key of your registered reCAPTCHA app	ABCD123...	
filterCategor ies	LinkListProperty	Configures filter op- tions for the comment moderation list. You can add navigation and taxonomy documents.		
Context Settings for Every Channel				

Table 6.3. Context Settings for Every Channel

```
<?xml version="1.0" encoding="UTF-8"?>
<Struct xmlns="http://www.coremedia.com/2008/struct"
  xmlns:xlink="http://www.w3.org/1999/xlink">
  <StructProperty Name="elasticSocial">
    <Struct>
      <BooleanProperty Name="enabled">
        true
      </BooleanProperty>
      <StringProperty Name="commentType">
        ANONYMOUS
      </StringProperty>
      <StringProperty Name="reviewType">
        REGISTERED
      </StringProperty>
    </Struct>
  </StructProperty>
</Struct>
```

```

<StringProperty Name="commentModerationType">
  PRE_MODERATION
</StringProperty>
<StringProperty Name="reviewModerationType">
  PRE_MODERATION
</StringProperty>
</Struct>
</StructProperty>
</Struct>

```

Example 6.9. Context Settings for Every Channel

6.3.2 Displaying Custom Information in Studio

You can show additional information inside the moderation tab and user management window of *CoreMedia Studio* by extending the *Studio* web application (server side) and modifying the *ElasticSocialStudioPlugin.mxml* (client side).

Server Side: REST JsonCustomizer

Provide a *JsonCustomizer* to the *Studio* web application that adds the additional information to the data that is transferred from the REST backend to the *Studio* app for users:

```

@Named
public class MyCommunityUserJsonCustomizer implements
JsonCustomizer<CommunityUser> {
    public void customize(CommunityUser communityUser, Map<String, Object>
serializedObject) {
        serializedObject.put("additional", communityUser.getProperty("information",
String.class));
    }
}

```

or for comments:

```

@Named
public class MyCommentJsonCustomizer implements JsonCustomizer<Comment> {
    public void customize(Comment comment, Map<String, Object> serializedObject)
    {
        serializedObject.put("additional", comment.getProperty("information",
String.class));
    }
}

```

Client Side [1]: Display Custom Properties

Three extension points are provided for displaying custom properties for comments or users.

1. Extend the `CommentExtensionTabPanel` to add components for comments that are displayed above the approve and reject buttons inside the moderation/archive tab (use `activeContributionAdministration` in the expression for the `ElasticPluginLabel` in order to reference the active contribution administration, depending on whether the moderation or the archive tab is active):

```
<editor:rules>
...
<elastic:CommentExtensionTabPanel>
  <elastic:plugins>
    <ui:AddItemsPlugin>
      <ui:items>
        <Panel ui="{PanelSkin.COLLAPSIBLE_200}"
              title="additionalInformation">
          <items>
            <es:ElasticPluginLabel fieldLabel="additional"
expression="activeContributionAdministration.displayed.additional"/>
          </items>
        </Panel>
      </ui:items>
    </ui:AddItemsPlugin>
  </elastic:plugins>
</elastic:CommentExtensionTabPanel>
...
</editor:rules>
```

2. Extend the `UserProfileExtensionTabPanel` to add components for user profiles that are displayed above the approve and reject buttons inside the moderation tab:

```
<editor:rules>
...
<elastic:UserProfileExtensionTabPanel>
  <elastic:plugins>
    <ui:AddItemsPlugin>
      <ui:items>
        <Panel ui="{PanelSkin.COLLAPSIBLE_200}"
              title="additionalInformation">
          <items>
            <es:ElasticPluginLabel fieldLabel="additional"
expression="activeContributionAdministration.displayed.additional"/>
          </items>
        </Panel>
      </ui:items>
    </ui:AddItemsPlugin>
  </elastic:plugins>
</elastic:UserProfileExtensionTabPanel>
...
</editor:rules>
```

3. Extend the `CustomUserInformationContainer` to add components that are displayed below the user meta information panel inside the user management view:

```

<editor:rules>
...
<elastic:CustomUserInformationContainer>
  <elastic:plugins>
    <ui:AddItemsPlugin>
      <ui:items>
        <Container>
          <items>
            <es:ElasticPluginLabel fieldLabel="additional"
expression="userAdministration.edited.additional"/>
          </items>
        </Container>
      </ui:items>
    </ui:AddItemsPlugin>
  </elastic:plugins>
</elastic:CustomUserInformationContainer>
...
</editor:rules>

```

Client Side [2]: Edit Custom Properties

For all three extensions points described above it is also possible to not just display but to edit/moderate custom properties. Instead of `ElasticPluginLabel` just use `ElasticPluginPropertyField`. This provides a text field for editing the property. Number or Boolean fields are not provided but can be constructed analogously. When you construct your own property field it is important to register the corresponding property as being moderated. This can either be done directly by your property field [c.f. `ElasticPluginPropertyFieldBase`] or you use the `RegisterModeratedPropertiesPlugin` for this purpose.

6.3.3 Adding Custom Filters for Moderation View

The list of moderated items of the *Moderation View* includes a filter section (see chapter *Using Elastic Social* of the *CoreMedia Studio User Manual*). By default, this section encompasses a filter for showing/hiding comments and users and for filtering comments in terms of comment categories.

It is possible to add further filters. You have to add your custom `FilterPanel` to the container `ModeratedItemsSearchFilters` via the `AddItemsPlugin`.

Each `FilterPanel` has to implement the method `buildQuery()`. For the case of moderation list filters, it has to return a string denoting comment/user properties and their desired values for filtering. Comment properties have to be prefixed with `"comments_"`. User properties have to be prefixed with `"users_"`.

For instance, if your filter returned `"comments_authorName=Nick"`, only comments written by an author named *Nick* would show up. You can combine multiple property-value pairs by separating them with `"&"`

Note that you probably have to provide appropriate indexes for your database in order to prevent your custom filters to have a negative effect on query performance.

6.3.4 Emails

Sending emails is supported by *Elastic Social* and can easily be incorporated for common use cases in a project. *Elastic Social* provides listeners which can be implemented to send emails (see *Elastic Social* documentation).

In *CoreMedia Blueprint*, an example implementation and the corresponding mail templates are provided. For example the `SendRegistrationMailListener` is a provided listener to send emails with a link to confirm a registration.

The `MailTemplateService` allows you to generate and send emails with a template name and parameters.

In the provided implementation in *Blueprint* the template name references a document in the CMS with content type `CMMail` (email Template). The parameters define variables which can be used in the mail templates. Locale specific mail templates are used if a locale specific variant is available (locale specific suffix name).

Per default all properties of a `CommunityUser` (the model for a user) are available as variable in a mail template. For example you can use `$givenName` to include the given name of a user (if you use *FreeMarker* for templating as *CoreMedia Blueprint* does). Additional parameters must be provided programmatically by passing them as map `additionalParameters` to the `MailTemplateService`.

In *CoreMedia Blueprint*, the following mail templates for the user and moderation processes are already provided with the example content. For each mail template, the template name and additional parameters are described.

If you want to use different additional parameters, redefine the variable in the mail template and pass the corresponding parameter in the `additionalParameters` map. All properties of the `CommunityUser` can be used in the templates without changing the code.

Use case	Template Name	Additional Parameters
Registration	registration	<code>baseUrl</code> (registration activation link)

Use case	Template Name	Additional Parameters
User activated (pre-moderation)	userActivated	N/A
Reset Password	passwordreset	<i>baseUrl</i> (reset password link)
Profile Change	profileChanged	N/A
Comment Replied Mail Templates	commentReplied	<i>replyText</i> , <i>replyAuthorName</i> , <i>replyDate</i> , <i>commentText</i> , <i>commentDate</i> , <i>commentUrl</i>

Table 6.4. Mail Templates

Configuration

To enable email dispatch, the following configuration is needed:

- At least one application node needs to be configured as worker node. For more information see configuration of *taskqueues.worker-node* in the *Elastic Social* Manual. In *Blueprint*, the *elastic-worker-app* is configured as worker node.
- The application context needs to be set up with implementations of specific beans (*JavaMailSender* and *MailTemplateService*), more information is available in the *Elastic Social* Manual.
- The *mailSender* defined in *Blueprint* can be configured with the properties:

```
elastic.social.mail.smtp.server, default 'localhost'  
elastic.social.mail.smtp.port, default 25  
elastic.social.mail.protocol, default 'smtp'  
elastic.social.mail.username, default '<empty>'  
elastic.social.mail.password, default '<empty>'
```

6.3.5 Resend Registration Confirmation Mail from *Studio*

Process: A registration confirmation mail with an activation link can be resent from *CoreMedia Studio* for users with state `REGISTRATION_REQUESTED`. The resend registration confirmation mail contains a link to the registration flow of *Blueprint*.

The following configuration is needed in a properties file of the Studio web application to use this functionality:

- `es.cae.http.host`

6.3.6 Curated transfer

Contributions can be transformed into content objects for further use. In *CoreMedia Blueprint* the `CuratedTransferExtensionPoint` must be configured to define the type of content:

```
<editor:rules>
...
  <elastic:CuratedTransferExtensionPoint>
    <elastic:plugins>
      <ui:AddItemsPlugin>
        <ui:items>
          <TbSeparator
            itemId="{CURATED_TRANSFER_EXTENSION_POINT_SEP_FIRST_ITEM_ID}"/>
          <ui:IconButton itemId="createArticleBtn"
            scale="medium"
            ui="{ButtonSkin.WORKAREA.getSkin()}"
            tooltip="..."
            text="..."
            iconCls="...">
            <ui:baseAction>
              <bpb-components:OpenQuickCreateAction
                contentType="CMArticle"
                skipInitializers="true"
                onSuccess="{CuratedUtil.postCreateArticleFromComments}"/>
            </ui:baseAction>
          </ui:IconButton>
        </ui:items>
      </ui:AddItemsPlugin>
    </elastic:plugins>
  </elastic:CuratedTransferExtensionPoint>
...
</editor:rules>
```

The content property can be configured in `CuratedTransferResource.java`:

```
private static final String CONTENT_PROPERTY_TO_COPY_TO = "detailText";
```

6.3.7 reCAPTCHA

reCAPTCHA (see <http://www.google.com/recaptcha> for more information) is used to verify real user interaction for anonymous commenting and for registration.

Note: If reCAPTCHA is not configured, anonymous commenting is not possible!

Configure reCAPTCHA with the following settings:

- `recaptchaPublicKey`
- `recaptchaPrivateKey`

reCAPTCHA can be configured for the registration process with:

- `recaptchaForRegistrationRequired`

6.3.8 Sign Cookie

The `signCookie.privateKey` and `signCookie.publicKey` properties are used to configure a RSA key pair that is used to recognize returning unknown visitors via a signed token. The token is created and verified by `com.coremedia.blueprint.elastic.social.cae.guid.GuidCookieHandler`.

Private and public key must be set via Spring Settings for all deployed blueprint CAE instances.

The recommended way to create a key pair is to use external tools like OpenSSL. To generate a key pair with OpenSSL follow these steps:

- Generate Private Key: `openssl genpkey -algorithm RSA -pkeyopt rsa_keygen_bits:2048 -out private-key.pem`

Show Private Key: `openssl pkey -in private-key.pem -text`

Generate corresponding Public Key: `openssl pkey -in private-key.pem -out public-key.pem -pubout`

Show Public Key: `openssl pkey -in public-key.pem -pubin -text`

Another possible way to generate a key pair is to create a custom JVM based tool using the Java standard library classes `java.security.KeyFactory` and `java.security.KeyPairGenerator`.

A third but less recommended way is to simply not configure these keys, start your CAE instance and then copy the key pair from that CAE's log file. The generated key pair is logged at level WARN.

6.4 Adaptive Personalization

Feature is only supported in *eCommerce Blueprint*.



CoreMedia Adaptive Personalization is integrated in *CoreMedia Blueprint*. It extends *CoreMedia Studio* and the CAE with the following features:

- Specific content types for personalized content, personalized search, customer segments and test user profiles. See [Section 5.3.2, “Adaptive Personalization Content Types” \[150\]](#) for details.
- Specific editors in *CoreMedia Studio* for the content types.
- Different context sources to access taxonomy keywords, time related information and many more.
- Different search functions that can be used in personalized searches.

A main concept of *Adaptive Personalization* is context. When speaking about a context in terms of *CoreMedia Adaptive Personalization*, “a piece of data associated with a HTTP request” is meant. What data this is, is determined by the data sources you grant access to, for example a Geo Location service, your CRM or *CoreMedia Elastic Social*. *CoreMedia Adaptive Personalization* is a framework that manages these contexts and makes them available within your CoreMedia application.

Context

See the Adaptive Personalization Manual for detailed information, about how contexts work.

In the file `personalization-context.xml` in module `p13n-cae` you can see which contexts are used in *CoreMedia Blueprint*.

The following sections describe details of the integration, the module structure, key integration points and some details on context.

- [Section 5.3.2, “Adaptive Personalization Content Types” \[150\]](#) gives an overview over the content types introduced by *Adaptive Personalization*.
- [Section 6.4.1, “Key Integration Points” \[347\]](#) describes key integration points of *Adaptive Personalization*
- [Section 6.4.2, “Adaptive Personalization Extension Modules” \[347\]](#) summarizes where to find *Adaptive Personalization* related source code in *CoreMedia Blueprint*.
- [Section 6.4.3, “CAE Integration” \[349\]](#) shows how Adaptive Personalization is embedded into the CAE.
- [Section 6.4.4, “Studio Integration” \[352\]](#) presents the *Studio* integration.

6.4.1 Key Integration Points

- CoreMedia Elastic Social

As one example of providing context information that doesn't originate from the CMS, *CoreMedia Blueprint* comes with a ready-to-use integration for *CoreMedia Elastic Social*. As a result an editor can create Conditions in documents of type Personalized Search and Customer Segment that make use of a `CommunityUser`'s number of written comments, likes and ratings and/or simply information about the user himself (for example his given name).

Note that these features are only available when using *CoreMedia Adaptive Personalization* in combination with *CoreMedia Elastic Social*.

- Taxonomies

As depicted in [Section 5.3.3, "Tagging and Taxonomies" \[151\]](#), each HTTP request against the CAE is augmented with Taxonomies. For example if a page with Content related to sport is shown, a "Sport" Taxonomy is associated with the request. *CoreMedia Blueprint* is configured to make these semantic classifications accessible to editors, that is, they can define Conditions on them in documents of type Personalized Search and Customer Segment.

6.4.2 Adaptive Personalization Extension Modules

CoreMedia Adaptive Personalization is integrated into the CAE using the CoreMedia project extension mechanism.

Adaptive Personalization Extensions

- `p13n`

This is the basic *CoreMedia Adaptive Personalization* module. It provides essential implementation based on *Adaptive Personalization*, like definitions of contexts, custom content types and corresponding `ContentBeans`.

- `es-p13n`

This extension combines *CoreMedia Elastic Social* with *CoreMedia Adaptive Personalization*. It offers `ContextSources` that publish properties of *Elastic Social*'s `CommunityUser` to the user's context collection so that it is available for *Adaptive*

Personalization. This extension also offers convenience implementations for accessing and modifying user context, for example, the `com.coremedia.blueprint.personalization.elastic.InterestsService` which reads and writes contexts that refer to Subject Taxonomies.

Adaptive Personalization's Main Module in Detail

Module	Description	Content
p13n-cae	Generic CAE Plugin	ContentBean implementations for Adaptive Personalization content types, data view/Spring bean definitions, JMX configuration, ...
p13n-editor-lib	Runtime dependencies for <i>CoreMedia Site Manager</i>	XML schema for Adaptive Personalization's rule grammar, localization properties, ...
p13n-preview-cae	Preview CAE Plugin	Customizations specific to Preview CAE for example code to handle the evaluation of Test User Profiles
p13n-server	Bundles runtime dependencies for <i>Content Management Server</i>	XML schema for Adaptive Personalization's rule grammar, Adaptive Personalization content types, ...
p13n-studio	<i>Studio</i> plugin	DocumentForms corresponding to content types, custom UI components, localization properties, ...
p13n-studio-lib	Runtime dependencies for <i>CoreMedia Studio</i>	DocumentForms corresponding to content types, custom UI components, localization properties, ...
p13n-test-content	Encapsulates content and code for testing purposes	A prepared XML repository used during test execution, ...

Module	Description	Content
p13n-uitesting	Wrappers for <i>Adaptive Personalization</i> 's Studio UI components and the UI tests themselves	Wrapper for the rule property editor of a personalized content document, ...

Table 6.5. Adaptive Personalization's main Maven module in detail

6.4.3 CAE Integration

This section covers which contexts and `SearchFunctions` are available in *CoreMedia Blueprint*.

For a basic understanding of *Adaptive Personalization*'s key concepts and how to instrument them to fulfill project specific needs, please refer to the Adaptive Personalization Manual. To learn about CAE development in general, see the Content Application Developer Manual.

Configured Contexts

To make use of *Adaptive Personalization* a CAE must be configured with contexts. In order to deliver personalized content these contexts will be analyzed at runtime each time a request is being processed.

CoreMedia Blueprint is shipped with the following contexts configured:

Context	Description
cookieSource_keyword	Cookie based ContextSource to track keywords associated with a Page.
cookieSource_subject_taxonomies	Cookie based ContextSource to track Subject Taxonomies
cookieSource_location_taxonomies	Cookie based ContextSource to track Location Taxonomies
referrerSource	Cookie based ContextSource to track the referrer URL of the first request of a session.

Context	Description
systemDateTimeSource	Provides access to time related information.
lastVisitedSource	Cookie based ContextSource to track a user's visited Pages.
journeySegmentSource	Provides Access to the SFMC journeys to which a user is associated.

Table 6.6. Adaptive Personalization contexts configured for CoreMedia Blueprint

Have a look at `personalization-context.xml` in module `p13n-cae` to see what kind of data is contained in the contexts. Especially, notice the used `ContextCoDec` implementations.

Refer to the Adaptive Personalization Manual to see how to implement a Context Source.

Configured SearchFunctions

CoreMedia Blueprint comes with a content type called Personalized Search that represents a parametrized search query. You can use `SearchFunctions` to enrich the query String, which will be evaluated at request processing time. After evaluation, the `SearchFunctions` are replaced with values from contexts resulting in a personalized search query.

CoreMedia Blueprint is shipped with the following `SearchFunctions` configured:

Search Function	Description
contextProperty	<p>A search function that adds the value of a single context property to a search string.</p> <p>You can use the following parameters:</p> <ul style="list-style-type: none"><code>property</code> - the property of the context. Should be in the form: <code><context>.<property></code><code>field</code> - the search engine field in which you want to search. <p>Example:</p> <p>The context named "bar" contains a property "foo" which has a value "42". Then, the search function <code>contextProperty(property:bar.foo, field:field)</code> will be evaluated to 'field:42'.</p>

Search Function	Description
	<p>That is, the <i>Search Engine</i> searches in the field named "field" for the value "42".</p>
<code>userKeywords</code>	<p>A search function that selects from a user's context a set of keys that fulfill a weight constraint.</p> <p>You can use the following parameters:</p> <ul style="list-style-type: none">• <code>limit</code> - Limits the number of returned keys (a negative or missing value means no limit)• <code>field</code> - The search engine field which should be searched• <code>threshold</code> - The minimum weight of keys to be returned• <code>context</code> - The context containing the keys <p>Example:</p> <p>The context object named <code>myContext</code> contains the properties <code>{foo, 0.8}, {bar, 0.5}, {zork, 0.1}</code>. Then, the search function <code>userKeywords(threshold:0.5, limit:-1, field:field, context:myContext)</code> will be evaluated to <code>field:{foo bar}</code> and the searchfunction <code>userKeywords(threshold:0.5, limit:1, field:field, context:myContext)</code> will be evaluated to <code>field:{foo}</code>.</p>
<code>userSegments</code>	<p>A search function that selects the set of customer segments the active user belongs to.</p> <p>You can use the following parameters:</p> <ul style="list-style-type: none">• <code>field</code> - The search engine field which should be searched• <code>context</code> - The context that contains segment properties <p>Example:</p> <p>The context object named "myContext" contains the properties <code>{'content:42', true}, {'content:44', false}, {'content:46', true}</code>. Then, the search function <code>userSegments(field:field, context:myContext)</code> will be evaluated to <code>"field:[42 46]"</code>. This function is intended to be used with the user segmentation feature of <i>CoreMedia Adaptive Personalization</i>, which uses property keys of the form <code>content:<segmentId></code> (where <i>segmentId</i> is the numeric content id of a customer segment) to represent segments in a user's context.</p>

Table 6.7. *Predefined SearchFunctions in CoreMedia Blueprint*

See the Adaptive Personalization Manual for more information on `SearchFunctions` and the content type Personalized Search.

Enabling Test User Profiles in the Preview CAE

To make the Test Profile Selector work, the *Preview CAE* is provided a special context configuration: Its `ContextCollector` extends all properties of the generic CAE `ContextCollector`, but also adds a `TestContextSource` (see `p13n-preview-cae-context.xml` in `p13n-preview-cae`). This `TestContextSource` makes contexts from Test User Profile documents available by extracting the following information from a Test User Profile:

- Arbitrary contexts held in a plaintext blob using the `PropertiesTestContextExtractor`
- Subject/Location Taxonomies determined in a Struct property using the `TaxonomyExtractor`

The activation of the `TestContextSource` is triggered by passing a special URL parameter - `TestContextSource.QUERY_PARAMETER_TESTCONTEXTID` - to the *Preview CAE*.

Further reading:

- See [Section "Using Customer Personas" \[354\]](#) for the Test Profile Selector's usage
- The Adaptive Personalization Manual explains how to specify contexts in a Test User Profile document

6.4.4 Studio Integration

This section covers which `Conditions` are configured in *CoreMedia Blueprint* and how to use the Test Profile Selector.

For a basic understanding of *Adaptive Personalization*'s key concepts and how to instrument them to fulfill project specific needs, please refer to the Adaptive Personalization Manual. To learn about *Studio* development in general see the Studio Developer Manual.

Configured Conditions

To make use of contexts in documents of type Personalized Content or Customer Segment corresponding `Conditions` have to be implemented in Studio. *CoreMedia Blueprint* provides `Conditions` for all contexts listed in [Table 6.6, "Adaptive Personalization contexts configured for CoreMedia Blueprint"](#) [349] .




Figure 6.23. Conditions in Personalized Content and Customer Segment documents

Have a look at `CMSelectionRulesForm.exml` and `CMSegmentForm.exml` in module `p13n-studio` to get an idea about how to plug in `Conditions`.

Using Customer Personas

A Customer Persona is a collection of artificial context properties under the control of the editors. The type of properties to use depends on the configured contexts. For example the name of a visitor is a String while the number of likes performed is a numeric value.

12

English (United States)

Persona

Content

Image

E-Commerce System

User Segments

Female Customers

Registered Customers

Customers who are under 40 years of age

Add an e-Commerce user segment to the persona.

User Contracts

Add an e-Commerce user contract to the persona.

Elastic Social

Given Name

Sarah

Name

Veith

Birthday

08/15/1994

Email

sarah.veith@coremedia.com

Number of Comments

Number of Ratings

Number of Likes

Number of Explicit Interests

Gender

Female

User Logged In

Predictive Behavioral Targeting

Figure 6.24. Defining artificial context properties using Customer Personas

See Table 6.6, “Adaptive Personalization contexts configured for CoreMedia Blueprint” [349] for an overview of configured contexts.

Using the Customer Persona Selector an editor is able to test a Personalized Content document. By choosing a specific Customer Persona all its contexts are activated within the Preview CAE. As a result, the Preview CAE renders content as if corresponding contexts were available at request processing time.




Figure 6.25. Selecting Customer Personas to test Personalized Content and User Segment documents

See section [Section “Enabling Test User Profiles in the Preview CAE” \[352\]](#) to learn how Customer Personas are integrated into the Preview CAE. The Adaptive Personalization Manual describes in detail how to create and use Customer Personas.

6.5 Third-Party Integration

CoreMedia Blueprint comes with default integrations of third-party software.

CAUTION

CoreMedia ships various third-party tool example integrations - however any licensing or privacy compliance for the use of these tools remains the responsibility of the customer implementing and operating the product. Please review with your legal counsel.



6.5.1 Optimizely

Optimizely is a service which offers A/B testing for your website. You can define different rules for A/B testing using the editor on the Optimizely website.

CoreMedia Blueprint integrates Optimizely to perform A/B testing for channels.

To enable this for a certain channel proceed as follows:

1. Open the target channel in *CoreMedia Studio*.
2. Open the Settings tab.
3. Create a struct property of type Boolean in the "Local Settings" section with the name `optimizely.enabled` and set it to true.
4. Create a struct property of type String in the "Local Settings" section with the name `optimizely.id.external.account` and enter the project id you got from Optimizely.

Now the JavaScript provided by Optimizely will be included in each site of this channel and you can measure your website improvements. The "Local Settings" will be inherited to sub channels. That means, the project id can be set, for example for the root channel once and you can disable Optimizely using `optimizely.enabled` for each sub channel individually.

Remember also, if you adjust target links on your website the target site must be available in the channel, too. Otherwise, the Optimizely script will not be included on the target site and clicks cannot be tracked.

6.5.2 Open Street Map Integration

NOTE

This extension is discontinued since 1907.1. If you want to embed Open Street Map on your website, please see https://wiki.openstreetmap.org/wiki/Using_OpenStreetMap



The Open Street Map project creates and distributes free geographic data. *CoreMedia Blueprint* is prepared to include the project to display the location of location based taxonomies, but map integration are not included in the default templates.




Figure 6.26. Example for an Open Street Map integration in a website

In order to use Open Street Map on your site, you have to create a settings document and link it to the root channel of your site. The JavaScript for Open Street Map will be loaded using an aspect that is only enabled if the corresponding settings property is set. The available settings for Open Street Map are shown in the table below and must be configured to enable the map in the CAE. A template renders a map segment according to geographic coordinates stored in the string property `latitudeLongitude` of a linked location content, and pinpoints the matching location with a marker image (see `CMTeasable.map.jsp` for a usage example).

Setting	Struct Type	Mandatory	Description
detail.show.map	Boolean Property	not	If true, the Open Street Map aspect will be enabled.
map.zoom	Int Property	no	The map zoom factor to use.

Table 6.8. Settings for Open Street Map Integration

6.5.3 Google Analytics Integration

NOTE

Brand Blueprint feature



Brand Blueprint integrates Google Analytics into the website to get performance feedback. Have a look into the [Analytics Connectors Manual](#) to learn about the configuration.

Section 4.7.7, “Getting Analytics Feedback” in *Studio User Manual* and Section 4.2.6, “Adding Site Performance Widget” in *Studio User Manual* describe how to get the performance feedback in *CoreMedia Studio*.

6.5.4 Salesforce Marketing Cloud Integration

NOTE

In order to use this integration, you need a license for Marketing Automation Hub and Salesforce Marketing Cloud Connector.

Additionally, you need to license the SFMC integration from CoreMedia.



To activate the integration in the Blueprint Workspace you need to enable the SFMC extensions. To that end run the following Maven command in your workspace:

```
$ cd $CM BLUEPRINT_HOME/workspace-configuration/extensions
$ mvn extensions:sync -Denable=sfmc,sfmc-pl3n,sfmc-es-pl3n
```

Salesforce Marketing Cloud (SFMC) is a customer relationship management (CRM) tool by Salesforce. *CoreMedia Content Cloud* offers you an integration with the following features:

- Upload of content from the CoreMedia system into the SFMC system as assets. See [Section 6.1.16, “Uploading Content to Salesforce Marketing Cloud” \[323\]](#) for the configuration and Section 4.7.10, “Uploading Content to Salesforce Marketing Cloud” in *Studio User Manual* for the usage.
- SFMC Journey based personalization. See [Section “Configured Contexts” \[349\]](#) for a description of the personalization condition.

- Service API to push data into SFMC data extensions. See the CoreMedia API Javadoc for the class `com.coremedia.blueprint.base.sfm.libservices.dataextensions.SFMCDataExtensionService`

6.6 Advanced Asset Management

CoreMedia Advanced Asset Management consists of two parts:

- An Asset management component with new content types where you can manage your digital assets and licenses.
- An Asset management component which connects to a commerce system to manage assets for products and product variants of the commerce system.

CoreMedia Asset Management allows you to store and manage your digital assets (for example, high resolution pictures of products) and corresponding licenses in the CoreMedia system. You can customize the storage of assets and the set of available asset types and rendition formats.

Managing Assets

A rendition is a derivative of the raw asset, suitable for use in output channels, possibly with some further automated processing. A rendition might be, for example, a cropped and contrast adjusted image in a standardized file format whereas the original file might be stored in the proprietary format of the image editing software in use.

From such assets, you can create common content items, such as `Picture` or `Download` which you can use to enrich products and product variants (products for short) in the commerce system.

Enhancing Commerce Pages

- CMS images and even individual image crops can be used as product images.
- CMS videos can be used as product videos. They will be displayed together with the product images in a gallery.
- CMS content of type *Download* can be offered as additional content that can be downloaded for a product. Any type of binaries are supported, like PDF documents, ZIP archives or office documents.

Such product assets can be edited with *CoreMedia Studio* and will then be delivered by the CMS to enrich, for example, a product detail page.

This section describes the necessary configuration steps for either configuring and deploying *CoreMedia Asset Management* or for removing the contributing modules from the *CoreMedia Blueprint* workspace.

6.6.1 Product Asset Widget

eCommerce Connector specific feature



To present CMS assets on product detail pages you can add the *CoreMedia Product Asset Widget*. For *HCL Commerce*, you replace the default *HCL Commerce Full Image Widget* by the that displays images in an attractive gallery. This makes it particularly easy to present multiple product images and videos for a product.




Figure 6.27. Product image gallery in HCL Commerce delivered by the CMS

The *CoreMedia Product Asset Widget* can also be used to display a list of download links that are associated with the product. The download links are shown together with the product image gallery as *Additional Downloads* or in a separate slot on the product detail page.

See Section 3.11, “Deploying the CoreMedia Widgets” in *Connector for HCL Commerce Manual* for *HCL Commerce* or Section 6.4.4, “Finding CMS Content for Product Detail Pages” in *Connector for SAP Commerce Cloud Manual* for *SAP Commerce* to get the in-

formation on how to deploy the *CoreMedia Product Asset Widget*. For Salesforce you will find the description in the documentation of the commerce Workspace.

Assign Products to CMS Assets

CoreMedia Content Cloud allows you to manage assets in the CoreMedia system that will be used for products and SKUs in the commerce system.

To achieve this *Picture*, *Video* and *Download* documents can be linked with products. That means one picture, video or download can be (re)used for many products. All images and videos that link to the same product act together as a gallery of images and videos of the same product.




Figure 6.28. Assign a product to a picture

The same applies to downloads. All *Download* documents that link to the same product appear together in an *Available Downloads* list on the product detail page (if the option was used in the *CoreMedia Product Asset Widget*). The order of the images or downloads in the list is determined by the name (in alphabetic order).

You don't have to assign every existing SKU to an asset document, for example an image, in order to achieve that for each SKU, the same image is delivered. If a SKU is not directly assigned the CMS searches for all asset documents that are assigned to the master product of the SKU or uses the default image for the site (in case of an image).

See Section “Replacing Commerce Images in Products and SKUs with CMS Images” in *Studio User Manual* to learn how to assign products to images using the *CoreMedia Studio*.

6.6.2 Replaced Product and Category Images

Connector for HCL Commerce specific feature



In addition to the *Product Asset Widget* you can replace images directly by replacing the URL in the *HCL Commerce* system with a CoreMedia URL. The linking of product or category images from *HCL Commerce* to the CoreMedia *CAE* is done via Image URLs that you can add to the *Display* tab of the product or category definition.




Figure 6.29. Define Product Image URLs in Management Center

NOTE

Regardless of the usage of the *CoreMedia Product Asset Widget*, once the image URLs of a product are pointing to the CMS all occurrences of these product images (for example, on catalog overview pages) will be delivered by the CMS. If multiple images are assigned to one product, then the first image is taken (in alphabetical order).



The Image URL has the following format:

For a product:

```
http://[cmsHost]/blueprint/servlet/catalogimage/product/  
[storeId]/<Locale>/<Mapping>/<PartNumber>.jpg  
respectively in a multi-catalog scenario  
http://[cmsHost]/blueprint/servlet/catalogimage/product/
```

```
[storeId]/<Locale>/[catalogId]/<Mapping>/<PartNumber>.jpg
```

For a category:

```
http://[cmsHost]/blueprint/servlet/catalogimage/category/[storeId]/<Locale>/<Mapping>/<CategoryID>.jpg
```

respectively in a multi-catalog scenario

```
http://[cmsHost]/blueprint/servlet/catalogimage/category/[storeId]/<Locale>/[catalogId]/<Mapping>/<PartNumber>.jpg
```

Where the path segments have the following meaning:

Segment Name	Example	Description
[cmsHost]	[cmsHost]	The URL prefix of the server that can deliver CMS images. Typically, you will enter here the literal string [cmsHost] so the system can map it to a concrete URL prefix. Since the images are delivered from different servers depending on which side you are (preview or live) the hostname can alter between the systems. The placeholder [cmsHost] will then be replaced by a URL prefix containing the live host, provided the request comes from the live side. See also the <i>HCL Commerce</i> documentation "Configuration properties for content management system integration".
[storeId]	[storeId]	The ID of the <i>HCL Commerce</i> store for which the image is requested. An <i>HCL Commerce</i> store is configured for a specific site in the CoreMedia system. Typically, you will enter here the literal string [storeId] so the system can map it to a concrete store ID.
Locale	en_US	The locale of the store.
[catalogId]	[catalogId]	The ID of the <i>HCL Commerce</i> catalog for which the image is requested. This is required only in a multi-catalog scenario. Typically, you will enter here the literal string [catalogId] so the system can map it to a concrete catalog ID.
Mapping	thumbnail	The mapping between an image in the <i>HCL Commerce</i> product and the named image variant that is taken from the CoreMedia system.

Segment Name	Example	Description
PartNumber/CategoryID	GFR033_3301/PC_ToDrink	The product or SKU part number or category ID.

Table 6.9. Path segments in the image URL

Delivery of Images

The URL is resolved from the catalog picture handlers. The handlers map the "Named image format" segment to a cropped variant of a picture [see [Section 5.4.14, "Images" \[199\]](#) for details of crops]. *CoreMedia Blueprint* comes with the following definition:

```
<bean id="productCatalogPictureHandler"
class="com.coremedia.livecontext.asset.ProductCatalogPictureHandler"
parent="catalogPictureHandlerBase">
...
<property name="pictureFormats">
<map>
<entry value="portrait_ratio20x31/200/310">
<key>
<util:constant static-field=
"com.coremedia.livecontext.asset.CatalogPictureHandlerBase.FORMAT_KEY_THUMBNAIL"/>
</key>
</entry>
<entry value="portrait_ratio20x31/646/1000">
<key>
<util:constant static-field=
"com.coremedia.livecontext.asset.CatalogPictureHandlerBase.FORMAT_KEY_FULL"/>
</key>
</entry>
</map>
</property>
</bean>

<bean id="categoryCatalogPictureHandler"
class="com.coremedia.livecontext.asset.CategoryCatalogPictureHandler"
parent="catalogPictureHandlerBase">
...
</bean>
```

That is, a URL with a segment thumbnail maps to an image variant portrait_ratio20x31 with the width "200" and the height "310" and a URL with segment full maps to the same image variant portrait_ratio20x31 but with width "646" and height "1000". These are the values required by the HCL Aurora Starter Store.

You can customize the configuration via a Spring configuration as described in [Section "Mapping of Custom Picture Formats" \[367\]](#).

6.6.3 Extract Image Data During Upload

If your pictures files are enriched with the product codes as XMP/IPTC "artwork or object in the picture", the system automatically tries to extract data during the upload. How the data is used depends on the content item to which you upload the image.

- Upload to a Picture: The product codes are extracted and the system tries to add a reference to the product in the eCommerce repository with this product code.
- Upload to a Picture Asset: The product codes are extracted and are added to the Picture Asset.




Figure 6.30. Screenshot from Adobe Photoshop for a Picture containing XMP Data

While uploading the pictures via *CoreMedia Studio* into a `Picture` item, the system automatically extracts the product codes and adds references to the assigned products. At this process the product references contained in the original image data will be remembered. You have the option to reset to the original imported data after you have changed the assignments manually.

Upload to a Picture content item




Figure 6.31. Picture linked to XMP Product Reference

After an initial import, the status of the *Assigned Products* section is set to "inherited". All associated product references are shown as "read only" and can only be edited if the *Switch off inheritance* button is pressed.

Each reimport of the same image data (with an update of the blob) leads to an update of the associated product references unless the references have been changed manually. In general, the rule applies, that no data will be overwritten that have been changed manually.

6.6.4 Configuring Asset Management

In the following it is described how you can adapt *CoreMedia Asset Management* to your specific needs:

- Define which crops of an image are used in shop pages.
- Define from which CAEs the commerce system gets images.
- Define content types for your own assets.
- Define publication behavior for renditions of your assets.
- Define where large blobs should be stored.
- Define appropriate rights in the CoreMedia system for your asset content.

Mapping of Custom Picture Formats

eCommerce Connector specific feature



You can manage pictures in *CoreMedia Content Cloud* that are used in commerce products and SKUs pages. You can use Spring configuration, to map URL path segments to specific crops.

CoreMedia Blueprint comes with a predefined mapping defined in the `catalogPictureHandler` bean. If you want to define your own mapping you can overwrite the default setting as follows:

```
<customize:replace bean="catalogPictureHandler"
id="customizeCatalogPictureHandler"
property="pictureFormats">
  <description>
    Your custom picture formats for the Catalog Picture Handler
  </description>
  <map>
    <entry key="customFormat1" value="custom_crop1/300/410"/>
    <entry key="customFormat2" value="custom_crop2/700/1200"/>
  </map>
</customize:replace>
```

The `key` attribute in the `entry` tag is the identifier that is used in the request URL while value is the name of the crop of the image that will be used followed by the size of the image as `/width/height/` in pixel. The definition of crops is explained in [Section 5.4.14, "Images" \[199\]](#)

Placeholder Resolution for Asset URLs

Connector for HCL Commerce specific feature



In the *HCL Commerce* system you can use a placeholder in image URLs which is resolved through a database lookup in the `STORECONF` table. See the HCL documentation for more details at <https://help.hcltechsw.com/commerce/8.0.0/developer/refs/rwccmsresolve-contenttag.html>.

For example:

```
http://[cmsHost]:<CAEPort>/blueprint/servlet/catalogimage/product/
[storeId]/<Locale>/<Mapping>/<PartNumber>.jpg
```

The placeholders in the example above are `[cmsHost]` and `[storeId]`.

To resolve `[cmsHost]` - see the HCL documentation for `ResolveContentURLCmdImpl` for more information. If you want to connect preview and live *CAE* to one *Management Center* you can define different values for `wc.resolveContentURL.cmsHost` and `wc.resolveContentURL.cmsPreviewHost` in the `STORECONF` table.

If you use one extended sites catalog for multiple shops you can specify a `[storeId]` placeholder in your image URLs, which are dynamically resolved at runtime.

In a development setup you may share one *HCL Commerce* instance for preview and live delivery.

In order to identify the *CAE* (preview or live) from which the image should be delivered, the *Blueprint* workspace comes with a predefined Apache configuration. Depending on the shop URL, for example, `shop-helios.blueprint-box` versus `shop-preview-helios.blueprint-box` the Apache server adds a request header `X-FragmentHost` which contains the value preview or live. For more information about *Apache* configuration, look at the deployment tutorial in the *Blueprint* workspace at `deployment/chef/documentation/deployment-archive-tutorial.md`.

If you want to activate `[cmsHost]` resolution for a shared *HCL Commerce* preview/live environment, perform the following steps:

1. Register and map the `FragmentHostFilter` servlet to workspace/`Stores/WebContent/WEB-INF/web.xml` of the *HCL Commerce* to extract the `X-FragmentHost` header information from the request.

```
...
<filter>
  <filter-name>FragmentHostFilter</filter-name>

  <filter-class>com.coremedia.livecontext.servlet.FragmentHostFilter</filter-class>
</filter>
<filter-mapping>
  <filter-name>FragmentHostFilter</filter-name>
  <url-pattern>/*</url-pattern>
</filter-mapping>
...
```

2. Register the `CoreMediaResolveContentURLCmdImpl` in the *HCL Commerce*. This command resolves `[cmsHost]` placeholder in image URLs depending on a preview or live switch for the current request. It resolves `[storeId]` placeholder as well. To register the command perform the following SQL statement:

```
insert into cmdreg (storeent_id, interfacename, classname)
  values (0, 'com.ibm.commerce.content.commands.ResolveContentURLCmd',
  'com.coremedia.commerce.content.commands.CoreMediaResolveContentURLCmdImpl');
```

Refer to the *HCL* documentation for more details about registering custom command implementations in the command registry

To resolve `[storeId]` in Management Center, you have to register and map the `ImageFilter` servlet to workspace/`LOBTools/WebContent/WEB-INF/web.xml` of the *HCL Commerce*.

```

...
<filter>
  <filter-name>ImageFilter</filter-name>
  <filter-class>com.coremedia.livecontext.servlet.ImageFilter</filter-class>
</filter>
<filter-mapping>
  <filter-name>ImageFilter</filter-name>
  <url-pattern>/LoadImage</url-pattern>
</filter-mapping>
...

```

Content Types

CoreMedia Advanced Asset Management stores its data in the content repository in content items. *CoreMedia Content Cloud* contains the abstract root content type `AMAsset` (see Chapter 4, *Developing a Content Type Model* in *Content Server Manual* for a description of content types) as a starting point for assets. `AMAsset` defines a property `original` to store the raw editable form of the asset and another property `thumbnail` to store a thumbnail view. The thumbnail property can be used for a uniform preview of assets. If there is no sensible thumbnail for an asset, it can be left empty.

Concrete content types for specific assets, such as pictures or documents, need to extend the abstract content type `AMAsset`. Most probably, you will add more properties for different renditions of the asset. Names of rendition properties must be alphanumeric strings. By default, `AMPictureAsset` and `AMDocumentAsset` are provided as a non-abstract asset type, defining rendition properties for web delivery and for printing.

You can modify existing asset types or define additional asset types in the file `asset-management-plugin-doctypes.xml` in the `am-server` module. For each asset type, you need an appropriate form in *CoreMedia Studio*. *CoreMedia Blueprint* already defines suitable *Studio* forms for the `AMPictureAsset` and `AMDocumentAsset`. Change this form when you adapt the `AMPictureAsset` or `AMDocumentType` content type and add further forms for your own asset types.

When you add further rendition properties that hold very large blobs, modify the blob store configuration as described in Section 3.3, “Configuring Blob Storage” in *Content Server Manual*. Small renditions up to a few megabytes can be stored in the *Content Server* database and do not need additional configuration.

To prevent large blobs like the original rendition from being published, you can exclude them from publication process. For more information read [Section “Configure Rendition Publication” \[371\]](#).

*Abstract content type
AMAsset*

*Concrete content
types AMPictureAsset
and AMDocumentAs-
set*

*Defining your own as-
set types*

*Store large blobs in the
file system*

Configure Rendition Publication

Certain renditions can be excluded from publication. To do so the `am-server-component` comes with an `AssetPublishInterceptor` which reads the `metadata` property of assets to determine if a given rendition should be published or not.

The `AssetPublishInterceptor` bean is added to the *Content Server* and to the corresponding command-line tools. The following properties control the behavior of the interceptor:

<code>assetMetadataProperty</code>	The Struct property which contains the information whether to publish a rendition or not at path <code>renditions.<rendition-name>.show</code> . When the Boolean property <code>show</code> is <code>true</code> , the rendition blob will be published. Otherwise, the blob will not be available on the master server.
<code>interceptingSubtypes</code>	Boolean flag to control whether also subtypes of type should be intercepted or not.
<code>removeDefault</code>	The default value to control whether a rendition blob should be removed from publication or not. If unset the default is to remove blobs if nothing else is specified in either the metadata struct or in the removal overrides.
<code>removeOverride</code>	Overrides any setting or default for a given rendition. It contains a map from rendition name to removal flag. Thus, if you want the rendition <code>thumbnail</code> to be published in any case add an entry with key <code>thumbnail</code> and value <code>false</code> .
<code>type</code>	The document type the interceptor applies to. For subtype processing set the flag <code>interceptingSubtypes</code> accordingly.

Example 6.10, “Rendition Publication Configuration” [371] shows a possible configuration of the `AssetPublishInterceptor`.

```
<beans ...>
  <util:map id="removeOverride"
    key-type="java.lang.String"
    value-type="java.lang.Boolean">
    <entry key="thumbnail" value="false"/>
  </util:map>
```

```
<bean id="assetPublishInterceptor"
      class=
        "com.coremedia.blueprint.assets.server.AssetPublishInterceptor">
  <property name="type" value="AMAsset"/>
  <property name="interceptingSubtypes" value="true"/>
  <property name="assetMetadataProperty" value="metadata"/>
  <property name="removeDefault" value="true"/>
  <property name="removeOverride" ref="removeOverride"/>
</bean>
</beans>
```

Example 6.10. Rendition Publication Configuration

Blob Storage

Blobs of renditions can be stored in the database or in the file system. In general, content in the CoreMedia CMS is stored in a database, but for large blobs, the file system might be better suited for storage, because databases are not always optimized for this use case.

When you start the *Content Management Server* using `mvn spring-boot:run` in module `content-management-server-app` of the development installation, all blobs are stored in the database.

Blueprint default storage behavior

Blob storage is configured in the *Content Server's* Spring application context, see Section 3.3, "Configuring Blob Storage" in *Content Server Manual* for details. With the property `am.blobstore.rootdir`, you define the root directory for file system storage.

Configuration of blob storage

NOTE

Keep in mind, that storing a blob in the file system might double the required space, when you use the rendition in another content item, for example, in a *Picture*.

This is because, when you store a blob in the database and the same blob is used in different content items, then all the content items link to this blob. On the other hand, when you have stored a blob in the file system and this blob is used in another content item that does not define file system storage, then a copy of the blob will be created in the database.



Rights

Assets in the form of `AMAsset` documents are placed in the `/Assets` folder by default. Define rights rules for the content repository in such a way that only authorized users can create and change assets and that assets can only be placed in the folder

/Assets. Note that access rights for the root content type `Document_` automatically imply rights on assets.

Studio

The asset management extension of *CoreMedia Studio* is defined in the modules `am-studio` and `am-studio-component`.

In `am-studio` you can find the form definition for picture forms in the file `AMPictureAssetForm.xml`. Update this file if you change the set of renditions. Create additional form when you add further asset types. Localizations of asset types and rendition names can be added to the resource bundle `AMDocumentTypes`.

The module `am-studio-component` contains configuration information for the Studio REST backend. In the file `component-am-studio.xml` you can find the configuration of two write interceptors which update the asset metadata as renditions are uploaded using Studio.

Asset Download Portal

CoreMedia Advanced Asset Management comes with an asset download portal. You can configure the behavior of the portal in the `Asset Management Configuration` content item in *Studio* as shown in [Figure 6.32, “Configuration of the download portal”](#) [373].




Figure 6.32. Configuration of the download portal

The properties in the `download-portal` struct have the following meaning:

- root-page

A Page content item which defines the context of the download portal. The root page contains the *AM Download Portal Placeholder* in the *Main* placement.
- assets-per-page

The number of assets that are shown in one page.
- metadata-properties

The properties from the asset's metadata that are shown in the detail view of an asset.

The hierarchy of the assets in the download portal is determined by the Asset Download Portal taxonomy. That is, an asset content item is shown on the download portal, when it contains an asset category tag and a downloadable property.




Figure 6.33. Taxonomy for assets

7. Reference

This chapter contains detailed information about some of *CoreMedia Blueprint*'s features:

- [Section 7.1, "Content Type Model" \[376\]](#) shows UML diagrams of *CoreMedia Blueprint* content types.
- [Section 7.2, "Link Format" \[379\]](#) lists the controller, link schemes and link post-processors of *CoreMedia Blueprint*.
- [Reference - Predefined Users \[385\]](#) shows the predefined users that are available in the system for log in to *Studio*.
- [Section 7.4, "Database Users" \[391\]](#) shows the database users that are needed by the CoreMedia server components.
- [Section 7.5, "Cookies" \[392\]](#) lists all cookies delivered by *CoreMedia Content Cloud*.

7.1 Content Type Model

This section shows the content types of *CoreMedia Blueprint* as UML diagrams. Since the content type model exists of more than forty items it is split into the following diagrams:

- **Figure 7.1, “CoreMedia Blueprint Content Type Model - CMLocalized” [377]** shows the content types inheriting from CMLocalized.
- **Figure 7.2, “CoreMedia Blueprint Content Type Model - CMNavigation” [377]** shows the content types inheriting from CMNavigation.
- **Figure 7.3, “CoreMedia Blueprint Content Type Model - CMHasContexts” [378]** shows the content types inheriting from CMHasContexts.
- **Figure 7.4, “CoreMedia Blueprint Content Type Model - CMMedia” [378]** shows the content types inheriting from CMMedia.
- **Figure 7.5, “CoreMedia Blueprint Content Type Model - CMCollection” [378]** shows the content types inheriting from CMCollection.

The following diagrams contain most of the content types. The colors have the following meaning:

- Blue items are part of the basis Blueprint content items
- Yellow items are part of the eCommerce integration
- Green Items are part of the Adaptive Personalization Integration
- Red items are part of the Elastic Social Integration
- Gray items are part of the Analytics Integration

You can download the complete diagram as a `graphml` file from the online documentation page below *Other Documentation* named *CoreMedia Content Cloud Content Type Diagram*:




Figure 7.1. CoreMedia Blueprint Content Type Model - CMLocalized




Figure 7.2. CoreMedia Blueprint Content Type Model - CMNavigation




Figure 7.3. CoreMedia Blueprint Content Type Model - CMHasContexts




Figure 7.4. CoreMedia Blueprint Content Type Model - CMMedia




Figure 7.5. CoreMedia Blueprint Content Type Model - CMCollection

7.2 Link Format

The following table summarizes most of the corresponding link schemes and controllers of *CoreMedia Blueprint* as defined in `framework/spring/blueprint-handlers.xml`. See the Javadoc of the respective classes for further details.

CapBlobHandler

Description	Controller and link scheme for Blobs like Images in CSS, Images that do not have any scaling information or CMDownload documents.
Class	<code>com.coremedia.blueprint.cae.handlers.CapBlobHandler</code>
Example	<code>/blob/1784/4fb7741a1080d02953ac7d79c76c955c/media-data.ico</code> for a CSS background image

Table 7.1. CapBlobHandler

CodeResourceHandler

Description	Controller and link scheme for CSS and JavaScript stored in the CMS.
Class	<code>com.coremedia.blueprint.cae.handlers.CodeResourceHandler</code>
Example	<code>/code/1214/5/responsive-css.css</code> for a CSS

Table 7.2. CodeHandler

ExternalLinkHandler

Description	A Link scheme for external links stored in the CMS.
Class	<code>com.coremedia.blueprint.cae.handlers.ExternalLinkHandler</code>

Example `http://www.coremedia.com`

Table 7.3. ExternalLinkHandler

PageActionHandler	
Description	Controller and link scheme for CMAction beans which are for example used to perform a search.
Class	<code>com.coremedia.blueprint.cae.handlers.PageActionHandler</code>
Example	<code>/action/corporate/4420/action/search</code> for performing a search

Table 7.4. PageActionHandler

PageHandler	
Description	Controller and link scheme for pages.
Class	<code>com.coremedia.blueprint.cae.handlers.PageHandler</code>
Example	<code>/corporate/for-professionals/services</code> for a service page.

Table 7.5. PageHandler

PageRssHandler	
Description	Controller and link scheme for handling RSS
Class	<code>com.coremedia.blueprint.cae.handlers.PageRssHandler</code>
Format	<code>/service/rss/[SITE_URL_SEGMENT]/[CONTENT_ID]/feed.rss</code> for RSS feed with content id [CONTENT_ID]

Table 7.6. PageRssHandler

PreviewHandler	
----------------	--

Description	Controller and link scheme previewing content in CoreMedia Studio.
Class	<code>com.coremedia.blueprint.cae.handlers.PreviewHandler</code>
Example	<code>/preview?id=coremedia:///cap/content/3048%26view=fragmentPreview</code> for preview content as a fragment

Table 7.7. *PreviewHandler*

StaticUrlHandler	
Description	Controller and link scheme for generating static URLs based on Strings
Class	<code>com.coremedia.blueprint.cae.handlers.StaticUrlHandler</code>
Example	<code>/elastic/social/ratings</code> for a ES Post Controller

Table 7.8. *StaticUrlHandler*

TransformedBlobHandler	
Description	Controller and link scheme for transformed blobs
Class	<code>com.coremedia.blueprint.cae.handlers.TransformedBlobHandler</code>
Example	<code>/image/3126/landscape_ratio4x3/349/261/971b670685dffb69cfd28e55177d886db/Pi/mom-basa-image-image.jpg</code>

Table 7.9. *TransformedBlobHandler*

Link Post Processors

While link schemes are responsible for the path and possibly the parameters of a resource's URL, they are not aware of deployment aspects like domains, hosts, ports, servlet contexts, rewrite rules and the like. The Blueprint uses Link Post Processors to format links according to the particular environment.

The following link post processors are applied in `com.coremedia.blueprint.base.links.impl.BaseUriPrepender` and `com.coremedia.blueprint.base.links.impl.LinkAbsolutizer`.

- `prependBaseUri`

Prepends the "base URI" (web application and mapped servlet, for example `/blueprint/servlet`) to ALL (annotation based) links. This is required when the CAE web application is served directly by a web container with no prior URL rewriting.

- `makeAbsoluteUri`

Adds a prefix that makes the URI absolute. There are several cases in which URLs must be made absolute:

- a cross-site link: a URI pointing to a resource in a site that is served on a different domain
- externalized URIs: a URI should be send by mail or become part of an RSS feed

The prefixes for absolute URLs are specific for each site, therefore they are maintained in each site's settings in a struct named `absoluteUrlPrefixes`. The prefixes are different for the live and the preview CAE and must be maintained independently. A typical `absoluteUrlPrefixes` struct looks like this:




Figure 7.6. A basic `absoluteUrlPrefixes` Struct

NOTE

The URL prefixes must be at least a scheme-relative URL (beginning with `//`).



The Blueprint features an application property `link.urlPrefixType` that determines which `absoluteUrlPrefixes` entry is effective in a particular application. You will find `link.urlPrefixType` set appropriately in the `application.properties` of all components that use the `bbpase-links-impl` module, for example, for the `cae-live-webapp`:

```
# The live webapp builds live URLs
link.urlPrefixType=live
```

Example 7.1. Configuration of URL prefix type

While the standard Blueprint distinguishes only between preview and live URL prefixes, projects may add additional `absoluteUrlPrefixes` entries of arbitrary names for special URL prefixes and applications.

Why are struct lists needed after all, if they have only one entry? The above example is valid, but it does not show all configuration options. There are some optional features, and the equivalent complete struct would look like this:

12

Editing in progress

Settings

Content

Settings

×

+

String

⌵

☰

⬆

⬇

✂

📄

📄

✍

Property	Value	Type
▼ ...		Struct
▼ absoluteUrlPrefixes		Struct
▼ live		Struct List
▼ #1		Struct
▼ key		Struct
type	*	String
view	*	String
urlPrefix	//livecontext.example.org	String
▼ preview		Struct List
▼ #1		Struct
urlPrefix	//preview.livecontext.example.org	String

Figure 7.7. A complete `absoluteUrlPrefixes` Struct

You can declare special URL prefix rules for certain bean types or views, and you can specify an order for ambiguous rules. The default Blueprint does not make use of these options, but they reflect the format of the `key` field of the old `siteMap` `pings` entries, so that you do not lose any features when upgrading to this mechanism.

When you start over with a fresh Blueprint and look at the `SiteSettings` documents of our example content, the configuration looks yet a little different:




Figure 7.8. An initial `absoluteUrlPrefixes` `Struct`

CoreMedia supports a variety of deployments for various use cases like local development, production, quickrun, to name just a few. The appropriate URL prefixes in these setups vary from `//localhost:40080` to `//my.real.public.domain`. So there is no reasonable default to be hardcoded in the example content. Therefore, application properties in the values of `urlPrefix` are supported and use the well known `blueprint.site.mapping.*` properties which are declared in the CAEs' `application.properties` files. Initial content deployment is the only reason why these properties still exist, so you should not bother to maintain them for new sites in production repositories, but maintain the URL prefixes only in the content.

Force Scheme

In order to force a certain scheme (for example `http`, `https`, `ftp`) for a URL, two `cm` parameters must be set for the link: `absolute: true` and `scheme: <scheme-name>`.

7.3 Predefined Users

CoreMedia Blueprint provides some default users and groups that represent typical roles in an editorial staff. There are technical users with repository wide permissions and editorial users whose permissions are predominantly limited to a particular site or web presence [aside from a few exceptions like home folder access]. The editorial users and groups are only available if you activate the particular extension. Depending on your specific processes and roles, the default groups may be a more or less useful starting point for a production systems. The users, however, are meant as examples only. You are supposed to replace them with users that match your actual staff. The password of all default users is the same as the name.

In the *Blueprint* workspace you will find some `test-data/users` directories (one global and some in the extensions). The XML files in those directories declare the default users, groups and rules. They can be imported with the `restoreusers` command line tool. For the initial setup of your systems, you can adapt those files to your needs. The `test-data/content` sets provide home folders with suitable editor preferences documents for the users.

The following tables show the most important default users and groups in detail.

Global

Group name	Description
staff	Root group, essential common read permissions, home folder access
administratoren	All possible permissions
developer	All possible permissions but user authorization
global-manager	Editorial permissions for global themes and settings
composer-role, approver-role, publisher-role	Publication workflow roles

Table 7.10. Global groups

While some of the global groups contain users directly, most of them serve only as parent groups for the site-specific groups.

User name	Group	Description
Adam	administratoren	Administrator: IT operations, configuration, user authorization, workflow maintenance, recovery, performance analysis
Teresa	administratoren	Online Marketing Manager: Analytics analysis, campaign management, supervision
Dave	developer	Developer: Feature development, template development, performance tuning
Amy	asset-manager	Asset Manager: managing digital assets

Table 7.11. Global users

Since user and group names are unique within one repository, they differ for the members of the various web presences of Blueprint. The following users and groups reflect the eCommerce web presence. The roles of the Brand web presence are basically the same, and use similar names that you will easily recognize.

eCommerce

Group name	Description
global-site-manager-sf	All permissions for a web presence
local-site-manager-sf	Editorial permissions for a site, read rights for the master site
online-editor-sf-en-US	Finegrained permissions for his particular tasks
media-editor-sf-en-US	Finegrained permissions for his particular tasks on media objects

Table 7.12. Site specific groups for Salesforce Commerce

User name	Group	Description
Sally	global-site-manager-sf	Global site manager: organization of internal processes

User name	Group	Description
Peter SF, Pierre SF, Pietro SF, Yoshi SF, Yang SF (for their respective regions)	manager-sf-en-GB, manager-sf-fr-FR, manager-sf-it-IT, manager-sf-ja-JP, manager-sf-zh-CN	Local content manager: management of dynamic content, targeting rules, A-B-testing, topic pages for their particular regions
George SF	online-editor-sf-en-US	Online editor: writing articles, creating slideshows, editing images, tagging contents
Mark SF	media-editor-sf-en-US	Media editor: creating media objects, creating slideshows, video and audio objects, editing images, tagging media content

Table 7.13. Site specific users for Salesforce Commerce

Group name	Description
global-site-manager-h-b2c	All permissions for a web presence
local-site-manager-h-b2c	Editorial permissions for a site, read rights for the master site
online-editor-h-b2c-en-GB, online-editor-h-b2c-de-DE	Finegrained permissions for his particular tasks
media-editor-h-b2c-en-GB, media-editor-h-b2c-de-DE	Finegrained permissions for his particular tasks on media objects

Table 7.14. Site specific groups for SAP Commerce

User name	Group	Description
Rick H, Harry	global-site-manager-h-b2c	Global site manager: organization of internal processes
Peter H, Pierre H, Piet H, Pedro H, Yoshi H (for their respective regions)	manager-h-b2c-en-GB, manager-h-b2c-fr-FR, manager-h-b2c-de-DE, manager-h-b2c-es-ES, manager-h-b2c-ja-JP	Local content manager: management of dynamic content, targeting rules, A-B-testing, topic pages for their particular regions

User name	Group	Description
George H, Georg H	online-editor-h-b2c-en-GB, online-editor-h-b2c-de-DE	Online editor: writing articles, creating slideshows, editing images, tagging contents
Mark H, Amy, Markus H	media-editor-h-b2c-en-GB, media-editor-h-b2c-en-GB, media-editor-h-b2c-de-DE	Media editor: creating media objects, creating slideshows, video and audio objects, editing images, tagging media content

Table 7.15. Site specific users for SAP Commerce

Group name	Description
global-site-manager, global-site-manager-b2b, global-site-manager-calista	All permissions for a web presence
local-site-manager, local-site-manager-b2b, local-site-manager-calista	Editorial permissions for a site, read rights for the master site
online-editor-en-US, online-editor-de-DE, online-editor-b2b-en-US, online-editor-b2b-de-DE	Finegrained permissions for his particular tasks
media-editor-en-US, media-editor-de-DE, media-editor-b2b-en-US, media-editor-b2b-de-DE	Finegrained permissions for his particular tasks on media objects

Table 7.16. Site specific groups for HCL Commerce

User name	Group	Description
Rick, Rick B2B, Rick Cal	global-site-manager, global-site-manager-b2b, global-site-manager-calista	Global site manager: organization of internal processes
Peter, Piet, Pierre, Pedro, Yoshi [for their respective re- gions]	manager-en-US, manager-de-DE, manager-fr-FR, manager-es-ES, manager-ja-JP	Local content manager: management of dynamic content, targeting rules, A-B-testing, topic pages for their particular regions

User name	Group	Description
Peter B2B, Piet B2B, Pierre B2B, Pedro B2B, Yoshi B2B (for their respective regions)	manager-b2b-en-US, manager-b2b-de-DE, manager-b2b-fr-FR, manager-b2b-es-ES, manager-b2b-ja-JP	Local content manager: management of dynamic content, targeting rules, A-B-testing, topic pages for their particular regions
Peter Cal, Piet Cal (for their respective regions)	manager-calista-en-US, manager-calista-de-DE	Local content manager: management of dynamic content, targeting rules, A-B-testing, topic pages for their particular regions
George, Georg, George B2B, Georg B2B	online-editor-en-US, online-editor-de-DE, online-editor-b2b-en-US, online-editor-b2b-de-DE	Online editor: writing articles, creating slideshows, editing images, tagging contents
Mark, Markus, Mark B2B, Markus B2B	media-editor-en-US, media-editor-de-DE, media-editor-b2b-en-US, media-editor-b2b-de-DE	Media editor: creating media objects, creating slideshows, video and audio objects, editing images, tagging media content

Table 7.17. Site specific users for HCL Commerce

Brand web presence

Group name	Description
global-site-manager-c	All permissions for a web presence
manager-c-en-US	Editorial permissions for a site, read rights for the master site
online-editor-c-en-US	Finegrained permissions for his particular tasks

Table 7.18. Site specific groups Brand web presence

User name	Group	Description
Rick C	global-site-manager-c	Global site manager: organization of internal processes

User name	Group	Description
Peter C, Piet C, Pedro C, Pierre C (for their respective regions)	manager-c-en-US, manager-c-de-DE, manager-c-es-ES, manager-c-fr-FR	Local content manager: management of dynamic content, targeting rules, A-B-testing, topic pages for their particular regions
George C, Marc C	online-editor-c-en-US	Online editor: writing articles, creating slideshows, editing images, tagging contents

Table 7.19. Site specific users Brand web presence

7.4 Database Users

The following table shows the database users that are required for CoreMedia components. For MySQL and Microsoft SQL server are scripts in the workspace, that create these users.

Component	User name	Description
<i>Content Management Server</i>	cm_management	This database user will manage the content of the <i>Content Management Server</i> . This database will require most of the space, since content is versioned.
<i>Master Live Server</i>	cm_master	This database user will manage the content of the <i>Master Live Server</i> . Up to two versions of each published content will be stored.
<i>Replication Live Server</i>	cm_replication	This database user will manage the content of the <i>Replication Live Server</i> . Up to two version of each published content will be stored.
<i>CAE Feeder</i> for preview	cm_mcaefeeder	This database user will persist data for the <i>CAE Feeder</i> working in the management environment. Content is not versioned.
<i>CAE Feeder</i> for live site	cm_caefeeder	This database user will persist data for the delivery environment. Content is not versioned.
<i>Studio Server</i> for editorial comments feature	cm_editorial_comments	This database user will persist data for the editorial comments feature.

Table 7.20. Database Users

7.5 Cookies

Several customer facing modules of *CoreMedia Content Cloud* use cookies to fulfill their tasks.

Blueprint delivery CAE

The Blueprint delivery CAE is configured to not write any cookies. However, session cookies CM_SESSIONID and JSESSIONID are written, when a website visitor logs into the Blueprint delivery CAE. The name of these cookies may vary, depending on the deployment scenario.

Elastic Social

Elastic Social writes only one cookie:

guid A globally unique ID to identify the user's web browser

Adaptive Personalization

In the default configuration, *CoreMedia Adaptive Personalization* writes the cookies described in the list. *CoreMedia Adaptive Personalization* can also be configured to store data in *CoreMedia Elastic Social* user profiles.

cmKeywordCookie	Scoring of keywords attached to the visited contents.
cmLastVisited	A fixed-sized list of the last visited contents.
cmLocationTaxonomiesCookie	Scoring of location taxonomies attached to the visited contents
cmReferrerCookie	Search engine and search query that lead the visitor to the site.
cmSubjectTaxonomiesCookie	Scoring of subject taxonomies attached to the visited contents.

eCommerce

When you use eCommerce, the Commerce Server writes cookies. For *HCL Commerce* the cookies are documented at https://help.hcltechsw.com/commerce/8.0.0/admin/concepts/cse_cookies.html.

Glossary

Blob	Binary Large Object or short blob, a property type for binary objects, such as graphics.
CAE Feeder	Content applications often require search functionality not only for single content items but for content beans. The <i>CAE Feeder</i> makes content beans searchable by sending their data to the <i>Search Engine</i> , which adds it to the index.
Content Application Engine (CAE)	<p>The <i>Content Application Engine</i> [CAE] is a framework for developing content applications with <i>CoreMedia CMS</i>.</p> <p>While it focuses on web applications, the core frameworks remain usable in other environments such as standalone clients, portal containers or web service implementations.</p> <p>The CAE uses the Spring Framework for application setup and web request processing.</p>
Content Bean	A content bean defines a business oriented access layer to the content, that is managed in <i>CoreMedia CMS</i> and third-party systems. Technically, a content bean is a Java object that encapsulates access to any content, either to CoreMedia CMS content items or to any other kind of third-party systems. Various CoreMedia components like the CAE Feeder or the data view cache are built on this layer. For these components the content beans act as a facade that hides the underlying technology.
Content Delivery Environment	<p>The <i>Content Delivery Environment</i> is the environment in which the content is delivered to the end-user.</p> <p>It may contain any of the following modules:</p> <ul style="list-style-type: none"> • <i>CoreMedia Master Live Server</i> • <i>CoreMedia Replication Live Server</i> • <i>CoreMedia Content Application Engine</i> • <i>CoreMedia Search Engine</i> • <i>Elastic Social</i> • <i>CoreMedia Adaptive Personalization</i>
Content Feeder	The <i>Content Feeder</i> is a separate web application that feeds content items of the CoreMedia repository into the <i>CoreMedia Search Engine</i> . Editors can use the <i>Search Engine</i> to make a full text search for these fed items.

Content item	In <i>CoreMedia CMS</i> , content is stored as self-defined content items. Content items are specified by their properties or fields. Typical content properties are, for example, title, author, image and text content.
Content Management Environment	<p>The <i>Content Management Environment</i> is the environment for editors. The content is not visible to the end user. It may consist of the following modules:</p> <ul style="list-style-type: none"> • <i>CoreMedia Content Management Server</i> • <i>CoreMedia Workflow Server</i> • <i>CoreMedia Importer</i> • <i>CoreMedia Site Manager</i> • <i>CoreMedia Studio</i> • <i>CoreMedia Search Engine</i> • <i>CoreMedia Adaptive Personalization</i> • <i>CoreMedia Preview CAE</i>
Content Management Server	Server on which the content is edited. Edited content is published to the Master Live Server.
Content Repository	<i>CoreMedia CMS</i> manages content in the Content Repository. Using the Content Server or the UAPI you can access this content. Physically, the content is stored in a relational database.
Content Server	<p><i>Content Server</i> is the umbrella term for all servers that directly access the CoreMedia repository:</p> <p><i>Content Servers</i> are web applications running in a servlet container.</p> <ul style="list-style-type: none"> • <i>Content Management Server</i> • <i>Master Live Server</i> • <i>Replication Live Server</i>
Content type	A content type describes the properties of a certain type of content. Such properties are for example title, text content, author, ...
Contributions	Contributions are tools or extensions that can be used to improve the work with <i>CoreMedia CMS</i> . They are written by CoreMedia developers - be it clients, partners or CoreMedia employees. CoreMedia contributions are hosted on GitHub at https://github.com/coremedia-contributions .
Controm Room	<i>Controm Room</i> is a <i>Studio</i> plugin, which enables users to manage projects, work with workflows, and collaborate by sharing content with other <i>Studio</i> users.
CORBA [Common Object Request Broker Architecture]	<p>The term <i>CORBA</i> refers to a language- and platform-independent distributed object standard which enables interoperation between heterogenous applications over a network. It was created and is currently controlled by the Object Management Group [OMG], a standards consortium for distributed object-oriented systems.</p> <p>CORBA programs communicate using the standard IIOP protocol.</p>

CoreMedia Studio	<p><i>CoreMedia Studio</i> is the working environment for business specialists. Its functionality covers all of the stages in a web-based editing process, from content creation and management to preview, test and publication.</p> <p>As a modern web application, <i>CoreMedia Studio</i> is based on the latest standards like Ajax and is therefore as easy to use as a normal desktop application.</p>
Dead Link	A link, whose target does not exist.
DTD	<p>A Document Type Definition is a formal context-free grammar for describing the structure of XML entities.</p> <p>The particular DTD of a given Entity can be deduced by looking at the document prolog:</p> <pre><!DOCTYPE coremedia SYSTEM "http://www.coremedia.com/dtd/coremedia.dtd"</pre> <p>There're two ways to indicate the DTD: Either by Public or by System Identifier. The System Identifier is just that: a URL to the DTD. The Public Identifier is an SGML Legacy Concept.</p>
Elastic Social	<i>CoreMedia Elastic Social</i> is a component of <i>CoreMedia CMS</i> that lets users engage with your website. It supports features like comments, rating, likings on your website. <i>Elastic Social</i> is integrated into <i>CoreMedia Studio</i> so editors can moderate user generated content from their common workplace. <i>Elastic Social</i> bases on NoSQL technology and offers nearly unlimited scalability.
EXML	EXML is an XML dialect used in former CoreMedia Studio version for the declarative development of complex Ext JS components. EXML is Jangaroo 2's equivalent to Apache Flex (formerly Adobe Flex) MXML and compiles down to ActionScript. Starting with release 1701 / Jangaroo 4, standard MXML syntax is used instead of EXML.
Folder	A folder is a resource in the CoreMedia system which can contain other resources. Conceptually, a folder corresponds to a directory in a file system.
Home Page	The main entry point for all visitors of a site. Technically it is often referred to as root document and also serves as provider of the default layout for all subpages.
IETF BCP 47	Document series of <i>Best current practice</i> [BCP] defined by the Internet Engineering Task Force (IETF). It includes the definition of IETF language tags, which are an abbreviated language code such as en for English, pt-BR for Brazilian Portuguese, or nan-Hant-TW for Min Nan Chinese as spoken in Taiwan using traditional Han characters.
Importer	Component of the CoreMedia system for importing external content of varying format.
IOR (Interoperable Object Reference)	A CORBA term, <i>Interoperable Object Reference</i> refers to the name with which a CORBA object can be referenced.

Jangaroo	<p><i>Jangaroo</i> is a JavaScript framework developed by CoreMedia that supports ActionScript as an input language which is compiled down to JavaScript. You will find detailed descriptions on the Jangaroo webpage http://www.jangaroo.net.</p>
Java Management Extensions (JMX)	<p>The Java Management Extensions is an API for managing and monitoring applications and services in a Java environment. It is a standard, developed through the Java Community Process as JSR-3. Parts of the specification are already integrated with Java 5. JMX provides a tiered architecture with the instrumentation level, the agent level and the manager level. On the instrumentation level, MBeans are used as managed resources.</p>
JSP	<p>JSP (Java Server Pages) is a template technology based on Java for generating dynamic HTML pages.</p> <p>It consists of HTML code fragments in which Java code can be embedded.</p>
Locale	<p>Locale is a combination of country and language. Thus, it refers to translation as well as to localization. Locales used in translation processes are typically represented as IETF BCP 47 language tags.</p>
Master Live Server	<p>The <i>Master Live Server</i> is the heart of the <i>Content Delivery Environment</i>. It receives the published content from the <i>Content Management Server</i> and makes it available to the <i>CAE</i>. If you are using the <i>CoreMedia Multi-Master Management Extension</i> you may use multiple <i>Master Live Server</i> in a CoreMedia system.</p>
Master Site	<p>A master site is a site other localized sites are derived from. A localized site might itself take the role of a master site for other derived sites.</p>
MIME	<p>With Multipurpose Internet Mail Extensions (MIME), the format of multi-part, multimedia emails and of web documents is standardised.</p>
MXML	<p>MXML is an XML dialect used by Apache Flex (formerly Adobe Flex) for the declarative specification of UI components and other objects. CoreMedia Studio uses the Open Source compiler Jangaroo 4 to translate MXML and ActionScript sources to JavaScript that is compatible with Ext JS 6.</p>
Personalisation	<p>On personalised websites, individual users have the possibility of making settings and adjustments which are saved for later visits.</p>
Projects	<p>A project is a collection of content items in CoreMedia CMS created by a specific user. A project can be managed as a unit, published or put in a workflow, for example.</p>
Property	<p>In relation to CoreMedia, properties have two different meanings:</p> <p>In CoreMedia, content items are described with properties (content fields). There are various types of properties, for example, strings (such as for the author), Blobs (for example, for images) and XML for the textual content. Which properties exist for a content item depends on the content type.</p> <p>In connection with the configuration of CoreMedia components, the system behavior of a component is determined by properties.</p>

Glossary |

Replication Live Server	The aim of the <i>Replication Live Server</i> is to distribute load on different servers and to improve the robustness of the <i>Content Delivery Environment</i> . The <i>Replication Live Server</i> is a complete Content Server installation. Its content is a replicated image of the content of a <i>Master Live Server</i> . The <i>Replication Live Server</i> updates its database due to change events from the <i>Master Live Server</i> . You can connect an arbitrary number of <i>Replication Live Servers</i> to the <i>Master Live Server</i> .
Resource	A folder or a content item in the CoreMedia system.
ResourceUri	A ResourceUri uniquely identifies a page which has been or will be created by the <i>Active Delivery Server</i> . The ResourceUri consists of five components: Resource ID, Template ID, Version number, Property names and a number of key/value pairs as additional parameters.
Responsive Design	Responsive design is an approach to design a website that provides an optimal viewing experience on different devices, such as PC, tablet, mobile phone.
Site	<p>A site is a cohesive collection of web pages in a single locale, sometimes referred to as localized site. In <i>CoreMedia CMS</i> a site especially consists of a site folder, a site indicator and a home page for a site.</p> <p>A typical site also has a master site it is derived from.</p>
Site Folder	All contents of a site are bundled in one dedicated folder. The most prominent document in a site folder is the site indicator, which describes details of a site.
Site Indicator	A site indicator is the central configuration object for a site. It is an instance of a special content type, most likely <u>CMSite</u> .
Site Manager	<p>Swing component of CoreMedia for editing content items, managing users and workflows.</p> <p>The Site Manager is deprecated for editorial use.</p>
Site Manager Group	Members of a site manager group are typically responsible for one localized site. Responsible means that they take care of the contents of that site and that they accept translation tasks for that site.
Template	<p>In CoreMedia, JSPs used for displaying content are known as Templates.</p> <p>OR</p> <p>In <i>Blueprint</i> a template is a predeveloped content structure for pages. Defined by typically an administrative user a content editor can use this template to quickly create a complete new page including, for example, navigation, predefined layout and even predefined content.</p>
Translation Manager Role	Editors in the translation manager role are in charge of triggering translation workflows for sites.

Glossary |

User Changes web application	The <i>User Changes</i> web application is a <i>Content Repository</i> listener, which collects all content, modified by <i>Studio</i> users. This content can then be managed in the <i>Control Room</i> , as a part of projects and workflows.
Version history	A newly created content item receives the version number 1. New versions are created when the content item is checked in; these are numbered in chronological order.
Weak Links	<p>In general <i>CoreMedia CMS</i> always guarantees link consistency. But links can be declared with the <i>weak</i> attribute, so that they are not checked during publication or withdrawal.</p> <p>Caution! Weak links may cause dead links in the live environment.</p>
Workflow	A workflow is the defined series of tasks within an organization to produce a final outcome. Sophisticated applications allow you to define different workflows for different types of jobs. So, for example, in a publishing setting, a document might be automatically routed from writer to editor to proofreader to production. At each stage in the workflow, one individual or group is responsible for a specific task. Once the task is complete, the workflow software ensures that the individuals responsible for the next task are notified and receive the data they need to execute their stage of the process.
Workflow Server	The <i>CoreMedia Workflow Server</i> is part of the Content Management Environment. It comes with predefined workflows for publication and global-search-and-replace but also executes freely definable workflows.
XLIFF	XLIFF is an XML-based format, standardized by OASIS for the exchange of localizable data. An XLIFF file contains not only the text to be translated but also metadata about the text. For example, the source and target language. <i>CoreMedia Studio</i> allows you to export content items in the XLIFF format and to import the files again after translation.

Index

A

- A/B testing, 356
- access rights, 161
- actions, 195
 - webflow, 198
- Adaptive Personalization, 346
 - CAE, 349
 - CAE integration, 349
 - conditions, 353
 - content types, 150
 - context, 346
 - extension, 347
 - extension modules, 347
 - integration points, 347
 - search functions, 350
 - test user profiles, 352
- AdaptivePersonalization
 - Studio, 352
- Amazon EC2, 30
 - [see also [Amazon Linux](#)]
- Amazon Linux
 - supported environments reference, **30**
- Apache Tomcat [see [Tomcat](#)]
- Application
 - Architecture, 57
- Application Plugins, 72
- approver-role, 279
- Asset Management, 360
 - AMAsset, 370
 - Asset Widget, 361
 - blob storage, 372
 - catalogPictureHandler, 365
 - content types, 370
 - download portal, 373
 - metadata, 366
- Asset Widget, 361
- assets, 144, 161

B

- BeansForPlugins, 82
- blueprint
 - Brand Blueprint, 27
 - eCommerce Blueprint, 27
 - removal, 91
- Brand Blueprint, 27

C

- CAE, 129
 - Maven configuration, 131
 - Personalization, 349
- CAE Feeder, 131
- classify, 151
- client code, 162, 191
 - merging, 194
 - minification, 193
 - performance, 193
 - preview, 192
- CMChannel, 163
- CMCollection, 180
- CMJavaScript, 191
- CMLocalized, 244
- CMSCSS, 191
- CMTaxonomy, 152
 - properties, 153
- CMTeasable, 187, 245
- CMViewtype, 181
- common content
 - types, 145
- Component
 - Artifact, 58
- composer-role, 279
- content, 144
 - media, 149
- content assets
 - properties, 147
- content lists, 179
- content type
 - CMLocalized, 244
 - CMTeasable, 245
- content type model, **376**
 - extensions:automerger, 245
 - extensions:translatable, 245
 - extensions:weakLink, 244
- Content Types
 - extending, 123
- content types, 161

- assets, 161
- client code, 162
- navigation and page structure, 161
- technical content types, 162
- content visibility, 203
- ContentToTranslateItemTransformer, 249
- context, 164, 346
 - determine, 164
- CoreMedia Blueprint
 - folder structure, 162
- CoreMedia modules, 295
- country
 - locale, 227
- create content
 - add menu item, 307
- create from template
 - dialog, 312
 - new template folder, 313
 - template locations, 312

D

- data privacy
 - personal data, 132
- Data Privacy
 - personal data, 356
 - third party, 356
- Database
 - Configuration, 105
 - Users, 105
- database
 - MongoDB, 106
 - users, 391
- Deployment Archive
 - quick start, 35
- document type model [see [content type model](#)]
- Documentation, 30
- dynamic templating, 187
 - add template to page, 189
 - upload templates, 189

E

- eCommerce Blueprint, 27
- Elastic Social
 - CAPTCHA, 344
 - configuration, 332
 - curated transfer, 343
 - custom information, 338
 - emails, 341

- features, 331
 - mail templates, 341
- end user interactions, 195
- Extension, 67, 92, 102
 - content types, 124
 - dependencies, 93
 - Elastic Social, 101
 - Personalization, 102
- Extension Tool, 67
- Extensions, 67
- extensions:automerge, 245
- extensions:translatable, 245
- extensions:weakLink, 244

F

- FreeMarker, 187

G

- global site manager, 233
- group, 279
 - approver-role, 279
 - composer-role, 279
 - publisher-role, 279

H

- Hardware Prerequisites, 32-33
- home page, **228**
- Hybris Commerce [see [SAP Hybris Commerce](#)]

I

- IBM WebSphere Commerce, **34**
- IBM WebSphere Commerce 7 Feature Pack 7
 - supported environments reference, 34
- IBM WebSphere Commerce 7 Feature Pack 8
 - supported environments reference, 34
- IBM WebSphere Commerce 8 Mod Pack 1
 - supported environments reference, 34
- IBM WebSphere Commerce 8 Mod Pack 4
 - supported environments reference, 34
- IETF BCP 47, 227
- Images, 199
 - configure sizes, 199
 - default JPEG quality, 201
 - High Resolution/Retina, 201
- import-themes, 225

J

Java Plugins, 73

K

keywords, 151

L

language

locale, 227

layout

localization, 178

library

Image Gallery, 301

link

weak, 231, 244, 274-276

link format, 379

local site manager, **229**

locale, **227**, 232

IETF BCP 47, 227

LocaleSettings, **232**, 233

localization, 227

localized site, 228

M

mail templates, 341

MailTemplateService, 341

master site, **228**

Maven

changing groupId, 104

coremedia-application, 66

Extension, 92

settings.xml, 31

media content, 149

minification, 193

MongoDB, 106

supported environments reference, **30**

multi-site, 227

administration, 232

CMLocalized, 244

CMTeasable, 245

content types, **244**

derived site, 229

global site manager, 233

groups, 233

local site manager, **229**

master site, **228**, 229

permissions, 233

site, **228**

SiteModel, 237, **238**, 280

SitesService, **237**

structure, 229

translation manager role, **229**, 233, 280-281

MySQL

supported environments reference, **30**

N

navigation, 163

navigation and page structure, 161

O

Open Street Map, 314, 357

OpenCalais

disable, 158

Optimizely, 356

P

page grid, 167

configure new layout, 172

editor, 169

incompatible changes, 171

inheriting placements, 168

layout locations, 171

lock placements, 168

predefined layout, 170

personal data, 132, 356

Personalization

content types, 102

placement, 167

placement editor, 171

placements

localization, 178

predefined user, 385

predefined workflows, 278

publisher-role, 279

Q

quick start, **35**

R

rights concept, 161

robots.txt, 205

example configuration, 207

RobotsHandler, 206

S

Salesforce Marketing Cloud

uploading content, 323

Salesforce Marketing Cloud integration, 359

SAP Hybris Commerce, **34**

search, 212

search functions, 350

search landing pages, 224

keywords, 224

ServerExport, **246**

ServerImport, **246**

settings

linked, 165

local, 165

settings.xml, 31

SignCookie

RSA Key, 344

site, **228**

derived site, 229

global site manager, 233

home page, **228**, 230

interdependence, **231**

local site manager, **229**

locale, **227**, 232

LocaleSettings, **232**, 233

localized site, 228

master site, **228**, 229

multi-site, 227

site folder, **228**, 230

site id, **228**

site identifier, **228**

site indicator, **228**, 230-231, 234, 237

site manager group, **228**, 234, 280-281

site name, **228**

SiteModel, 234, 236-237, **238**, 280

SitesService, **237**

translation manager role, **229**, 233, 280-281

translation workflow robot user, 234

site manager group, **228**, 234, 280-281

sitemap, 204, 209

maximum number of URLs, 209

SiteModel, 237, **238**, 280

SitesService, **237**

Software Prerequisites, 32

Solr, 212

SpringAwareLongAction, 249

Studio, 125

bookmarks, 303

create content, 305

create from template, 311

external preview, 303

Jangaroo, 126

library, 301

Maven, 126

Open Street Map, 314

Personalization, 352

plugin, 125

plugins, 296

query form, 296

settings, 304

site selection, 315

SWC packaging, 66

upload content to Salesforce Marketing Cloud, 323

upload files, 316

Studio Client Plugins, 85

Studio enhancements, 296

suggestion strategy, 157

supported environments, **30**

Amazon Linux, 30

databases, 30

directory services, 30

HCL Commerce 7, 34

HCL Commerce 8, 34

HCL Commerce 9, 34

Java, 30

MongoDB, 30

MySQL, 30

operating systems, 30

servlet container, 30

Tomcat, 30

web browsers, 30

SWC packaging, 66

T

tag management

tag manager, 225

taxonomies, 151

as conditions for dynamic lists, 152

hierarchical organisation, 153

implement new suggestion strategy, 157

location, 153

related content, 152

site specific, 158

taxonomy editor, 154

- taxonomy resolver strategy, 157
- teaser management, 186
- technical content types, 162
- Test System Setup
 - preconfigured quick start, **33**
- third party, 356
 - [see also [Data Privacy](#)]
- Tomcat
 - supported environments reference, **30**
- topic pages, 218
 - configuration, 219
 - managed, 220
 - taxonomy, 218
- translation, 227
 - configuration, 267
 - customization, 272
 - Studio, 272
 - UI, **272**
 - workflow, **280**, 282
 - workflow action, 282
 - XLIFF, **247**, 248, 269
 - Configuration, 269
 - Translation Item, **249**
- translation manager, **229**, 233, 280-281
- translation manager role, **229**, 233, 280-281
- translation workflow robot user, 234

U

- upload files
 - configuration, 317
- URLs, 201
- User Changes application, 21
- users
 - predefined, 385

V

- validFrom, 203
- Vanity URLs, 201
- view repositories, 190
- view type selector, 181
- view types, 180
 - localization, 178, 182
- viewType, 149
- visibility, 203

W

- weak link, 231, 244, 274-276

- Webflow actions, 198
- website
 - navigation, 163
 - page assembly, 167
 - settings, 165
 - structure, 167
- website search, 212
- WebSphere Commerce [see [IBM WebSphere Commerce](#)]
- workflow
 - action, 282
 - publication, 278
 - translation, 280, 282
- workflow action, 282
 - AutoMergeSyncAction, 290
 - AutoMergeTranslationAction, 288, 290
 - CompleteTranslationAction, 291-292
 - CreateTranslationTreeData, 284
 - CreateTranslationTreeDataAction, 285
 - ExtractPerformerAction, 287-288
 - FilterDerivedContentsAction, 286
 - GetDerivedContentsAction, 283-285
 - GetSiteManagerGroupAction, 286-287
 - RollbackTranslationAction, 292-293
- Workspace
 - Configuration, 104
 - Structure, 66

X

- XLIFF, **247**, 248, 269
 - Configuration, 269
 - properties, 269
 - translatableExpressions, 271
 - Translation Item, **249**
 - translation unit, 248
 - XliffExporter, 250
 - XliffExportOptions, 251
 - XliffImporter, 251
- XliffExporter, 250
- XliffExportOptions, 251
- XliffImporter, 251
- XML Localization Interchange File Format, **247**, 248